ResNet-18 Add-ons: Results

CSE 4109 · AI for Health · Aaron's part (8 November 2026)

1. The question

- **Task:** classify each candidate cell in the MIDOG++ breast subset as a mitotic figure or an imposter.
- **Evaluation:** leave-one-scanner-out.
  - Train on two scanners and test on all 50 cases of the third, unseen scanner.
  - Each of CS2, S360 and XR takes a turn as the test scanner.
- **Repeats:** 5 seeds per configuration. Results are the mean over 3 folds × 5 seeds.
- **Threshold:** chosen on validation data from the training scanners only. The test scanner's labels are never used.
- **Statistics:** two-level paired bootstrap, B = 5000.
  - Cases are resampled within each fold.
  - Both arms of a comparison use the same seeds.

2. Main table: five models × three inference modes

Model	F1 as trained	F1 + TTA	F1 + AdaBN + TTA	AUROC as trained	AUROC + AdaBN + TTA
Baseline	0.673	0.690	0.743	0.846	0.882
+ Stain	0.713	0.714	0.759	0.867	0.894
+ GRL	0.687	0.690	0.748	0.854	0.886
+ Stain + GRL	0.714	0.727	**0.766**	0.881	**0.901**
ResNet all	**0.733**	**0.745**	**0.766**	**0.884**	0.898

Across a row: test-time steps


- **TTA (test-time augmentation):** each image is flipped and rotated into 8 versions, and the predictions are averaged. It needs no extra data and is almost a free gain.
- **AdaBN:** BatchNorm means and variances are re-estimated on **unlabelled** images from the test scanner.
  - In effect, the model takes a look at the new scanner's colour distribution before it predicts.
  - We cross-fit it: statistics estimated on half of the cases are used to predict the other half. That way no image is used both to adapt and to evaluate.
  - This step gives the largest gain of the three inference modes.

Down a column: training-time add-ons

- **Stain:** random stain jitter on the H and E channels only (HED jitter, $\sigma = 0.05$) during training. It keeps the model from relying on one scanner's colours.
- **GRL:** a scanner-classification head behind a gradient reversal layer. It pushes the features to carry no information about which scanner an image came from.
- **Soft labels:** the target is the fraction of raters who voted "mitotic", not a hard 0/1.
  - Candidates with only 2 raters were all unanimous.
  - So soft labels change the target only for the 925 candidates with 3 raters (about 21 %).

ResNet all combines all three training add-ons with TTA and cross-fitted AdaBN. It is the "+all" cell of the team grid.

- With AdaBN + TTA it reaches F1 0.766 (95 % CI [0.740, 0.786]).
- Precision is 0.729, recall 0.820 and AUROC 0.898.



Heatmap of the main table: one row per model, one column per inference mode

3. Key finding: test-time adaptation absorbs most of the training add-on gain

Inference mode	Baseline	ResNet all	Gap from training add-ons
As trained	0.673	0.733	**+0.060**
AdaBN + TTA	0.743	0.766	**+0.023**


- **Most of the gap closes at test time.** With no add-ons, the baseline goes from 0.673 to 0.743 through AdaBN + TTA alone.
- **A plausible explanation is overlap.** Stain augmentation and GRL target colour and scanner differences, and AdaBN partly corrects those at test time.
  - We did **not** test this mechanism directly, so it is a hypothesis.
- **Corollary 1:** with AdaBN + TTA, ResNet all and the simpler + Stain + GRL are tied. The difference is −0.000, 95 % CI [−0.015, 0.014].
- **Corollary 2:** as trained, all beats + Stain + GRL by +0.020 [0.001, 0.038], mostly on the S360 fold.
  - So soft labels make a clear difference only without test-time adaptation.

4. What each component contributes (6 pre-registered tests)

Each test removes one component from ResNet all and measures the drop in F1. The 6 tests are Holm-adjusted together. They were written into `ADDONS_PROTOCOL.md` before phase-2 training, so they are confirmatory.

Component (removed at AdaBN + TTA)	ΔF1 [95 % CI]	Holm p	Verdict
Stain augmentation	+0.024 [0.011, 0.038]	< 0.003	significant
TTA	+0.015 [0.006, 0.024]	0.013	significant
AdaBN (TTA kept)	+0.020 [0.001, 0.040]	0.097	unadjusted CI excludes 0; not significant after Holm
GRL	+0.012 [0.001, 0.025]	0.097	unadjusted CI excludes 0; not significant after Holm
Soft labels	+0.007 [–0.006, 0.020]	0.284	not significant
all (AdaBN + TTA) vs baseline as trained	**+0.093 [0.064, 0.127]**	**< 0.003**	**significant**

“Not significant” does not mean “no effect”. It means no effect larger than the upper CI bound. For example, soft labels contribute at most about 0.02.



The 6 confirmatory tests: dots are ΔF1, bars are 95 % CIs, filled dots are significant after Holm

5. What we tried that was not better (exploratory)

- **TENT / TENT+IM** (test-time entropy minimisation that keeps updating the BN parameters): with TTA, within noise of AdaBN. More complex, not better.
- **AdaBN estimated on random tissue crops** instead of candidate patches: F1 drops by 0.178.
  - The model calls almost every candidate positive: recall 0.998, precision only 0.42.
  - The threshold calibration breaks. AdaBN statistics must come from images of the same kind as the test samples.
- **UDA-DANN** (adversarial alignment to the unlabelled target scanner during training): no better than AdaBN, and a more complicated pipeline.
- **EMA weights and Macenko stain normalisation** (phase 1): they help as trained but give no gain after AdaBN + TTA. Macenko even loses 0.015. This matches the pattern in section 3.
- **5-seed ensembles:** add about 0.02 F1.
  - The ResNet all ensemble reaches F1 0.785 and AUROC 0.908 at AdaBN + TTA, and F1 0.754 as trained.
  - Ensembles were not in the pre-registered protocol, so they are described but not tested.

The full methods and all numbers are in `Aaron_Method_Report.pdf`. Code and results files are in the `aaron_model/` folder of the GitHub repository.