

Namespace CAST_Client_Service

Classes

[CAST_Client_Service](#)

This class is the integration point into the Centralized Automation for Software Tools (CAST) Add the DLL as a reference file to your custom framework The key methods to call within your custom framework are

1. updateFrameworkFunctionality
2. updateTestState
3. updateTestResult
4. uploadTestResultFolder The key fields to track CAST Action requests are
5. _startTestRun
6. _stopTestRun
7. _pauseTestRun
8. _resumeTestRun
9. _abortTestRun

Class CAST_Client_Service

Namespace: [CAST_Client_Service](#)

Assembly: CAST_Client_Service.dll

This class is the integration point into the Centralized Automation for Software Tools (CAST) Add the DLL as a reference file to your custom framework The key methods to call within your custom framework are

1. updateFrameworkFunctionality
2. updateTestState
3. updateTestResult
4. uploadTestResultFolder The key fields to track CAST Action requests are
5. _startTestRun
6. _stopTestRun
7. _pauseTestRun
8. _resumeTestRun
9. _abortTestRun

```
public static class CAST_Client_Service
```

Inheritance

[object](#)  ← CAST_Client_Service

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Fields

_abortRun

_abortRun contains the current state of the ABORT Action on the CAST Server

```
public static bool _abortRun
```

Field Value

[bool](#) 

_customAction

_customAction needs work

```
public static bool _customAction
```

Field Value

[bool](#)

_pauseRun

_pauseRun contains the current state of the PAUSE Action on the CAST Server

```
public static bool _pauseRun
```

Field Value

[bool](#)

_resumeRun

_resumeRun contains the current state of the RESUME Action on the CAST Server

```
public static bool _resumeRun
```

Field Value

[bool](#)

_startRun

_startRun contains the current state of the START Action on the CAST Server

```
public static bool _startRun
```

Field Value

[bool](#)

_stopRun

_stopRun contains the current state of the STOP Action on the CAST Server

```
public static bool _stopRun
```

Field Value

[bool](#)

currentUUID

currentUUID is the RabbitMQ Queue name

```
public static string currentUUID
```

Field Value

[string](#)

customActionList

Assign Custom Actions per registered Client

```
public static List<string> customActionList
```

Field Value

[List](#) <[string](#)>

customActionStateList

Track state of each Custom Action

```
public static List<bool> customActionStateList
```

Field Value

[List](#) <[bool](#)>

reloadUUID

reloadUUID is intended to provide functionality around restarting the previous Run

```
public static bool reloadUUID
```

Field Value

[bool](#)

Methods

abortRun(ref string, ref string)

This method processes Abort Action Requests from the RabbitMQ Server

```
public static string abortRun(ref string service_uuid, ref string action)
```

Parameters

service_uuid [string](#)

action [string](#)

Returns

[string](#)

callCustomAction(ref string, ref string)

This method processes Custom Action Requests from the RabbitMQ Server

```
public static string callCustomAction(ref string service_uuid, ref string action)
```

Parameters

service_uuid [string](#)

action [string](#)

Returns

[string](#)

closeQueue()

This method is used to close the RabbitMQ Queue assigned to your test framework

```
public static void closeQueue()
```

downloadTestScript(string)

This method will be used to receive files from the CAST Server

```
public static void downloadTestScript(string service_uuid)
```

Parameters

service_uuid [string](#)

pauseRun(ref string, ref string)

This method processes Pause Action Requests from the RabbitMQ Server

```
public static string pauseRun(ref string service_uuid, ref string action)
```

Parameters

service_uuid [string](#)

action [string](#)

Returns

[string](#)

registerAction(string, string, bool, bool, bool, string)

This method is used to register custom actions

```
public static Task<string> registerAction(string actionName, string actionDescription,  
bool hideBeforeStart, bool hideAfterStart, bool hideAfterComplete, string actionIcon = "fa  
fa-check")
```

Parameters

actionName [string](#)

actionDescription [string](#)

hideBeforeStart [bool](#)

hideAfterStart [bool](#)

hideAfterComplete [bool](#)

actionIcon [string](#)

Returns

[Task](#) <[string](#)>

resumeRun(ref string, ref string)

This method processes Resume Action Requests from the RabbitMQ Server

```
public static string resumeRun(ref string service_uuid, ref string action)
```

Parameters

service_uuid [string](#)

action [string](#)

Returns

[string](#)

startRun(ref string, ref string)

This method processes Start Action Requests from the RabbitMQ Server

```
public static string startRun(ref string service_uuid, ref string action)
```

Parameters

service_uuid [string](#)

action [string](#)

Returns

[string](#)

startService()

Setup and register the CAST Client environment and listen for Action requests. This method gets called when the DLL is loaded

```
public static void startService()
```


stopService()

This method will update the CAST Service when the run completes

```
public static void stopService()
```

updateFrameworkFunctionality(bool, bool, bool, bool, bool, bool, bool, string, string, string, string, string)

This method is used to register your framework within the CAST Server

```
public static void updateFrameworkFunctionality(bool startEnabled, bool stopEnabled, bool pauseEnabled, bool resumeEnabled, bool abortEnabled, bool restartEnabled, bool uploadResultEnabled, string frameworkName, string filterOnGroup, string filterOnOwner, string filterOnLocation, string filterOnKeyword = null)
```

Parameters

startEnabled [bool](#) 

stopEnabled [bool](#) 

pauseEnabled [bool](#) 

resumeEnabled [bool](#) 

abortEnabled [bool](#) 

restartEnabled [bool](#) 

uploadResultEnabled [bool](#) 

frameworkName [string](#) 

filterOnGroup [string](#) 

filterOnOwner [string](#) 

filterOnLocation [string](#) 

filterOnKeyword [string](#) 

updateResult(string)

This method is used to update data on the CAST Server during your run

```
public static void updateResult(string result)
```

Parameters

result [string](#)

updateState(string, string)

This method is used to update CAST with the current state of your framework

```
public static Task<string> updateState(string state, string color = "black")
```

Parameters

state [string](#)

color [string](#)

Returns

[Task](#) <[string](#)>

uploadFile(string, string, bool)

This method is used to upload Zipped files to the CAST File Storage Service. Note that there is a 10mb size limit on the file

```
public static void uploadFile(string pathReference, string fileName, bool cleanupExistingZip  
= true)
```

Parameters

pathReference [string](#)

fileName [string](#)

cleanupExistingZip [bool](#)

uploadOutputFolder(string, string, bool)

This method is used to upload the contents of the output folder to the CAST File Storage Service

```
public static void uploadOutputFolder(string pathReference, string workingDirectory, bool  
cleanupZip = true)
```

Parameters

pathReference [string](#)

workingDirectory [string](#)

cleanupZip [bool](#)