

# Runbook: AGPH Data Integrity Extract

| Item                   | Value                                                                                                                                  |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Script                 | <code>Export-AgphData.ps1</code>                                                                                                       |
| Purpose                | Extract HYP and MCH records from AGPHPROD to pipe-delimited files and copy them to the SharePoint <i>Data integrity reports</i> folder |
| Database               | Oracle, host <code>10.153.128.14</code> , port <code>1526</code> , SID <code>AGPHPROD</code>                                           |
| Output                 | <code>HYP_yyyyMMdd.csv</code> , <code>MCH_yyyyMMdd.csv</code>                                                                          |
| SharePoint destination | <a href="#">Tremblant Data integrity reports &gt; Documents partagés &gt; Data integrity reports</a>                                   |
| Runtime                | Windows PowerShell 5.1                                                                                                                 |
| Typical volume         | HYP ≈ 41,200 rows; MCH ≈ 13,300 rows (1 Oct 2026)                                                                                      |

## 1. What the script does

| Step | Action                                                                                                                             |
|------|------------------------------------------------------------------------------------------------------------------------------------|
| 1    | Loads the Oracle driver ( <code>Oracle.ManagedDataAccess.dll</code> ) from the script folder                                       |
| 2    | Connects to <code>10.153.128.14:1526/AGPHPROD</code> using the supplied credential                                                 |
| 3    | Runs the HYP query and writes <code>HYP_yyyyMMdd.csv</code>                                                                        |
| 4    | Runs the MCH query and writes <code>MCH_yyyyMMdd.csv</code>                                                                        |
| 5    | Prints the row count and path for each file                                                                                        |
| 6    | Asks <b>Copy these files to SharePoint?</b> (default <b>No</b> )                                                                   |
| 7    | On <b>Yes</b> : copies both files to the OneDrive-synced SharePoint folder. It asks before overwriting a file that already exists. |

### Queries

|                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>-- HYP SELECT HYP003_NO_PRET, DGA003_NO_DOSSIER, HYP006_STATUT, HYP054_NO_PRET_SEQ, HYP023_CMPT_DEB FROM AGPH_SYST.HYP h WHERE HYP054_NO_PRET_SEQ = 0  -- MCH SELECT MCH003_NO_MARGE, DGA003_NO_DOSSIER, MCH004_NO_MARGE_SEQ, MCH016_STATUT FROM AGPH_SYST.MCH m WHERE MCH004_NO_MARGE_SEQ = 0</pre> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### File format

| Property   | Value               |
|------------|---------------------|
| Delimiter  | Pipe <code> </code> |
| Header row | None                |

| Property    | Value                                           |
|-------------|-------------------------------------------------|
| Encoding    | UTF-8, no BOM                                   |
| Line ending | CRLF (Windows)                                  |
| NULL values | Empty field, e.g. 123  A                        |
| Numbers     | Invariant culture ( . as the decimal separator) |

## 2. Prerequisites

| # | Requirement                                                                                          | How to check                                                                                                        |
|---|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| 1 | Windows PowerShell 5.1                                                                               | <code>\$PSVersionTable.PSVersion</code>                                                                             |
| 2 | Network access to 10.153.128.14 on port 1526                                                         | <code>Test-NetConnection 10.153.128.14 -Port 1526</code> , which should return <code>TcpTestSucceeded : True</code> |
| 3 | Oracle account with <code>SELECT</code> on <code>AGPH_SYST.HYP</code> and <code>AGPH_SYST.MCH</code> | The same login works in SQL Developer                                                                               |
| 4 | <code>Oracle.ManagedDataAccess.dll</code> <b>version 19.18.0</b> in the same folder as the script    | See section 3.1                                                                                                     |
| 5 | SharePoint library synced through OneDrive (needed only for the copy step)                           | See section 3.3                                                                                                     |

## 3. One-time setup

Use a **new** PowerShell window for every step below.

### 3.1 Install the Oracle driver (19.18.0)

```
cd $env:USERPROFILE\Downloads
[Net.ServicePointManager]::SecurityProtocol = [Net.SecurityProtocolType]::Tls12
Invoke-WebRequest https://www.nuget.org/api/v2/package/Oracle.ManagedDataAccess/19.18.0 -OutFile
odp.zip
Expand-Archive odp.zip -DestinationPath odp -Force
Copy-Item .\odp\lib\net40\Oracle.ManagedDataAccess.dll .
Unblock-File .\Oracle.ManagedDataAccess.dll
Unblock-File .\Export-AgphData.ps1
```

**Use 19.18.0, not 23.x.** Version 23.x needs six extra .NET files that aren't on a standard Windows PC. Versions 19.24 and later need two or three. If nuget.org is blocked, download the `.nupkg` file in a browser, rename it to `.zip`, then continue from `Expand-Archive`.

## 3.2 Save the Oracle credential

```
Get-Credential -UserName <oracle_user> -Message "AGPHPROD password" |  
Export-Clixml C:\Users\<you>\Downloads\agph.cred
```

| Rule                                                        | Reason                                                                       |
|-------------------------------------------------------------|------------------------------------------------------------------------------|
| Create the file as the Windows user who will run the script | Windows encrypts the file so only that user, on that machine, can decrypt it |
| Recreate it whenever the Oracle password changes            | Otherwise you get ORA-01017                                                  |
| Never store the password in plain text                      | Bank security policy                                                         |

## 3.3 Sync the SharePoint folder

1. Open the [Data integrity reports](#) folder in a browser.
2. Click **Sync** (or **Add shortcut to My files**).
3. In File Explorer, confirm that a local **Data integrity reports** folder appears, usually under `C:\Users\<you>\Banque Laurentienne\...` or `OneDrive - Banque Laurentienne\...`.
4. (Optional) Shift + right-click the folder, choose **Copy as path**, and keep the path for `-SharePointSyncFolder`.

## 4. Run procedure

### 4.1 Standard run (interactive)

```
cd $env:USERPROFILE\Downloads  
.\Export-AgphData.ps1 -Credential (Import-Clixml .\agph.cred) -OutputDir .\Extracts
```

Expected output:

```
Connected to 10.153.128.14:1526/AGPHPROD  
HYP: 41,224 rows -> C:\Users\<you>\Downloads\Extracts\HYP_20261001.csv  
MCH: 13,276 rows -> C:\Users\<you>\Downloads\Extracts\MCH_20261001.csv  
  
SharePoint  
Copy these files to SharePoint 'Data integrity reports'?  
  HYP_20261001.csv  
  MCH_20261001.csv  
[Y] Yes [N] No [?] Help (default is "N"): Y  
Copied -> ...Data integrity reports\HYP_20261001.csv  
Copied -> ...Data integrity reports\MCH_20261001.csv  
OneDrive will upload the files to SharePoint in the background.
```

## 4.2 With an explicit SharePoint folder

```
.\Export-AgphData.ps1 -Credential (Import-Clixml .\agph.cred) -OutputDir .\Extracts `
    -SharePointSyncFolder "C:\Users\<you>\...\Data integrity reports"
```

## 4.3 Unattended or scheduled run (no prompt, no copy)

Task Scheduler action. Program: `powershell.exe` . Arguments:

```
-NoProfile -ExecutionPolicy Bypass -Command "& 'C:\Scripts\Export-AgphData.ps1' -Credential (Import-Clixml 'C:\Scripts\agph.cred') -OutputDir 'C:\Scripts\Extracts' -SkipUpload; exit $LASTEXITCODE"
```

Use `-Command`, not `-File`. With `-File`, PowerShell passes arguments as plain text, so `(Import-Clixml ...)` is never run and the credential fails. Run the task as the same Windows account that created the `.cred` file.

## 4.4 Parameters

| Parameter                          | Default                                                         | Use                                                                  |
|------------------------------------|-----------------------------------------------------------------|----------------------------------------------------------------------|
| <code>-Credential</code>           | <i>(prompt)</i>                                                 | <code>(Import-Clixml &lt;path&gt;.cred)</code>                       |
| <code>-UserName</code>             | <i>(prompt)</i>                                                 | Prompts for the password only                                        |
| <code>-OutputDir</code>            | Current folder                                                  | Where the CSV files are written; created if missing                  |
| <code>-DbHost</code>               | <code>10.153.128.14</code>                                      | Database host                                                        |
| <code>-Port</code>                 | <code>1526</code>                                               | Listener port                                                        |
| <code>-Sid</code>                  | <code>AGPHPROD</code>                                           | SID, or the service name when used with <code>-UseServiceName</code> |
| <code>-UseServiceName</code>       | Off                                                             | Connect with <code>SERVICE_NAME</code> instead of <code>SID</code>   |
| <code>-DllPath</code>              | <code>&lt;script folder&gt;\Oracle.ManagedDataAccess.dll</code> | Driver location                                                      |
| <code>-SharePointSyncFolder</code> | Auto-detected under <code>%USERPROFILE%</code>                  | Local synced <i>Data integrity reports</i> folder                    |
| <code>-SkipUpload</code>           | Off                                                             | Skips the SharePoint prompt and copy                                 |
| <code>-FetchSizeMB</code>          | <code>16</code>                                                 | Oracle fetch buffer size                                             |

## 5. Post-run verification

| Check       | Command or action                                                    | Pass criteria     |
|-------------|----------------------------------------------------------------------|-------------------|
| Files exist | <code>Get-ChildItem .\Extracts\*_\$(Get-Date -f yyyyMMdd).csv</code> | 2 files, size > 0 |

| Check      | Command or action                                                                  | Pass criteria                                                                                     |
|------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Format     | <code>Get-Content .\Extracts\HYP_\$(Get-Date -f yyyyMMdd).csv -TotalCount 3</code> | Pipe-delimited, no header                                                                         |
| Row count  | <code>(Get-Content .\Extracts\HYP_\$(Get-Date -f yyyyMMdd).csv).Count</code>       | Matches <code>SELECT COUNT(*) ...</code> with the same <code>WHERE</code> clause in SQL Developer |
| Volume     | Compare with the previous run                                                      | Within the normal range (see the summary table at the top)                                        |
| SharePoint | Open the SharePoint folder in a browser                                            | Both files appear with today's date; the OneDrive icon shows a green check                        |

## 6. Exit codes

| Code | Meaning                                                                                                 |
|------|---------------------------------------------------------------------------------------------------------|
| 0    | Export finished (copy done, declined, or skipped)                                                       |
| 1    | Failed. The error is printed, e.g. <code>Export failed: ORA-...</code> , a missing DLL, or a copy error |

## 7. Troubleshooting

| Symptom                                                                          | Cause                                                                      | Fix                                                                                                                 |
|----------------------------------------------------------------------------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Oracle.ManagedDataAccess.dll not found at ...                                    | Driver missing from the script folder                                      | Follow section 3.1, or pass <code>-DllPath</code>                                                                   |
| Add-Type : Unable to load one or more of the requested types                     | Older script version loading a 23.x driver                                 | Use the current script and driver 19.18.0                                                                           |
| Could not load file or assembly ... System.Text.Json (or similar)                | 23.x or 19.24+ driver in use                                               | Replace it with 19.18.0 (section 3.1)                                                                               |
| Copy-Item : The process cannot access the file ... being used by another process | The DLL is loaded in the current PowerShell window                         | Close <b>all</b> PowerShell windows, open a new one, retry                                                          |
| NuGet\Install-Package : The module 'NuGet' could not be loaded                   | That command works only in Visual Studio                                   | Use the <code>Invoke-WebRequest</code> steps in section 3.1                                                         |
| Get-Credential prompts for Message:                                              | PowerShell needs <code>-Message</code> when <code>-UserName</code> is used | Add <code>-Message "AGPHPROD password"</code> , or type any text                                                    |
| ORA-12505: listener does not currently know of SID                               | Wrong host, or the name is a service name rather than a SID                | Confirm host <code>10.153.128.14</code> (not <code>172.20.3.16</code> ); otherwise try <code>-UseServiceName</code> |
| ORA-12514: listener does not know of service                                     | Wrong service name                                                         | Get the exact name from SQL Developer, <code>tnsnames.ora</code> , or the DBA                                       |
| ORA-12170 / ORA-12541 / connection timeout                                       | Network or firewall                                                        | <code>Test-NetConnection 10.153.128.14 -Port 1526</code> ; check VPN; raise a firewall request                      |

| Symptom                                                         | Cause                                               | Fix                                                                                              |
|-----------------------------------------------------------------|-----------------------------------------------------|--------------------------------------------------------------------------------------------------|
| ORA-01017: invalid username/password                            | Wrong or expired password                           | Recreate the .cred file (section 3.2)                                                            |
| ORA-28000: account is locked                                    | Account locked                                      | Ask the DBA to unlock it                                                                         |
| ORA-00942: table or view does not exist                         | No grant on AGPH_SYST.HYP or MCH                    | Ask the DBA for SELECT access                                                                    |
| Import-Clixml : Key not valid for use in specified state        | .cred file created by another user or on another PC | Recreate it as the account running the script                                                    |
| Invalid -SharePointSyncFolder path / Illegal characters in path | Placeholder (e.g. <library>) or a typo in the path  | Use <b>Copy as path</b> on the real synced folder (section 3.3)                                  |
| Synced SharePoint folder not found, then the browser opens      | Library not synced on this PC                       | Sync it (section 3.3), or drag the files into the browser window that opens                      |
| ... cannot be loaded because running scripts is disabled        | Execution policy                                    | Unblock-File .\Export-AgphData.ps1, or run with powershell.exe -ExecutionPolicy Bypass -File ... |
| Files are in Downloads, not Extracts                            | -OutputDir not supplied                             | Add -OutputDir .\Extracts                                                                        |
| Row count is zero or far below normal                           | Data issue or wrong environment                     | Re-run the query in SQL Developer; escalate to the data owner before you upload                  |

## 8. Security and housekeeping

| Item           | Guidance                                                                                         |
|----------------|--------------------------------------------------------------------------------------------------|
| Credentials    | Keep them only in the encrypted .cred file; never in the script, command history, or email       |
| Extract files  | They contain loan and account identifiers. Store them only on bank-managed drives and SharePoint |
| Local copies   | Delete old files in Extracts after you confirm the SharePoint upload, per the retention policy   |
| Script changes | Keep the script under version control ( kso1o13/fscpr d ); test changes before production use    |

## 9. Contacts and escalation

| Issue                                     | Contact                                            |
|-------------------------------------------|----------------------------------------------------|
| Database access, account lock, grants     | DBA team — TBD                                     |
| Network or firewall to 10.153.128.14:1526 | Network / Infrastructure — TBD                     |
| SharePoint site access                    | Site owner, Tremblant Data integrity reports — TBD |
| Script defects                            | Application Development — TBD                      |

## 10. Change log

| Date       | Change                                                                                  |
|------------|-----------------------------------------------------------------------------------------|
| 2026-10-01 | Initial version: Oracle extract to pipe-delimited files                                 |
| 2026-10-01 | Driver now loaded with <code>Assembly.LoadFrom</code> ; standardised on ODP.NET 19.18.0 |
| 2026-10-01 | Default host corrected to <code>10.153.128.14</code>                                    |
| 2026-10-01 | Added the SharePoint copy prompt (OneDrive sync)                                        |
| 2026-10-01 | An invalid SharePoint path is handled without crashing; <code>-LiteralPath</code> used  |