

Lecture 9

Functions in MIPS (II)

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Objectives for this lecture

- Function calling.
- To be able to **access** function **arguments** in MIPS
- To understand the steps for **function return**
- To be able to implement function return in MIPS

Function calling convention

These **steps** must be performed **every time** a function starts:

1. Save temporary registers
2. Save arguments
3. Call function with **jal** instruction
4. Save **\$ra** register
5. Save **\$fp** register
6. Update **\$fp**
7. Allocate local variables

Table 4: **Function calling convention**

On function call:

Caller: saves temporary registers on stack passes arguments on stack calls function using <code>jal fn_label</code>	Callee: saves <code>\$ra</code> and <code>\$fp</code> on stack copies <code>\$sp</code> to <code>\$fp</code> allocates local variables on stack
---	---

On function return:

Callee: sets <code>\$v0</code> to return value clears local variables off stack restores saved <code>\$fp</code> and <code>\$ra</code> off stack returns to caller with <code>jr \$ra</code>	Caller: clears arguments off stack restores temporary registers off stack uses return value in <code>\$v0</code>
---	--

power.py


```
def main():  
    base = 0  
    exp = 0  
    result = 0  
  
    base = int(input())  
    exp = int(input())  
  
    result = power(base, exp)  
    print(result)  
  
def power(b, e):  
    result = 1  
  
    while e > 0:  
        result *= b  
        e -= 1  
    return result  
  
main()
```

two *results*, but they are different.... local variables

power.py

```
def main():  
    base = 0  
    exp = 0  
    result = 0  
  
    base = int(input())  
    exp = int(input())  
    → result = power(base, exp)  
    print(result)  
  
def power(b, e):  
    result = 1  
  
    while e > 0:  
        result *= b  
        e -= 1  
    return result  
  
main()
```

Assume user has entered **3** for **base** and **4** for **exp**



power.py

```
def main():
    base = 0
    exp = 0
    result = 0

    base = int(input())
    exp = int(input())
    → result = power(base, exp)
    print(result)

def power(b, e):
    result = 1

    while e > 0:
        result *= b
        e -= 1
    return result

main()
```

```
.text
main:
    # 3 * 4 = 12 bytes local
    addi $fp, $sp, 0
    addi $sp, $sp, -12

    # Initialize locals
    sw $0, -12($fp)
    sw $0, -8($fp)
    sw $0, -4($fp)


    addi $v0, $0, 5
    syscall
    sw $v0, -12($fp) # base

    addi $v0, $0, 5
    syscall
    sw $v0, -8($fp) # exp
```

Caller

Step 1: Save temporary registers by pushing their values on stack

(not needed in this program)



Caller

Step 2: Push function arguments onto the stack

```
def power(b, e):
```

\$sp → base

exp

result

3

4

0

0x7FFF038C

0x7FFF0390

0x7FFF0394

0x7FFF0398

0x7FFF039C

\$fp →

0x7FFF03A0

Caller

Note the **offsets**.

b at 0(\$sp)

e at 4(\$sp)

\$sp →

arg 1 (b)

arg 2 (e)

base

exp

result

\$fp →

	3	0x7FFF038C
	4	0x7FFF0390
	3	0x7FFF0394
	4	0x7FFF0398
	0	0x7FFF039C
		0x7FFF03A0

Step 2: Push function arguments onto the stack

```
def power(b, e):
```

Caller

```
.  
# push 2 * 4 = 8 bytes  
# of arguments  
addi $sp, $sp, -8  
  
# arg 1 = base  
lw $t0, -12($fp) # base  
sw $t0, 0($sp)  # arg 1  
  
# arg 2 = exp  
lw $t0, -8($fp) # exp  
sw $t0, 4($sp)  # arg 2
```

\$sp → arg 1 (b)

arg 2 (e)

base

exp

result

\$fp →


	3	0x7FFF038C
	4	0x7FFF0390
	3	0x7FFF0394
	4	0x7FFF0398
	0	0x7FFF039C
		0x7FFF03A0

Caller

jal power

Step 3: Call function with **jal**

(no visible effect on stack)



```

def main():
    base = 0
    exp = 0
    result = 0

    base = int(input())
    exp = int(input())

    result = power(base, exp)
    print(result)

def power(b, e):
    result = 1

    while e > 0:
        result *= b
        e -= 1
    return result

main()

```

\$sp → arg 1 (b)

arg 2 (e)

base

exp

result


\$fp →

	3	0x7FFF038C
	4	0x7FFF0390
	3	0x7FFF0394
	4	0x7FFF0398
	0	0x7FFF039C
		0x7FFF03A0

Callee

Step 4 and 5:
Save **\$ra** and **\$fp**

(can do both
steps at once)



Callee

Saved **\$sp**
contains address of
other location in
stack

Step 4 and 5:
Save **\$ra** and **\$fp**

(can do both
steps at once)

\$sp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

\$fp →

	0x7FFF0380
0x7FFF03A0	0x7FFF0384
0x0040005C	0x7FFF0388
3	0x7FFF038C
4	0x7FFF0390
3	0x7FFF0394
4	0x7FFF0398
0	0x7FFF039C
	0x7FFF03A0

Callee

\$sp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

\$fp →

		0x7FFF0380
0x7FFF03A0		0x7FFF0384
0x0040005C		0x7FFF0388
3		0x7FFF038C
4		0x7FFF0390
3		0x7FFF0394
4		0x7FFF0398
0		0x7FFF039C
		0x7FFF03A0

power: **# Save \$ra and \$fp**

addi \$sp, \$sp, -8

sw \$ra, 4(\$sp)


sw \$fp, 0(\$sp)

Callee

```
# Copy $sp to $fp  
addi $fp, $sp, 0
```

Step 6:
Save **\$sp** into **\$fp**

now main's local
variables are
inaccessible



Callee

\$fp → **\$sp** → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

		0x7FFF0380
	0x7FFF03A0	0x7FFF0384
	0x0040005C	0x7FFF0388
	3	0x7FFF038C
	4	0x7FFF0390
	3	0x7FFF0394
	4	0x7FFF0398
	0	0x7FFF039C
		0x7FFF03A0

Step 7:
allocate local
variables

in this function,
one local variable **result**

Callee

Allocate local variables
1 * 4 = 4 bytes.
addi \$sp, \$sp, -4

Initialize locals.
addi \$t0, \$0, 1
sw \$t0, -4(\$fp) # result

Step 7:
allocate local
variables

in this function,
one local variable **result**

\$sp → result
\$fp → saved \$fp
saved \$ra
arg 1 (b)
arg 2 (e)

base
exp
result

1	0x7FFF0380
0x7FFF03A0	0x7FFF0384
0x0040005C	0x7FFF0388
3	0x7FFF038C
4	0x7FFF0390
3	0x7FFF0394
4	0x7FFF0398
0	0x7FFF039C
	0x7FFF03A0

\$fp always points
to an old **saved**
copy of \$fp

\$sp → result

\$fp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

1	0x7FFF0380
0x7FFF03A0	0x7FFF0384
0x0040005C	0x7FFF0388
3	0x7FFF038C
4	0x7FFF0390
3	0x7FFF0394
4	0x7FFF0398
0	0x7FFF039C
	0x7FFF03A0

Frame Pointers

Stack frames

data on the stack
associated with a function



\$sp → result
\$fp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

1	0x7FFF0380
0x7FFF03A0	0x7FFF0384
0x0040005C	0x7FFF0388
3	0x7FFF038C
4	0x7FFF0390
3	0x7FFF0394
4	0x7FFF0398
0	0x7FFF039C
	0x7FFF03A0

Calling

- Function calling
 - **jal** and **jr** instructions
- Function calling convention:
for making a function call
- Structure of stack: stack frames


Function returning

power.py

```
def main():  
    base = 0  
    exp = 0  
    result = 0  
  
    base = int(input())  
    exp = int(input())  
  
    result = power(base, exp)  
    print(result)  
  
def power(b, e):  
    result = 1  
  
    while e > 0:  
        result *= b  
        e -= 1  
    return result  
  
main()
```



```
def power(b, e):  
    result = 1  
  
    while e > 0:  
        result *= b  
        e -= 1  
    return result
```



```
power: # Save $ra and $fp  
    addi $sp, $sp, -8  
    sw $ra, 4($sp)  
    sw $fp, 0($sp)
```

```
# copy $sp into $fp  
addi $fp, $sp, 0
```

```
# Allocate local variables  
# 1 * 4 = 4 bytes.  
addi $sp, $sp, -4  
  
# Initialize locals.  
addi $t0, $0, 1  
sw $t0, -4($fp) # result
```

What next?

Example: callee

```
def power(b, e):  
    result = 1  
  
    while e > 0:  
        result *= b  
        e -= 1  
    return result
```

```
# Loop  
loop: # Stop if !(e > 0)  
      lw $t0, 12($fp) # e  
      slt $t0, $0, $t0  
      beq $t0, 0, end
```


```
# result = result * b  
lw $t0, -4($fp) # result  
lw $t1, 8($fp) # b  
mult $t0, $t1  
mflo $t0  
sw $t0, -4($fp) # result
```

```
# e = e - 1  
lw $t0, 12($fp) # e  
addi $t0, $t0, -1  
sw $t0, 12($fp) # e
```


```
# Repeat loop.  
j loop
```

```
end: # Now ready to return.  
# Continued ...
```


Stack frames



Local variables



Function parameters



\$sp → **result**

\$fp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

1	0x7FFF0380
0x7FFF03A0	0x7FFF0384
0x0040005C	0x7FFF0388
3	0x7FFF038C
4	0x7FFF0390
3	0x7FFF0394
4	0x7FFF0398
0	0x7FFF039C
	0x7FFF03A0

Loop

loop: **# Stop if !(e > 0)**

lw \$t0, 12(\$fp) **# e**

slt \$t0, \$0, \$t0

beq \$t0, 0, end

result = result * b

lw \$t0, -4(\$fp) **# result**

lw \$t1, 8(\$fp) **# b**

mult \$t0, \$t1

mflo \$t0

sw \$t0, -4(\$fp) **# result**

e = e - 1

lw \$t0, 12(\$fp) **# e**

addi \$t0, \$t0, -1

sw \$t0, 12(\$fp) **# e**

Repeat loop.

j loop

end: **# Now ready to return.**

Continued ...

\$sp → **result**

\$fp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

81

0x7FFF03A0

0x0040005C

3

0

3

4

0

0x7FFF0380

0x7FFF0384

0x7FFF0388

0x7FFF038C

0x7FFF0390

0x7FFF0394

0x7FFF0398

0x7FFF039C

0x7FFF03A0

Loop

loop: **# Stop if !(e > 0)**

lw \$t0, 12(\$fp) **# e**

slt \$t0, \$0, \$t0

beq \$t0, 0, end

result = result * b

lw \$t0, -4(\$fp) **# result**

lw \$t1, 8(\$fp) **# b**

mult \$t0, \$t1

mflo \$t0

sw \$t0, -4(\$fp) **# result**

e = e - 1

lw \$t0, 12(\$fp) **# e**

addi \$t0, \$t0, -1

sw \$t0, 12(\$fp) **# e**

Repeat loop.

j loop

end: **# Now ready to return.**

Continued ...

Function return

- When returning from a function, **the stack must be restored to its initial state**
- This is achieved by undoing the steps made during calling of function, in **reverse order**
- **Return first**, in **\$v0** (if necessary)... then reverse convention

Calling:

1. Save temporary registers
2. Save arguments
3. Call function with **jal** instruction
4. Save **\$ra** register
5. Save **\$fp** register
6. Update **\$fp**
7. Allocate local variables

Returning:

1. Set **\$v0** to return value
2. Deallocate local variables
3. Restore **\$fp**
4. Restore **\$ra**
5. Return with **jr** instruction
6. Deallocate arguments
7. Restore temporary registers

Table 4: **Function calling convention**

On function call:

Caller: saves temporary registers on stack passes arguments on stack calls function using <code>jal fn_label</code>	Callee: saves <code>\$ra</code> and <code>\$fp</code> on stack copies <code>\$sp</code> to <code>\$fp</code> allocates local variables on stack
---	---

On function return:

Callee: sets <code>\$v0</code> to return value clears local variables off stack restores saved <code>\$fp</code> and <code>\$ra</code> off stack returns to caller with <code>jr \$ra</code>	Caller: clears arguments off stack restores temporary registers off stack uses return value in <code>\$v0</code>
---	--

```
# Return result in $v0  
lw $v0, -4($fp) # result
```

\$v0 = 81

Step 1: Put return value in register **\$v0**

(no visible effect on the stack)

\$sp → **result**

\$fp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result


81	0x7FFF0380
0x7FFF03A0	0x7FFF0384
0x0040005C	0x7FFF0388
3	0x7FFF038C
0	0x7FFF0390
3	0x7FFF0394
4	0x7FFF0398
0	0x7FFF039C
	0x7FFF03A0

Returning

Remove local var.
addi \$sp, \$sp, 4

Step 2: Deallocate local variables by popping allocated space off stack

(one local variable to be deleted)



\$sp → **\$fp** → saved \$fp

saved \$ra

Remove local var.
addi \$sp, \$sp, 4

Step 2: Deallocate local variables by popping allocated space off stack

(one local variable to be deleted)


arg 1 (b)

arg 2 (e)

base

exp

result



\$sp → **\$fp** → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)

base

exp

result

Restore \$fp and \$ra

lw \$fp, 0(\$sp)

lw \$ra, 4(\$sp)

addi \$sp, \$sp, 8

Step 3 and 4: Restore saved values of **\$fp** and **\$ra** by popping of stack

(can do both steps at once)

		0x7FFF0380
	0x7FFF03A0	0x7FFF0384
	0x0040005C	0x7FFF0388
	3	0x7FFF038C
	0	0x7FFF0390
	3	0x7FFF0394
	4	0x7FFF0398
	0	0x7FFF039C
		0x7FFF03A0

Callee

Returning

\$fp = 0x7FFF03A0
\$ra = 0x0040005C

\$sp → saved \$fp

saved \$ra

arg 1 (b)

arg 2 (e)


base

exp

result

\$fp →

```
# Restore $fp and $ra
lw $fp, 0($sp)
lw $ra, 4($sp)
addi $sp, $sp, 8
```



\$fp points back to
main's stack frame

```
# Restore $fp and $ra
lw $fp, 0($sp)
lw $ra, 4($sp)
addi $sp, $sp, 8
```

Step 3 and 4: Restore
saved values of **\$fp**
and **\$ra** by popping
of stack

(can do both steps
at once)

\$sp

→ arg 1 (b)

arg 2 (e)


base

exp

result

\$fp

→



Return to caller.
jr \$ra

Step 5: Return by
executing **jr \$ra**

(nothing visible
on the stack)

\$sp → arg 1 (b)


arg 2 (e)

base

exp

result

\$fp →



power.py


```
def main():  
    base = 0  
    exp = 0  
    result = 0  
  
    base = int(input())  
    exp = int(input())  
  
    result = power(base, exp)  
    print(result)  
  
def power(b, e):  
    result = 1  
  
    while e > 0:  
        result *= b  
        e -= 1  
    return result  
  
main()
```

Caller

Remove arguments, they
are no longer needed.
2 * 4 = 8 bytes.
addi \$sp, \$sp, 8

Step 6: Clear function arguments by popping them off the stack

(nothing visible on the stack)



Caller

b and **e** are no longer needed

Remove arguments, they
are no longer needed.
2 * 4 = 8 bytes.
addi \$sp, \$sp, 8

Step 6: Clear function arguments by popping them off the stack

(nothing visible on the stack)

\$sp →

arg 1 (b)


arg 2 (e)

base

exp

result

\$fp →



Caller

Step 7: Restore any saved temporary registers by popping value of the stack

(we did not have any)

\$sp →

base

exp

result

3

4

0

0x7FFF0380

0x7FFF0384

0x7FFF0388

0x7FFF038C

0x7FFF0390


0x7FFF0394

0x7FFF0398

0x7FFF039C

\$fp →

0x7FFF03A0



Caller

Store return value
in result.
sw \$v0, -4(\$fp) # result

\$v0 = 81

Use returned value
found in **\$v0**

store returned value
in a variable


\$sp →

base

exp

result

\$fp →



Caller

```
def main():  
    base = 0  
    exp = 0  
    result = 0  
  
    base = int(input())  
    exp = int(input())  
  
    result = power(base, exp)  
    print(result)
```

main stores return value
into local variable return

```
# Store return value  
# in result.  
sw $v0, -4($fp) # result
```

\$v0 = 81

Use returned value
found in **\$v0**

store returned value
in a variable


\$sp →

base

exp

result

\$fp →



**After call
stack is
in its
original state**

\$sp →

base

exp

result

3

4

81

0x7FFF0380

0x7FFF0384

0x7FFF0388

0x7FFF038C

0x7FFF0390


0x7FFF0394

0x7FFF0398

0x7FFF039C

\$fp →

0x7FFF03A0



Caller prep

Callee prep

Table 4: **Function calling convention**

On function call:

Caller:

saves temporary registers on stack
passes arguments on stack
calls function using `jal fn_label`

Callee:

saves `$ra` and `$fp` on stack
copies `$sp` to `$fp`
allocates local variables on stack

On function return:

Callee:

sets `$v0` to return value
clears local variables off stack
restores saved `$fp` and `$ra` off stack
returns to caller with `jr $ra`

Caller:

clears arguments off stack
restores temporary registers off stack
uses return value in `$v0`

Callee clean-up

Caller clean up

Function calling convention

In summary, **caller**:

1. **saves** temporary registers by pushing their values on stack
2. **pushes** arguments on stack
3. calls the function with **jal** instruction

(function runs until it returns, then...)

4. clears function arguments by **popping** allocated space
5. **restores** saved temporary registers by popping their values off the stack
6. uses the return value found in **\$v0**

In summary, **callee:**

1. saves **\$ra** by pushing its value on stack
2. saves **\$fp** by pushing its value on stack
3. copies **\$sp** to **\$fp**
4. **allocates** local variables

(body of function goes here, then:)

5. chooses return value by setting register **\$v0**
6. **deallocates** local variables by popping allocated space
7. restores **\$fp** by popping its saved value
8. restores **\$ra** by popping its saved value
9. returns with **jr \$ra**

Going further

Official MIPS stack frame convention

- Doesn't use \$fp at all!
- Slightly more efficient than FIT1008 convention
- Can be generated by compilers
- Hard for humans to write/understand

Summary

- Accessing function parameters
- Returning from functions
- Function calling/returning convention