

Lecture 24

Recursive Sorting and Complexity

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Overview

- To review in more depth two different “divide and conquer” sorting algorithms:
 - **Merge Sort**
 - **Quick Sort**
- To be able to **implement** them and compare their efficiency for different classes of inputs

Divide and Conquer: **Sorting**

General Idea


```
def sort(array):  
    if len(array) > 1:  
        split(array, first_part, second_part)  
        sort(first_part)  
        sort(second_part)  
        combine(first_part, second_part)
```

- **Merge Sort** has a simple split and a elaborate combine
- **Quick Sort** has a elaborate split and a simple combine

Merge Sort

```
def merge_sort(array):  
    tmp = [None] * len(array)  
    start = 0  
    end = len(array)-1  
    merge_sort_aux(array, start, end, tmp)
```

the array start index end index temporary array



def merge_sort_aux(array, start, end, tmp):

The diagram consists of four labels at the top: 'the array', 'start index', 'end index', and 'temporary array'. Below each label is an arrow pointing down to a parameter in the function signature 'def merge_sort_aux(array, start, end, tmp):'. Specifically, an arrow points from 'the array' to 'array', from 'start index' to 'start', from 'end index' to 'end', and from 'temporary array' to 'tmp'.

Merge Sort

```
def merge_sort_aux(array, start, end, tmp):  
    if start < end: # 2 or more still to sort  
        mid = (start + end)//2
```

```
    # split into two halves
```

```
    merge_sort_aux(array, start, mid, tmp)
```

```
    merge_sort_aux(array, mid+1, end, tmp)
```

```
    # merge
```

```
    merge_arrays(array, start, mid, end, tmp)
```

sorted result



define what the “two lists” are

Merge Sort

```
def merge_sort_aux(array, start, end, tmp):  
    if start < end: # 2 or more still to sort  
        mid = (start + end)//2  
  
        # split into two halves  
        merge_sort_aux(array, start, mid, tmp)  
        merge_sort_aux(array, mid+1, end, tmp)  
  
        # merge  
        merge_arrays(array, start, mid, end, tmp)  
  
        # copy tmp back into the original  
        for i in range(start, end+1):  
            array[i] = tmp[i]
```


Merge

L:

3	5	15	28	30	32
---	---	----	----	----	----

i=6

R:

10	14	22	43	50
----	----	----	----	----

j=5

tmp:

3	5	10	14	15	22	28	30	32	43	50
---	---	----	----	----	----	----	----	----	----	----


```
def merge_arrays(array, start, mid, end, tmp):
```

```
def merge_arrays(array, start, mid, end, tmp):  
    i = start  
    j = mid+1
```

Set-up indices: i for the left, j for the right.

```
def merge_arrays(array, start, mid, end, tmp):  
    i = start  
    j = mid+1  
    for k in range(start, end+1):
```

```
def merge_arrays(array, start, mid, end, tmp):  
    i = start  
    j = mid+1  
    for k in range(start, end+1):
```

k loops through (relevant part of) tmp

```
def merge_arrays(array, start, mid, end, tmp):
```

```
    i = start
```

```
    j = mid+1
```

```
    for k in range(start, end+1):
```

```
        elif array[i] <= array[j]: # array[i] is the item to copy
```

```
            tmp[k] = array[i]
```

```
            i += 1
```

```
def merge_arrays(array, start, mid, end, tmp):
```

```
    i = start
```

```
    j = mid+1
```

```
    for k in range(start, end+1):
```

```
        elif array[i] <= array[j]: # array[i] is the item to copy
```

```
            tmp[k] = array[i]
```

```
            i += 1
```

```
        else:
```

```
            tmp[k] = array[j] # array[j] is the item to copy
```

```
            j += 1
```

```
def merge_arrays(array, start, mid, end, tmp):  
    i = start  
    j = mid+1  
    for k in range(start, end+1):  
        if i > mid: # left finished, copy right  
            tmp[k] = array[j]  
            j += 1  
  
        elif array[i] <= array[j]: # array[i] is the item to copy  
            tmp[k] = array[i]  
            i += 1  
        else:  
            tmp[k] = array[j] # array[j] is the item to copy  
            j += 1
```

```
def merge_arrays(array, start, mid, end, tmp):  
    i = start  
    j = mid+1  
    for k in range(start, end+1):  
        if i > mid: # left finished, copy right  
            tmp[k] = array[j]  
            j += 1  
        elif j > end: # right finished, copy left  
            tmp[k] = array[i]  
            i += 1  
        elif array[i] <= array[j]: # array[i] is the item to copy  
            tmp[k] = array[i]  
            i += 1  
        else:  
            tmp[k] = array[j] # array[j] is the item to copy  
            j += 1
```



Key idea for complexity of recursion:

- How many recursive calls do we make in each version?
- How much work do we do per call?


Merge Sort Analysis

- **Natural:** Typically the method that you would use when sorting a pile of books, CDs cards, etc.
- Most of the work is in the **merging**
- Uses more **space** than other sorts
- Close to optimal in number of comparisons. Good for languages where comparison is expensive.

Merge sort



splitting is $O(1)$



merging is $O(n)$

Total Running Time: $O(n \log n)$

height
is
 $O(\log n)$

height
is
 $O(\log n)$

Quicksort




Top-10 algorithms 20th century (SIAM)

Quick Sort

- **Partition** the list
- Sort the first part (recursively)
- Sort the second part (recursively)

Partition

- Choose an item in the list, called it the **pivot**.
- The **first part** consists of all those **items** which are **less than the pivot**.
- The **second part** consists of all those **items larger than or equal to the pivot (except the pivot)**.



- **Partition:** Elaborate, based on a pivot p .
- **Combination:** Simple append, pivot in the middle.

Example Partition

array:

5	89	35	14	24	15	37	13	20	7	70
---	----	----	----	----	----	----	----	----	---	----

start:0

end:10

Example Partition

array:

5	89	35	14	24	15	37	13	20	7	70
---	----	----	----	----	----	----	----	----	---	----

Randomly choose a pivot, which happens to be in the middle

Example Partition

array:

5	89	35	14	24	15	37	13	20	7	70
---	----	----	----	----	----	----	----	----	---	----

partition:

5	89	35	14	24	15	37	13	20	7	70
---	----	----	----	----	----	----	----	----	---	----

result

7	14	5	13	15	35	37	89	20	24	70
---	----	---	----	----	----	----	----	----	----	----



pivot position: 4

note that the pivot defines the boundaries

sort first half (using QS), sort second half (using QS)


Quicksort

```
def quick_sort(array):  
    start = 0  
    end = len(array)-1  
    quick_sort_aux(array, start, end)  
  
def quick_sort_aux(array, start, end):  
    if start < end:  
        boundary = partition(array, start, end)  
        quick_sort_aux(array, start, boundary-1)  
        quick_sort_aux(array, boundary+1, end)
```


sort second half




swap with first element



index increases if necessary




k always increases



Example Partition

randomly pick element in position 5




array:

5	89	35	14	24	15	37	13	20	7	70
---	----	----	----	----	----	----	----	----	---	----


15	89	35	14	24	5	37	13	20	7	70
----	----	----	----	----	---	----	----	----	---	----

Example Partition

index:4




$x < 15$



$x \geq 15$



After last swap, pivot is in the correct position

Example Partition






swap with first element




```
def swap(array, i, j):  
    array[i], array[j] = array[j], array[i]
```

```
def partition(array, start, end):  
    mid = (start+end)//2  
    pivot = array[mid]  
    swap(array, start, mid)  
    index = start  
    for k in range(start+1, end+1):  
        if array[k] < pivot:  
            index += 1  
            swap(array, k, index)  
    swap(array, start, index)  
    return index
```

Quicksort: Number of partitions depends on the pivot




Best case: The size of the problem is reduced by half with every partition

Worst case: The size of the problem is reduced by 1 with every partition

Quick sort's best case

partition is $O(n)$


height
is
 $O(\log n)$



Running time in the best case: $O(n \log n)$

Quick sort's worst case

partition is $O(n)$



Running time in the worst case: $O(n^2)$

Summary

	Best case	Worst case
Quicksort	$O(n \log n)$	$O(n^2)$
Mergesort	$O(n \log n)$	$O(n \log n)$

How common is quicksort's worst case?

Not too common if choosing a random pivot.

Summary

Divide and Conquer and Recursive Algorithms
(for sorting).

Merge Sort

- Easy: Split
- Elaborate: merge method

Quick Sort

- Elaborate split: partition method
- Easy combination