

Lecture 16

Lists and Sorted List (Array Implementation)

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Put everything together...
and implement some
Abstract Data Types

List ADT

- Sequence of items
- Possible **Operations**:
 - ➔ Add item
 - ➔ Remove item
 - ➔ Find item
 - ➔ Retrieve item
 - ➔ Next item
 - ➔ First item
 - ➔ Is last item
 - ➔ Is empty
 - ➔ Print

We already use one implementation of a List ADT

```
In [1]: 1 a_python_list = [1, 2, 3, 4]
```

create a list

```
In [2]: 1 type(a_python_list)
```

```
Out[2]: list
```

```
In [3]: 1 a_python_list.append(5)
```

add to a list

```
In [4]: 1 a_python_list
```

```
Out[4]: [1, 2, 3, 4, 5]
```

```
In [5]: 1 a_python_list.index(4)
```

```
Out[5]: 3
```

find item

```
In [6]: 1 a_python_list.index(0)
```

```
-----  
ValueError                                Traceback (most recent call last)  
<ipython-input-6-37cf3d11497f> in <module>()  
----> 1 a_python_list.index(0)
```

```
ValueError: 0 is not in list
```

and more...


Implementing your own List ADT

- How do we start? Easy:
 - Create a **new file** (called *my_list.py*)
 - Import the `build_array` function so that you can create arrays.
 - Add any **operations/methods** users may need to use.
- What operations?
 - **Create a list**, **access** an element, compute the **length**
 - Determine whether **is empty**
 - Determine whether it **has a given item**
 - Find the **position of an item** (if in)
 - **Add/delete** an item
 - **Delete/insert** the item in position *i*


Visualising lists implemented with arrays

- Consider a list defined:
 - Over an array of size 6
 - Currently with one element (Charles)

- We will visualise it like this:



Visual Clarity:
Arrow, **Colour**, Counter
(**count**) mean same
thing...




Invariant: count points to the first free position in the array


In other words: valid data appear in the $0..count-1$ positions

Empty vs Full

count: 0



count: 6



Creating a list

```
from referential_array import build_array
```

```
class List:
```

```
    def __init__(self, max_capacity):  
        assert max_capacity > 0, "Size should be positive"  
        self.array = build_array(max_capacity)  
        self.count = 0
```

So that we can
create the array

Instance variables

Simple methods

```
def length(self):  
    return self.count  
  
def is_empty(self):  
    return self.count == 0  
  
def is_full(self):  
    return self.count >= len(self.the_array)
```


Adding an element to a list

- **Input:**
 - List (in our case: array + count)
 - **Element to be added**
- **Output:**
 - List
 - Contains all original elements in the same order AND the input one (this is the *post-condition*)

Adding an element

Recall: count indicates the first empty position (if any)

Example: add "Ada"




Adding an element

Recall: count indicates the first empty position (if any)

Example: add "Ada"

Add the item at position *count*
Increment *count*

count: 2



Adding an element

- Algorithm: add item to the_array, then increment count
- Does it always work?
- We are assuming we can always add...
- What if it is full? What to do then?
 - One possibility: return **True** if we can, **False** otherwise
 - This changes the output AND the postcondition
 - Create a new larger array copy things over?
 - What does Python do with its own lists? lists are never full...

Function add

```
def add(self, new_item):  
    has_space_left = not self.is_full()  
    if has_space_left:  
        self.the_array[self.count] = new_item  
        self.count += 1  
    return has_space_left
```

What if this raises an Exception instead of returning a boolean?

Deleting an element from a list

- **Input:**
 - List (in our case: array + count)
 - **Position of the element to be deleted**
- **Output:**
 - List
 - Contains all original elements EXCEPT the deleted element
 - **Assume:** Remaining elements retain initial ordering.

Example: delete item in position 2

count: 5

the_array

Ada

Alan

Charles

Grace

Konrad

???

0


1

2

3

4

5



Example: delete item in position 2

count: 5

the_array

Ada

Alan

Charles

Grace

Konrad

???

0

1


2

3

4


5

Example: delete item in position 2




Move items appearing after the deleted item

Example: delete item in position 2



Move items appearing after the deleted item

Example: delete item in position 2



Move items appearing after the deleted item

Decrement count

```
def delete(self, index):  
    valid_index = index >= 0 and index < self.count  
    if (valid_index):  
        for i in range(index, self.count-1):  
            self.the_array[i] = self.the_array[i+1]  
        self.count -= 1  
    return valid_index
```

```
def print(self):  
    for i in range(self.count):  
        print(self.the_array[i], end=" ")
```

SortedList ADT

- Sequence of items in increasing order
- Possible Operations:
 - **Create** a list
 - **Add item** to the list
 - **Delete** an **item** at a given position from the list
 - Check whether the list **is empty**
 - Check whether the list **is full**
 - Get the **length** of the list.


```
from referential_array import build_array
```

```
class SortedList:
```

```
    def __init__(self, max_capacity):  
        if max_capacity <= 0:  
            raise ValueError("Size should be positive")  
        self.the_array = build_array(max_capacity)  
        self.count = 0
```

```
    def __len__(self):  
        return self.count
```

```
    def is_empty(self):  
        return self.count == 0
```


```
    def is_full(self):  
        return self.count >= len(self.the_array)
```

Adding an element to a sorted list

- **Sorted list:** Element at position i is \leq than that at position $i+1$
- **Input:**
 - Sorted list
 - `new_item` to be added
- **Output:**
 - Sorted list
 - **False** if the list was full; **True**, then the list contains all original elements in the same order together with the `new_item` (postcondition)
- **Note:**
 - the “Sorted” is also a pre/postcondition

Example: add "Alan"
to the sorted list.

count: 4



the_array

Ada

Charles

Grace

Konrad

???

???

0

1

2


3

4

5

Example: add "Alan"
to the sorted list.

count: 4




the_array

Ada	Charles	Grace	Konrad	???	???
0	1	2	3	4	5


If there is space, find the correct position

Example: add "Alan"
to the sorted list.




If there is space, find the correct position

Example: add "Alan"
to the sorted list.



If there is space, find the correct position
Make room by moving all to the right.

Example: add "Alan"
to the sorted list.




If there is space, find the correct position

Make room by moving all to the right.

Put item in position.

Example: add "Alan"
to the sorted list.




If there is space, find the correct position

Make room by moving all to the right.

Put item in position.

Example: add "Alan"
to the sorted list.




If there is space, find the correct position

Make room by moving all to the right.

Put item in position.

Update count

Example: add "Alan"
to the sorted list.



If there is space, find the correct position

Make room by moving all to the right.

Put item in position.

Update count

then **return True**

If the array has some space left:

find correct ***index*** at which to add item.

make room: move all items from **index** to **count-1** to the right

put item in position **index**.

increment **count**

return **True**.

else:

return **False**.

```
def add(self, item):  
    # do I have space?  
    has_space_left = not self.is_full()  
    # figure out position  
    if has_space_left:  
        # figure out position of the new item  
        position = 0  
        for i in range(self.count):  
            if self.array[i] < item:  
                position += 1  
            else:  
                break  
        # position is the place where the new guy goes  
        for i in range(self.count - 1, position - 1, -1):  
            # move item in position i to position i+1  
            self.array[i+1] = self.array[i]  
        # add new item  
        self.array[position] = item  
        self.count += 1  
    return has_space_left
```

Overloading operators

- Any class can **redefine** certain special operations:
- By simply defining the **associated method** inside the class

Operation	Class Method
str(obj)	__str__(self)
len(obj)	__len__(self)
item in obj	__contains__(self,item)
y = obj[ndx]	__getitem__(self,ndx)
obj[ndx] = value	__setitem__(self,ndx,value)
obj == rhs	Python checks whether the appropriate method is available to the object. If not defined , the built-in operation (if any) is used.
obj < rhs	
...	
obj + rhs	
...	

```
def length(self):
    return self.count
```

```
def is_empty(self):
    return self.count == 0
```

```
def is_full(self):
    return self.count >= len(self.the_array)
```

Operation	Class Method
str(obj)	__str__(self)
len(obj)	__len__(self)
item in obj	__contains__(self,item)
y = obj[ndx]	__getitem__(self,ndx)
obj[ndx] = value	__setitem__(self,ndx,value)
obj == rhs	__eq__(self,rhs)
obj < rhs	__lt__(self,rhs)
...	
obj + rhs	__add__(self,rhs)
...	

```
def __len__(self):
    return self.count
```

```
def is_empty(self):
    return len(self) == 0
```

```
def is_full(self):
    return len(self) >= len(self.the_array)
```

Operation	Class Method
str(obj)	__str__(self)
len(obj)	__len__(self)
item in obj	__contains__(self,item)
y = obj[ndx]	__getitem__(self,ndx)
obj[ndx] = value	__setitem__(self,ndx,value)
obj == rhs	__eq__(self,rhs)
obj < rhs	__lt__(self,rhs)
...	
obj + rhs	__add__(self,rhs)
...	

Operation	Class Method
str(obj)	__str__(self)
len(obj)	__len__(self)
item in obj	__contains__(self,item)
y = obj[ndx]	__getitem__(self,ndx)
obj[ndx] = value	__setitem__(self,ndx,value)
obj == rhs	__eq__(self,rhs)
obj < rhs	__lt__(self,rhs)
...	
obj + rhs	__add__(self,rhs)
...	



Item in List

```
>>> the_list = [1, 2, 3, 4, 5]
```

```
>>> x = 3
```

```
>>> x in the_list
```

```
True
```

```
>>> y = 8
```


```
>>> y in the_list
```

```
False
```

Item in List

```
def __contains__(self, item):  
    for k in range(len(self)):  
        if item == self.the_array[k]:  
            return True  
    return False
```

Linear Search



Can you do Binary Search
since the list is always sorted?

Summary

- Implementing lists using arrays:
 - Class structure for a list
 - Add an element to an unsorted list
 - Delete an element
 - A list that is always sorted
 - Add / Delete/ Search