

Lecture 34

Heaps and Heap sort

FIT 1008
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.


Operations

add:


- put at the bottom
- while order is broken, rise.

get_max:

- swap root with last item
- remove last item
- while order is broken, sink.



sink
(swapping with
largest child)




left child in last position means
k has only one child



```
def largest_child(self, k):  
    # Check for only one child.  
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:  
        return 2*k  
    else:  
        return 2*k+1
```

Make the item at index k sink to the correct position.

```
def sink(self, k):  
    while 2*k <= self.count:  
        child = self.largest_child(k)  
        if self.array[k] >= self.array[child]:  
            break  
        self.swap(child, k)  
        k = child
```



k=1

self.count = 10

self.array

	15	20	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



k=1

self.count = 10

self.array

	15	20	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



child = 2

k=1

self.count = 10

self.array

	15	20	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```

child = 2

k=1

self.count = 10

self.array

	15	20	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



`child = 2`

`k=1`

`self.count = 10`

`self.array`

	15	20	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10


```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1
  
```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child
  
```



child = 2

k=1

self.count = 10

self.array

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10


```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1
  
```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child
  
```



`child = 2`

`k = 2`

`self.count = 10`

`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



`child = 2`

`k = 2`

`self.count = 10`

`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



`child = 5`

`k = 2`

`self.count = 10`

`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



`child = 5`

`k = 2`

`self.count = 10`

`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```



`child = 5`

`k = 2`

`self.count = 10`

`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1


```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```

`child = 5`

`k = 2`

`self.count = 10`

`self.array`

	20	15	12	14	15	5	7	3	8	10
0	1	2	3	4	5	6	7	8	9	10

```

def largest_child(self, k):
    # Check for only one child.
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:
        return 2*k
    else:
        return 2*k+1

```

Make the item at index k sink to the correct position.

```

def sink(self, k):
    while 2*k <= self.count:
        child = self.largest_child(k)
        if self.array[k] >= self.array[child]:
            break
        self.swap(child, k)
        k = child

```

best case: $O(1)$

worst case: $O(\log N)$

(may need to consider
comparison operations)

Complexity of get_max

- Loop in **sink** can iterate at most depth times $\approx \log(N)$ (after depth iterations, the new item is at the root)
- **Best case: $O(1)$** *OCompare when the item is larger or equal than largest children.
- **Worst case: $O(\log N)$** *OCompare when the item sinks all the way to the bottom.

Homework: (key, value)

```
def largest_child(self, k):  
    # Check for only one child.  
    if 2*k == self.count or self.array[2*k] > self.array[2*k+1]:  
        return 2*k  
    else:  
        return 2*k+1
```

Make the item at index k sink to the correct position.


```
def sink(self, k):  
    while 2*k <= self.count:  
        child = self.largest_child(k)  
        if self.array[k] >= self.array[child]:  
            break  
        self.swap(child, k)  
        k = child
```



Just the key...

Heap sort



[5, -7, 10, -3, 13, 20, 25, 1]




	25	10	20	1	-3	5	13	-7
0	1	2	3	4	5	6	7	8

[5, -7, 10, -3, 13, 20, 25, 1]

not a heap




[5, -7, 10, -3, 13, 20, 25, 1]



	20	10	13	1	-3	5	-7	25
0	1	2	3	4	5	6	7	8


[5, -7, 10, -3, 13, 20, 25, 1]

not a heap



	-7	10	13	1	-3	5	20	25
0	1	2	3	4	5	6	7	8


[5, -7, 10, -3, 13, 20, 25, 1]



	13	10	5	1	-3	-7	20	25
0	1	2	3	4	5	6	7	8


[5, -7, 10, -3, 13, 20, 25, 1]

not a heap



	-7	10	5	1	-3	13	20	25
0	1	2	3	4	5	6	7	8


[5, -7, 10, -3, 13, 20, 25, 1]



	10	1	5	-7	-3	13	20	25
0	1	2	3	4	5	6	7	8


[5, -7, 10, -3, 13, 20, 25, 1]

not a heap



	-3	1	5	-7	10	13	20	25
0	1	2	3	4	5	6	7	8




[5, -7, 10, -3, 13, 20, 25, 1]





	5	1	-3	-7	10	13	20	25
0	1	2	3	4	5	6	7	8

[5, -7, 10, -3, 13, 20, 25, 1]

not a heap





[5, -7, 10, -3, 13, 20, 25, 1]



	1	-7	-3	5	10	13	20	25
0	1	2	3	4	5	6	7	8

[5, -7, 10, -3, 13, 20, 25, 1]



	-3	-7	1	5	10	13	20	25
0	1	2	3	4	5	6	7	8

[5, -7, 10, -3, 13, 20, 25, 1]

-7

-3

1

5

10

13

20

25

-7

-3

1

5

10

13

20

25

0

1

2

3

4



5

6

7

8

[5, -7, 10, -3, 13, 20, 25, 1]





[5, -7, 10, -3, 13, 20, 25, 1]

	-7	-3	1	5	10	13	20	25
--	----	----	---	---	----	----	----	----

0 1 2 3 4 5 6 7 8



Heap sort

- For each element in the array:
 - ➔ Add it to the Heap: $O(\log(N))$**N times**
- While heap contains elements:
 - ➔ Get max item: $O(\log(N))$**N times**

$$\begin{aligned}\log n! &= \log(1 \cdot 2 \cdot 3 \cdot \dots \cdot n) \\ &= \log 1 + \log 2 + \log 3 + \dots + \log n \\ &\leq \log n + \log n + \log n + \dots + \log n \\ &= n \log n\end{aligned}$$

Heap sort

Construction can also be done in linear time

- For each element in the array:
 - ➔ Add it to the Heap: $O(\log(N))$**N times**
- While heap contains elements:
 - ➔ Get max item: $O(\log(N))$**N times**

worst case: $O(N \log N)$

Summary

- A simple Heap implementation
 - rise
 - sink
 - largest_child
- Heap Sort