

# Lecture 19

## Linked Queues

FIT 1008  
Introduction to Computer Science



COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Objectives for these this lecture

- To understand:
  - The concept of linked data structures
  - Their use in **implementing queues**
- To be able to:
  - Implement, use and modify **linked queues**.
  - Decide when it is appropriate to use them (rather than arrays)



“Form an orderly queue to the left..”

# Remember array-based queues?


front: 3

rear: 1

count: 4

the\_array

29	6	3	24	36	7
0	1	2	3	4	5




rear



front

# Linked Queue



**Important:** Rear now designates the last node

No need for circularity.

**count** is optional...

```
from node import Node
```

```
class Queue:
```

```
    def __init__(self):  
        self.front = None  
        self.rear = None
```

```
    def is_empty(self):  
        return self.front is None
```

```
    def is_full(self):  
        return False
```

```
    def reset(self):  
        self.front = None  
        self.rear = None
```

# Append: algorithm

## Circular array implementation:

- If the array is full raise exception
- Else
  - Increase rear % length of the array
  - Add the item at the position designated by rear

No need for is\_full check.  
If no more memory can be allocated the system will raise an exception.

## Linked implementation:

- Create a **new node** that contains item and points to None
- Link the current rear to it
- Change rear to point to new node.


Would this work?

```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```




Let's try


```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```





```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```



```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```




```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```



**\*\*Goal\*\***


```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```



- Create a new node for item
- Make a link from current rear to new node
- The new node becomes the new rear

Boundary cases

```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```




If the queue is empty  
we need to do something with **front**



Would this work?

```
def append(self, item):  
    self.rear.next = Node(item, None)  
    self.rear = self.rear.next
```


Nope



- Create a new node for item
- If the queue is empty:
  - Make the new node be the front
- If the queue is not empty:
  - Make a link from current rear to new node
- The new node becomes the new rear

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```


- Create a new node for item
- If the queue is empty:
  - Make the new node be the front
- If the queue is not empty:
  - Make a link from current rear to new node
- The new node becomes the new rear



```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```




```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```






```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front.item = -3  
q.rear.item = 14
```

```
q.append(54)
```



```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front = None  
q.rear = None
```

```
q.append(54)
```



```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front = None  
q.rear = None
```

```
q.append(54)
```



```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front = None  
q.rear = None
```

```
q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front = None  
q.rear = None
```


```
q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```

None



rear



front



new\_node

```
q.front = None  
q.rear = None
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



None



rear



front




new\_node

```
q.front = None  
q.rear = None
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front = None  
q.rear = None
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
q.front = None  
q.rear = None
```

```
q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```




```
if q.front is q.rear
```

```
    q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```






```
if q.front is q.rear
```

```
    q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```


```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```



```
if q.front is q.rear
```

```
    q.append(54)
```

```
def append(self, item):  
    new_node = Node(item, None)  
    if self.is_empty():  
        self.front = new_node  
    else:  
        self.rear.next = new_node  
    self.rear = new_node
```

# Useful to check cases

- A few nodes.
- Empty.
- Single node.

# Serve: algorithm

## **Circular array implementation:**


- If the array is empty raise exception
- Else
  - Remember item to return
  - Increase front % length of the array
  - Return the item

## **Linked implementation:**


- If the array is empty raise exception
- Else
  - Remember item to return
  - Change front to point to the next node
  - Return the item

Would this work?


```
def serve(self):  
    item = self.front.item  
    self.front = self.front.next  
    return item
```








- Remember the item in the front node.




- Remember the item in the front node.
- Make the next node the new front




- Remember the item in the front node.
- Make the next node the new front
- Return the item

Boundary cases...




**If the queue is empty we need to  
raise an Exception**



- If the queue is empty we raise an Exception
- Remember the item in the front node.
- Make the next node the new front
- If front is pointing to None (i.e., queue is now empty)
  - Point rear to None
- Return the item

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```


- If the queue is empty we raise an Exception
- Remember the item in the front node.
- Make the next node the new front
- If front is pointing to None (i.e., queue is now empty)
  - Point rear to None
- Return the item



`q.serve()`


```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```






`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), "The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```






```
q.serve()
```

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




```
q.serve()
```

```
def serve(self):  
    assert not self.is_empty(), "The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```




```
q.serve()
```

```
def serve(self):  
    assert not self.is_empty(), "The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



```
q.serve()
```

```
def serve(self):  
    assert not self.is_empty(), "The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



```
q.serve()
```

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



`q.serve()`


```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```







`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```



`q.serve()`

```
def serve(self):  
    assert not self.is_empty(), " The queue is empty"  
    temp = self.front.item  
    self.front = self.front.next  
    if self.is_empty():  
        self.rear = None  
    return temp
```

# Summary

- Queues implemented with linked data structures