

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act. Do not remove this notice

Prepared by: [Arun Konagurthu]

FIT3155: Advanced Algorithms and Data Structures

Week 5: **Binomial heap** and its amortized analysis

Faculty of Information Technology, Monash University

What is covered in this lecture?

Binomial heap and its amortized analysis

Original reference

Jean Vuillemin, A Data Structure for Manipulating Priority Queues
Communications of the ACM, 21(4) 309-314. [\[link\]](#)

Source material and recommended reading

- Weiss, Data Structures and Algorithm Analysis (Chapters 6.8, 11.1, 11.2)
- Cormen et al., Introduction to Algorithms (Chapter 19) [\[link\]](#)

Priority queues (implemented using heaps)

Recall from FIT2004 that the heap data structure was used in several applications:

- Heap sort
- Dijkstra's shortest path algorithm
- Prim's algorithm

Recall also that this data structure supports the following operations*:

- **insert** a new element (containing key w/ payload) into a heap
- identify the **min** element in an existing heap
- **extract-min** (identify and delete min) element in an existing heap
- **decrease-key** of an element in an existing heap

*As with these slides, default heap operations in the rest of the slides are defined over a **min**-heap. One could alternatively define **max**, **extract-max**, **increase-key** operations on a **max**-heap.

Mergeable heaps

Today (binomial heap) and next start of next lecture (Fibonacci heap), we will learn about mergeable heaps that support (at least) the following operations[†]:

insert: inserts a new element into the existing heap

min: finds the min element in the heap

extract-min: finds and deletes the min element in the heap

merge: merges two heaps into one

decrease-key: decreases the elements key

delete: removes an element from the heap

[†]Again, the slides define these default heap operations over a **min**-heap. One could alternatively define **max**, **extract-max**, **increase-key** operations on a **max**-heap.


Before Binomial **heap**, let us define a binomial **tree**



Binomial trees are defined recursively:

- The binomial tree of order **0** (or B_0 in short) is a single node tree
- The binomial tree of order **1** (B_1) is created from two B_0 trees, by making one B_0 tree the child of the other.
- The binomial tree of order **2** (B_2) is created from two B_1 trees, by making one B_1 tree the child of the other.
- and so on...


Before Binomial **heap**, let us define a binomial **tree**



Binomial trees are defined recursively:

- The binomial tree of order 0 (or B_0 in short) is a single node tree
- The binomial tree of order 1 (B_1) is created from two B_0 trees, by making one B_0 tree the child of the other.
- The binomial tree of order 2 (B_2) is created from two B_1 trees, by making one B_1 tree the child of the other.
- and so on...


Before Binomial **heap**, let us define a binomial **tree**



Binomial trees are defined recursively:

- The binomial tree of order **0** (or B_0 in short) is a single node tree
- The binomial tree of order **1** (B_1) is created from two B_0 trees, by making one B_0 tree the child of the other.
- The binomial tree of order **2** (B_2) is created from two B_1 trees, by making one B_1 tree the child of the other.
- and so on...


Before Binomial **heap**, let us define a binomial **tree**



Binomial trees are defined recursively:

- The binomial tree of order **0** (or B_0 in short) is a single node tree
- The binomial tree of order **1** (B_1) is created from two B_0 trees, by making one B_0 tree the child of the other.
- The binomial tree of order **2** (B_2) is created from two B_1 trees, by making one B_1 tree the child of the other.
- and so on...

Before Binomial **heap**, let us define a binomial **tree**



Binomial trees are defined recursively:


- The binomial tree of order **0** (or B_0 in short) is a single node tree
- The binomial tree of order **1** (B_1) is created from two B_0 trees, by making one B_0 tree the child of the other.
- The binomial tree of order **2** (B_2) is created from two B_1 trees, by making one B_1 tree the child of the other.
- and so on...

Properties of a Binomial tree

Any binomial tree of order k has the following properties:

- The number of nodes in any B_k is 2^k .
- The height of any B_k is k .
- The root node of any B_k tree has k subtrees as children.
- Deleting the root node of B_k (with its edges/links) yields k independent lower order binomial trees $B_{k-1}, B_{k-2}, \dots, B_0$.

Example: Binomial tree, B_5 :




Properties of a Binomial tree

Any binomial tree of order k has the following properties:

- The number of nodes in any B_k is 2^k .
- The height of any B_k is k .
- The root node of any B_k tree has k subtrees as children.
- Deleting the root node of B_k (with its edges/links) yields k independent lower order binomial trees $B_{k-1}, B_{k-2}, \dots, B_0$.

Example: Binomial tree, B_5 :




Properties of a Binomial tree

Any binomial tree of order k has the following properties:

- The number of nodes in any B_k is 2^k .
- The height of any B_k is k .
- The root node of any B_k tree has k subtrees as children.
- Deleting the root node of B_k (with its edges/links) yields k independent lower order binomial trees $B_{k-1}, B_{k-2}, \dots, B_0$.

Example: Binomial tree, B_5 :




Properties of a Binomial tree

Any binomial tree of order k has the following properties:


- The number of nodes in any B_k is 2^k .
- The height of any B_k is k .
- The root node of any B_k tree has k subtrees as children.
- Deleting the root node of B_k (with its edges/links) yields k independent lower order binomial trees $B_{k-1}, B_{k-2}, \dots, B_0$.

Example: Binomial tree, B_5 :



Why are these trees called **binomial**?

Example: Binomial tree, B_5



Main property

A main property of any B_k tree is that the **number of nodes** at any given depth d is given by the **binomial coefficient** $\binom{k}{d}$, that is “ k -choose- d ”

What is a binomial heap?


A binomial **heap** is a forest (i.e., a set) of binomial **trees** such that:

- **each** binomial tree in the set satisfies the heap property – i.e., **each** tree-node's key is \leq its children's keys.
- There is **at most** one (i.e. either 0 or 1) binomial tree of any given order in that set.


Example

On the right is a binomial **heap** that contains a collection/set of binomial **trees**:

- **one** B_4 tree
- **zero** B_3 trees
- **zero** B_2 trees
- **one** B_1 tree
- **one** B_0 tree




How to find which order trees are there in a Binomial heap?



For the above binomial **heap**:

- $N = 19$.
- (Minimal) Binary representation of 19 gives: $\overset{4}{1} \overset{3}{0} \overset{2}{0} \overset{1}{1} \overset{0}{1}$
- The '1's above are at bit positions $0, 1$ and 4
- Therefore, the binomial **heap** with $N = 19$ contains 3 binomial **trees**: B_0, B_1, B_4 trees.

Binomial heap properties




Properties

For any binomial **heap** containing N elements, the following properties hold:

- The '1's in the **minimal binary representation** of N tell us which order/degree binomial **trees** form the binomial **heap** of N elements.
- There are at most $\lfloor \log_2 N \rfloor + 1$ binomial **trees**
- The height of each binomial **tree** is $\leq \lfloor \log_2 N \rfloor$
- the element with **minimum** key in the entire heap will be one of the root nodes of the **trees** in the collection.

Binomial heap properties




Properties

For any binomial **heap** containing N elements, the following properties hold:

- The '1's in the **minimal binary representation** of N tell us which order/degree binomial **trees** form the binomial **heap** of N elements.
- There are at most $\lfloor \log_2 N \rfloor + 1$ binomial **trees**
 - The height of each binomial **tree** is $\leq \lfloor \log_2 N \rfloor$
 - the element with **minimum** key in the entire heap will be one of the root nodes of the **trees** in the collection.

Binomial heap properties




Properties

For any binomial **heap** containing N elements, the following properties hold:

- The '1's in the **minimal binary representation** of N tell us which order/degree binomial **trees** form the binomial **heap** of N elements.
- There are at most $\lfloor \log_2 N \rfloor + 1$ binomial **trees**
- The height of each binomial **tree** is $\leq \lfloor \log_2 N \rfloor$
- the element with **minimum** key in the entire heap will be one of the root nodes of the **trees** in the collection.

Binomial heap properties




Properties

For any binomial **heap** containing N elements, the following properties hold:



- The '1's in the **minimal binary representation** of N tell us which order/degree binomial **trees** form the binomial **heap** of N elements.
- There are at most $\lfloor \log_2 N \rfloor + 1$ binomial **trees**
- The height of each binomial **tree** is $\leq \lfloor \log_2 N \rfloor$
- the element with **minimum** key in the entire heap will be one of the root nodes of the **trees** in the collection.

Representing a binomial heap

- Unlike **binary** heaps, **binomial** heaps are stored explicitly using a **tree** data structure.
- Each node x :
 - ▶ is denoted by a x .**key** (one may also include additional information as x .**payload**).
 - ▶ has a pointer x .**parent** to its parent node
 - ▶ has a pointer x .**child** to its **leftmost** child node
 - ★ If node x has zero children, then x .**child** = nil
 - ▶ has a pointer x .**sibling** to the immediate **sibling** of x to its right.
 - ★ If node x is the rightmost child of its parent, then x .**sibling** = nil
 - ▶ stores x .**degree** which is the number of children of x (i.e., same as the **order** of the binomial tree rooted at x)
- Finally, the roots of the binomial trees within a binomial heap are organized in a linked list, referred to as the **root list**.



Binomial heap data structure representation – example




[†]Image from CLRS: Introduction to Algorithms

operations on a binomial heap

Merging two binomial trees into one

- First, merging two binomial trees, each of the same order (say) k results in an order $k + 1$ binomial tree, where:
 - the two roots are linked, such that...
 - ...the root containing the larger key becomes the child of the root with smaller key.




Binomial **heap** operation – **merge** two binomial **heaps** into one

- With merging of two binomial **trees** established (see previous slide), we can now define **merging** of two binomial **heaps** (each containing a collection of trees).
- Heaps are merged in a way that is **reminiscent** of how we add two numbers in binary:

Example: addition of $19 + 7 = 26$ in binary

Order:	4	3	2	1	0
carry:		1	1	1	
	1	0	0	1	1
+	0	0	1	1	1
Result:	1	1	0	1	0

Example of merging 2 binomial heaps containing 19 and 7 elements each




(To be discussed during the lecture)

Implementing $\text{merge}(H_1, H_2)$ – first phase

Merging any two binomial heaps can be implemented in 2 phases:

First phase


Combine the root level linked-lists (root lists) of H_1 and H_2 , such that the degrees are **monotonically increasing**. Note: This potentially **violates** the binomial heap property that requires **at most** one binomial tree of any given degree – see slide #10.



Implementing $\text{merge}(H_1, H_2)$ – second phase

Second phase

Scan the combined root list (from first phase) and iteratively check the degrees of successive root nodes to **consolidate** them by merging trees (with same degrees) in order to get back a valid binomial heap (with **at most** one tree of any degree).



Complexity of $\text{merge}(H_1, H_2)$

Let H_1 contain n_1 elements, and H_2 contain n_2 elements, and $N = n_1 + n_2$

- Running time is $O(\log N)$ worst-case:
 - ▶ First phase results in a root list with **at most** $\lfloor \log n_1 \rfloor + \lfloor \log n_2 \rfloor + 2$ nodes.
 - ▶ In second phase, each iteration takes $O(1)$ time, with **at most** $\lfloor \log n_1 \rfloor + \lfloor \log n_2 \rfloor + 2$ iterations.
 - ▶ Since: $\lfloor \log n_1 \rfloor + \lfloor \log n_2 \rfloor + 2 \leq 2\lfloor \log N \rfloor + 2$
 - ▶ Thus, merging two heaps, in worst case, requires $O(\log N)$ effort.

Binomial **heap** operation – **extract-min**

We use this to identify and delete the minimum element among all **root nodes** of the trees in the heap.

- Identify the **min** node among the nodes in the root level of the heap, and delete it.
- From slide #8, we know that deleting the root node of any B_k tree yields: $B_{k-1}, B_{k-2}, \dots, B_0$.
- Promote these subtrees to the root level of the existing binomial heap. The result is similar to the result after first phase of merge operation...
- ...with potentially multiple trees of the same degree (violating binomial heap def'n – see slide #10).
- Now consolidate this current state of the tree so that **at most** one binomial tree of any degree will be present. This is same as the second phase of **merge**.

To be discussed with an example during the lecture. Take notes!

Binomial **heap** operation – **extract-min**

We use this to identify and delete the minimum element among all **root nodes** of the trees in the heap.

- Identify the **min** node among the nodes in the root level of the heap, and delete it.
- From slide #8, we know that deleting the root node of any B_k tree yields: $B_{k-1}, B_{k-2}, \dots, B_0$.
- Promote these subtrees to the root level of the existing binomial heap. The result is similar to the result after first phase of merge operation...
- ...with potentially multiple trees of the same degree (violating binomial heap def'n – see slide #10).
- Now consolidate this current state of the tree so that **at most** one binomial tree of any degree will be present. This is same as the second phase of **merge**.

To be discussed with an example during the lecture. Take notes!

Binomial **heap** operation – **extract-min**

We use this to identify and delete the minimum element among all **root nodes** of the trees in the heap.

- Identify the **min** node among the nodes in the root level of the heap, and delete it.
- From slide #8, we know that deleting the root node of any B_k tree yields: $B_{k-1}, B_{k-2}, \dots, B_0$.
- Promote these subtrees to the root level of the existing binomial heap. The result is similar to the result after first phase of merge operation...
- ...with potentially multiple trees of the same degree (violating binomial heap def'n – see slide #10).
- Now consolidate this current state of the tree so that **at most** one binomial tree of any degree will be present. This is same as the second phase of **merge**.

To be discussed with an example during the lecture. Take notes!

Binomial **heap** operation – **extract-min**

We use this to identify and delete the minimum element among all **root nodes** of the trees in the heap.

- Identify the **min** node among the nodes in the root level of the heap, and delete it.
- From slide #8, we know that deleting the root node of any B_k tree yields: $B_{k-1}, B_{k-2}, \dots, B_0$.
- Promote these subtrees to the root level of the existing binomial heap. The result is similar to the result after first phase of merge operation...
- ...with potentially multiple trees of the same degree (violating binomial heap def'n – see slide #10).
- Now consolidate this current state of the tree so that **at most** one binomial tree of any degree will be present. This is same as the second phase of **merge**.

To be discussed with an example during the lecture. Take notes!

Binomial **heap** operation – **extract-min**

We use this to identify and delete the minimum element among all **root nodes** of the trees in the heap.

- Identify the **min** node among the nodes in the root level of the heap, and delete it.
- From slide #8, we know that deleting the root node of any B_k tree yields: $B_{k-1}, B_{k-2}, \dots, B_0$.
- Promote these subtrees to the root level of the existing binomial heap. The result is similar to the result after first phase of merge operation...
- ...with potentially multiple trees of the same degree (violating binomial heap def'n – see slide #10).
- Now consolidate this current state of the tree so that **at most** one binomial tree of any degree will be present. This is same as the second phase of **merge**.

To be discussed with an example during the lecture. Take notes!

Running time of **extract-min** operation

- Running time is $O(\log N)$ worst-case – **why?**
 - ▶ Effort required to find the **min** is $O(\log N)$. (see slide #12)
 - ▶ Effort required to promote (to root level) and merge subtrees formed upon deletion of the min element is $O(\log N)$ (see slide #21)
 - ▶ Total effort: $O(\log N)$

Running time of **extract-min** operation

- Running time is $O(\log N)$ worst-case – **why?**
 - ▶ Effort required to find the **min** is $O(\log N)$. (see slide #12)
 - ▶ Effort required to promote (to root level) and merge subtrees formed upon deletion of the min element is $O(\log N)$ (see slide #21)
 - ▶ Total effort: $O(\log N)$

Running time of **extract-min** operation

- Running time is $O(\log N)$ worst-case – **why?**
 - ▶ Effort required to find the **min** is $O(\log N)$. (see slide #12)
 - ▶ Effort required to promote (to root level) and merge subtrees formed upon deletion of the min element is $O(\log N)$ (see slide #21)
 - ▶ Total effort: $O(\log N)$

Running time of **extract-min** operation

- Running time is $O(\log N)$ worst-case – **why?**
 - ▶ Effort required to find the **min** is $O(\log N)$. (see slide #12)
 - ▶ Effort required to promote (to root level) and merge subtrees formed upon deletion of the min element is $O(\log N)$ (see slide #21)
 - ▶ Total effort: $O(\log N)$

Binomial **heap** operation – **decrease-key**

We want to decrease key of any node x in a binomial heap containing N elements. [‡]

- decrease key of node x .
- if min-heap property is violated, i.e. $x.key < (x.parent).key$, bubble up node x (i.e., swap with parent).
- Running time (worst-case): $O(\log N)$ – depth of the binomial tree in which x resides is bounded above by $\lfloor \log N \rfloor$

To be discussed with an example during the lecture. Take notes!

[‡]Note: as with binary heaps, binomial (and Fibonacci) heaps are inefficient to **search** for any node x (except the root); For this reason, **decrease-key**(x) assumes a pointer to x as part of its input.

Binomial **heap** operation – **delete**

We want to delete any node x in a binomial heap containing N elements.
§

- run **decrease-key** by setting x to $-\infty$.
- run **extract-min**.
- Running time (worst-case): $O(\log N)$.

§ Note: as with binary heaps, binomial (and Fibonacci) heaps are inefficient to **search** for any node x (except the root); For this reason, **delete**(x) assumes a pointer to x as part of its input.

Binomial **heap** operation – **insert**

We want to insert a new element x into an existing binomial heap H_1

- Make a new binomial heap H_2 with x as its **only** element.
- run **merge**(H_1, H_2).
- At face value, the run-time per single **insert** takes $O(\log N)$ effort.

Amortized analysis of **insert** operation

Consider the problem of building a **binomial** heap of N elements:

- From FIT2004, we know that at least a **binary** heap of N elements can be built in $O(N)$ time.
- What about a **binomial** heap then?

claim

A **binomial** heap of N elements can be built by N successive inserts in $O(N)$ -time.

Amortized analysis of **insert** operation ...continued(2)

- Time required for inserting **each** element x into a heap H_1 (starting from an empty heap) involves:
 - ▶ time to create a new binomial heap H_2 containing only 1 element x – which requires constant effort, **plus**
 - ▶ time to merge H_2 into H_1 . It isn't fully clear yet how many merges (between same-order binomial trees) will be required in each insert operation.
- Total over N insertions requires:
 - ▶ $O(N)$ **plus**
 - ▶ total merging time.

Amortized analysis of **insert** operation ...continued(3)

It is easy to see (by beholding how the numbers starting from 0 change when 1 is added each time):

- the **first insertion** into an empty H_1 heap requires **zero** merges. **Why?**
- the second insertion involves exactly **one** merge between two B_0 binomial trees, yielding a heap containing one B_1 tree.
- the **third insertion** involves **zero** merges
 - ▶ H_1 before insertion contains 2 elements (contained in 1 B_1 tree).
 - ▶ merging the new inserted element into H_1 adds only a new B_0 tree to the existing B_1 tree. Therefore no merges.
- the fourth insertion involves exactly **two** merges – **why?**
- the **fifth insertion** involves **zero** merges – **why?**
- \vdots

Amortized analysis of **insert** operation ...continued(3)

When inserting N elements, if the binary representation of number elements in H_1 before each insertion ends in

-**0**, the effort takes only 1 unit of time.
-**01**, the effort takes only 2 units of time.
-**011**, the effort takes only 3 units of time.
-**0111**, the effort takes only 4 units of time.
- ...**01111**, the effort takes only 5 units of time.
- \vdots

Total time over N insertions

- $T = \frac{N}{2} \times 1 + \frac{N}{4} \times 2 + \frac{N}{8} \times 3 \dots = 2N$
- This is an instance of an **Arithmetico-Geometric series**.

Thus total time is bounded by $O(N)$, implying that each **insert** into a binomial heap is $O(1)$ amortized!

Summary

Operation	Binary heap	Binomial heap
make-new-heap	$O(1)$	$O(1)$
min	$O(1)$	$O(\log N)$
extract-min	$O(\log N)$	$O(\log N)$
merge	$O(N)$	$O(\log N)$
decrease-key	$O(\log N)$	$O(\log N)$
delete	$O(\log N)$	$O(\log N)$
insert	$O(\log N)$ worst-case $O(1)$ amortized	$O(\log N)$ worst-case $O(1)$ amortized

In the next lecture...

Fibonacci heaps

--o0o--

END

--o0o--