BUS X1 DIN 41612 (YACC1 V3.2)
BOARD SELECT ($D000 BLOCK) + TEXT RAM $D000–$D7FF
PORTS PA–PE: 6845 (PA/PB), CONTROL + STATUS (PC)
POWER UNITS + DECOUPLING
CLOCKS + CHARACTER PIPELINE (DOTS: 6 OR 8 DOTS A CHARACTER)
GRAPHICS RAM $D800–$DFFF: SLOT LOGIC (GFX–ON = 1) / DIRECT MODE (GFX–ON = 0)
DOT COMBINE + VIDEO OUT
PS/2: ATMEGA328P + LATCHES (PD, PE), INT
VCC
PWR_FLAG
GND

PWR_FLAGs: the bus supplies VCC and GND (X1, six pins each).

Design note: BACKLOG.md Video card V2.0; theory: docs/cards/video.md
Circuit source: v20_netlist.py; this sheet is generated by gen_v20.py
Text + graphics (8–dot mode), 6845 and every register on ports PA–PE, PS/2 keyboard and mouse
YACC1
Sheet: /
File: video–v2.0.kicad_sch
Title: YACC1 video card V2.0
Size: A0 Date: 2026–10–22 **Rev: V2.0**
KiCad E.D.A. 10.0.6 Id: 1/1