P8X ALU CARD REV B (conventional carry, LDZN, SETC/CLRC, carry-coupled shifter) - traditional wiring (auto-drafted)

Bus rails top with taps in column gaps; dot = junction, plain crossing = no connection; rail glyphs = +5V/GND; X = no connect.

ALUS[0..3]
AQ[0..7]
BQ[0..7]
D[0..7]
DLD[0..3]
DOE[0..3]
F[0..7]
G[0..7]
R[0..7]
T2Q[0..7]
TQ[0..7]

J1
A3 D0
A4 D1
A5 D2
A6 D3
A7 D4
A8 D5
A9 D6
A10 D7
A11 -RES
A12 DOE0
A13 DOE1
A14 DOE2
A15 DOE3
A16 DLD0
A17 DLD1
A18 DLD2
A19 DLD3
A24 CLK
A26 LDF
A27 FC
A28 FZ
A29 FN
A30 FV
B27 CLRC
C19 ALUS0
C20 ALUS1
C21 ALUS2
C22 ALUS3
C23 ALUM
C24 CIN
C25 SH0
C26 SH1
C28 LDZN
C29 SHCIN
C30 SETC
+5V (6 PINS)
GND (30 PINS)
DIN41612 96P BUS

U1
A REG
U2
A OUT
U3
B REG
U4
B OUT
U5
T REG
U6
T OUT
U7
T2 REG
U8
T2 OUT
U9
ALU LO
U10
ALU HI
U11
CLA
U12
SH1 LO
U13
SH1 HI
U14
SH2 LO
U15
SH2 HI
U16
ALU OUT
U17
FLAGS
U18
Z DET
U19
74HCT08
U20
DOE DEC
U21
DLD DEC
U22
FLAG MUX
U23
FLAG OUT
U24
74HCT32
U25
74HCT00
U26
C FLAG FF
U27
BUS Z-DET
U28
SHIFT-OUT MUX
U29
C-SRC MUX
U30
SHIN MUX
U31
74HCT08 CLK/FORCE
RP1
1K
LED3
PWR-GRN
R4
1K
LED4
ALU-GRN
R5
1K
LED5
LDF-YEL

-DOEA
-DOEB
-DOET
-DOET2
-LDA
-LDB
-LDT
-LDT2
-DOEALU
-DOEFLG
-RES
ALUM
CIN
CLK
CLRC
FC
FN
FV
FZ
LDF
LDZN
SETC
SH0
SH1
SHCIN
CFLG
CG0
CG1
CNX
CP0
CP1
SHIN
-SETCb
ALUK
CFLGI
CLKFZN
CLKFC
FENZN
FQC
FQN
FQV
FQZ
LDFK
LEDAL
LEDLF
LEDP
NC
NSRC
SHANY
SHOUT
ZBH
ZBL
ZBUS
ZFLG
ZH
ZL
ZSRC
-CLRb
-CLRCb