

## SourceCode: Make an E-Commerce Website for Sporty Shoes

### Open Pom.xml add Dependencies

```
<?xml version="1.0" encoding="UTF-8"?>

<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
    https://maven.apache.org/xsd/maven-4.0.0.xsd">

  <modelVersion>4.0.0</modelVersion>

  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
    <version>2.5.1</version>
    <relativePath/> <!-- lookup parent from repository -->
  </parent>
  <groupId>com.project</groupId>
  <artifactId>SportyShoes</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <name>SportyShoes</name>
  <description>phase3 project for Spring Boot</description>
  <properties>
    <java.version>11</java.version>
  </properties>
  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-data-jdbc</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-thymeleaf</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-webflux</artifactId>
    </dependency>

    <dependency>
<groupId>org.eclipse.persistence</groupId>
<artifactId>javax.persistence</artifactId>
<version>2.1.0</version>
<scope>compile</scope>
```

```

</dependency>
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-devtools</artifactId>
        <scope>runtime</scope>
        <optional>true</optional>
    </dependency>

    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-test</artifactId>
        <scope>test</scope>
    </dependency>
    <dependency>
        <groupId>io.projectreactor</groupId>
        <artifactId>reactor-test</artifactId>
        <scope>test</scope>
    </dependency>
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-batch</artifactId>
    </dependency>

    <dependency>
        <groupId>org.projectlombok</groupId>
        <artifactId>lombok</artifactId>
        <optional>true</optional>
    </dependency>
    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-data-jpa</artifactId>
    </dependency>

    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-web-services</artifactId>
    </dependency>
    <dependency>
        <groupId>com.h2database</groupId>
        <artifactId>h2</artifactId>
        <scope>runtime</scope>
    </dependency>
    <dependency>
        <groupId>mysql</groupId>
        <artifactId>mysql-connector-java</artifactId>
        <scope>runtime</scope>
    </dependency>
</dependencies>

<build>
    <plugins>
        <plugin>

```

```

        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-maven-plugin</artifactId>
    </plugin>
</plugins>
</build>

</project>

```

## Src/main/java

By default Spring creates package **com.project.SportyShoes**

### Create GlobalExceptionHandler.java

```

package com.project.SportyShoes;

import org.springframework.web.bind.annotation.ControllerAdvice;
import org.springframework.web.bind.annotation.ExceptionHandler;

@ControllerAdvice
public class GlobalExceptionHandler {

    @ExceptionHandler(Exception.class)
    public String handleException1(Exception e) {

        e.printStackTrace();

        return "Some error has occurred, please contact to administrator";

    }

}

```

### Create SportyShoesApplication.java

```

package com.project.SportyShoes;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

```

```

public class SportyShoesApplication {

    public static void main(String[] args) {

        SpringApplication.run(SportyShoesApplication.class, args);

    }

}

```

## **Create package com.project.SportyShoes.controller**

### **Create CategoriesController.java**

```

package com.project.SportyShoes.controller;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;

import com.project.SportyShoes.entity.Categories;
import com.project.SportyShoes.service.CategoriesService;

@Controller

public class CategoriesController {

    @Autowired

    private CategoriesService catserv;

```

```

@RequestMapping("/listcat")

public String viewListPage(Model model)
{
    List<Categories> listCategories= catserv.listAll();

    model.addAttribute("listCategories", listCategories);

    return "manage";
}

@RequestMapping("/new")

public String addNewCatPage(Model model)
{
    Categories categories= new Categories();

    model.addAttribute("categories", categories);

    return "new_category";
}

@RequestMapping(value = "/save", method = RequestMethod.POST)

public String saveCategory(@ModelAttribute("categories") Categories categories, Model m)
{
    catserv.save(categories);

    List<Categories> listCategories= catserv.listAll();

    m.addAttribute("listCategories", listCategories);

    return "manage";
}

@RequestMapping("/delete/{id}")

public String deleteCategory(@PathVariable(name = "id") long id, Model m)
{
    catserv.delete(id);

    List<Categories> listCategories= catserv.listAll();

```

```

        m.addAttribute("listCategories", listCategories);

        return "manage";
    }
}

```

## Create LoginController.java

```

package com.project.SportyShoes.controller;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PostMapping;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.servlet.ModelAndView;
import com.project.SportyShoes.entity.Login;
import com.project.SportyShoes.service.LoginService;

@Controller

public class LoginController {

    @Autowired

    private LoginService ls;

    @GetMapping("/")

    public ModelAndView login() {

        ModelAndView mav = new ModelAndView("login");

        mav.addObject("user", new Login());

        return mav;

    }

    @PostMapping("/adminlogin")

    public String signUp(@ModelAttribute("user") Login user ) {

```

```

Login oauthUser = null;

System.out.println("from login"+ user);

if(user.getPassword() != "" ) {

    System.out.println("logging in");

    oauthUser = ls.signin(user.getUsername(), user.getPassword());

    return "menu";

} else {

    if (user.getNewPassword() != "" ) {

        System.out.println("Changing new password");

        oauthUser = ls.changePassword(user.getUsername(), user.getNewPassword());

        if(oauthUser == null ) {

            return "invalid_credentials";

        }

        return "menu";

    }

    return "invalid_credentials";

}

}

//@GetMapping("/forgotPassword")

//public String update(@ModelAttribute("user") Login user){

    //Login changepw = userService.updatePassword(user.);

    //System.out.println(changepw);

    //if(Objects.nonNull(changepw))

    //{

    //return "redirect:/";

    //} else {

        //return "redirect:/login";

```

```

        //}

    //}

    //{

    //}

    @RequestMapping("/logout")

    public String logoutDo()

    {

        return "conform_logout";

    }

    //@PostMapping("/reset")

    //public String resetPassword(@ModelAttribute("userchange") Login user) {

        //System.out.println("form reset");

        //Boolean changePassword = ls.changePassword(user.getUsername(),
user.getPassword());

        //if(!changePassword) {

        //    return "usernotfound";

        //}

        //return "menu";

    //}

/*    @GetMapping("/forgotpw")

    public String resetPassword1(@ModelAttribute("change") Login change ) {

        System.out.println("from login"+ change);

        Boolean oauthUser = ls.changePassword(change.getUsername(), change.getPassword());

        System.out.print(oauthUser);

        if(Objects.nonNull(oauthUser))

        {

```



```

        return "menu";

    } else {

        return "invalid_credentials";

    }

}*/

}

```

## Create ProductController.java

```

package com.project.SportyShoes.controller;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.Model;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;

import com.project.SportyShoes.entity.Categories;
import com.project.SportyShoes.entity.Product;
import com.project.SportyShoes.service.ProductService;

@Controller
public class ProductController {

    @Autowired
    public ProductService prodserv;

    @RequestMapping("/listprod")
    public String viewListProductPage(Model model)
    {
        List<Product> listProduct= prodserv.listAll();
        model.addAttribute("listProduct", listProduct);
        return "product_manage";
    }

    @RequestMapping("/newproduct")
    public String addNewProductPage(Model model)
    {
        Product product= new Product();
        model.addAttribute("product", product);

        return "new_product";
    }

    @RequestMapping(value = "/saveproduct", method = RequestMethod.POST)

```

```

    public String saveCategory(@ModelAttribute("product") Product product, Model md)
    {

        prodserv.save(product);
        List<Product> listProduct= prodserv.listAll();
        md.addAttribute("listProduct", listProduct);

        return "product_manage";

    }

}

```

### Create UserDetailsController.java

```

package com.project.SportyShoes.controller;

import java.util.ArrayList;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Controller;

import org.springframework.ui.Model;

import org.springframework.web.bind.annotation.GetMapping;

import org.springframework.web.bind.annotation.GetMapping;

import org.springframework.web.bind.annotation.PathVariable;

import org.springframework.web.bind.annotation.RequestMapping;

import org.springframework.web.bind.annotation.RequestParam;

import org.springframework.web.servlet.ModelAndView;

import com.project.SportyShoes.entity.UserDetails;

import com.project.SportyShoes.service.UserDetailsService;

@Controller

public class UserDetailsController {

```

```

@Autowired

UserDetailsService userservice;

//@GetMapping("/list")

//public List<UserDetails> getUserDetails()

//{

        //List<UserDetails> listuser = new ArrayList<UserDetails>();

        //listuser= userservice.getUsers();

        // return listuser;

//}

@GetMapping("/index")

public String viewUserDetails(Model model)

{

        List<UserDetails> listUsers= userservice.listAll();

        System.out.println("listUsers" + listUsers);

        model.addAttribute("listUsers",listUsers);

        return "/index";

}

// @GetMapping("/find")

// public List<UserDetails> findusername(@RequestParam("username") String username)

// {

//         List<UserDetails> searchuser =new ArrayList<UserDetails>();

//         searchuser = userservice.get(username);

//         System.out.println("user"+ searchuser);

//         return searchuser;

// }

@GetMapping("/user/{username}")

```

```

        public String findUserName(@PathVariable(name="username")String username)
        {

            System.out.println("i am here");

            ModelAndView mav = new ModelAndView("find");

            List<UserDetails> userdetails=userservice.get(username);

            mav.addObject("userdetails", userdetails);

            return "finduser";

        }

    }

```

## Create package com.project.SportyShoes.entity

### Create BaseEntity.java

```

package com.project.SportyShoes.entity;

import lombok.Data;

import lombok.EqualsAndHashCode;

import javax.persistence.Column;

import javax.persistence.EntityListeners;

import javax.persistence.MappedSuperclass;

import java.util.Date;

@MappedSuperclass

@Data

@EqualsAndHashCode

@EntityListeners(EntityListener.class)

public abstract class BaseEntity {

    @Column(nullable = false, updatable = false)

    private Date createDate;

    @Column(insertable = false)

    private Date lastUpdateDate;

```

```

public Date getCreateDate() {

    return createDate;

}

public void setCreateDate(Date createDate) {

    this.createDate = createDate;

}

public Date getLastUpdateDate() {

    return lastUpdateDate;

}

public void setLastUpdateDate(Date lastUpdateDate) {

    this.lastUpdateDate = lastUpdateDate;

}

}

```

### Create Categories.java

```

package com.project.SportyShoes.entity;

import javax.persistence.Entity;

import javax.persistence.GeneratedValue;

import javax.persistence.GenerationType;

import javax.persistence.Id;

import javax.persistence.Table;

@Entity

@Table(name="categories")

public class Categories {

    @Id

    @GeneratedValue(strategy=GenerationType.IDENTITY)

    private long id;

    private String categoryName;

```

```
public long getId() {  
    return id;  
}  
  
public void setId(long id) {  
    this.id = id;  
}  
  
public Categories() {  
    super();  
    // TODO Auto-generated constructor stub  
}  
  
public Categories(long id, String categoryName) {  
    super();  
    this.id = id;  
    this.categoryName = categoryName;  
}  
  
@Override  
public String toString() {  
    return "Categories [id=" + id + ", categoryName=" + categoryName + "];"  
}  
  
public String getCategoryName() {  
    return categoryName;  
}  
  
public void setCategoryName(String categoryName) {  
    this.categoryName = categoryName;  
}
```

```
/*public String women;

public String men;

public String kids;

public Categories() {

    super();

    // TODO Auto-generated constructor stub

}

public Categories(long id, String women, String men, String kids) {

    super();

    this.id = id;

    this.women = women;

    this.men = men;

    this.kids = kids;

}

public long getId() {

    return id;

}

public void setId(long id) {

    this.id = id;

}

public String getWomen() {

    return women;

}

public void setWomen(String women) {

    this.women = women;

}

public String getMen() {
```

```

        return men;
    }

    public void setMen(String men) {

        this.men = men;
    }

    public String getKids() {

        return kids;
    }

    public void setKids(String kids) {

        this.kids = kids;
    }

    @Override

    public String toString() {

        return "Categories [id=" + id + ", women=" + women + ", men=" + men + ", kids=" + kids
+ "]\n";
    }

}

```

### Create EntityLister.java

```

package com.project.SportyShoes.entity;

import javax.persistence.PrePersist;

import javax.persistence.PreUpdate;

import java.util.Date;

```



```

public class EntityListener {

    @PrePersist

    public void prePersist(BaseEntity entity) {

        Date now = new Date();

        entity.setCreateDate(now);

    }

    @PreUpdate

    public void preUpdate(BaseEntity entity) {

        Date now = new Date();

        entity.setLastUpdateDate(now);

    }

}

```

### Create Login.java

```

package com.project.SportyShoes.entity;

import javax.persistence.Entity;

import javax.persistence.GeneratedValue;

import javax.persistence.GenerationType;

import javax.persistence.Id;

import javax.persistence.Table;

@Entity

@Table(name="login")

public class Login {

    @Id

```

```
@GeneratedValue(strategy= GenerationType.IDENTITY)

private Long id;

private String username;

private String password;

private String newPassword;


public String getNewPassword() {

    return newPassword;

}

public void setNewPassword(String newPassword) {

    this.newPassword = newPassword;

}

public Login(Long id, String username, String password, String newPassword) {

    super();

    this.id = id;

    this.username = username;

    this.password = password;

    this.newPassword = newPassword;

}

public Login() {

    super();

    // TODO Auto-generated constructor stub

}

public Login(Long id, String username, String password) {

    super();

    this.id = id;

    this.username = username;
```

```

        this.password = password;
    }

    public Long getId() {

        return id;
    }

    public void setId(Long id) {

        this.id = id;
    }

    public String getUsername() {

        return username;
    }

    public void setUsername(String username) {

        this.username = username;
    }

    public String getPassword() {

        return password;
    }

    public void setPassword(String password) {

        this.password = password;
    }

    @Override

    public String toString() {

        return "Login [id=" + id + ", username=" + username + ", password=" + password + ",
newPassword=" + newPassword+ "]";
    }

}

```

**Create Product.java**

```
package com.project.SportyShoes.entity;

import javax.persistence.Entity;

import javax.persistence.GeneratedValue;

import javax.persistence.GenerationType;

import javax.persistence.Id;

import javax.persistence.Table;

@Entity

@Table(name="product")

public class Product {

    @Id

    @GeneratedValue(strategy=GenerationType.IDENTITY)

    private long id;

    private String productName;

    private String category;

    private long price;

    private Boolean status;

    private String size;

    public Product() {

        super();

        // TODO Auto-generated constructor stub

    }

    public long getId() {

        return id;

    }

    public void setId(long id) {

        this.id = id;

    }

}
```

```
}

public String getProductName() {

    return productName;

}

public void setProductName(String productName) {

    this.productName = productName;

}

public String getCategory() {

    return category;

}

public void setCategory(String category) {

    this.category = category;

}

public long getPrice() {

    return price;

}

public void setPrice(long price) {

    this.price = price;

}

public Boolean getStatus() {

    return status;

}

public void setStatus(Boolean status) {

    this.status = status;

}

public String getSize() {

    return size;

}
```

```

    }

    public void setSize(String size) {

        this.size = size;

    }

    @Override

    public String toString() {

return "Product [id=" + id + ", productName=" + productName + ", category=" + category + ", price=" +
price+ ", status=" + status + ", size=" + size + "]\n";

    }

    public Product(long id, String productName, String category, long price, Boolean status, String
size) {

        super();

        this.id = id;

        this.productName = productName;

        this.category = category;

        this.price = price;

        this.status = status;

        this.size = size;

    }

}

```

### Create UserDetails.java

```

package com.project.SportyShoes.entity;

import java.sql.Date;

import javax.persistence.Entity;

import javax.persistence.GeneratedValue;

```

```

import javax.persistence.GenerationType;

import javax.persistence.Id;

import javax.persistence.Table;

@Entity(name = "userdetails")

@Table(name="userdetails")

public class UserDetails extends BaseEntity {

    @Id

    @GeneratedValue(strategy= GenerationType.IDENTITY)

    public long userId;

    public String username;

    public String emailId;

    public String phone;

    public String productPurchased;

    public Date purchaseDate;

    public String category;

    public UserDetails() {

        super();

        // TODO Auto-generated constructor stub

    }

    public UserDetails(long userId, String username, String emailId, String phone, String
productPurchased,

        Date purchaseDate, String category) {

        super();

        this.userId = userId;

        this.username = username;

        this.emailId = emailId;

```

```
        this.phone = phone;

        this.productPurchased = productPurchased;

        this.purchaseDate = purchaseDate;

        this.category = category;
    }

    public long getUserId() {

        return userId;
    }

    public void setUserId(long userId) {

        this.userId = userId;
    }

    public String getUsername() {

        return username;
    }

    public void setUsername(String username) {

        this.username = username;
    }

    public String getEmailId() {

        return emailId;
    }

    public void setEmailId(String emailId) {

        this.emailId = emailId;
    }

    public String getPhone() {

        return phone;
    }

    public void setPhone(String phone) {
```



```

        this.phone = phone;
    }

    public String getProductPurchased() {

        return productPurchased;
    }

    public void setProductPurchased(String productPurchased) {

        this.productPurchased = productPurchased;
    }

    public Date getPerchaseDate() {

        return purchaseDate;
    }

    public void setPerchaseDate(Date purchaseDate) {

        this.purchaseDate = purchaseDate;
    }

    public String getCategory() {

        return category;
    }

    public void setCategory(String category) {

        this.category = category;
    }

    @Override

    public String toString() {

        return "UserDetails [userId=" + userId + ", username=" + username + ", emailId=" +
emailId + ", phone=" + phone
                                + ", productPurchased=" + productPurchased + ", perchaseDate=" +
purchaseDate + ", category=" + category
                                + "]";
    }

```

```
}
```

### Create package com.project.SportyShoes.jdbc

### Create CategoriesRepository.java

```
package com.project.SportyShoes.jdbc;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.SportyShoes.entity.Categories;

public interface CategoriesRepository extends JpaRepository<Categories, Long> {

}
```

### Create LoginRepository.java

```
package com.project.SportyShoes.jdbc;

import org.springframework.data.jpa.repository.JpaRepository;

import org.springframework.data.jpa.repository.Modifying;

import org.springframework.data.jpa.repository.Query;

import org.springframework.data.repository.query.Param;

import org.springframework.stereotype.Repository;

import com.project.SportyShoes.entity.Login;

import lombok.val;

@Repository

public interface LoginRepository extends JpaRepository<Login, Long> {

    Login findByUsernameAndPassword(String username, String password);

    Login findByUsername(String username);

    //Login findByEmail(String emailId);

    //Login findByResetPassword(String resetPassword);

}
```

```

        @Modifying
        @Query("update Login log set log.password = :password where log.id = :id")

        void changePassword(@Param(value="password") String password, @Param(value = "id") Long id);

    }

```

### Create ProductRepository.java

```

package com.project.SportyShoes.jdbc;

import org.springframework.data.jpa.repository.JpaRepository;

import com.project.SportyShoes.entity.Product;

public interface ProductRepository extends JpaRepository<Product, Long>{

}

```

### Create UserDetailsRepository.java

```

package com.project.SportyShoes.jdbc;

import java.util.List;

import org.springframework.data.jpa.repository.JpaRepository;

import org.springframework.stereotype.Repository;

import com.project.SportyShoes.entity.UserDetails;

@Repository

public interface UserDetailsRepository extends JpaRepository<UserDetails, Long> {

    public List<UserDetails> findByusername(String username);

}

```

### Create package com.project.SportyShoes.service

#### Create CategoriesService.java

```

package com.project.SportyShoes.service;

import java.util.List;

import javax.transaction.Transactional;

import org.springframework.beans.factory.annotation.Autowired;

```

```
import org.springframework.stereotype.Service;

import com.project.SportyShoes.entity.Categories;

import com.project.SportyShoes.jdbc.CategoriesRepository;
```

```
@Service
```

```
@Transactional
```

```
public class CategoriesService {

    @Autowired

    private CategoriesRepository catrepo;

    public List<Categories> listAll()
    {

        return catrepo.findAll();

    }

    public void save(Categories categories)
    {

        catrepo.save(categories);

    }

    public Categories get(long id)
    {

        return catrepo.findById(id).get();

    }

    public void delete(long id)
    {

        catrepo.deleteById(id);

    }

}
```

**Create LoginService.java**

```
package com.project.SportyShoes.service;
```

```
import org.springframework.beans.factory.annotation.Autowired;
```

```
import org.springframework.stereotype.Service;
```

```
import com.project.SportyShoes.entity.Login;
```

```
import com.project.SportyShoes.entity.UserDetails;
```

```
import com.project.SportyShoes.jdbc.LoginRepository;
```

```
@Service
```

```
public class LoginService{
```

```
    @Autowired
```

```
    private LoginRepository repo;
```

```
    public Login signin(String username, String password) {
```

```
        Login user = repo.findByUsernameAndPassword(username, password);
```

```
        System.out.println("from service" + user);
```

```
        return user;
```

```
    }
```

```
    public Login changePassword(String username, String newPassword) {
```

```
        // TODO Auto-generated method stub
```

```
        Login uplogin = null;
```

```
        Login user1 = repo.findByUsername(username);
```

```
        if(user1 !=null ) {
```

```
            System.out.println("user1" + user1);
```

```

        repo.changePassword(newpassword, user1.getId());

        uplogin = repo.findByUsername(username);

        System.out.println("Password Changed");

        return uplogin;

    }

    return null;

}

}

// Login login=repo.findByEmail(email);

    // if(login != null)

        //{

            // login.setResetPassword(resetPassword);

            //repo.save(login);

        //}

        //else {

            //System.out.println("couldnot find the emailid");

        //}

    //}

//catch (Exception e) {

    //e.printStackTrace(e.getMessage());

    //}

//}

//public Login getByResetPassword(String resetPassword)

//{

    // return repo.findByResetPassword(resetPassword);

    //}

```

```
//}
```

### Create ProductService.java

```
package com.project.SportyShoes.service;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

import com.project.SportyShoes.entity.Categories;
import com.project.SportyShoes.entity.Product;
import com.project.SportyShoes.jdbc.ProductRepository;

@Service

public class ProductService {

    @Autowired

    public ProductRepository prodrepo;

    public List<Product> listAll()
    {

        return prodrepo.findAll();

    }

    public void save(Product product)
    {

        prodrepo.save(product);

    }

}
```

### Create UserDetailsService.java

```

package com.project.SportyShoes.service;

import java.util.ArrayList;

import java.util.List;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Service;

import com.project.SportyShoes.entity.UserDetails;

import com.project.SportyShoes.jdbc.UserDetailsRepository;

@Service

public class UserDetailsService {

    @Autowired

    UserDetailsRepository userRepo;

    //public List<UserDetails> listAll(){

        //List<UserDetails> ud=new ArrayList<UserDetails>();

        //ud= userRepo.findAll();

        //System.out.println("userdetails "+ud);

        //return ud;

    //}

    public List<UserDetails> listAll()

    {

        return userRepo.findAll();

    }

    public List<UserDetails> get(String username) {

        return userRepo.findByusername(username);

    }

}

```



```

/*public List<UserDetails> searchUsers(String username) {

        List<UserDetails> su= new ArrayList<UserDetails>();

        su= userRepo.findByusername(username);

        return su;

    }*/
}

```

## Src/main/resources

### Open application.properties

```

spring.datasource.url=jdbc:mysql://localhost:3306/mywork
spring.datasource.username=root
spring.datasource.password=password
#auto create tables fromspring boot
spring.jpa.generate-ddl=true
spring.jpa.hibernate.ddl-auto = update
server.port = 8080
#logging.level.root=WARN
logging.level.org.springframework.web: DEBUG
spring.jpa.open-in-view=true
spring.thymeleaf.cache=true
spring.thymeleaf.prefix=classpath:/templates/
spring.thymeleaf.suffix=.html
spring.jpa.show-sql=true
api.base.path = http://localhost:/mywork

```

### Create Folder templates and

### Create conform\_logout.html.

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>

```

```

</head>
<body>
<a href="/">Conform Logout</a>

</body>
</html>

```

## Create finduser.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<div align="center">
<H3>Find User By UserName</H3>
<br>
<form action="#" th:action="@{/find{username}}" th:object="${userdetails}" method="post">
<table border="0" cellpadding="10">
<tr>
<td>
<td>UserName:</td>
<td><input type="text" th:field="*{username}"/>
</td>
<tr>
<td colspan="2"><button type="submit">Search</button> </td>
</tr>
</table>
</form>
</div>
</body>
</html>

```

## Create Index.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>List OF User Details</title>
</head>
<body>
<div align="center">
<H1>List of All The Users</H1>
<br/>
<table border="1" cellpadding="10">
<thead>
<tr>
<th>UserId</th>

```

```

<th>UserName</th>
<th>email Id</th>
<th>Phone</th>
<th>Product Purchased</th>
<th>Purchase Date</th>
<th>Category</th>
<th>Create Date</th>
<th>Last Update Date</th>
</tr>
</thead>
<tbody>
<tr th:each="userdetails : ${listUsers}">
  <td th:text="${userdetails.userId}">UserId</td>
  <td th:text="${userdetails.username}">UserName</td>
  <td th:text="${userdetails.emailId}">email Id</td>
  <td th:text="${userdetails.phone}">Phone</td>
  <td th:text="${userdetails.productPurchased}">Product Purchased</td>
  <td th:text="${userdetails.purchaseDate}">Purchase Date</td>
  <td th:text="${userdetails.category}">Category</td>
  <td th:text="${userdetails.createDate}">Create Date</td>
  <td th:text="${userdetails.lastUpdateDate}">Last Update Date</td>
</tr>
</tbody>
</table>
<a href="/logout">LogOut</a>
</div>
</body>
</html>

```

## Create invalid\_credentials.html

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<h1>Invalid Credentials</h1><br>
<br>
<a href="/">try Again</a>

</body>
</html>

```

## Create login.html

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>

```

```

</head>
<body>
<div align="center">
<h2>Wellcome To Sporty Shoes Web App!!!</h2>

<table width="100%" height="100%" border="0" cellpadding="0" align="center">
<tr>
<td align="center" valign="middle">
<table class="table-bordered" width="350" border="0" cellpadding="3" cellspacing="3" bgcolor="#ffffff">
<form action="#" th:action="@{/adminlogin}" th:object="${user}" method="post">
<tr>
<td height="25" colspan="2" align="left" valign="middle" bgcolor="#ffffff" class="style2">
<div align="center">
<strong>Admin Login</strong>
</div>
</td>
<td>
<tr>
<td>Username</td>
<td><input type="text" th:field="*{username}"
class="form-control" /></td>
</tr>
<tr>
<td>Password</td>
<td><input type="password" th:field="*{password}"
class="form-control" /></td>
</tr>
<tr>
<td>New Password</td>
<td><input type="password" th:field="*{newPassword}"
class="form-control" /></td>
</tr>
<tr>
<td colspan="2"><button type="submit" class="btn btn-
info" align="right">login/change password</button></td>
</tr>
</form>
</table>
</td>
</tr>
</table>
</body>
</html>

```

## Create manage.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>Manage Category Unit</title>
</head>

```

```

<body>
<div align="center">
<h1>Categories List</h1><br>
<div align="center">
<a href="/new">Create New Category</a>
</div>
<table border="1" cellpadding="10"><thead><tr>
<th>id</th>
<th>Name</th>
<th>Action</th>
</tr>
</thead>
<tbody>
<tr th:each="categories : ${listCategories}">
<td th:text="${categories.id}">id</td>
<td th:text="${categories.categoryName}">Name</td>
<td><a th:href="@{/delete/{id}(id=${categories.id})}">Delete</a></td>
</tr>
</tbody>
</table>
<a href="/logout">LogOut</a>
</div>
</body>
</html>

```

## Create menu.html

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<h1>Admin Work System</h1>
<a href="/listcat">Click here to Manage Categories</a><br>
<a href="/index">Click here to view the list of users</a><br>
<a href="/listprod">Click here to view the products List</a><br>
<br>
<br>
<a href="/logout">LogOut</a>
</body>
</html>

```

## Create new\_category.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
__xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>Create New Category</title>

```

```

</head>
<body>
<div align="center">
<h1>Create New Category</h1>
<br/>
<form action="#" th:action="@{/save}" th:object="${categories}"
    method="post">

    <table border="0" cellpadding="10">
        <tr>
            <td>Name:</td>
            <td><input type="text" th:field="*{categoryName}" /></td>
        </tr>
        <tr>
            <td colspan="2"><button type="submit">Save</button> </td>
        </tr>
    </table>
</form>
<a href="/logout">LogOut</a>
</div>
</body>
</html>

```

## Create new\_product.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
    __xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>Create New Category</title>
</head>
<body>
<div align="center">
<h1>Create New Product</h1>
<br/>
<form action="#" th:action="@{/saveproduct}" th:object="${product}"
    method="post">

    <table border="0" cellpadding="10">
        <tr>
            <td>Product Name:</td>
            <td><input type="text" th:field="*{productName}" /></td>
        </tr>
        <tr>
            <td>Category:</td>
            <td><input type="text" th:field="*{category}" /></td>
        </tr>
        <tr>
            <td>Price:</td>
            <td><input type="text" th:field="*{price}" /></td>
        </tr>
    </table>

```

```

        <tr>
            <td>Status:</td>
            <td><input type="text" th:field="*{status}" /></td>
        </tr>
        <tr>
            <td>size:</td>
            <td><input type="text" th:field="*{size}" /></td>
        </tr>

        <tr>
            <td colspan="2"><button type="submit">Save</button> </td>
        </tr>
    </table>
</form>

</div>
</body>
</html>

```

## Create product\_manage.html

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>Manage Product Unit</title>
</head>
<body>
<div align="center">
<h1>Products List</h1><br>
<h2><b><a href="/newproduct">Create New ProductList</a></b></h2>
<table border="1" cellpadding="10">
<thead>
<tr>
<th>Product id</th>
<th>Product Name</th>
<th>Category</th>
<th>Price</th>
<th>Status</th>
<th>size</th>
</tr>
</thead>
<tbody>
<tr th:each="product : ${listProduct}">
<td th:text="${product.id}">Product id</td>
<td th:text="${product.productName}">Product Name</td>
<td th:text="${product.category}">Category</td>
<td th:text="${product.price}">Price</td>
<td th:text="${product.status}">Status</td>
<td th:text="${product.size}">size</td>

```

```

</tr></tbody>
</table>
<a href="/logout">Logout</a>
</div>
</body>
</html>

```

## Create relogin.html

```

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<div align="center">
<h2>Change Password!!!</h2>
<table width="100%" height="100%" border="0" cellpadding="0" align="center">
<tr>
<td align="center" valign="middle">
<table class="table-bordered" width="350" border="0" cellpadding="3" cellspacing="3" bgcolor="#ffffff">
<form action="#" th:action="@{/}" th:object="${userchange}" method="post">
<tr>
<td height="25" colspan="2" align="left" valign="middle" bgcolor="#ffffff" class="style2">
<div align="center">
<strong>Change Password</strong>
</div>
</td>
</tr>
<tr>
<td>Username</td>
<td><input type="text" th:field="*{username}" name="username" /></td>
</tr>
<tr>
<td>New Password</td>
<td><input type="password" th:field="*{password}" name="password" /></td>
</tr>
<tr>
<td colspan="2"><button type="submit" class="btn btn-info" align="right">Change
Password</button></td>
</tr>
</form>
</table>
</td>
</tr>
</table>
</div>
</body>
</html>

```

## Create usernotfound.html



```
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:th="http://www.thymeleaf.org">
<head>
<meta charset="ISO-8859-1">
<title>User Not Found</title>
</head>
<body>
    <h1>User not found !</h1>
</body>
</html>
```