SECTION 1: REGULATORY CERTIFICATIONS & HIPAA BAA GOVERNANCE

Section 1.2 - HIPAA & HITECH Business Associate Agreement (BAA) Execution

We unconditionally execute the customer's standard HIPAA/HITECH Omnibus Rule Business Associate Agreement (BAA) and maintain annual independent third-party HIPAA Security Rule (45 CFR Part 164 Subpart C) and HITECH Subtitle D compliance audits across all optical transport, SD-WAN orchestration, Cloud Interconnect PoPs, and 24x7 US Healthcare NOC facilities.

Section 1.4 - HITRUST CSF v11 r2 & ISO/IEC 27001:2022 Certification Scope

All 9 Pacific Northwest and Western US Regional PoPs (POP-SEA-01 Seattle, POP-QCY-01 Quincy, POP-BEL-01 Bellevue, POP-TAC-01 Tacoma, POP-SPO-01 Spokane, POP-PDX-01 Portland, POP-EUG-01 Eugene, POP-BOI-01 Boise, and POP-SAC-01 Sacramento) hold active HITRUST CSF v11 r2 Validated Certifications and ISO/IEC 27001:2022 certificates.

Section 1.5 - AICPA SOC 2 Type II Continuous Compliance Attestation

Our latest 12-month AICPA SOC 2 Type II examination report (audited by Deloitte & Touche LLP) covers all five Trust Services Criteria (Security, Availability, Processing Integrity, Confidentiality, and Privacy) with zero high-severity exceptions.

SECTION 2: CRYPTOGRAPHIC STANDARDS & LINE-RATE ENCRYPTION

Section 2.1 - FIPS 140-3 Level 3 Line-Rate Encryption (IPsec & Optical MACsec)

All managed SD-WAN appliances enforce FIPS 140-3 Level 3 validated AES-256-GCM IPsec data-plane encryption with SHA-512 HMAC authentication and Diffie-Hellman Group 21 (ECDH P-521) Perfect Forward Secrecy. Underlying 10Gbps and 100Gbps optical wavelengths enforce hardware IEEE 802.1AE MACsec 256-bit encryption on Ciena 6500/Waveserver and Nokia 7750 SR interfaces.

SECTION 3: ZERO-TRUST CLINICAL VRF MICRO-SEGMENTATION

Section 3.2 - Clinical VRF Micro-Segmentation & Medical IoT Isolation

Each clinic uCPE appliance enforces up to 16 isolated VRF routing instances and stateful Layer-7 zone-based firewalls that strictly segregate Epic EHR clinical workstations, PACS/DICOM radiology imaging, Tele-ICU robotics, infusion pumps, and guest Wi-Fi traffic.

SECTION 4: KEY MANAGEMENT (BYOK / HYOK) & PENETRATION TESTING

Section 4.3 - FIPS 140-3 Key Management, Cloud HSM & Customer BYOK

Standard enterprise profiles utilize FIPS 140-3 Level 3 Cloud HSM key hierarchies with 60-minute automated IKEv2 re-keying and Customer-Held Key Encryption Keys (BYOK). Custom 15-minute IKEv2 re-key rotation intervals are supported via dedicated controller security profiles subject to joint branch CPE CPU benchmark validation.

Section 7.2 - Customer Red-Team & Vulnerability Testing Protocol

Customers may conduct annual and ad-hoc gray-box or black-box penetration testing against dedicated customer VRFs and CPE management enclaves upon providing a 24-hour electronic notification to our Healthcare SOC so automated core DDoS mitigation scrubbers can safelist the authorized testing source prefixes.