

Boom Test

Name	
Date	Employee #
Instructor's Name	
Ultimately who is responsible for the safe opera	ation of the aerial platform?
A. Operator	B. Equipment owner
2. Safety decals, warnings and operator hazards s	should be legible and should be:
A. Permanently affixed to each unit for operate to read and understand	ors B. In the qualified operator's lunch
C. In the equipment price list	
3. What are three hazards described in the operat	or's manual?
4. List at least three things the operator must che	ck on the machine as part of the pre-operation inspection.
5. List at least three things that the operator must	t check for as part of the work site inspection.

Boom Test 2 of 2

6. If the operator has any questions about the operation	ons or application of the machine he/she should:
A. Do the best he/she can under the circumstances	B. Experiment
C. Modify or make alterations as required	D. Stop operation and seek assistance from the employer, owner/dealer or manufacturer before further operation
7. You should take time to read the warning decals on	a lift because:
A. They will tell you how to start the unit	B. OSHA requires that you do
C. They contain information which may save your life	D. Both A and B
8. The five principles of safe machine operation are:	
 Avoid hazardous situations 	
Always perform a ins	pection before each work shift
Always perform a	prior to use
• Inspect theplace	
Only use the machine as it was intended	
10. It is the user's responsibility to keep and maintain ensure that a copy of each is stored:	the manuals as supplied by the manufacturer and to
11. All occupants of a self propelled boom must wear:	
11. All the necessary safety rules & operating instruction found in the	ons for safely operating an aerial work platform are
12. Aerial platforms are intended to be elevated only of surfaces.	on