**Markdown** is a simple way to format text that looks great on any device. It doesn't do anything fancy like change the font size, color, or type — just the essentials, using keyboard symbols you already know.

<div align="center">

**TRY OUR 10 MINUTE MARKDOWN TUTORIAL**

</div>

| Type | Or | … to Get |
|------|----|----|
| `*Italic*` | `_Italic_` | *Italic* |
| `**Bold**` | `__Bold__` | **Bold** |
| `# Heading 1` | `Heading 1`<br>`=========` | # Heading 1 |
| `## Heading 2` | `Heading 2`<br>`---------` | ## Heading 2 |
| `[Link](http://a.com)` | `[Link][1]`<br>`⋮`<br>`[1]: http://b.org` | [Link](#) |
| `![Image](http://url/a.png)` | `![Image][1]`<br>`⋮`<br>`[1]: http://url/b.jpg` | M↓ |
| `> Blockquote` | | Blockquote |
| `* List`<br>`* List`<br>`* List` | `- List`<br>`- List`<br>`- List` | • List<br>• List<br>• List |
| `1. One`<br>`2. Two`<br>`3. Three` | `1) One`<br>`2) Two`<br>`3) Three` | 1. One<br>2. Two<br>3. Three |

| Type | Or | … to Get |
|---|---|---|
| Horizontal Rule<br><br>`---` | Horizontal Rule<br><br>`***` | Horizontal Rule<br>――――――― |
| `` `Inline code` with backticks `` | | `Inline code` with backticks |
| ```` ``` ````<br>`# code block`<br>`print '3 backticks or'`<br>`print 'indent 4 spaces'`<br>```` ``` ```` | `····# code block`<br>`····print '3 backticks or'`<br>`····print 'indent 4 spaces'` | `# code block`<br>`print '3 backticks or'`<br>`print 'indent 4 spaces'` |

**Want to experiment with Markdown?**

Try our [10 minute interactive tutorial](#), or [play with the reference CommonMark implementation](#).

**Need more detail?**

Refer to [the official CommonMark spec](#), or [discuss CommonMark with us](#).