MIGHTYFIX
LIQUID NAILS

High Strength Synthetic Rubber Adhesive —

Technical Data Sheet



Brand	**MightyFix**	**Product Name**	**Liquid Nails**
Colour	**White**	**Net Content**	**300 mL**

PRODUCT DESCRIPTION

MightyFix Liquid Nails is a high-performance, solvent-based adhesive formulated from styrene-butadiene-styrene (SBS) thermoplastic elastomers. Commonly known as “liquid nails,” it delivers strong initial tack, rapid curing, and excellent elasticity, making it an efficient bonding solution to replace traditional nails and screws in decoration, furniture assembly, and general hardware applications.

PRODUCT FEATURES

- **Quick positioning –** generates high initial adhesive strength instantly, without the need for long-term clamping or support.
- **Convenient & non-destructive –** no drilling or nailing required; no noise or dust; no damage to walls or substrates. Suitable for spot or strip application and DIY friendly.
- **Rapid curing –** surface cures in as little as 60 seconds, reaching full strength within 48 hours — fast enough to replace iron nails.
- **Wide adhesion –** bonds firmly to most building materials, including wood, board, concrete, tile, stone, metal, glass, and most plastics, with excellent cross-material performance.
- **Underwater use –** cured adhesive maintains bond strength in wet and underwater conditions.

RECOMMENDED SUBSTRATES

Wood, timber, board and paneling, concrete, tile, natural stone, most metals, glass, and most plastics, with excellent cross-material adhesion.

TECHNICAL SPECIFICATIONS

Parameter	Unit	Typical Value
Appearance	--	Light-coloured paste
Specific Gravity	g/mL	1.01 – 1.4
Solid Content	%	68 – 72
Viscosity	Pa·s	300,000
Tack-Free Time	Minutes	5 – 10
Complete Curing	Hours	24
Shear Strength	kPa	20 – 30
Temperature Resistance (cured)	°C	-20 to 31

Properties listed are based on laboratory-controlled tests. All values are subject to a tolerance of 5–10%.

APPLICATION INSTRUCTIONS

- Ensure surfaces are clean, dry, and free of dust, oil, or grease.
- Cut the cartridge nozzle to the desired bead size and load into a standard caulking gun.
- Apply in a continuous bead or spot pattern to one surface and press materials firmly together.
- Hold or brace in position until initial tack is achieved (approx. 5–10 minutes). Allow 24 hours for complete curing.

IMPORTANT NOTES

Before the adhesive has fully cured, uncured residue can be cleaned with water. Once dry, cured residue can be removed by scraping or light grinding. This product may be used in conjunction with flooring installations. Adhesion strength may weaken at elevated temperatures; avoid application on metal surfaces that have been exposed to direct sunlight for extended periods.

PACKAGING

300 mL cartridge, White.

STORAGE

Store in a cool, dry place below 30°C, away from direct sunlight. Use within 12 months from the date of production.

The information contained in this Technical Data Sheet is provided in good faith and believed to be accurate at the time of issue. As application conditions and end-use vary, MightyFix makes no warranty, expressed or implied, regarding results obtained, and recommends the user conduct their own trials to determine suitability for a specific purpose. This document supersedes all previous versions.