

DW_fp_exp2


Floating-Point Base-2 Exponential (2^a)

Version, STAR and Download Information: [IP Directory](#)

Features and Benefits

- The precision is controlled by parameters, and covers formats in the IEEE Standard 754
- Exponents can range from 3 to 31 bits
- Fractional part of the floating-point number can range from 2 to 58 bits
- A parameter controls the use of denormal values.

Revision History



Description

The DW_fp_exp2 component computes the Base-2 exponential of a floating-point input *a*, delivering an output $z=2^a$ that is also a floating-point value.

The parameter *ieee_compliance* controls the use of denormals and NaNs, as done for other FP operators in this library. When *ieee_compliance* = 0, the operator takes NaN values as infinities, and denormals as zeros. When *ieee_compliance* = 1, the component accepts and generates denormalized values, handles NaN inputs, and delivers NaN outputs when appropriate. Independently of the value of this parameter, the floating-point format can be adjusted to match one of the formats defined in the IEEE Standard 754.

The output status is an 8-bit value that carries the status flags for the FP operation, as described in [Datapath Floating-Point Overview](#).

Table 1-1 Pin Description

Pin Name	Width	Direction	Function
a	<i>sig_width</i> + <i>exp_width</i> + 1 bits	Input	Input data
z	<i>sig_width</i> + <i>exp_width</i> + 1 bits	Output	Base-2 exponential = 2 ^a
status	8 bits	Output	See STATUS Flags in the <i>Datapath Floating-Point Overview</i>

Table 1-2 Parameter Description

Parameter	Values	Description
<i>sig_width</i>	2 to 58 ^a	Word length of fraction field of floating-point numbers <i>a</i> and <i>z</i> .
<i>exp_width</i>	3 to 31	Word length of biased exponent of floating-point numbers <i>a</i> and <i>z</i> .

Table 1-2 Parameter Description (Continued)

Parameter	Values	Description
ieee_compliance	0 or 1	When 1, the generated architecture is capable of dealing with denormals and NaNs.
arch	0 to 2 Default: 2	Implementation selection 0: Area optimized 1: Speed optimized 2: Implementation released in 2007.12

a. The synthesis model fully supports this range, as does the Verilog simulation model in VCS, but the VHDL simulation model (in all simulators) and the Verilog simulation model in non-VCS simulators are limited to a range of 2 - 36.

Table 1-3 Synthesis Implementations

Implementation Name	Function	License Feature Required
rtl	Implement using the Datapath Generator technology combined with static DesignWare components	DesignWare

Table 1-4 Simulation Model

Model	Function
DW02.DW_FP_EXP2_CFG_SIM	Design unit name for VHDL simulation
dw/dw02/src/DW_fp_exp2_sim.vhd	VHDL simulation model source code
dw/sim_ver/DW_fp_exp2.v	Verilog simulation model source code

Given the properties of algorithms to compute the exponential function, and the goal to have a component with good QoR, this component does not have rounding mode control as other FP components in the library. The output is bounded to have 1ulp error.

The *arch* parameter controls implementation alternatives for this component. Different values result in different numerical behavior, but the error on the computed values is always bounded by 1 ulp. You should experiment with this parameter to find out which value provides the best QoR for your design constraints and technology. Using *arch* = 0 (area optimized implementation) usually provides the best QoR for most time constraints.

Alternative Implementation of Floating-point Base-2 Exponential with DW_lp_fp_multifunc

The floating-point base-2 exponential operation can also be implemented by DW_lp_fp_multifunc component (a member of the minPower Library, licensed separately), which evaluates the value of floating-point base-2 exponential with 1 ulp error bound. There will be 1 ulp difference between the value from DW_lp_fp_multifunc and the value from DW_fp_exp2. Performance and area of the synthesis results are different between the DW_fp_exp2 and base-2 exponential implementation of the DW_lp_fp_multifunc, depending on synthesis constraints, library cells and synthesis environments. By comparing performance

and area between the base-2 exponential implementation of DW_lp_fp_multifunc and DW_fp_exp2 component, the DW_lp_fp_multifunc provides more choices for the better synthesis results.

Below is an example of the Verilog description for the floating-point base-2 exponential of the DW_lp_fp_multifunc. For more detailed information, see the [DW_lp_fp_multifunc](#) datasheet.

```
DW_lp_fp_multifunc #(sig_width, exp_width, ieee_compliance, 64) U1 (  
    .A(A) ,  
    .FUNC(16'h0040) ,  
    .RND(3'h0) ,  
    .Z(Z) ,  
    .STATUS(STATUS)  
);
```

For more information on the floating-point system defined for all the floating-point components in the DesignWare Library, including status bits and floating-point formats, refer to the [Datapath Floating-Point Overview](#).

Related Topics

- [Datapath Floating-Point Overview](#)
- [DesignWare Building Block IP Documentation Overview](#)

HDL Usage Through Component Instantiation - VHDL

```
library IEEE,DWARE;
use IEEE.std_logic_1164.all;
use DWARE.DW_Foundation_comp_arith.all;

entity DW_fp_exp2_inst is
    generic (
        inst_sig_width : POSITIVE := 10;
        inst_exp_width : POSITIVE := 5;
        inst_ieee_compliance : INTEGER := 0;
        inst_arch : INTEGER := 2
    );
    port (
        inst_a : in std_logic_vector(inst_sig_width+inst_exp_width downto 0);
        z_inst : out std_logic_vector(inst_sig_width+inst_exp_width downto 0);
        status_inst : out std_logic_vector(7 downto 0)
    );
end DW_fp_exp2_inst;

architecture inst of DW_fp_exp2_inst is

begin

    -- Instance of DW_fp_exp2
    U1 : DW_fp_exp2
        generic map (
            sig_width => inst_sig_width,
            exp_width => inst_exp_width,
            ieee_compliance => inst_ieee_compliance,
            arch => inst_arch
        )
        port map (
            a => inst_a,
            z => z_inst,
            status => status_inst
        );

end inst;

-- pragma translate_off
configuration DW_fp_exp2_inst_cfg_inst of DW_fp_exp2_inst is
    for inst
    end for; -- inst
end DW_fp_exp2_inst_cfg_inst;
-- pragma translate_on
```

HDL Usage Through Component Instantiation - Verilog

```
module DW_fp_exp2_inst( inst_a, z_inst, status_inst );

parameter inst_sig_width = 10;
parameter inst_exp_width = 5;
parameter inst_ieee_compliance = 0;
parameter inst_arch = 2;

input [inst_sig_width+inst_exp_width : 0] inst_a;
output [inst_sig_width+inst_exp_width : 0] z_inst;
output [7 : 0] status_inst;

// Instance of DW_fp_exp2
DW_fp_exp2 #(inst_sig_width, inst_exp_width, inst_ieee_compliance, inst_arch) U1 (
    .a(inst_a),
    .z(z_inst),
    .status(status_inst) );

endmodule
```

Revision History

For notes about this release, see the [DesignWare Building Block IP Release Notes](#).

For lists of both known and fixed issues for this component, refer to the [STAR report](#).

For a version of this datasheet with visible change bars, click [here](#).

Date	Release	Updates
July 2018	O-2018.06-SP1	<ul style="list-style-type: none">■ For STAR 9001366624, in Table 1-2 on page 1, clarified the range of <i>sig_width</i> for the VHDL simulation model (in all simulators) and the Verilog simulation model for non-VCS simulators■ Added this Revision History table and the document links on this page

Copyright Notice and Proprietary Information

© 2018 Synopsys, Inc. All rights reserved. This Synopsys software and all associated documentation are proprietary to Synopsys, Inc. and may only be used pursuant to the terms and conditions of a written license agreement with Synopsys, Inc. All other use, reproduction, modification, or distribution of the Synopsys software or the associated documentation is strictly prohibited.

Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

SYNOPSYS, INC., AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Trademarks

Synopsys and certain Synopsys product names are trademarks of Synopsys, as set forth at <https://www.synopsys.com/company/legal/trademarks-brands.html>.

All other product or company names may be trademarks of their respective owners.

Third-Party Links

Any links to third-party websites included in this document are for your convenience only. Synopsys does not endorse and is not responsible for such websites and their practices, including privacy practices, availability, and content.

Synopsys, Inc.
690 E. Middlefield Road
Mountain View, CA 94043
www.synopsys.com

