



DW01_incdec

Incrementer-Decrementer

Version, STAR and Download Information: [IP Directory](#)

Features and Benefits

- Parameterized word length

Description

DW01_incdec is an incrementer-decrementer. DW01_incdec either adds 1 to (INC_DEC=0) or subtracts 1 (INC_DEC=1) from an input number A to produce the output SUM.




Table 1-1 Pin Description

Pin Name	Width	Direction	Function
A	<i>width</i> bit(s)	Input	Input data
INC_DEC	1 bit	Input	Increment control 0 = increment ($A + 1$) 1 = decrement ($A - 1$)
SUM	<i>width</i> bit(s)	Output	Increment ($A + 1$) or decrement ($A - 1$)

Table 1-2 Parameter Description

Parameter	Values	Function
width	≥ 1	Word length of A and SUM

Table 1-3 Synthesis Implementations^a

Implementation Name	Function	License Feature Required
rpl	Ripple carry synthesis model	none
cla	Carry look-ahead synthesis model	none
pparch	Delay-optimized flexible parallel-prefix	DesignWare
apparch	Area-optimized flexible architecture that can be optimized for area, for speed, or for area, speed	DesignWare

a. During synthesis, Design Compiler will select the appropriate architecture for your constraints. However, you may force Design Compiler to use any architectures described in this table. For more, see [DesignWare Building Block IP User Guide](#)

Table 1-4 Obsolete Synthesis Implementations^a

Implementation	Function	Replacement Implementation
clf	Fast carry-look-ahead synthesis model	pparch

a. DC versions and DesignWare EST releases linked to DC versions prior to 2007.03 will still include these implementations.

Table 1-5 Simulation Models

Model	Function
DW01.DW01_INCDEC_CFG_SIM	Design unit name for VHDL simulation
dw/dw01/src/DW01_incdec_sim.vhd	VHDL simulation model source code
dw/sim_ver/DW01_incdec.v	Verilog simulation model source code

Related Topics

- [Math – Arithmetic Overview](#)
- [DesignWare Building Block IP Documentation Overview](#)

HDL Usage Through Operator Inferencing - VHDL

```
library IEEE;
use IEEE.std_logic_1164.all;
use IEEE.std_logic_arith.all;

entity DW01_incdec_oper is
  generic(wordlength: integer := 8 );
  port(in1      : in STD_LOGIC_VECTOR(wordlength-1 downto 0);
       inc_dec  : in STD_LOGIC;
       sum      : out STD_LOGIC_VECTOR(wordlength-1 downto 0) );
end DW01_incdec_oper;

architecture oper of DW01_incdec_oper is
  signal in_signed,sum_signed: SIGNED(wordlength-1 downto 0);
begin

  in_signed <= SIGNED(in1);
  process (in_signed, inc_dec)
  begin
    if (inc_dec = '1') then
      sum_signed <= in_signed - 1;
    else
      sum_signed <= in_signed + 1;
    end if;
  end process;
  sum <= STD_LOGIC_VECTOR(sum_signed);
end oper;
```

HDL Usage Through Operator Inferencing - Verilog

```
module DW01_incdec_oper(in1,inc_dec,sum);  
    parameter wordlength = 8;  
  
    input [wordlength-1:0] in1;  
    input inc_dec;  
    output [wordlength-1:0] sum;  
    reg [wordlength-1:0] sum;  
  
    always @(in1 or inc_dec)  
    begin  
        if (inc_dec == 1)  
            sum = in1 - 1;  
        else  
            sum = in1 + 1;  
        end  
    endmodule
```

HDL Usage Through Component Instantiation - VHDL

```
library IEEE,DWARE,DWARE;
use IEEE.std_logic_1164.all;
use DWARE.DWpackages.all;
use DWARE.DW_foundation_comp.all;

entity DW01_incdec_inst is
  generic ( inst_width : NATURAL := 8 );
  port ( inst_A          : in std_logic_vector(inst_width-1 downto 0);
        inst_INC_DEC    : in std_logic;
        SUM_inst        : out std_logic_vector(inst_width-1 downto 0) );
end DW01_incdec_inst;

architecture inst of DW01_incdec_inst is
begin
  -- Instance of DW01_incdec
  U1 : DW01_incdec
    generic map ( width => inst_width )
    port map ( A => inst_A, INC_DEC => inst_INC_DEC, SUM => SUM_inst );
end inst;

-- pragma translate_off
configuration DW01_incdec_inst_cfg_inst of DW01_incdec_inst is
  for inst
  end for; -- inst
end DW01_incdec_inst_cfg_inst;
-- pragma translate_on
```

HDL Usage Through Component Instantiation - Verilog

```
module DW01_incdec_inst( inst_A, inst_INC_DEC, SUM_inst );

    parameter width = 8;

    input [width-1 : 0] inst_A;
    input inst_INC_DEC;
    output [width-1 : 0] SUM_inst;

    // Instance of DW01_incdec
    DW01_incdec #(width)
        U1 ( .A(inst_A), .INC_DEC(inst_INC_DEC), .SUM(SUM_inst) );
endmodule
```

Copyright Notice and Proprietary Information

© 2018 Synopsys, Inc. All rights reserved. This Synopsys software and all associated documentation are proprietary to Synopsys, Inc. and may only be used pursuant to the terms and conditions of a written license agreement with Synopsys, Inc. All other use, reproduction, modification, or distribution of the Synopsys software or the associated documentation is strictly prohibited.

Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

SYNOPSYS, INC., AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Trademarks

Synopsys and certain Synopsys product names are trademarks of Synopsys, as set forth at <https://www.synopsys.com/company/legal/trademarks-brands.html>.

All other product or company names may be trademarks of their respective owners.

Third-Party Links

Any links to third-party websites included in this document are for your convenience only. Synopsys does not endorse and is not responsible for such websites and their practices, including privacy practices, availability, and content.

Synopsys, Inc.
690 E. Middlefield Road
Mountain View, CA 94043
www.synopsys.com

