


# DW\_fp\_addsub

## Floating-Point Adder/Subtractor

Version, STAR and Download Information: [IP Directory](#)

### Features and Benefits

- The precision is controlled by parameters, and covers formats in the IEEE standard
- Exponents can range from 3 to 31 bits
- Fractional part of the floating-point number can range from 2 to 253 bits
- Fully compatible with the IEEE 754 Floating-point standard<sup>1</sup> with proper set of parameters
- DesignWare datapath generator is employed for better power and QoR



### Description

DW\_fp\_addsub is a floating-point component that is capable of adding or subtracting two floating-point values, *a* and *b*, to produce a floating-point result *z*. The control over the arithmetic operation is done through the input *op*. The input *rnd* is a 3-bit rounding mode (see [Rounding Modes](#) in the *Datapath Floating-Point Overview*) and the output *status* is an 8-bit status flag.

**Table 1-1 Pin Description**

Pin Name	Width	Direction	Function
a	<i>sig_width</i> + <i>exp_width</i> + 1 bits	Input	Input data
b	<i>sig_width</i> + <i>exp_width</i> + 1 bits	Input	Input data
op	1 bit	Input	Defines the operation: 0: Addition 1: Subtraction
z	<i>sig_width</i> + <i>exp_width</i> + 1 bits	Output	<i>a op b</i>
status	8 bits	Output	See <a href="#">STATUS Flags</a> in the <i>Datapath Floating-Point Overview</i>
rnd	3 bits	Input	Rounding mode

1. For more information, see [IEEE 754 Compatibility](#) in the *Datapath Floating-Point Overview*.

**Table 1-2 Parameter Description**

Parameter	Values	Description
sig_width	2 to 253 bits Default: 23	Word length of fraction field of floating-point numbers a, b, and z
exp_width	3 to 31 bits Default: 8	Word length of biased exponent of floating-point numbers a, b, and z
ieee_compliance	0 or 1 Default: 0	When 1, the generated architecture is fully compliant with IEEE 754 standard, including the use of denormals and NaNs.

**Table 1-3 Synthesis Implementations**

Implementation Name	Function	License Feature Required
rtl	Area-optimized synthesis model	DesignWare
str	Delay-optimized synthesis model	DesignWare

**Table 1-4 Simulation Models**

Model	Function
DW02.DW_FP_ADDSUB_CFG_SIM	Design unit name for VHDL simulation
dw/dw02/src/DW_fp_addsub_sim.vhd	VHDL simulation model source code
dw/sim_ver/DW_fp_addsub.v	Verilog simulation model source code

**Table 1-5 Functional Description**

a	b	op	status <sup>a</sup>	z <sup>b</sup>
a (floating-point)	b (floating-point)	0	*	a + b (floating-point)
a (floating-point)	b (floating-point)	1	*	a - b (floating-point)

a. The details of status flags, if used, can be found in [Table 9](#) of the Datapath Floating-Point Overview.

b. The actual value of the result is defined by the rounding mode.

The parameter *ieee\_compliance* controls the functionality of this component. When the parameter is 0, the component is backward compatible with the DW\_add\_fp component (previously available in this library). The DW\_add\_fp does not work with NaNs and denormals. NaNs are considered infinities and denormals are considered zeros.

When the *ieee\_compliance* parameter is set to 1, the component is fully compliant with the IEEE 754 standard, and therefore operates with NaNs and denormals.

For more information about the floating-point system defined for all the DW\_fp components, including status flag bits, and integer and floating-point formats, refer to the topic titled [Datapath Floating-Point Overview](#).

## Related Topics

- [Datapath Floating-Point Overview](#)
- [DesignWare Building Block IP Documentation Overview](#)

## HDL Usage Through Component Instantiation - Verilog

```
module DW_fp_addsub_inst( inst_a, inst_b, inst_rnd, inst_op, z_inst,
                        status_inst );

    parameter sig_width = 23;
    parameter exp_width = 8;
    parameter ieee_compliance = 0;

    input [sig_width+exp_width : 0] inst_a;
    input [sig_width+exp_width : 0] inst_b;
    input [2 : 0] inst_rnd;
    input inst_op;
    output [sig_width+exp_width : 0] z_inst;
    output [7 : 0] status_inst;

    // Instance of DW_fp_addsub
    DW_fp_addsub #(sig_width, exp_width, ieee_compliance)
        U1 ( .a(inst_a), .b(inst_b), .rnd(inst_rnd),
            .op(inst_op), .z(z_inst), .status(status_inst) );

endmodule
```

## HDL Usage Through Component Instantiation - VHDL

```
library IEEE,DWARE;
use IEEE.std_logic_1164.all;
use DWARE.dw_foundation_comp.all;
-- If using numeric types from std_logic_arith package,
-- comment the preceding line and uncomment the following line:
-- use DWARE.DW_Foundation_comp_arith.all;

entity DW_fp_addsub_inst is
  generic (
    inst_sig_width : POSITIVE := 23;
    inst_exp_width : POSITIVE := 8;
    inst_ieee_compliance : INTEGER := 0
  );
  port (
    inst_a : in std_logic_vector(inst_sig_width+inst_exp_width downto 0);
    inst_b : in std_logic_vector(inst_sig_width+inst_exp_width downto 0);
    inst_rnd : in std_logic_vector(2 downto 0);
    inst_op : in std_logic;
    z_inst : out std_logic_vector(inst_sig_width+inst_exp_width downto 0);
    status_inst : out std_logic_vector(7 downto 0)
  );
end DW_fp_addsub_inst;

architecture inst of DW_fp_addsub_inst is

begin
  -- Instance of DW_fp_addsub
  U1 : DW_fp_addsub
    generic map ( sig_width => inst_sig_width,
                  exp_width => inst_exp_width,
                  ieee_compliance => inst_ieee_compliance )
    port map ( a => inst_a, b => inst_b, rnd => inst_rnd,
              op => inst_op, z => z_inst, status => status_inst );

end inst;

-- pragma translate_off
configuration DW_fp_addsub_inst_cfg_inst of DW_fp_addsub_inst is
  for inst
  end for; -- inst
end DW_fp_addsub_inst_cfg_inst;
-- pragma translate_on
```

## Copyright Notice and Proprietary Information

© 2018 Synopsys, Inc. All rights reserved. This Synopsys software and all associated documentation are proprietary to Synopsys, Inc. and may only be used pursuant to the terms and conditions of a written license agreement with Synopsys, Inc. All other use, reproduction, modification, or distribution of the Synopsys software or the associated documentation is strictly prohibited.

### Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

### Disclaimer

SYNOPSYS, INC., AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

### Trademarks

Synopsys and certain Synopsys product names are trademarks of Synopsys, as set forth at <https://www.synopsys.com/company/legal/trademarks-brands.html>.

All other product or company names may be trademarks of their respective owners.

### Third-Party Links

Any links to third-party websites included in this document are for your convenience only. Synopsys does not endorse and is not responsible for such websites and their practices, including privacy practices, availability, and content.

Synopsys, Inc.  
690 E. Middlefield Road  
Mountain View, CA 94043  
[www.synopsys.com](http://www.synopsys.com)

