


oauth2-passkey

Passwordless Authentication Library for Rust

Kimitoshi Takahashi | Tokyo Rust Show & Tell | 2026/03/31




GitHub




Author

Try it Yourself!



passkey-demo.ccmp.jp



Give it a try & tell me your thoughts!


- *Admin access granted to all*
- *Privacy masked*
- *Ephemeral: data resets on restart*

Flow: Google Login → Passkey Setup

Step-by-step:


1. **OAuth2 Login**
→ create user linked with Google account
2. **Passkey Promotion**
→ register Passkey → link to user
3. **Next Login**
→ use either Passkey or Google OAuth2

Internal DB structure:




One user can have multiple OAuth2 accounts and multiple Passkey credentials.

How OAuth2/OIDC Works



Page-redirect: Google → code → id_token → session

How Passkey/WebAuthn Works



JavaScript-driven: challenge → sign → verify → session

Usage: Add Auth in 3 Steps

Step 1: Configure .env (swap sqlite → postgres/mysql to change DB):

```
GENERIC_DATA_STORE_TYPE=sqlite
GENERIC_DATA_STORE_URL='sqlite:/tmp/auth.db'
GENERIC_CACHE_STORE_TYPE=memory
OAUTH2_GOOGLE_CLIENT_ID='xxx.apps.googleusercontent.com'
```

Steps 2-3: Initialize and merge router — login UI, account mgmt & admin panel built-in.

```
use oauth2_passkey_axum::{AuthUser, oauth2_passkey_full_router};

#[tokio::main]
async fn main() -> Result<(), Box<dyn std::error::Error>> {
    dotenv().ok();
    oauth2_passkey_axum::init().await?; // 2. Initialize
    let app = Router::new()
        .route("/", get(index))
        .merge(oauth2_passkey_full_router()); // 3. Merge router
    spawn_http_server(3001, app).await?;
    Ok(())
}
```

Page Protection

AuthUser extractor (via FromRequestParts):

```
// Required auth – redirects to login if not authenticated
async fn protected(user: AuthUser) -> impl IntoResponse { ... }

// Optional auth – allows anonymous access
async fn public(user: Option<AuthUser>) -> impl IntoResponse { ... }
```

Middleware — choose 401 vs redirect, and skip DB when user info isn't needed:

```
let app = Router::new()
    .route("/api/1", get(h1))
    .route_layer(from_fn(is_authenticated_401))
    .route("/api/2", get(h2))
    .route_layer(from_fn(is_authenticated_user_401));

async fn h1(Extension(csrf): Extension<CsrfToken>) { ... }
async fn h2(Extension(user): Extension<AuthUser>) { ... }
```

is_authenticated_{Variant}

Variant	Error	DB?	Ext.
401	401	No	CsrfToken
user_401	401	Yes	AuthUser
redirect	Login	No	CsrfToken
user_redirect	Login	Yes	AuthUser

Storage & LazyLock Pattern

Switch DB by changing .env only — no code changes:

```
# Data store (pick one):
GENERIC_DATA_STORE_TYPE=sqlite
GENERIC_DATA_STORE_URL='sqlite:/tmp/auth.db'

GENERIC_DATA_STORE_TYPE=postgres
GENERIC_DATA_STORE_URL='postgres://id:pw@host:5432/db'

GENERIC_DATA_STORE_TYPE=mysql
GENERIC_DATA_STORE_URL='mysql://id:pw@host:3306/db'
```

```
# Cache store (pick one):
GENERIC_CACHE_STORE_TYPE=memory

GENERIC_CACHE_STORE_TYPE=redis
GENERIC_CACHE_STORE_URL='redis://host:6379'
```

SQLite/PostgreSQL/MySQL abstracted via DataStore trait, held in a LazyLock:

```
static GENERIC_DATA_STORE: LazyLock<Mutex<Box<dyn DataStore>>>
    = LazyLock::new(|| { /* reads env, builds pool */ });

// Dispatch – no runtime downcasting needed
let store = GENERIC_DATA_STORE.lock().await;
match (store.as_sqlite(), store.as_postgres(), store.as_mysql()) {
    (Some(pool), _, _) => do_sqlite(pool).await?,
    (_, Some(pool), _) => do_postgres(pool).await?,
    (_, _, Some(pool)) => do_mysql(pool).await?,
    _ => return Err(...),
}
```


Why LazyLock instead of Axum State?

- **Axum State:** user composes AppState; 80+ internal fns all need &State
- **LazyLock:** just init() — globals accessed directly; fail-fast at startup

Integrating with Your App's Database

Your app adds its own tables linked by AuthUser.id:

```
async fn create_todo(
    State(state): State<AppState>,
    user: AuthUser, // from oauth2-passkey
    Form(form): Form<TodoForm>,
) -> Result<Response, ...> {
    db::create_todo(
        &state.pool,
        &user.id, // → todos.user_id
        &form.title
    ).await?;
    Ok(Redirect::to("/").into_response())
}
```



Summary

- **Library:** OAuth2 + Passkey/WebAuthn auth for Axum; Passkey Promotion, Built-in UI, Account Linking
- **Setup:** init().await? + merge(oauth2_passkey_full_router()) — 3 lines to add auth
- **Protect:** AuthUser extractor or is_authenticated_* middleware (401/redirect, ±DB query)
- **Storage:** SQLite/PostgreSQL/MySQL + Memory/Redis — switch via .env, no code changes

- **crates.io:** oauth2-passkey, oauth2-passkey-axum
- **GitHub:** github.com/ktaka-ccmp/oauth2-passkey
- **Demo:** passkey-demo.ccmp.jp