

5.40 atmost1

DESCRIPTION

LINKS

Origin	[365]
Constraint	<code>atmost1(SETS)</code>
Synonym	<code>pair_atmost1.</code>
Argument	<code>SETS : collection(s—svar, c—int)</code>
Restrictions	<code>required(SETS, [s, c])</code> <code>SETS.c ≥ 1</code>
Purpose	<p>Given a collection of set variables s_1, s_2, \dots, s_n and their respective cardinality c_1, c_2, \dots, c_n, the <code>atmost1</code> constraint forces the following two conditions:</p> <ul style="list-style-type: none"> • $\forall i \in [1, n] : s_i = c_i$, • $\forall i, j \in [1, n] (i < j) : s_i \cap s_j \leq 1$.
Example	$\left(\begin{array}{cc} s - \{5, 8\} & c - 2, \\ s - \{5\} & c - 1, \\ s - \{5, 6, 7\} & c - 3, \\ s - \{1, 4\} & c - 2 \end{array} \right)$ <p>The <code>atmost1</code> constraint holds since:</p> <ul style="list-style-type: none"> • $\{5, 8\} = 2, \{5\} = 1, \{5, 6, 7\} = 3, \{1, 4\} = 2$. • $\{5, 8\} \cap \{5\} \leq 1, \{5, 8\} \cap \{5, 6, 7\} \leq 1, \{5, 8\} \cap \{1, 4\} \leq 1,$ $\{5\} \cap \{5, 6, 7\} \leq 1, \{5\} \cap \{1, 4\} \leq 1,$ $\{5, 6, 7\} \cap \{1, 4\} \leq 1$.
Typical	<code> SETS > 1</code>
Symmetries	<ul style="list-style-type: none"> • Items of <code>SETS</code> are permutable. • All occurrences of two distinct values of <code>SETS.s</code> can be swapped; all occurrences of a value of <code>SETS.s</code> can be renamed to any unused value.
Arg. properties	Contractible wrt. <code>SETS</code> .
Remark	When we have only two set variables the <code>atmost1</code> constraint was called <code>pair_atmost1</code> in [428].

Algorithm	C. Bessière <i>et al.</i> have shown in [68] that it is NP-hard to enforce bound consistency for the <code>atmost1</code> constraint. Consequently, following the first filtering algorithm from A. Sadler and C. Gervet [365], W.-J. van Hove and A. Sabharwal have proposed an algorithm that enforces bound-consistency when the <code>atmost1</code> constraint involves only two sets variables [428].
Systems	<code>at_most1</code> in MiniZinc .
Keywords	constraint arguments: constraint involving set variables. constraint type: predefined constraint. filtering: bound-consistency.