5.59 cardinality_atmost

DESCRIPTION LINKS GRAPH AUTOMATON

Origin

Derived from global_cardinality.

Constraint

cardinality_atmost(ATMOST, VARIABLES, VALUES)

Arguments

ATMOST : dvar

VARIABLES : collection(var-dvar)
VALUES : collection(val-int)

Restrictions

```
ATMOST \geq 0
ATMOST \leq |VARIABLES|
required(VARIABLES, var)
required(VALUES, val)
distinct(VALUES, val)
```

Purpose

ATMOST is the maximum number of occurrences of each value of VALUES within the variables of the collection VARIABLES.

Example

```
(2,\left\langle 2,1,7,1,2\right\rangle ,\left\langle 5,7,2,9\right\rangle )
```

In this example, values 5, 7, 2 and 9 occur respectively 0, 1, 2 and 0 times within the collection $\langle 2,1,7,1,2\rangle$. As a consequence, the cardinality_atmost constraint holds since its first argument ATMOST is assigned to the maximum number of occurrences 2.

Typical

```
\begin{split} & \texttt{ATMOST} > 0 \\ & \texttt{ATMOST} < |\texttt{VARIABLES}| \\ & |\texttt{VARIABLES}| > 1 \\ & |\texttt{VALUES}| > 0 \\ & |\texttt{VARIABLES}| > |\texttt{VALUES}| \end{split}
```

Symmetries

- Items of VARIABLES are permutable.
- Items of VALUES are permutable.
- An occurrence of a value of VARIABLES.var that does not belong to VALUES.val can be replaced by any other value that also does not belong to VALUES.val.
- All occurrences of two distinct values in VARIABLES.var or VALUES.val can be swapped; all occurrences of a value in VARIABLES.var or VALUES.val can be renamed to any unused value.

Arg. properties

Functional dependency: ATMOST determined by VARIABLES and VALUES.

Usage

An application of the cardinality_atmost constraint is to enforce a maximum use of values.

20030820 757

RemarkThis is a restricted form of a variant of the among constraint and of the global_cardinality constraint. In the original global_cardinality constraint, one

specifies for each value its minimum and maximum number of occurrences.

Algorithm See global_cardinality [342].

See also generalisation: global_cardinality (single count variable replaced by an individ-

 $ual \verb| count variable| for each value|), \verb| multi_inter_distance| (window of size 1 replaced)|$

by window of DIST consecutive values).

implied by: among.

Keywords application area: assignment.

characteristic of a constraint: automaton, automaton with array of counters.

constraint arguments: pure functional dependency.

constraint type: value constraint.

filtering: arc-consistency.

final graph structure: acyclic, bipartite, no loop.

modelling: at most, functional dependency.

 Arc input(s)
 VARIABLES VALUES

 Arc generator
 PRODUCT → collection (variables, values)

 Arc arity
 2

 Arc constraint(s)
 variables.var = values.val

 Graph property(ies)
 MAX_ID = ATMOST

 Graph class
 • ACYCLIC

 • BIPARTITE
 • NO_LOOP

Graph model

Parts (A) and (B) of Figure 5.133 respectively show the initial and final graph associated with the **Example** slot. Since we use the **MAX_ID** graph property, the vertex that has the maximum number of predecessor is stressed with a double circle.




Figure 5.133: Initial and final graph of the cardinality_atmost constraint

20030820 759

Automaton

Figure 5.134 depicts the automaton associated with the cardinality_atmost constraint. To each variable VAR $_i$ of the collection VARIABLES corresponds a 0-1 signature variable S_i . The following signature constraint links VAR $_i$ and S_i : VAR $_i \in \text{VALUES} \Leftrightarrow S_i$.




Figure 5.134: Automaton of the cardinality_atmost constraint