

## 5.207 k\_disjoint

	DESCRIPTION	LINKS	GRAPH
Origin	Derived from <a href="#">disjoint</a>		
Constraint	<code>k_disjoint(SETS)</code>		
Type	VARIABLES : <a href="#">collection</a> (var—dvar)		
Argument	SETS : <a href="#">collection</a> (set — VARIABLES)		
Restrictions	<a href="#">required</a> (VARIABLES, var) $ \text{VARIABLES}  \geq 1$ <a href="#">required</a> (SETS, set) $ \text{SETS}  > 1$		
Purpose	Given $ \text{SETS} $ sets of domain variables, the <code>k_disjoint</code> constraint forces that no value is assigned to more than one set.		
Example	$(\langle \text{set} - \langle 1, 9, 1, 5 \rangle, \text{set} - \langle 2, 7, 7, 0, 6, 8 \rangle, \text{set} - \langle 4, 4, 3 \rangle \rangle)$		
	The <code>k_disjoint</code> constraint holds since: <ul style="list-style-type: none"> <li>• The set of values <math>\{1, 5, 9\}</math> and <math>\{0, 2, 6, 7, 8\}</math> respectively assigned to the variables of the first and second collections have an empty intersection.</li> <li>• The set of values <math>\{1, 5, 9\}</math> and <math>\{3, 4\}</math> respectively assigned to the variables of the first and third collections have an empty intersection.</li> <li>• The set of values <math>\{0, 2, 6, 7, 8\}</math> and <math>\{3, 4\}</math> respectively assigned to the variables of the second and third collections have an empty intersection.</li> </ul>		
Typical	$ \text{VARIABLES}  > 1$		
Symmetries	<ul style="list-style-type: none"> <li>• Items of SETS are <a href="#">permutable</a>.</li> <li>• Items of SETS.set are <a href="#">permutable</a>.</li> <li>• An occurrence of a value of VARIABLES.var can be <a href="#">replaced</a> by any value of VARIABLES.var.</li> <li>• All occurrences of two distinct values of SETS.set.var can be <a href="#">swapped</a>; all occurrences of a value of SETS.set.var can be <a href="#">renamed</a> to any unused value.</li> </ul>		
Arg. properties	<a href="#">Contractible</a> wrt. SETS.		
See also	<a href="#">part of system of constraints: disjoint.</a> <a href="#">used in graph description: disjoint.</a>		

**Keywords**

**characteristic of a constraint:** disequality.

**constraint type:** system of constraints, decomposition, value constraint.

**modelling:** empty intersection.

Arc input(s)	SETS
Arc generator	$\text{CLIQUE}(<) \mapsto \text{collection}(\text{set1}, \text{set2})$
Arc arity	2
Arc constraint(s)	$\text{disjoint}(\text{set1.set}, \text{set2.set})$
Graph property(ies)	$\text{NARC} =  \text{SETS}  * ( \text{SETS}  - 1) / 2$

**Graph model** Parts (A) and (B) of Figure 5.479 respectively show the initial and final graph associated with the **Example** slot. To each vertex corresponds a collection of variables, while to each arc corresponds a **disjoint** constraint.




Figure 5.479: Initial and final graph of the  $k_{\text{disjoint}}$  constraint

20050816

1477