



Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Switch>en

Switch#conf t

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#int fa0/1

Switch(config-if)#int vlan 1

^  
% Invalid input detected at '^' marker.

Switch(config-if)#int vlan 1

Switch(config-if)#no sh

Switch(config-if)#

%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

Switch(config-if)#ip address 192.168.0.2 255.255.255.0

Switch(config-if)#exit

Switch(config)#

Copy

Port	Link	VLAN	IP Address	MAC Address
FastEthernet0/1	Up	1	--	000A.4197.D301
FastEthernet0/2	Down	1	--	000A.4197.D302
FastEthernet0/3	Down	1	--	000A.4197.D303
FastEthernet0/4	Down	1	--	000A.4197.D304
FastEthernet0/5	Down	1	--	000A.4197.D305
FastEthernet0/6	Down	1	--	000A.4197.D306
FastEthernet0/7	Down	1	--	000A.4197.D307
FastEthernet0/8	Down	1	--	000A.4197.D308
FastEthernet0/9	Down	1	--	000A.4197.D309
FastEthernet0/10	Down	1	--	000A.4197.D30A
FastEthernet0/11	Down	1	--	000A.4197.D30B
FastEthernet0/12	Down	1	--	000A.4197.D30C
FastEthernet0/13	Down	1	--	000A.4197.D30D
FastEthernet0/14	Down	1	--	000A.4197.D30E
FastEthernet0/15	Down	1	--	000A.4197.D30F
FastEthernet0/16	Down	1	--	000A.4197.D310
FastEthernet0/17	Down	1	--	000A.4197.D311
FastEthernet0/18	Down	1	--	000A.4197.D312
FastEthernet0/19	Down	1	--	000A.4197.D313
FastEthernet0/20	Down	1	--	000A.4197.D314
FastEthernet0/21	Down	1	--	000A.4197.D315
FastEthernet0/22	Down	1	--	000A.4197.D316
FastEthernet0/23	Down	1	--	000A.4197.D317
FastEthernet0/24	Down	1	--	000A.4197.D318
GigabitEthernet0/1	Down	1	--	000A.4197.D319
GigabitEthernet0/2	Down	1	--	000A.4197.D31A
Vlan1	Up	1	192.168.0.2/24	0004.9A7C.8191

FastEthernet0/6

FastEthernet0/7

FastEthernet0/8

net0/9

net0/10

net0/11

net0/12

net0/13

net0/14

net0/15

net0/16

net0/17

net0/18

net0/19

net0/20

net0/21

net0/22

net0/23

net0/24

hernet0/1

hernet0/2

уя коман

учаться д

удалённо

оющую ко

elnet 192.1

g 192.168.0

ection to 1

инение 3

ить наст

```

Cisco Packet Tracer PC Command Line 1.0
C:\>telnet 192.168.0.2
Trying 192.168.0.2 ...Open

```

Copyright (c) 1986-2013 by Cisco Systems, Inc.  
Compiled Wed 26-Jun-13 02:49 by mnguyen

Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Switch>en

Switch#conf t

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#int fa0/1

Switch(config-if)#int vlan 1

% Invalid input detected at '^' marker.

Switch(config-if)#int vlan 1

Switch(config-if)#no sh

Switch(config-if)#

%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

Switch(config-if)#ip address 192.168.0.2 255.255.255.0

Switch(config-if)#exit

Switch(config)#line vty 0 5

Switch(config-line)#pass 111

Switch(config-line)#

Copy

```
Switch>show vlan
```

VLAN Name		Status	Ports
1	default	active	Fa0/1, Fa0/2, Fa0/3, Fa0/4 Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
1002	fddi-default	active	
1003	token-ring-default	active	
1004	fddinet-default	active	
1005	trnet-default	active	

  

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
1002	fddi	101002	1500	-	-	-	-	-	0	0
1003	tr	101003	1500	-	-	-	-	-	0	0
1004	fdnet	101004	1500	-	-	-	ieee	-	0	0
1005	trnet	101005	1500	-	-	-	ibm	-	0	0

--More--

Copy

Paste

```
% Unknown command or computer name, or unable to find comp
```

```
Switch>
```

```
Switch>en
```

```
Switch#conf t
```

```
Enter configuration commands, one per line. End with CNTL
```

```
Switch(config)#line vty 0 5
```

```
Switch(config-line)#pass 111
```

```
Switch(config-line)#enable secret 123
```

```
Switch(config)#
```

```
Switch>en
```

```
Password:
```

```
Switch#conf t
```

```
Enter configuration commands, one per line. End with CNTL/Z.
```

```
Switch(config)#
```