



```

Router(config-if)#ip address 192.168.0.1 255.255.255.0
Router(config-if)#ip address 192.168.0.1 255.255.255.0
Router(config-if)#
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#
Router(config-if)#ip address 192.168.0.3 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

Router(config-if)#exit
Router(config)#int fa0/1
Router(config)#
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address
% Incomplete command.
Router(config-if)#ip address
% Incomplete command.
Router(config-if)#int fa0/0
Router(config-if)#ip address 192.168.0.3 255.255.255.0
Router(config-if)#no sh
Router(config-if)#exit
Router(config)#int fa0/1
Router(config-if)#ip address 192.168.3.1 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Router(config-if)#exit
Router(config)#

```

Copy

```

Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address 192.168.1.1 255.255.255.0
Router(config-if)#ip address 192.168.1.1 255.255.255.0
Router(config-if)#
Router(config-if)#
Router(config-if)#
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address
% Incomplete command.
Router(config-if)#ip address
% Incomplete command.
Router(config-if)#
Router(config-if)#exit
Router(config)#int fa0/1
Router(config-if)#ip address 192.168.1.3 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

```

Copy

Paste

```

Router(config-if)#ip address
% Incomplete command.
Router(config-if)#ip address
% Incomplete command.
Router(config-if)#
Router(config-if)#exit
Router(config)#int fa0/1
Router(config-if)#ip address 192.168.1.3 255.255.255.0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Router(config-if)#exit
Router(config)#int fa0/0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)#ip address 192.168.3.2 255.255.255.0
Router(config-if)#no sh
Router(config-if)#

```

Copy

Paste

- GLOBAL
- Settings
- Algorithm Settings
- INTERFACE
- FastEthernet0
- Bluetooth

Global Settings

Display Name PC0

Interfaces FastEthernet0

Gateway/DNS IPv4

☐ DHCP

☒ Static

Default Gateway 192.168.0.3

DNS Server

Gateway/DNS IPv6

☐ Automatic

☒ Static

Default Gateway

DNS Server

Global Settings

Display Name

Interfaces

Gateway/DNS IPv4

☐ DHCP

☒ Static

Default Gateway

DNS Server

Gateway/DNS IPv6

☐ Automatic

☒ Static

Default Gateway

DNS Server

```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthe:
```

```
Router(config)#ip route 0.0.0.0 0.0.0.0 192.168.3.2
```

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 192.168.1.1

Pinging 192.168.1.1 with 32 bytes of data:

Reply from 192.168.0.3: Destination host unreachable.

Reply from 192.168.0.3: Destination host unreachable.

Reply from 192.168.0.3: Destination host unreachable.

Request timed out.

Ping statistics for 192.168.1.1:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>

C:\>ping 192.168.1.3

Pinging 192.168.1.3 with 32 bytes of data:

Reply from 192.168.1.3: bytes=32 time<1ms TTL=254

Reply from 192.168.1.3: bytes=32 time<1ms TTL=254

Reply from 192.168.1.3: bytes=32 time<1ms TTL=254

Reply from 192.168.1.3: bytes=32 time<1ms TTL=254

Ping statistics for 192.168.1.3:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms