

```
Motherboard serial number      : FOC10093R12
Power supply serial number     : AZS1007032H
Model revision number          : B0
Motherboard revision number    : B0
Model number                   : WS-C2960-24TT-L
System serial number           : FOC1010X104
Top Assembly Part Number       : 800-27221-02
Top Assembly Revision Number   : A0
Version ID                     : V02
CLEI Code Number               : COM3L00BRA
Hardware Board Revision Number : 0x01
```

Switch	Ports	Model	SW Version	SW Image
*	1 26	WS-C2960-24TT-L	15.0(2)SE4	C2960-LANBASEK9-M

```
Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnnguyen
```

Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up

```
Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname lsw
lsw(config)#
```

Copy

```
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up


Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname lsw
lsw(config)#int vlan 1
lsw(config-if)#no sh

lsw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

lsw(config-if)#ip address 192.168.0.2 255.255.255.0
lsw(config-if)#exit
lsw(config)#
```

Co

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up

```
Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname lsw
lsw(config)#int vlan 1
lsw(config-if)#no sh
```

```
lsw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up
```

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

```
lsw(config-if)#ip address 192.168.0.2 255.255.255.0
lsw(config-if)#exit
lsw(config)#line vty 0 4
lsw(config-line)#pass 111
lsw(config-line)#enable secret 123
lsw(config)#
```

Copy

Paste

C:\>ping 192.168.0.3

Pinging 192.168.0.3 with 32 bytes of data:

Request timed out.

Reply from 192.168.0.3: bytes=32 time<1ms TTL=255

Reply from 192.168.0.3: bytes=32 time<1ms TTL=255

Reply from 192.168.0.3: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.0.3:

Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>