

Continuous Time Dynamic Modeling in dynr and OpenMx

Michael D. Hunter

School of Psychology
Georgia Institute of Technology

July 9, 2017
Dynamic Modeling Workshop
IMPS
New York City, New York

Plan

- ▶ Discrete vs Continuous Time
- ▶ Software
- ▶ General Modeling
- ▶ Examples


Discrete-Time Parameters Depend on the Lag

Simulation Design


- ▶ 2-occasion data
- ▶ 3 variables
- ▶ 100 individuals
- ▶ Continuous generating process
- ▶ Sampled in discrete time
- ▶ Measurement Interval: 7 hours to 1 year
- ▶ Fit discrete- & continuous-time structural equation models to each sampling interval
- ▶ Compare parameters across conditions

Discrete-Time Parameters Depend on the Lag

Condidate Models




Cross-lagged Panel Model




Continuous-Time Structural
Equation Model


Discrete-Time Parameters Depend on the Lag



The Dependence has an Analytic Form



Continuous-Time Parameters Do Not Depend on Lag



Summary

- ▶ One-occasion mediation has no causal direction.
- ▶ Cross-lagged panel designs obtain different estimates for each measurement interval.
- ▶ Continuous-time models obtain constant estimates for every measurement interval.
- ▶ Estimated discrete-time parameters match those analytically predicted.
- ▶ Continuous-time models even work on two-occasion data!


Implications

- ▶ Researchers using different lags will find different results, even when the process is the same!
- ▶ Researchers using the same lag will find different results, depending on which lag they pick!
- ▶ Also applies to pre-test post-test designs!

Limitations

- ▶ Continuous convergence problems?
- ▶ Operation with real data?
- ▶ Mis-specified/imperfect models?

Software



OpenMx \geq 2.0

Recent Features

- ▶ objective function = $\underbrace{\text{expectation function}}_{\text{data generation}} + \underbrace{\text{fit function}}_{\text{data comparison}}$
- ▶ Multiple optimizers: SLSQP, NPSOL, CSOLNP
- ▶ New Models: Item factor analysis, GREML, state space, LISREL
- ▶ New Helpers: mxFactorScores, mxGenerateData, mxMI, mxRefModels, mxTryHard

OpenMx \geq 2.7

More Recent Features

- ▶ Handy S3 methods: logLik, confint, anova, coef, simulate
- ▶ New Fit Functions for multigroup, mixtures, hidden Markov models, weighted least squares
- ▶ Utilities: mxSE, mxAutoStart, nonparametric and parametric mxBootstrap, mxCheckIdentification, mxGetExpected

Why dynr?

Why make a new package for this?

- ▶ Linear and nonlinear models
- ▶ Multiple subjects
- ▶ Intuitive interface
- ▶ Fast
- ▶ Great reporting
- ▶ Combine dynamics for continuous and categorical latent variables

dynr preparation

- ▶ Gather data with `dynr.data()`
- ▶ Prepare *recipes* with
 - ▶ `prep.measurement()`
 - ▶ `prep.*Dynamics()`
 - ▶ `prep.initial()`
 - ▶ `prep.noise()`
 - ▶ `prep.regimes()` (optional)
- ▶ Mix recipes and data into a model with `dynr.model()`
- ▶ Cook model with `dynr.cook()`
- ▶ Serve results with
 - ▶ `summary()`
 - ▶ `plot()`
 - ▶ `dynr.ggplot()`
 - ▶ `plotFormula()`
 - ▶ `printex()`

Example 0

OpenMx

See `StateSpaceExpectationCodeListings.R` for OpenMx examples of

1. Process factor analysis in discrete and continuous time
2. Use of `mxSE` to compute standard error on transformed parameters
3. Hypothesis testing of nested models
4. Kalman scores
5. Data generation
6. Multisubject models

State Space Model

Measurement

- Structural Equation Measurement Model

$$\mathbf{y}_i = \Lambda \boldsymbol{\eta}_i + K \mathbf{x}_i + \boldsymbol{\varepsilon}_i \quad \text{with} \quad \boldsymbol{\varepsilon}_i \sim \mathcal{N}(\mathbf{0}, \Theta) \quad (1)$$

- State Space Measurement Model

$$\mathbf{y}_i = \Lambda \boldsymbol{\eta}_i + K \mathbf{x}_i + \boldsymbol{\varepsilon}_i \quad \text{with} \quad \boldsymbol{\varepsilon}_i \sim \mathcal{N}(\mathbf{0}, \Theta) \quad (2)$$

State Space Model

Transition/Structural

- Structural Equation Structural Model

$$\boldsymbol{\eta}_i = B\boldsymbol{\eta}_i + \Gamma\mathbf{x}_i + \boldsymbol{\zeta}_i \quad \text{with} \quad \boldsymbol{\zeta}_i \sim \mathcal{N}(\mathbf{0}, \Psi) \quad (3)$$

- State Space Structural Model in Discrete Time

$$\boldsymbol{\eta}_{i+1} = B\boldsymbol{\eta}_i + \Gamma\mathbf{x}_i + \boldsymbol{\zeta}_i \quad \text{with} \quad \boldsymbol{\zeta}_i \sim \mathcal{N}(\mathbf{0}, \Psi) \quad (4)$$

- State Space Structural Model in Continuous Time

$$\frac{d\boldsymbol{\eta}}{dt} = B\boldsymbol{\eta}_i + \Gamma\mathbf{x}_i + \boldsymbol{\zeta}_i \quad \text{with} \quad \boldsymbol{\zeta}_i \sim \mathcal{N}(\mathbf{0}, \Psi) \quad (5)$$

Notation

Structure


Durbin & Koopman	$\alpha_t = T_t \alpha_{t-1} + R_t \eta_t$
LISCOMP	$\eta_t = B_t \eta_{t-1} + \Gamma_t x_t + \zeta_t$
West & Harrison	$\theta_t = G_t \theta_{t-1} + w_t$
Kalman	$x_t = F_t x_{t-1} + B_t u_t + w_t$
Åstrom & Murray	$x_t = A_t x_{t-1} + B_t u_t + v_t$
OpenMx	$x_t = A_t x_{t-1} + B_t u_t + q_t$

Notation


Measurement




Durbin & Koopman	$\mathbf{y}_t = \mathbf{Z}_t \boldsymbol{\alpha}_t + \boldsymbol{\varepsilon}_t$
LISCOMP	$\mathbf{y}_t = \boldsymbol{\Lambda}_t \boldsymbol{\eta}_t + \mathbf{K}_t \mathbf{u}_t + \boldsymbol{\varepsilon}_t$
West & Harrison	$\mathbf{a}_t = \mathbf{F}_t \boldsymbol{\theta}_t + \mathbf{v}_t$
Kalman	$\mathbf{z}_t = \mathbf{H}_t \mathbf{x}_t + \mathbf{v}_t$
Åstrom & Murray	$\mathbf{y}_t = \mathbf{C}_t \mathbf{x}_t + \mathbf{D}_t \mathbf{u}_t + \mathbf{w}_t$
OpenMx	$\mathbf{y}_t = \mathbf{C}_t \mathbf{x}_t + \mathbf{D}_t \mathbf{u}_t + \mathbf{r}_t$




Structural Equation Models



State Space Models







Structural Equation Modeling: A Multidisciplinary Journal, 00: 1–18, 2017
Copyright © Taylor & Francis Group, LLC
ISSN: 1070-5511 print / 1532-8007 online
DOI: <https://doi.org/10.1080/10705511.2017.1369354>



TEACHER'S CORNER

State Space Modeling in an Open Source, Modular, Structural Equation Modeling Environment

Michael D. Hunter

University of Oklahoma Health Sciences Center



Damped and Forced Harmonic Oscillator

- As a second-order system

$$\frac{d^2x}{dt^2} = -kx - c\frac{dx}{dt} + \zeta \quad (6)$$

- As a vector of first-order systems

$$\begin{pmatrix} \frac{dx}{dt} \\ \frac{d^2x}{dt^2} \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ -k & -c \end{pmatrix} \begin{pmatrix} x \\ \frac{dx}{dt} \end{pmatrix} + \begin{pmatrix} 0 \\ \zeta \end{pmatrix} \quad (7)$$

- The Measurement Model

$$y = \begin{pmatrix} 1 & 0 \end{pmatrix} \begin{pmatrix} x \\ \frac{dx}{dt} \end{pmatrix} + \epsilon \quad (8)$$

Example 1a

dynr

See `LinearSDE.R` for dynr examples of

1. Model specification of a damped and forced harmonic oscillator
2. Bound setting
3. Model reporting with `printex`, `plotFormula`, `plot`, and `autoplot`
4. Kalman scores

Example 1b

OpenMx

See `StateSpaceContinuous.R` for OpenMx examples of

1. Undamped linear oscillator
2. Damped linear oscillator
3. Process factor analysis

Example 2

dynr

See PFA.R for dynr examples of

1. Process factor analysis
2. `prep.loadings()` function for easier factor loadings specification

Example 3

OpenMx

See `ModificationIndexCheck.R` for OpenMx examples of

1. Using modification indices with state space models
2. Model modification “on the fly”
3. Data generation from a model

Questions?

