Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	1	0	1	1	1	0	0	B	$\cdots$

1: Flip each bit of the input: $1 \to 0$ and $0 \to 1$
2: Go to the first input symbol

Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	1	0	1	1	1	0	0	B	$\cdots$



Flip each bit of the input: $1 \to 0$ and $0 \to 1$.

Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	0	1	1	1	0	0	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	1	1	1	0	0	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	1	1	0	0	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	1	0	0	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	0	0	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	0	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Go to the first input symbol.

Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Construct a **Turing machine** that **computes** the function:

$$f(w \in \{0,1\}^*) = (\text{the flip of each bit in } w)$$

$\cdots$	B	0	1	0	0	0	1	1	B	$\cdots$



Computed! $f(1011100) = 0100011$