

# Lecture 18 – Normal Forms of Context-Free Grammars

## COSE215: Theory of Computation

Jihyeok Park



2025 Spring

- A **context-free grammar (CFG)** is a 4-tuple:

$$G = (V, \Sigma, S, R)$$

where

- $V$ : a finite set of **variables** (nonterminals)
  - $\Sigma$ : a finite set of **symbols** (terminals)
  - $S \in V$ : the **start variable**
  - $R \subseteq V \times (V \cup \Sigma)^*$ : a set of **production rules**.
- 
- How to **simplify** a CFG?

- A **context-free grammar (CFG)** is a 4-tuple:

$$G = (V, \Sigma, S, R)$$

where

- $V$ : a finite set of **variables** (nonterminals)
  - $\Sigma$ : a finite set of **symbols** (terminals)
  - $S \in V$ : the **start variable**
  - $R \subseteq V \times (V \cup \Sigma)^*$ : a set of **production rules**.
- 
- How to **simplify** a CFG?

Let's put it in **Chomsky normal form (CNF)**!

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
    Nullable Variables
3. Eliminating Unit Productions  
    Unit Pairs
4. Eliminating Useless Variables  
    Generating Variables  
    Reachable Variables
5. Putting CFG in CNF

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
    Nullable Variables
3. Eliminating Unit Productions  
    Unit Pairs
4. Eliminating Useless Variables  
    Generating Variables  
    Reachable Variables
5. Putting CFG in CNF

## Definition (Chomsky Normal Form)

A CFG  $G$  is in **Chomsky normal form (CNF)** if all productions are of the form for some  $A, B, C \in V$  and  $a \in \Sigma$ :

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a \quad \text{OR} \quad S \rightarrow \epsilon$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

## Definition (Chomsky Normal Form)

A CFG  $G$  is in **Chomsky normal form (CNF)** if all productions are of the form for some  $A, B, C \in V$  and  $a \in \Sigma$ :

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a \quad \text{OR} \quad S \rightarrow \epsilon$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

Consider the following CFG:

$$\begin{array}{lll} S \rightarrow 0ABC \mid 1B \mid BB & A \rightarrow ABB0 \mid C & C \rightarrow CC \mid \epsilon \\ & B \rightarrow 0B \mid 1 & D \rightarrow 1D \mid AA \end{array}$$

Is it possible to put this CFG in CNF?

## Definition (Chomsky Normal Form)

A CFG  $G$  is in **Chomsky normal form (CNF)** if all productions are of the form for some  $A, B, C \in V$  and  $a \in \Sigma$ :

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a \quad \text{OR} \quad S \rightarrow \epsilon$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

Consider the following CFG:

$$\begin{array}{ll} S \rightarrow 0ABC \mid 1B \mid BB & A \rightarrow ABB0 \mid C \quad C \rightarrow CC \mid \epsilon \\ & B \rightarrow 0B \mid 1 \quad D \rightarrow 1D \mid AA \end{array}$$

Is it possible to put this CFG in CNF? **Yes!**

$$\begin{array}{lll} S \rightarrow XS_1 \mid XB \mid YB \mid BB & A \rightarrow AA_1 \mid BA_2 & B \rightarrow XB \mid 1 \\ S_1 \rightarrow AB & A_1 \rightarrow BA_2 & X \rightarrow 0 \\ & A_2 \rightarrow BX & Y \rightarrow 1 \end{array}$$



## Definition (Chomsky Normal Form)

A CFG  $G$  is in **Chomsky normal form (CNF)** if all productions are of the form for some  $A, B, C \in V$  and  $a \in \Sigma$ :

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a \quad \text{OR} \quad S \rightarrow \epsilon$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

Consider the following CFG:

$$\begin{array}{lll} S \rightarrow 0ABC \mid 1B \mid BB & A \rightarrow ABB0 \mid C & C \rightarrow CC \mid \epsilon \\ & B \rightarrow 0B \mid 1 & D \rightarrow 1D \mid AA \end{array}$$

Is it possible to put this CFG in CNF? **Yes!**

$$\begin{array}{lll} S \rightarrow XS_1 \mid XB \mid YB \mid BB & A \rightarrow AA_1 \mid BA_2 & B \rightarrow XB \mid 1 \\ S_1 \rightarrow AB & A_1 \rightarrow BA_2 & X \rightarrow 0 \\ & A_2 \rightarrow BX & Y \rightarrow 1 \end{array}$$

Let's learn how to put a CFG in CNF!

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
    Nullable Variables
3. Eliminating Unit Productions  
    Unit Pairs
4. Eliminating Useless Variables  
    Generating Variables  
    Reachable Variables
5. Putting CFG in CNF

The following productions are called  **$\epsilon$ -productions**:

$$A \rightarrow \epsilon$$

Is it possible to eliminate all  **$\epsilon$ -productions** from a CFG?

The following productions are called  **$\epsilon$ -productions**:

$$A \rightarrow \epsilon$$

Is it possible to eliminate all  **$\epsilon$ -productions** from a CFG?

No, if an empty word  $\epsilon$  is in the language of the CFG (i.e.,  $\epsilon \in L(G)$ ), then we cannot generate the empty word without  $\epsilon$ -productions.

The following productions are called  **$\epsilon$ -productions**:

$$A \rightarrow \epsilon$$

Is it possible to eliminate all  **$\epsilon$ -productions** from a CFG?

No, if an empty word  $\epsilon$  is in the language of the CFG (i.e.,  $\epsilon \in L(G)$ ), then we cannot generate the empty word without  $\epsilon$ -productions.

However, we can eliminate all  $\epsilon$ -productions from a CFG  $G$  to construct a new CFG  $G'$  such that:

$$L(G') = L(G) \setminus \{\epsilon\}$$

The following productions are called  **$\epsilon$ -productions**:

$$A \rightarrow \epsilon$$

Is it possible to eliminate all  **$\epsilon$ -productions** from a CFG?

No, if an empty word  $\epsilon$  is in the language of the CFG (i.e.,  $\epsilon \in L(G)$ ), then we cannot generate the empty word without  $\epsilon$ -productions.

However, we can eliminate all  $\epsilon$ -productions from a CFG  $G$  to construct a new CFG  $G'$  such that:

$$L(G') = L(G) \setminus \{\epsilon\}$$

We can do it by following the steps below:

- 1 Find all **nullable variables**.
- 2 Construct a new CFG by **replacing** nullable variables with  $\epsilon$  in **all combinations** and **removing** all  $\epsilon$ -productions in production rules.

## Definition (Nullable Variables)

For a given CFG  $G = (V, \Sigma, S, R)$ , a variable  $A \in V$  is **nullable** if

$$A \Rightarrow^* \epsilon$$

## Definition (Nullable Variables)

For a given CFG  $G = (V, \Sigma, S, R)$ , a variable  $A \in V$  is **nullable** if

$$A \Rightarrow^* \epsilon$$

We can inductively define the set of **nullable variables**:

- **(Basis Case)** If  $A \rightarrow \epsilon \in R$ , then  $A$  is nullable.
- **(Induction Case)** If  $A \rightarrow X_1 X_2 \cdots X_n \in R$  and  $X_1, X_2, \dots, X_n$  are all nullable, then  $A$  is nullable.



Consider the following CFG:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

- 1 Find all **nullable variables**:

Consider the following CFG:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

- 1 Find all **nullable variables**:  $\{A, C, D\}$

Consider the following CFG:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

- 1 Find all **nullable variables**:  $\{A, C, D\}$
- 2 Construct a new CFG by **replacing** nullable variables with  $\epsilon$  in **all combinations** and **removing** all  $\epsilon$ -productions in production rules:

Consider the following CFG:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

- 1 Find all **nullable variables**:  $\{A, C, D\}$
- 2 Construct a new CFG by **replacing** nullable variables with  $\epsilon$  in **all combinations** and **removing** all  $\epsilon$ -productions in production rules:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid C$$

$$D \rightarrow 1D \mid 1 \mid AA \mid A$$

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
Nullable Variables
3. Eliminating Unit Productions  
Unit Pairs
4. Eliminating Useless Variables  
Generating Variables  
Reachable Variables
5. Putting CFG in CNF

The following productions are called **unit productions**:

$$A \rightarrow B$$

The following productions are called **unit productions**:

$$A \rightarrow B$$

Is it possible to eliminate **unit productions**?

The following productions are called **unit productions**:

$$A \rightarrow B$$

Is it possible to eliminate **unit productions**?

Yes, we can do it by following the steps below:

- 1 Find all **unit pairs**.
- 2 Construct a new CFG by **adding** all possible non-unit productions of  $B$  to  $A$  for each unit pair  $(A, B)$ .



## Definition (Unit Pairs)

For a given CFG  $G = (V, \Sigma, S, R)$ , a pair of variables  $(A, B) \in V \times V$  is a **unit pair** if

$$A \Rightarrow^* B$$

## Definition (Unit Pairs)

For a given CFG  $G = (V, \Sigma, S, R)$ , a pair of variables  $(A, B) \in V \times V$  is a **unit pair** if

$$A \Rightarrow^* B$$

We can inductively define the set of **unit pairs**:

- **(Basis Case)**  $(A, A)$  is a unit pair for all  $A \in V$ .
- **(Induction Case)** If  $(A, B)$  is a unit pair and  $B \rightarrow C \in R$ , then  $(A, C)$  is a unit pair.

# Eliminating Unit Productions – Example

After eliminating  $\epsilon$ -productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid C$$

$$D \rightarrow 1D \mid 1 \mid AA \mid A$$

- 1 Find all **unit pairs**:

After eliminating  $\epsilon$ -productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid C$$

$$D \rightarrow 1D \mid 1 \mid AA \mid A$$

① Find all **unit pairs**:

$$\{(S, S), (A, A), (A, C), (B, B), (C, C), (D, D), (D, A), (D, C)\}$$

After eliminating  $\epsilon$ -productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid C$$

$$D \rightarrow 1D \mid 1 \mid AA \mid A$$

- 1 Find all **unit pairs**:

$$\{(S, S), (A, A), (A, C), (B, B), (C, C), (D, D), (D, A), (D, C)\}$$

- 2 Construct a new CFG by **adding** all possible non-unit productions of  $B$  to  $A$  for each unit pair  $(A, B)$ .

After eliminating  $\epsilon$ -productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid C$$

$$D \rightarrow 1D \mid 1 \mid AA \mid A$$

- 1 Find all **unit pairs**:

$$\{(S, S), (A, A), (A, C), (B, B), (C, C), (D, D), (D, A), (D, C)\}$$

- 2 Construct a new CFG by **adding** all possible non-unit productions of  $B$  to  $A$  for each unit pair  $(A, B)$ .

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
Nullable Variables
3. Eliminating Unit Productions  
Unit Pairs
4. Eliminating Useless Variables  
Generating Variables  
Reachable Variables
5. Putting CFG in CNF

What are useless variables?

- **Non-generating variables:** Variables that cannot derive any word.
- **Unreachable variables:** Variables unreachable from the start variable.

Is it possible to eliminate **useless variables**?



What are useless variables?

- **Non-generating variables:** Variables that cannot derive any word.
- **Unreachable variables:** Variables unreachable from the start variable.

Is it possible to eliminate **useless variables**?

Yes, we can do it by following the steps below:

- 1 Find all **generating variables**.
- 2 Find all **reachable variables**.
- 3 Construct a new CFG by **removing** all productions that contain non-generating variables or come from unreachable variables.

## Definition (Generating Variables)

For a given CFG  $G = (V, \Sigma, S, R)$ , a variable  $A \in V$  is a **generating variable** if for some  $w \in \Sigma^*$ ,

$$A \Rightarrow^* w$$

## Definition (Generating Variables)

For a given CFG  $G = (V, \Sigma, S, R)$ , a variable  $A \in V$  is a **generating variable** if for some  $w \in \Sigma^*$ ,

$$A \Rightarrow^* w$$

We can inductively define the set of **generating variables**:

- **(Basis Case)** There is no basis case.
- **(Induction Case)** If  $A \rightarrow \alpha \in R$  and  $\alpha$  contains only symbols or generating variables, then  $A$  is a generating variable.

## Definition (Reachable Variables)

For a given CFG  $G = (V, \Sigma, S, R)$ , a variable  $A \in V$  is a **reachable variable** if there exists a derivation:

$$S \Rightarrow^* \alpha A \beta$$

## Definition (Reachable Variables)

For a given CFG  $G = (V, \Sigma, S, R)$ , a variable  $A \in V$  is a **reachable variable** if there exists a derivation:

$$S \Rightarrow^* \alpha A \beta$$

We can inductively define the set of **reachable variables**:

- **(Basis Case)** The start variable  $S$  is reachable variable.
- **(Induction Case)** If  $A \in V$  is a reachable variable and  $A \rightarrow \alpha \in R$ , then all variables in  $\alpha$  are reachable variables.

# Eliminating Useless Variables – Example

After eliminating  $\epsilon$ -productions and unit productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

- 1 Find all **generating variables**:

# Eliminating Useless Variables – Example

After eliminating  $\epsilon$ -productions and unit productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

- ① Find all **generating variables**:  $\{S, A, B, D\}$  –  $C$  is non-generating.

# Eliminating Useless Variables – Example

After eliminating  $\epsilon$ -productions and unit productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

- 1 Find all **generating variables**:  $\{S, A, B, D\}$  –  $C$  is non-generating.
- 2 Find all **reachable variables**:



# Eliminating Useless Variables – Example

After eliminating  $\epsilon$ -productions and unit productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

- 1 Find all **generating variables**:  $\{S, A, B, D\}$  –  $C$  is non-generating.
- 2 Find all **reachable variables**:  $\{S, A, B, C\}$  –  $D$  is unreachable.

# Eliminating Useless Variables – Example

After eliminating  $\epsilon$ -productions and unit productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

- 1 Find all **generating variables**:  $\{S, A, B, D\}$  –  $C$  is non-generating.
- 2 Find all **reachable variables**:  $\{S, A, B, C\}$  –  $D$  is unreachable.
- 3 Construct a new CFG by **removing** all productions that contain non-generating variables or come from unreachable variables.

# Eliminating Useless Variables – Example

After eliminating  $\epsilon$ -productions and unit productions:

$$S \rightarrow 0ABC \mid 0BC \mid 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0 \mid CC$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC$$

$$D \rightarrow 1D \mid 1 \mid AA \mid ABB0 \mid BB0 \mid CC$$

- 1 Find all **generating variables**:  $\{S, A, B, D\}$  –  $C$  is non-generating.
- 2 Find all **reachable variables**:  $\{S, A, B, C\}$  –  $D$  is unreachable.
- 3 Construct a new CFG by **removing** all productions that contain non-generating variables or come from unreachable variables.

$$S \rightarrow 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0$$

$$B \rightarrow 0B \mid 1$$

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
    Nullable Variables
3. Eliminating Unit Productions  
    Unit Pairs
4. Eliminating Useless Variables  
    Generating Variables  
    Reachable Variables
5. Putting CFG in CNF

# Putting CFG in CNF

Our goal is to put a CFG in **Chomsky normal form (CNF)** consisting of:

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

We can put a CFG in CNF by following the steps below:

Our goal is to put a CFG in **Chomsky normal form (CNF)** consisting of:

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

We can put a CFG in CNF by following the steps below:

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

Our goal is to put a CFG in **Chomsky normal form (CNF)** consisting of:

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

We can put a CFG in CNF by following the steps below:

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .
- 2 Eliminate  $\epsilon$ -productions, unit productions, and useless variables.

Our goal is to put a CFG in **Chomsky normal form (CNF)** consisting of:

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

We can put a CFG in CNF by following the steps below:

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .
- 2 Eliminate  $\epsilon$ -productions, unit productions, and useless variables.
- 3 Rewrite all RHSs whose length  $> 1$  to contain only variables: if a symbol  $a$  appears in the RHS, replace it with a new variable  $A$  and introduce a new production rule  $A \rightarrow a$ .



Our goal is to put a CFG in **Chomsky normal form (CNF)** consisting of:

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

We can put a CFG in CNF by following the steps below:

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .
- 2 Eliminate  $\epsilon$ -productions, unit productions, and useless variables.
- 3 Rewrite all RHSs whose length  $> 1$  to contain only variables: if a symbol  $a$  appears in the RHS, replace it with a new variable  $A$  and introduce a new production rule  $A \rightarrow a$ .
- 4 Replace all RHSs whose length is greater than 2 with a chain of variables. To do so, if  $A \rightarrow X_1X_2 \cdots X_n$  is a production with  $n > 2$ , then replace it with a sequence of productions:

$$A \rightarrow X_1A_1 \quad A_1 \rightarrow X_2A_2 \quad \cdots \quad A_{n-2} \rightarrow X_{n-1}X_n$$

Our goal is to put a CFG in **Chomsky normal form (CNF)** consisting of:

$$A \rightarrow BC \quad \text{OR} \quad A \rightarrow a$$

where  $B \neq S$  and  $C \neq S$ . And  $S \rightarrow \epsilon$  is allowed only if  $\epsilon \in L(G)$ .

We can put a CFG in CNF by following the steps below:

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .
- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables.
- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables: if a symbol  $a$  appears in the RHS, replace it with a new variable  $A$  and introduce a new production rule  $A \rightarrow a$ .
- ④ Replace all RHSs whose length is greater than 2 with a chain of variables. To do so, if  $A \rightarrow X_1X_2 \cdots X_n$  is a production with  $n > 2$ , then replace it with a sequence of productions:

$$A \rightarrow X_1A_1 \quad A_1 \rightarrow X_2A_2 \quad \cdots \quad A_{n-2} \rightarrow X_{n-1}X_n$$

- ⑤ If  $\epsilon$  is in the original language, add a production  $S \rightarrow \epsilon$  (or  $S' \rightarrow \epsilon$ ).

# Putting CFG in CNF – Example 1

Let's put the following CFG in CNF:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

# Putting CFG in CNF – Example 1

Let's put the following CFG in CNF:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

# Putting CFG in CNF – Example 1

Let's put the following CFG in CNF:

$$S \rightarrow 0ABC \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid C$$

$$B \rightarrow 0B \mid 1$$

$$C \rightarrow CC \mid \epsilon$$

$$D \rightarrow 1D \mid AA$$

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .
- 2 Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S \rightarrow 0AB \mid 0B \mid 1B \mid BB$$

$$A \rightarrow ABB0 \mid BB0$$

$$B \rightarrow 0B \mid 1$$

$$\begin{aligned}S &\rightarrow 0AB \mid 0B \mid 1B \mid BB \\A &\rightarrow ABB0 \mid BB0 \\B &\rightarrow 0B \mid 1\end{aligned}$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$\begin{aligned}S &\rightarrow 0AB \mid 0B \mid 1B \mid BB \\A &\rightarrow ABB0 \mid BB0 \\B &\rightarrow 0B \mid 1\end{aligned}$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$\begin{aligned}S &\rightarrow XAB \mid XB \mid YB \mid BB & X &\rightarrow 0 \\A &\rightarrow ABBX \mid BBX & Y &\rightarrow 1 \\B &\rightarrow XB \mid 1\end{aligned}$$

$$\begin{aligned}S &\rightarrow 0AB \mid 0B \mid 1B \mid BB \\A &\rightarrow ABB0 \mid BB0 \\B &\rightarrow 0B \mid 1\end{aligned}$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$\begin{aligned}S &\rightarrow XAB \mid XB \mid YB \mid BB & X &\rightarrow 0 \\A &\rightarrow ABBX \mid BBX & Y &\rightarrow 1 \\B &\rightarrow XB \mid 1\end{aligned}$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:



$$\begin{aligned} S &\rightarrow 0AB \mid 0B \mid 1B \mid BB \\ A &\rightarrow ABB0 \mid BB0 \\ B &\rightarrow 0B \mid 1 \end{aligned}$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$\begin{aligned} S &\rightarrow XAB \mid XB \mid YB \mid BB & X &\rightarrow 0 \\ A &\rightarrow ABBX \mid BBX & Y &\rightarrow 1 \\ B &\rightarrow XB \mid 1 \end{aligned}$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

$$\begin{aligned} S &\rightarrow XS_1 \mid XB \mid YB \mid BB & A &\rightarrow AA_1 \mid BA_2 & B &\rightarrow XB \mid 1 \\ S_1 &\rightarrow AB & A_1 &\rightarrow BA_2 & X &\rightarrow 0 \\ & & A_2 &\rightarrow BX & Y &\rightarrow 1 \end{aligned}$$

$$\begin{aligned} S &\rightarrow 0AB \mid 0B \mid 1B \mid BB \\ A &\rightarrow ABB0 \mid BB0 \\ B &\rightarrow 0B \mid 1 \end{aligned}$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$\begin{aligned} S &\rightarrow XAB \mid XB \mid YB \mid BB & X &\rightarrow 0 \\ A &\rightarrow ABBX \mid BBX & Y &\rightarrow 1 \\ B &\rightarrow XB \mid 1 \end{aligned}$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

$$\begin{aligned} S &\rightarrow XS_1 \mid XB \mid YB \mid BB & A &\rightarrow AA_1 \mid BA_2 & B &\rightarrow XB \mid 1 \\ S_1 &\rightarrow AB & A_1 &\rightarrow BA_2 & X &\rightarrow 0 \\ & & A_2 &\rightarrow BX & Y &\rightarrow 1 \end{aligned}$$

- ⑤ If  $\epsilon$  is in the original language, add a production  $S \rightarrow \epsilon$ :

$$\begin{aligned} S &\rightarrow 0AB \mid 0B \mid 1B \mid BB \\ A &\rightarrow ABB0 \mid BB0 \\ B &\rightarrow 0B \mid 1 \end{aligned}$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$\begin{aligned} S &\rightarrow XAB \mid XB \mid YB \mid BB & X &\rightarrow 0 \\ A &\rightarrow ABBX \mid BBX & Y &\rightarrow 1 \\ B &\rightarrow XB \mid 1 \end{aligned}$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

$$\begin{aligned} S &\rightarrow XS_1 \mid XB \mid YB \mid BB & A &\rightarrow AA_1 \mid BA_2 & B &\rightarrow XB \mid 1 \\ S_1 &\rightarrow AB & A_1 &\rightarrow BA_2 & X &\rightarrow 0 \\ & & A_2 &\rightarrow BX & Y &\rightarrow 1 \end{aligned}$$

- ⑤ If  $\epsilon$  is in the original language, add a production  $S \rightarrow \epsilon$ : **No.**

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- 2 Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- 1 If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- 2 Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$



## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$S' \rightarrow ASB \mid AB \quad S \rightarrow ASB \mid AB \quad A \rightarrow a \quad B \rightarrow b$$

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$S' \rightarrow ASB \mid AB \quad S \rightarrow ASB \mid AB \quad A \rightarrow a \quad B \rightarrow b$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$S' \rightarrow ASB \mid AB \quad S \rightarrow ASB \mid AB \quad A \rightarrow a \quad B \rightarrow b$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

$$S' \rightarrow AS_1 \mid AB \quad S \rightarrow AS_1 \mid AB \quad S_1 \rightarrow SB \quad A \rightarrow a \quad B \rightarrow b$$

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$S' \rightarrow ASB \mid AB \quad S \rightarrow ASB \mid AB \quad A \rightarrow a \quad B \rightarrow b$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

$$S' \rightarrow AS_1 \mid AB \quad S \rightarrow AS_1 \mid AB \quad S_1 \rightarrow SB \quad A \rightarrow a \quad B \rightarrow b$$

- ⑤ If  $\epsilon$  is in the original language, add a production  $S' \rightarrow \epsilon$ :

## Putting CFG in CNF – Example 2

Let's put the following CFG in CNF:

$$S \rightarrow aSb \mid \epsilon$$

- ① If  $S$  on RHSs, add a new start variable  $S'$  and a production  $S' \rightarrow S$ .

$$S' \rightarrow S \quad S \rightarrow aSb \mid \epsilon$$

- ② Eliminate  $\epsilon$ -productions, unit productions, and useless variables:

$$S' \rightarrow aSb \mid ab \quad S \rightarrow aSb \mid ab$$

- ③ Rewrite all RHSs whose length  $> 1$  to contain only variables:

$$S' \rightarrow ASB \mid AB \quad S \rightarrow ASB \mid AB \quad A \rightarrow a \quad B \rightarrow b$$

- ④ Replace all RHSs whose length  $> 2$  with a chain of variables:

$$S' \rightarrow AS_1 \mid AB \quad S \rightarrow AS_1 \mid AB \quad S_1 \rightarrow SB \quad A \rightarrow a \quad B \rightarrow b$$

- ⑤ If  $\epsilon$  is in the original language, add a production  $S' \rightarrow \epsilon$ : **Yes.**

$$S' \rightarrow \epsilon \mid AS_1 \mid AB \quad S \rightarrow AS_1 \mid AB \quad S_1 \rightarrow SB \quad A \rightarrow a \quad B \rightarrow b$$

1. Chomsky Normal Form (CNF)
2. Eliminating  $\epsilon$ -Productions  
Nullable Variables
3. Eliminating Unit Productions  
Unit Pairs
4. Eliminating Useless Variables  
Generating Variables  
Reachable Variables
5. Putting CFG in CNF

- Properties of Context-Free Languages

Jihyeok Park

[jihyeok\\_park@korea.ac.kr](mailto:jihyeok_park@korea.ac.kr)

<https://plrg.korea.ac.kr>