



Lecture 11a - Balanced Binary Search Tree (Red Black Tree) - Part A

Fall 2025, Korea University

Instructor: Gabin An (gabin_an@korea.ac.kr)

Hope you had a great Chuseok! 🌾



In today's class, we'll


- Take a Quiz#2
- Review Binary Search Tree (BST)
- Learn Self-Balancing BSTs
- Learn Red-Black Trees
 - Definition & Properties
 - Operations:
 - Tree Rotation (Left / Right)
 - Insertion (with Rotation & Recoloring) - *next class*
 - Deletion (with Rotation & Recoloring) - *next class*

Quiz #2 ★


- Time limit: 15 minutes
- Start time: 13:40
- Materials: Lecture slides/notes may be used (open notes, not open internet)

Binary Search Tree (BST) 🌲


A binary search tree is a binary tree where all keys in a node's left subtree are less than the node's key, and all keys in its right subtree are greater.




BST



BST




Not a BST



Not a BST

search(i)




search(3)

→ 4 (large! search in the left tree)

→ 2 (small! search in the right tree)

→ 3 (found!!)

- **What if the element does not exist in our BST?:** We simply return the node that would be the parent of this node if we inserted it into our tree.



search(3.5)

→ 4 (large! search in the left tree)

→ 2 (small! search in the right tree)


→ 3 (small! but the right child is NIL; return node 3)

(3.5) ← does not exist


insert(i)

- Find the parent node `x` where `i` should be inserted using `search(i)`.
- Create a new node `y` with `key(y)=i` and no children and attach `y` to `x`.

Example: `insert(3)`




-> `search(3)`
-> 4 (large! search in the left tree)
-> 2 (small! search in the right tree)
-> NIL (parent node found)




delete(i)

- Deletion is a bit more complicated.
- To delete a node `x` that exists in our tree, we consider several cases:
 - Case 1: `x` has no children
 - We simply remove it.
 - Case 2: `x` has only one child `c`
 - We **elevate** `c` to take `x`'s position in the tree.
 - Case 3: `x` has two children, a left child `c1` and right child `c2`
 - We find `x`'s **immediate successor** `z` and have `z` take `x`'s position in the tree. Then, we remove the original successor (Case 1 or Case 2).




Time Complexity of `search(i)`, `insert(i)`, and `delete(i)`

- **Search** runs in $O(\text{height of tree})$ in the worst case.
- **Insert** and **delete** call `search` a constant number of times and do $O(1)$ extra work, so their runtimes are also $O(\text{height of tree})$.
- Height of tree:
 - **Best case** (completely balanced): $O(\log n)$, **Worst case** (long chain): $O(n)$



Balanced



Long Leftward Path



Long Rightward Path

It's Time to Learn Self-Balancing BSTs.

Operation	Sorted Array	BST (height h)	Balanced BST
Search	$\Theta(\log n)$	$\Theta(h)$	$\Theta(\log n)$
Insert	$\Theta(n)$ 🤔	$\Theta(h)$	$\Theta(\log n)$
Delete	$\Theta(n)$ 🤔	$\Theta(h)$	$\Theta(\log n)$

- Sorted arrays: fast search, slow updates.
- Unbalanced BST: updates are fast **only if** $h(\text{height of tree}) = O(\log n)$.
 - Worst case: $h = O(n) \rightarrow$ linked-list-like performance.
- Solution: **Self-balancing BSTs** (AVL tree, red-black tree, etc.).

Idea of Balancing

- Keep tree height close to $\log n$ after every insertion/deletion.
- **Self-balancing BSTs:**
 - Detect when the tree is becoming too tall or skewed.
 - Apply **rotations** and **recoloring/restructuring** to restore balance.
- Many variants exist such as AVL trees (strict height balance) and Red–Black trees (color-based, less strict, easier insert/delete), Splay trees, Treaps, etc.
- In this class, we focus on **Red–Black Trees**.
 - Widely used in libraries (`std::map` , `TreeMap`).


Red-Black Tree: Definition

A Red-Black Tree is a BST with an extra bit of storage (color) per node.

Properties:

1. Every node is red or black.
2. The root is black.
3. NILs are black.
4. The children of a red node are black.
5. For every node x , all x to NIL paths have the same number of black nodes on them.

Examples




1. Every node is red or black.
2. The root is black.
3. NILs are black.
4. The children of a red node are black.
5. For every node x , all x to NIL paths have the same number of black nodes on them.

Why These Properties Work

- Property 4 limits consecutive reds → prevents skewed long chains of red nodes.
- Property 5 forces black nodes to be evenly distributed → keeps height small.

A chain of 3 nodes is not possible in the Red-Black tree.




All Possible Structure of a 3-noded Red-Black Tree

Claim: A red-black tree with n nodes has height $\leq 2 \log_2(n + 1) = O(\log n)$

Proof. For a node x ,

- let $b(x)$ be its *black height* (i.e., # black nodes on any $x \rightarrow \text{NIL}$ path excluding x)
- let $s(x)$ be the subtree size (including x).



- Notice that the black height is at least half of the height because there are **no two consecutive red nodes** on any root-to-NIL path.
 - $b(x) \geq \frac{h(x)}{2}$ (where $h(x)$ is the height of x)

Claim: A red-black tree with n nodes has height $\leq 2 \log_2(n + 1) = O(\log n)$

Proof (Continued).

Let's show $s(x) \geq 2^{b(x)} - 1$ via induction on the height of x :

Base case ($h = 0$): NIL node has $b(x) = 0$ and $2^0 - 1 = 0$ non-NIL descendants. ✓

Inductive step: Using the *IH* $s(y) \geq 2^{b(y)} - 1$ for children y of x , i.e., $b(y) \geq b(x) - 1$

$$s(x) = 1 + s(\text{left}(x)) + s(\text{right}(x)) \geq 1 + \left(2^{b(x)-1} - 1\right) + \left(2^{b(x)-1} - 1\right) = 2^{b(x)} - 1$$

Therefore, $s(x) \geq 2^{b(x)} - 1$ for every x in a red-black tree. ✓

Finally, when r is a root,

$$n = s(r) \geq 2^{b(r)} - 1 \geq 2^{h(r)/2} - 1 \quad \rightarrow \quad h = h(r) \leq 2 \log_2(n + 1) \quad \blacksquare$$

Live Visualization: Red–Black Tree

 Try it: <https://www.cs.usfca.edu/~galles/visualization/RedBlack.html>

What to observe as you insert/delete:

- **No two reds in a row** (Property 4)
- **Uniform black-height** on all root→leaf paths (Property 5)
- **Rotations** (left/right) and **recoloring** after each update

Suggested demo sequence

- Insert: 41, 38, 31, 12, 19, 8
- Delete: 8, 12, 19, 38

Basic Operations on a Red-Black Tree

1. **Search:** Same as in a normal BST (binary search based on key ordering).
2. **Insertion:** Insert as in a normal BST, then fix any violations of red-black properties via **rotations and recoloring**.
3. **Deletion:** Delete as in a normal BST, then restore red-black properties through **rotations and recoloring**.

Rotation

- **Purpose:** Maintain balance after insertion/deletion
 - Tree rotations can be performed in $O(1)$ time.
- **Types:**
 - i. Left Rotation
 - ii. Right Rotation

Recall: BST's Subtree Property




1. If $\text{left}(x)$ is y and $\text{right}(y)$ is z , then all keys in z 's subtree satisfy:

- $y < \text{keys} < x$


2. If $\text{right}(x)$ is y and $\text{left}(y)$ is z , then all keys in z 's subtree satisfy:

- $x < \text{keys} < y$

Left Rotation




- **Goal:** Move a node down to the left, bring its right child up.




- $x < a < y < b$

Right Rotation




- **Goal:** Move a node down to the left, bring its right child up.




- $a < y < b < x$

Next Class: Red-Black Tree Insertion / Deletion


41 → 38 → 31 → 12 → 19 → 8



Let's delete $8 \rightarrow 12 \rightarrow 19 \rightarrow 39$



② Delete 12



Credits & Resources

Lecture materials adapted from:

- Stanford CS161 slides and lecture notes
 - <https://stanford-cs161.github.io/winter2025/>
- *Algorithms Illuminated* by Tim Roughgarden
 - <https://algorithmsilluminated.com/>

Reference:

- <https://www.geeksforgeeks.org/dsa/introduction-to-red-black-tree>
- <https://www.geeksforgeeks.org/dsa/c-program-red-black-tree-insertion/>
- <https://studyglance.in/ds/display.php?tno=27&topic=Red-Black-Tree>