TPM Specification Design

Perry Alexander Brigid Halling

$July\ 26,\ 2012$

Contents

1	Introduction				
2	Modeling Approach				
	2.1	TPM Abstract State	2		
	2.2	TPM Abstract Command Definitions	2		
	2.3	TPM Abstract Outputs	5		
	2.4	Defining Abstract TPM Command Execution	5		
	2.5	Sequencing TPM Commands	6		
3	Ver	ification Approach	7		
A	Tru	sted Platform Definitions	8		
В	Cryptography Notations				
\mathbf{C}	C Intel Secure Boot				
$\mathbf{L}^{:}$	ist	of Figures			
	1	Abstract TPM and system state record data structure	2		
	2	TPM command data type	3		
	3	Abstract TPM outputs	3		
	4	Weak bisimulation relation between an abstract transition system $A=(S,\Sigma,\Delta)$ and a concrete transition system $C=(s,\sigma,\delta)$	7		

Figure 1: Abstract TPM and system state record data structure.

List of Tables

- 1 TPM command mapping to PVS command representation. . . . 4

Abstract

The abstract goes here...

1 Introduction

2 Modeling Approach

2.1 TPM Abstract State

Figure 1 is the PVS record structure used to represent the internal state of the TPM and necessary external state of the environment it is running in.

2.2 TPM Abstract Command Definitions

Figure 2 is the PVS data type used to represent the abstract syntax of the TPM command set.

Table 1 maps TPM concrete commands to their abstract PVS representations.

Table 2 maps external commands that interact with the TPM to their PVS representations.

```
tpmInput : DATATYPE
BEGIN
%% Startup commands
  ABS_Init : ABS_Init?
  ABS_Startup : ABS_Startup? % Only clear implemented
  ABS_SaveState : ABS_SaveState? % unimplemented
%% PCRs, seals and keys
  ABS_Extend(h:HV,i:PCRINDEX) : ABS_Extend?
  ABS_Unseal(s:(sealBlob?),uk:(asymKey?)) : ABS_Unseal?
  ABS_Seal(sk:(asymKey?),data:BLOB) : ABS_Seal?
  ABS_LoadKey2(1k:(wrapKey?)): ABS_LoadKey2?
  ABS_CreateWrapKey(wk,parentk:(asymKey?)): ABS_CreateWrapKey?
%% Quotes and Identities
  ABS_Quote(aik:(wrapKey?),nonce:BLOB,pm:PCRMASK) : ABS_Quote?
  ABS_MakeIdentity(naik:(asymKey?),k:(symKey?)) : ABS_MakeIdentity?
  ABS_ActivateIdentity(caik:(wrapKey?),k:(symKey?)) : ABS_ActivateIdentity?
%% Ownership management
  ABS_TakeOwnership : ABS_TakeOwnership?
  ABS_OwnerClear : ABS_OwnerClear? % unimplemented
  ABS_ForceClear : ABS_ForceClear? % unimplemented
  ABS_DisableOwnerClear : ABS_DisabelOwnerClear? % unimplemented
%% Software Commands
  ABS_senter : ABS_senter? % implemented all actions as one senter
  ABS_sinit : ABS_sinit? % partially implemented
  ABS_Save(i:nat,v:tpmAbsOutput) : ABS_Save?
  ABS_Read(i:nat) : ABS_Read?
%% CA Commands
  ABS_certify(aik:(wrapKey?),ek:(asymKey?),freshk:(symKey?)) : ABS_certify?
%% Invented, imaginary Commands
 noopCom : noopCom?
END tpmInput;
```

Figure 2: TPM command data type.

```
tpmAbsOutput : DATATYPE
BEGIN
  outNothing : outNothing?
  outError(errorVal:nat) : outError?
  outQuote(oqk:KEY,oqnon:BLOB,oqpcrs:list[PCR]) : outQuote?
  outWrapKey(owk:KEY) : outWrapKey?
  outAsymKey(oask:KEY) : outSymKey?
  outSymKey(osk:KEY) : outSymKey?
  outBlob(obl:BLOB) : outBlob?
  outCertReq(ocertaik:(wrapKey?),ocertek:(asymKey?),ofreshk:(symKey?)) : outCertReq?
  outIdentity(oidentaik:(wrapKey?),oidentc:(outCertReq?)) : outIdentity?
  outIdentActivation(oactc:(certBlob?),osessk:(symKey?),oactek:(asymKey?)) : outFullQuote?
  outPCR(pcr:PCR) : outPCR?
END tpmAbsOutput;
```

Figure 3: Abstract TPM outputs

TPM	Abstract PVS	Concrete PVS
Command	Command	Command
Startup		
TPM_Init	ABS_Init	
$TPM_{L}Startup$	ABS_Startup	
$TPM_{L}SaveState$	ABS_SaveState	
PCRs, seals and keys		
$TPM_{L}Extend$	ABS_Extend(h,i)	
TPM_Seal	ABS_Seal(sk,data)	
TPM_{Bind}		
$TPM_{L}Unbind$		
TPM_Unseal	ABS_Unseal(s,uk)	
$TPM_{L}CreateWrapKey$	ABS_CreateWrapKey(wk,parentk)	
TPM_LoadKey2	ABS_LoadKey2(k)	
Quotes and Identities		
$TPM_{L}Quote$	ABS_Quote(aik,b,pm)	
$TPM_{L}Makeldentity$	ABS_MakeIdentity(naik,k)	
TPM_ActivateIdentity	ABS_ActivateIdentity(caik,k)	
Ownership		
TPM_TakeOwnership	ABS_TakeOwnership	
TPM_OwnerClear		
$TPM_{L}ForceClear$		
$TPM_DisableOwnerClear$		

Table 1: TPM command mapping to PVS command representation.

External	Abstract PVS	Concrete PVS
Command	Command	Command
senter	ABS_senterCom	
sinit	ABS_sinitCom	
Save to memory	ABS_Save(i,v)	
Read from memory	ABS_Read(i)	
CA certification	ABS_certify(aik,ek,freshk)	
Power On	powerCom	
Power Off	offCom	

Table 2: System commands interacting with TPM.

2.3 TPM Abstract Outputs

2.4 Defining Abstract TPM Command Execution

The technique for specifying TPM command execution is to define a transition from tmpAbsState (figure 1) and tpmInput (figure 2) to tpmAbsState:

```
\mathtt{executeCom} \; : \; \mathtt{tpmAbsState} \; \rightarrow \; \mathtt{tpmInput} \; \rightarrow \; \mathtt{tpmAbsState}
```

and a transition from tmpAbsState (figure 1) and tpmInput (figure 2) to tpmAbsOutput:

```
{\tt outputCom} \; : \; {\tt tpmAbsState} \; \rightarrow \; {\tt tpmInput} \; \rightarrow \; {\tt tpmAbsOutput}
```

Given s:tpmAbsState and c:tpmAbsInput the output, state pair resulting from executing c are defined as:

```
(\text{outputCom}(s,c), \text{executeCom}(s,c))
```

This is a standard technique for defining state transition and output functions for any transition system.

As one would expect, executeCom and outputCom are defined by cases over tpmAbsInput. For each command in tpmAbsInput a function is defined for generating the next state and for generating output. These commands are named within the specification using the suffix State and Out respectively for easy identification.

As a concrete example, consider the ABS_ActivateIdentity input. The function activateIdentityState defines how the TPM state is modified:

```
activateIdentityState(s:tpmAbsState,a:(wrapKey?),k:(symKey?)) : tpmAbsState =
loadKey2State(s,a);
```

while, the function activateIdentityOut defines the TPM output generated by the command:

```
activateIdentityOut(s:tpmAbsState,a:(wrapKey?),k:(symKey?)) : tpmAbsOutput =
   IF checkKeyRoot(a,srk(s)) THEN outSymKey(k) ELSE outNothing ENDIF;
```

Note that many commands in the current abstract model either modify state or generate output. In such cases only the pertinent function is defined with the CASES construct used to assemble the functions defaulting to not modifying the state and generating a null output.

2.5 Sequencing TPM Commands

Sequencing of TPM commands is a matter of using the output state from one command as the input to the next command. The classical mechanism for doing this involves executing a command and manually feeding its outputs to the next state. Using a LET form, to execute i;i' would look like the following:

```
LET (s',o') = (executeCom(s,i),outputCom(s,i)) IN
  (executeCom(s',i'),outputCom(s',i'))
```

where the tick denotes next.

The notation typically used does not use the LET, performing calls directly:

```
(executeCom(executeCom(s,i),outputCom(s,i)),
  outputCom(executeCom(s,i),outputCom(s,i)))
```

TPM command execution is inherently sequential, making this notation exceptionally obtuse and difficult manage. Thus, we choose to use an alternative approach that uses a *state monad* to model sequential execution. In effect, the state monad threads the state through sequential execution in the background.

To understand the state monad, lets first define a simple data type, State, having a single field called state that holds a function from an abstract state to an abstract state, abstract output pair:

```
State : DATATYPE
BEGIN
   state(runState:[tpmAbsState->[tpmAbsOutput,tpmAbsState]]):state?
END State
```

Given s, a value of type tpmAbsState, and m, a State, the application:

```
runState(m)(s)
```

will result in a tpmAbsOutput, tpmAbsState pair. This is precisely the output expected. Note that the use of State and state in this definition is somewhat misleading. Neither is actually a state, but a state monad that given a state will generate a new state. The data type should be viewed as a kind of state generation or next-state function, not a single state.²

Two functions must be defined for any instance of a monad – unit and bind (>>=). We will also define sequence (>>) command that is a special case of bind commonly defined in most state monad implementation.

First we define unit, frequently called return in the literature. It's form is:

¹We use the semicolon in the canonical style to represent sequential execution.

²The notation used here is consistent with the literature.

```
unit(x:tpmAbsOutput):State = state(LAMBDA (s:tpmAbsState) : (x,s));
```

What unit does is lift a member of tmpAbsState into State – given a tpmAbsState produce a State for it. Specifically, when unit is provided with a tpmAbsState it should give back a State whose runState field should simply produce it.

3 Verification Approach

The approach taken for verification is establishing a *weak bisimulation* [Sangiorgi, 2012] relation between an abstract requirements model and a model derived from the TPM specification as shown in figure 4.

We say that $A=(S,\Sigma,\Delta)$ is an abstract model where S is a set of abstract states, Σ is a set of actions on states and input, and $\Delta:S\times\Sigma\to\Sigma$ is a transitions on state and action. Similarly, we say that $C=(s,\sigma,\delta)$ is a concrete state—where s is a set of concrete states, σ is a set of actions on states and input, and $\delta:s\times\sigma\to\sigma$ is a transition function.

We relate the abstract and concrete models through an abstraction function, $\alpha: s \to S$, and concretization function, $\gamma: S \to 2^s$. The abstraction and concretization functions must form a Galois Connection such that:

$$s \in \gamma(\alpha(s))$$

Specifically, when making the result of an abstraction concrete, the original state must be in the resulting set. Note that the concretization function may result in multiple states due to the necessity of specifying unknown detail.

We say that A and C are weakly bisimilar $(A \sim C)$ if when $\alpha(s) = S$ then $\alpha(\delta^*(s)) = \Delta(S)$ for all inputs to s.




Figure 4: Weak bisimulation relation between an abstract transition system $A = (S, \Sigma, \Delta)$ and a concrete transition system $C = (s, \sigma, \delta)$.

Definition 1

$$A \sim C \equiv \forall s_0 : s \cdot \exists S_0 : S \cdot \alpha(s_0) = S_0 \Rightarrow \alpha(\delta^*(s_0)) = \Delta(S_0)$$

In the formal TPM model tpmAbsState defines S while tpmConcState defines s.

Glossary

This glossary is intended to document some common acronyms as well as define some common terms. It is currently a bit haphazard and a number of elements are missing.

A Trusted Platform Definitions

Trusted Platform Module (TPM) – Hardware Trusted Platform Module as defined by TCG.

Process Configuration Register (PCR) – Registers defined in the TPM. In the TPM there are at least 16 and they are 20 bytes wide.

Bound to PCR – Encryption including PCR values that must match TPM PCR values before decryption is performed.

Sealed to State – Operation performed by the TPM where data is encrypted and bound to PCRs or a PCR composite that must be checked before unsealing. Only data is sealed.

- **Wrapped Key** An asymmetric key with its private key encrypted and its public key visible. Only keys are wrapped.
- Virtual TPM (vTPM) A virtual Trusted Platform Module
- **Certified Key (CK)** Asymmetric key with private key signed by the AIK private key.
- **Endorsement Key (EK)** Asymmetric key who's private key is in the TPM hardware. Private key is used to sign data from TPM while public key is used to encrypt sensitive data sent to the TPM. The EK is set by the TPM factory and may not be reset.
- Attestation Identity Key (AIK) Asymmetric key whose private key is used for only two purposes: (i) sign (or attest to) TPM internal state; (ii) sign (or certify) other general purpose keys. AIKs are generated by a TPM, certified by a trusted third party, and used for signing in lieu of the EK.
- **Storage Root Key (SRK)** Root of secure storage hierarchy. Used to encrypt storage keys that exist outside the TPM. The SRK may be reset.
- Attestation Identity Certificate (AIC) Certificate provided by a trusted third party binding an AIK to a specific trusted platform.
- **Digest** 20-byte Value contained in a PCR.
- PCR Composite Single digest value generated from a collection of PCR values
- **Quote** A value along with a set of PCR values or PCR composite signed by a TPM using an AIK.
- Root of Trust for Measurement (RTM) the "place to stand" for measurement. Effectively a hardware-based trusted launch point that will faithfully measure, start and pass control to its target without trusting other components.
- Root of Trust for Storage (RTS) the "place to stand" for measurement storage. Effectively a trusted hardware store that will store measurements with integrity without trusting other components.
- Root of Trust for Reporting (RTR) the "place to stand" for generating quotes and providing evidence with integrity and authenticity. Effectively a trusted hardware component that generates and signs quotes.

B Cryptography Notations

Hash Notation #data - The hash of data.

Certificate Notation $[[cert]]_{key}$ - Certificate, cert, signed by key.

Signed Data Notation $\{|data|\}_{kev^{-1}}$ - data, signed by key.

Encrypted Data Notation $\{data\}_{key}$ - data encrypted with key.

Sealed Data Notation $seal(data, \{pcrs\})$ - data sealed to pcrs.

Wrapped Key Notation $wrap(k, \{pcrs\})$ - Equivalent to the key pair $(seal(k^{-1}, \{pcrs\}), k)$

C Intel Secure Boot

Trusted eXecution Technology (TXT) - Intel's trusted boot support.

- Measured Launch Environment (MLE) Run time environment providing a measured boot. Initialized and started by the SINIT command execution.
- **SENTER or GETSEC** Intel's trusted boot command. Provides synchronization, special bus cycles, and a special environment residing on the CPU (ACEA).
- **Secure INITialization Instructions (SINIT)** Code for performing secure initialization. Loaded by SENTER and validated by the ACM.
- **Authenticated Code Execution Area (ACEA)** CPU resident environment for executing code known as the Authenticated Code Module (ACM). Boot sequence involving SENTER and SINIT is as follows:
 - 1. Load SINIT and MLE into memory
 - 2. Invoke SENTER (GETSEC)
 - 3. Establish special environment (ACEA)
 - 4. Load SINIT into ACEA
 - 5. Validate SINIT digital signature and store SINIT identity in TPM
 - 6. SINIT measures MLE in memory and stores MLE identity in TPM
 - 7. SINIT passes control to MLE
- **Authenticated Code Module (ACM)** Code running in the ACEA. May be used for validating platform configuration, measuring the measured launch environment, cleaning up after crashes.

References

D. Sangiorgi. *Introduction to Bisimulation and Coinduction*. Cambridge University Press, 2012.