References

[1]   Ahonen, S. and Eskelinen, P., "Mobile terminal location for UMTS," *IEEE Aerospace and Electronic Systems Magazine,* vol. 18, no. 2, pp. 23-27, 2003.

[2]   Akgul, F. O. and Pahlavan, K., "AOA assisted NLOS error mitigation for TOA-based indoor positioning systems," in *IEEE Military Communications Conference*, Orlando, USA, 2007, pp. 1-5.

[3]   Al-Jazzar, S. and Caffery Jr, J., "ML and Bayesian TOA location estimators for NLOS environments," in *IEEE 56th Vehicular Technology Conference*, Vancouver, Canada, 2002, pp. 1178-1181.

[4]   Bachrach, A., Garamifard, A., Gurdan, D., He, R., Prentice, S., Stumpf, J., and Roy, N., "Co-ordinated tracking and planning using air and ground vehicles," in *International Symposium on Experimental Robotics*, Athens, Greece, 2008.

[5]   Bahl, P. and Padmanabhan, V. N., "RADAR: An in-building RF-based user location and tracking system," in *19th Annual Joint Conference of the IEEE Computer and Communications Societies*, Tel Aviv, Israel, 2000, pp. 775-784.

[6]   Bahl, P., Padmanabhan, V. N., and Balachandran, A., "A software system for locating mobile users: Design, evaluation, and lessons," *Online document, Microsoft Research, February,* 2000.

[7]   Bellusci, G., Yan, J., Janssen, G. J. M., and Tiberius, C. C. J., "An ultra-wideband positioning demonstrator using audio signals," in *4th Workshop on Positioning, Navigation and Communication*, Hannover, Germany, 2007, pp. 71-76.

[8]   Borras, J., Hatrack, P., and Mandayam, N. B., "Decision theoretic framework for NLOS identification," in *48th IEEE Vehicular Technology Conference*, Ottawa, Canada, 1998, pp. 1583-1587.

[9]   Bosse, M., Rikoski, R., Leonard, J., and Teller, S., "Vanishing points and 3d lines from omnidirectional video," *The Visual Computer,* vol. 19, no. 6, pp. 417-430, 2003.

[10]   Brunato, M. and Battiti, R., "Statistical learning theory for location fingerprinting in wireless LANs," *Computer Networks,* vol. 47, no. 6, pp. 825-845, 2005.

[11]   Burgard, W., Cremers, A. B., Fox, D., Hänel, D., Lakemeyer, G., Schulz, D., Steiner, W., and Thrun, S., "Experiences with an interactive museum tour-guide robot," *Artificial Intelligence,* vol. 114, no. 1-2, pp. 3-55, 1999.

[12]   Caffery, J. J., *Wireless location in CDMA cellular radio systems*. Boston: Kluwer, 1999.

[13]   Caffery, J. J., "A new approach to the geometry of TOA location," in *52nd Vehicular Technology Conference*, Boston, USA, 2000, pp. 1943-1949.

[14]   Caffery, J. J. and Stuber, G. L., "Overview of radiolocation in CDMA cellular systems," *IEEE Communications Magazine,* vol. 36, no. 4, pp. 38-45, 1998.

[15]   Casper, J. and Murphy, R. R., "Human-robot interactions during the robot-assisted urban search and rescue response at the world trade center," *IEEE Transactions on Systems, Man, and Cybernetics, Part B,* vol. 33, no. 3, pp. 367-385, 2003.

[16]   Castellanos, J. A., Martinez, J. M., Neira, J., and Tardos, J. D., "Simultaneous map building and localization for mobile robots: A multisensor fusion approach," in *IEEE International Conference on Robotics and Automation*, Leuven, Belgium, 1998.

[17]   Castellanos, J. A., Neira, J., and Tardos, J. D., "Multisensor fusion for simultaneous localization and map building," *IEEE Transactions on Robotics and Automation,* vol. 17, no. 6, pp. 908-914, 2001.

[18]   Chan, Y. T. and Ho, K. C., "A simple and efficient estimator for hyperbolic location," *IEEE Transactions on Signal Processing,* vol. 42, no. 8, pp. 1905-1915, 1994.

[19]   Chan, Y. T., Tsui, W. Y., So, H. C., and Ching, P., "Time-of-arrival based localization under NLOS conditions," *IEEE Transactions on Vehicular Technology,* vol. 55, no. 1, pp. 17-24, 2006.

[20]   Chen, P. C., "A non-line-of-sight error mitigation algorithm in location estimation," in *IEEE Wireless Communications and Networking Conference*, New Orleans, USA, 1999, pp. 316-320.

[21]   Chen, Y., Kleisouris, K., Li, X., Trappe, W., and Martin, R. P., "The robustness of localization algorithms to signal strength attacks: A comparative study," in *Distributed Computing in Sensor Systems*. vol. 4026: Springer-Verlag Berlin Heidelberg New York, 2006, pp. 546-563.

[22]   Chen, Y. and Rui, Y., "Real-time speaker tracking using particle filter sensor fusion," *Proceedings of the IEEE,* vol. 92, no. 3, pp. 485-494, 2004.

[23]   Chen, Y. C., Chiang, J. R., Chu, H., Huang, P., and Tsui, A. W., "Sensor-assisted Wi-Fi indoor location system for adapting to environmental dynamics," in *8th Association for Computing Machinery International Symposium on Modeling, Analysis and Simulation of Wireless and Mobile Systems*, Montréal, Canada, 2005, pp. 118-125.

[24]   Civera, J., Davison, A. J., and Montiel, J. M. M., "Inverse depth parametrization for monocular SLAM," *IEEE Trans. Robotics,* vol. 24, no. 5, 2008.

[25]   Cong, L. and Zhang, W., "Non-line-of-sight error mitigation in TDOA mobile location," in *IEEE Global Communications Conference*, San Antonio, USA, 2001, pp. 680-684.

[26]   Cong, L. and Zhuang, W., "Hybrid TDOA/AOA mobile user location for wideband CDMA cellular systems," *IEEE Transactions on Wireless Communications,* vol. 1, no. 3, pp. 439-447, 2002.

[27]   Cong, L. and Zhuang, W., "Nonline-of-sight error mitigation in mobile location," *IEEE Transactions on Wireless Communications,* vol. 4, no. 2, pp. 560-573, 2005.

[28]   Coronato, A. and Esposito, M., "Towards an implementation of smart hospital: A localization system for mobile users and devices," in *6th Annual IEEE International Conference on Pervasive Computing and Communications*, Hong Kong, China, 2008, pp. 715-719.

[29]   Correal, N. S., Kyperountas, S., Shi, Q., and Welborn, M., "An UWB relative location system," in *IEEE Conference on Ultra Wideband Systems and Technologies*, Reston, USA, 2003.

[30]   Csorba, M., Uhlmann, J. K., and Durrant-Whyte, H. F., "New approach to simultaneous localization and dynamic map building," in *SPIE 10th Annual AeroSense Symposium*, Orlando, USA 1996, pp. 26-36.

[31]   Danicki, E., "The shock wave-based acoustic sniper localization," *Nonlinear Analysis,* vol. 65, no. 5, pp. 956-962, 2006.

[32]   Davison, A. J., Cid, Y. G., and Kita, N., "Real-time 3D SLAM with wide-angle vision," in *5th IFAC Symposium on Intelligent Autonomous Vehicles*, Lisbon, Portugal, 2004.

[33]   Davison, A. J., Reid, I. D., Molton, N. D., and Stasse, O., "MonoSLAM: Real-time single camera SLAM," *IEEE Transactions on Pattern Analysis and Machine Intelligence,* vol. 29, no. 6, pp. 1052-1067, 2007.

[34]   Denis, B., Keignart, J., and Daniele, N., "Impact of NLOS propagation upon ranging precision in UWB systems," in *IEEE Conference on Ultra Wideband Systems and Technologies*, Reston, USA, 2003, pp. 379-383.

[35]   DiBiase, J. H., "A high-accuracy, low-latency technique for talker localization in reverberant environments using microphone arrays," PhD dissertation, Brown University, Division of Engineering, Providence, Rhode Island, 2000.

[36]   DiBiase, J. H., Silverman, H. F., and Brandstein, M. S., "Robust localization in reverberant rooms," in *Microphone Arrays: Signal Processing Techniques and Applications*, Brandstein, M. S. and Ward, D., Eds.: Springer-Verlag Berlin Heidelberg New York, 2001, pp. 157-180.

[37]   Do, H., Silverman, H. F., and Yu, Y., "A real-time SRP-PHAT source location implementation using stochastic region contraction (SRC) on a large-aperture microphone array," in *32nd IEEE International Conference on Acoustics, Speech and Signal Processing*, Honolulu, USA, 2007, pp. 121-124.

[38]   Dosso, S. E., Collison, N. E. B., Heard, G. J., and Verrall, R. I., "Experimental validation of regularized array element localization," *The Journal of the Acoustical Society of America,* vol. 115, p. 2129, 2004.

[39]   Durrant-Whyte, H., "Uncertain geometry in robotics," *IEEE Transactions on Robotics and Automation,* vol. 4, no. 1, pp. 23-31, 1988.

[40]   Durrant-Whyte, H. and Bailey, T., "Simultaneous localization and mapping: Part I," *IEEE Robotics & Automation Magazine,* vol. 13, no. 2, pp. 99-110, 2006.

[41]   Elnahrawy, E., Li, X., and Martin, R. P., "The limits of localization using signal strength: A comparative study," in *1st Annual IEEE Communications Society Conference on Sensor and Ad Hoc Communications and Networks*, Santa Clara, USA, 2004, pp. 406-414.

[42]   Evennou, F. and Marx, F., "Advanced integration of WiFi and inertial navigation systems for indoor mobile positioning," *EURASIP Journal on Applied Signal Processing,* vol. 2006, pp. 1-11, 2006.

[43]   Falsi, C., Dardari, D., Mucchi, L., and Win, M. Z., "Time of arrival estimation for UWB localizers in realistic environments," *EURASIP Journal on Applied Signal Processing,* vol. 2006, pp. 1-13, 2006.

[44]   Fang, S. H. and Lin, T. N., "Robust wireless LAN location fingerprinting by SVD-based noise reduction," in *3rd International Symposium on Communications, Control and Signal Processing*, St. Julians, Malta, 2008, pp. 295-298.

[45]   Fang, S. H., Lin, T. N., and Lee, K. C., "A novel algorithm for multipath fingerprinting in indoor WLAN environments," *IEEE Transactions on Wireless Communications,* vol. 7, no. 9, pp. 3579-3588, 2008.

[46]   Ferris, B., Fox, D., and Lawrence, N., "WiFi-SLAM using Gaussian process latent variable models," in *20th International Joint Conference on Artificial Intelligence*, Hyderabad, India, 2007, pp. 2480-2485.

[47]   Ferris, B., Hahnel, D., and Fox, D., "Gaussian processes for signal strength-based location estimation," in *Robotics Science and Systems*, Philadelphia, USA, 2006.

[48]   Fleming, R. and Kushner, C., "Low-power, miniature, distributed position location and communication devices using ultra-wideband, nonsinusoidal communication technology," *Aetherwire Inc., Semi-Annual Technical Report, ARPA Contract J-FBI-94-058, Tech. Rep,* 1995.

[49]   Fontana, R. J. and Gunderson, S. J., "Ultra-wideband precision asset location system," in *IEEE Conference on Ultra Wideband Systems and Technologies*, Baltimore, USA, 2002, pp. 147-150.

[50]   Foy, W. H., "Position-location solutions by Taylor-series estimation," *IEEE Transactions on Aerospace and Electronic Systems,* vol. 12, no. 2, pp. 187-194, 1976.

[51]   Frampton, K. D., "Acoustic self-localization in a distributed sensor network," *IEEE Sensors Journal,* vol. 6, no. 1, pp. 166-172, 2006.

[52]   Frens, M. A. and Opstal, A. J., "A quantitative study of auditory-evoked saccadic eye movements in two dimensions," *Experimental Brain Research,* vol. 107, no. 1, pp. 103-117, 1995.

[53]   Garcia, M. A. and Solanas, A., "3D simultaneous localization and modeling from stereo vision," in *IEEE International Conference on Robotics and Automation*, New Orleans, USA, 2004, pp. 847-853.

[54]   Gezici, S., Tian, Z., Giannakis, G. B., Kobayashi, H., Molisch, A. F., Poor, H. V., and Sahinoglu, Z., "Localization via ultra-wideband radios: A look at positioning aspects for future sensor networks," *IEEE Signal Processing Magazine,* vol. 22, no. 4, pp. 70-84, 2005.

[55]   Ghassemzadeh, S. S., Greenstein, L. J., Sveinsson, T., Kavcic, A., and Tarokh, V., "UWB delay profile models for residential and commercial indoor environments," *IEEE Transactions on Vehicular Technology,* vol. 54, no. 4, pp. 1235-1244, 2005.

[56]   Gil-Pinto, A., Fraisse, P., and Zapata, R., "Wireless reception signal strength for relative positioning in a vehicle robot formation," in *IEEE 3rd Latin American Robotics Symposium*, Santiago, Chile, 2006, pp. 100-105.

[57]   Gill, P. E., Murray, W., and Wright, M. H., *Practical optimization*: Academic Press San Diego, 1981.

[58]   Girod, L. and Estrin, D., "Robust range estimation using acoustic and multimodal sensing," in *IEEE/RSJ International Conference on Intelligent Robots and Systems*, Maui, USA, 2001, pp. 1312-1320.

[59]   Goedemé, T., Nuttin, M., Tuytelaars, T., and Van Gool, L., "Omnidirectional vision based topological navigation," *International Journal of Computer Vision,* vol. 74, no. 3, pp. 219-236, 2007.

[60]   Graefenstein, J., Bouzouraa, M. E., GmbH, R. B., and Schwieberdingen, G., "Robust method for outdoor localization of a mobile robot using received signal strength in low power wireless networks," in *IEEE International Conference on Robotics and Automation*, Pasadena, USA, 2008, pp. 33-38.

[61]   Guivant, J. E. and Nebot, E. M., "Optimization of the simultaneous localization and map-building algorithm for real-time implementation," *IEEE Transactions on Robotics and Automation,* vol. 17, no. 3, pp. 242-257, 2001.

[62]   Guvenc, I., Chong, C. C., and Watanabe, F., "Joint TOA estimation and localization technique for UWB sensor network applications," in *IEEE 65th Vehicular Technology Conference*, Dublin, Ireland, 2007, pp. 1574-1578.

[63]   Haeberlen, A., Flannery, E., Ladd, A. M., Rudys, A., Wallach, D. S., and Kavraki, L. E., "Practical robust localization over large-scale 802.11 wireless networks," in *10th Annual International Conference on Mobile Computing and Networking*, Philadelphia, USA, 2004, pp. 70-84.

[64]   Halupka, D., Mathai, N. J., Aarabi, P., and Sheikholeslami, A., "Robust sound localization in 0.18 μm CMOS," *IEEE Transactions on Signal Processing,* vol. 53, no. 6, pp. 2243-2250, 2005.

[65]   Heidari, M. and Pahlavan, K., "Identification of the absence of direct path in ToA-based indoor localization systems," *International Journal of Wireless Information Networks,* vol. 15, no. 3, pp. 117-127, 2008.

[66]   Hightower, J. and Borriello, G., "Particle filters for location estimation in ubiquitous computing: A case study," in *UbiComp 2004: Ubiquitous Computing*: Springer-Verlag Berlin Heidelberg New York, 2004, pp. 88-106.

[67]   Hofman, P. M., Van Riswick, J. G., and Van Opstal, A. J., "Relearning sound localization with new ears," *Nature Neuroscience,* vol. 1, no. 5, pp. 417-421, 1998.

[68]   Hollinger, G., Djugash, J., and Singh, S., "Tracking a moving target in cluttered environments with ranging radios," in *IEEE International Conference on Robotics and Automation*, Pasadena, USA, 2008, pp. 1430-1435.

[69]   Hu, J. S., Liu, W. H., Cheng, C. C., and Yang, C. H., "Location and orientation detection of mobile robots using sound field features under complex environments," in *IEEE/RSJ International Conference on Intelligent Robots and Systems*, Beijing, China, 2006, pp. 1151-1156.

[70]   Irahhauten, Z., Bellusci, G., Janssen, G. J. M., Nikookar, H., and Tiberius, C., "Investigation of UWB ranging in dense indoor multipath environments," in *10th IEEE Singapore International Conference on Communication systems*, Singapore, Singapore, 2006, pp. 1-5.

[71]   Jensfelt, P., Kragic, D., Folkesson, J., and Bjorkman, M., "A framework for vision based bearing only 3D SLAM," in *IEEE International Conference on Robotics and Automation*, Orlando, USA, 2006, pp. 1944-1950.

[72]   Jourdan, D. B., "Wireless sensor network planning with application to UWB localization in GPS-denied environments," PhD dissertation, Massachusetts Institute of Technology, Department of Aeronautics and Astronautics, Cambridge, USA, 2006.

[73]   Jourdan, D. B., Deyst Jr, J. J., Win, M. Z., and Roy, N., "Monte Carlo localization in dense multipath environments using UWB ranging," in *IEEE International Conference on Ultra-Wideband*, Zurich, Switzerland, 2005, pp. 314-319.

[74]   Kanatas, A. G., Kountouris, I. D., Kostaras, G. B., and Constantinou, P., "A UTD propagation model in urban microcellular environments," *IEEE Transactions on Vehicular Technology,* vol. 46, no. 1, pp. 185-193, 1997.

[75]   Kapralos, B., Jenkin, M., and Milios, E., "Acoustical diffraction modeling utilizing the Huygens-Fresnel principle," in *IEEE International Workshop on Haptic Audio Visual*, Ottawa, Canada, 2005, pp. 39-44.

[76]   Kawai, T., "Sound diffraction by a many-sided barrier or pillar," *Journal of Sound and Vibration,* vol. 79, no. 2, pp. 229-242, 1981.

[77]   Kjærgaard, M. B., "A taxonomy for radio location fingerprinting," in *Location- and Context-Awareness*. vol. 4718, Hightower, J., Schiele, B., and Strang, T., Eds.: Springer-Verlag Berlin Heidelberg New York, 2007, pp. 139-156.

[78]   Knapp, C. and Carter, G., "The generalized correlation method for estimation of time delay," *IEEE Transactions on Acoustics, Speech and Signal Processing,* vol. 24, no. 4, pp. 320-327, 1976.

[79]   Kouyoumjian, R. G. and Pathak, P. H., "A uniform geometrical theory of diffraction for an edge in a perfectly conducting surface," *Proceedings of the IEEE,* vol. 62, no. 11, pp. 1448-1461, 1974.

[80]   Kumon, M., Shimoda, T., Kohzawa, R., Mizumoto, I., and Iwai, Z., "Audio servo for robotic systems with pinnae," in *International Conference on Intelligent Robots and Systems*, Edmonton, Canada, 2005, pp. 1881-1886.

[81]   Ladd, A. M., Bekris, K. E., Rudys, A. P., Wallach, D. S., and Kavraki, L. E., "On the feasibility of using wireless ethernet for indoor localization," *IEEE Transactions on Robotics and Automation,* vol. 20, no. 3, pp. 555-559, 2004.

[82]   Langelaan, J. and Rock, S., "Navigation of small UAVs operating in forests," in *AIAA Guidance, Navigation, and Control Conference and Exhibit*, Providence, USA, 2004, pp. 16-19.

[83]   Lavis, B., Furukawa, T., and Durrant Whyte, H. F., "Dynamic space reconfiguration for Bayesian search and tracking with moving targets," *Autonomous Robots,* vol. 24, no. 4, pp. 387-399, 2008.

[84]   Lee, J. Y. and Scholtz, R. A., "Ranging in a dense multipath environment using an UWB radio link," *IEEE Journal on Selected Areas in Communications,* vol. 20, no. 9, pp. 1677-1683, 2002.

[85]   Lee, J. Y. and Yoo, S., "Large error performance of UWB ranging in multipath and multiuser environments," *IEEE transactions on microwave theory and techniques,* vol. 54, no. 4, pp. 1887-1895, 2006.

[86]   Lee, S. W. and Mase, K., "Activity and location recognition using wearable sensors," *IEEE Pervasive Computing,* vol. 1, no. 3, pp. 24-32, 2002.

[87]   Lemaire, T., Lacroix, S., and Sola, J., "A practical 3D bearing-only SLAM algorithm," in *IEEE/RSJ International Conference on Intelligent Robots*, Edmonton, Canada, 2005, pp. 2449-2454.

[88]   Letchner, J., Fox, D., and LaMarca, A., "Large-scale localization from wireless signal strength," in *AAAI National Conference on Artificial Intelligence*, Pittsburgh, USA, 2005, pp. 15-20.

[89]   Li, J., Conan, J., and Pierre, S., "Mobile station location estimation for MIMO communication systems," in *3rd International Symposium on Wireless Communication Systems*, Valencia, Spain, 2006, pp. 561-564.

[90]   Li, Y. Z., Wang, L., Wu, X. M., and Zhang, Y. T., "Experimental analysis on radio transmission and localization of a Zigbee-based wireless healthcare monitoring platform," in *International Conference on Technology and Applications in Biomedicine*, Shenzhen, China, 2008, pp. 488-490.

[91]   Lim, H., Kung, L. C., Hou, J. C., and Luo, H., "Zero-configuration, robust indoor localization: Theory and experimentation," in *IEEE 25th Conference on Computer Communications*, Barcelona, Spain, 2006, pp. 123-125.

[92]   Lin, C. H., Cheng, J. Y., and Wu, C. N., "Mobile location estimation using density-based clustering technique for NLoS environments," *Cluster Computing,* vol. 10, no. 1, pp. 3-16, 2007.

[93]   Liu, L., Deng, P., and Fan, P., "A TOA reconstruction method based on ring of scatterers model," in *4th International Conference on Parallel and Distributed Computing, Applications and Technologies*, Chengdu, China, 2003, pp. 375-377.

[94]   Low, Z. N., Cheong, J. H., Law, C. L., Ng, W. T., and Lee, Y. J., "Pulse detection algorithm for line-of-sight (LOS) UWB ranging applications," *IEEE Antennas and Wireless Propagation Letters,* vol. 4, pp. 63-67, 2005.

[95]   Madigan, D., Einahrawy, E., Martin, R. P., Ju, W. H., Krishnan, P., and Krishnakumar, A. S., "Bayesian indoor positioning systems," in *24th Annual Joint Conference of the IEEE Computer and Communications Societies*, Miami, USA, 2005.

[96]   Mak, L. C. and Furukawa, T., "A 6 DoF visual tracking system for a miniature helicopter," in *2nd International Conference on Sensing Technology*, Palmerston North, New Zealand, 2007.

[97]   Mak, L. C., Kumon, M., Whitty, M., Katupitiya, J., and Furukawa, T., "Design and development of micro aerial vehicles and their cooperative systems for target search and tracking," *International Journal of Micro Air Vehicles,* vol. 1, no. 2, pp. 139-153, 2009.

[98]   Mak, L. C., Kumon, M., Whitty, M., Nicoletti, M., Xu, H., Zhan, K., Kalkbrenner, G., Abril, G. C., Atkins, D., Chare, C., Clarke, B., Khurmi, A., Ma, A., Qureshi, F., Zambrano, J. P., Upadhyay, A., Sammons, P., Hu, A. W. L., and Furukawa, T., "Design and development of the micro aerial vehicles for search, tracking And reconnaissance (MAVSTAR) for MAV08," in *1st US-Asian Demonstration and Assessment of Micro Aerial and Unmanned Ground Vehicle Technology*, Agra, India, 2008.

[99]   Mak, L. C., Whitty, M., and Furukawa, T., "A localisation system for an indoor rotary-wing MAV using blade mounted LED," *Sensor Review,* vol. 28, no. 2, pp. 125-131, 2008.

[100]   Miao, H., *Channel estimation and positioning for multiple antenna systems*. Oulu, Finland: University of Oulu, 2007.

[101]   Miao, H., Yu, K., Juntti, M. J., and Platform, H., "Positioning for NLOS propagation: Algorithm derivations and Cramer-Rao bounds," *IEEE Transactions on Vehicular Technology,* vol. 56, no. 5 Part 1, pp. 2568-2580, 2007.

[102]   Montesano, L., Minguez, J., and Montano, L., "Modeling the static and the dynamic parts of the environment to improve sensor-based navigation," in *International Conference on Robotics and Autonomation*, Barcelona, Spain, 2005, pp. 4556-4562.

[103]   Morelli, C., Nicoli, M., Rampa, V., and Spagnolini, U., "Hidden Markov models for radio localization in mixed LOS/NLOS conditions," *IEEE Transactions on Signal Processing,* vol. 55, no. 4, pp. 1525-1542, 2007.

[104]   Mountarlier, P. and Chatila, R., "Stochastic multi-sensory data fusion for mobile robot location and environmental modeling," in *Fifth International Symposium on Robotics Research*, Tokyo, Japan, 1989, pp. 85-94.

[105]   Mumolo, E., Nolich, M., and Vercelli, G., "Algorithms for acoustic localization based on microphone array in service robotics," *Robotics and Autonomous Systems,* vol. 42, no. 2, pp. 69-88, 2003.

[106]   Murphy, W. S. and Hereman, W., "Determination of a position in three dimensions using trilateration and approximate distances," Mathematical and Computer Sciences Dept., Colorado School of Mines, Tech. report MCS-95-07, 1995.

[107]   Nag, S., Barnes, M. A., Payment, T., and Holladay, G., "Ultrawideband through-wall radar for detecting the motion of people in real time," in *Processing of Conferences & Publications on Photonics, Optics, & Imaging*, San Jose, USA, 2002, pp. 48-57.

[108]   Nerguizian, C., Despins, C., and Affès, S., "Geolocation in mines with an impulse response fingerprinting technique and neural networks," *IEEE Transactions on Wireless Communications,* vol. 5, no. 3, pp. 603-611, 2006.

[109]   Nicoli, M., Morelli, C., and Rampa, V., "A jump Markov particle filter for localization of moving terminals in multipath indoor scenarios," *IEEE Transactions on Signal Processing,* vol. 56, no. 8, pp. 3801-3809, 2008.

[110]   Omologo, M. and Svaizer, P., "Acoustic event localization using a crosspower-spectrum phase based technique," in *International Conference on Spoken Language Processing*, San Diego, USA, 1994.

[111]   Oppermann, I., Hamalainen, M., and Linatti, J., *UWB theory and applications*. England: John Wiley and Sons, 2004.

[112]   Pan, J. J., Kwok, J. T., Yang, Q., and Chen, Y., "Multidimensional vector regression for accurate and low-cost location estimation in pervasive computing," *IEEE Transactions on Knowledge and Data Engineering,* pp. 1181-1193, 2006.

[113]   Pan, S. J., Kwok, J. T., Yang, Q., and Pan, J. J., "Adaptive localization in a dynamic wifi environment through multi-view learning," in *22nd AAAI Conference on Artificial Intelligence*, Vancouver, Canada, 2007, pp. 1102-1107.

[114]   Patwari, N., Ash, J. N., Kyperountas, S., Hero Iii, A. O., Moses, R. L., and Correal, N. S., "Locating the nodes: Cooperative localization in wireless sensor networks," *IEEE Signal Processing Magazine,* vol. 22, no. 4, pp. 54-69, 2005.

[115]   Paz, L. M., Pinies, P., Tardos, J. D., and Neira, J., "Large-scale 6-DOF SLAM with stereo-in-hand," *IEEE Transactions on Robotics,* vol. 24, no. 5, pp. 946-957, 2008.

[116]   Perera, L. D. L., Wijesoma, W. S., and Adams, M. D., "Data association in dynamic environments using a sliding window of temporal measurement frames," in *IEEE/RSJ International Conference on Intelligent Robots*, Edmonton, Canada, 2005, pp. 753-758.

[117]   Pupilli, M. and Calway, A., "Real-time camera tracking using a particle filter," in *British Machine Vision Conference*, Oxford, UK, 2005, pp. 519-528.

[118]   Qi, Y., Kobayashi, H., and Suda, H., "On time-of-arrival positioning in a multipath environment," *IEEE Transactions on Vehicular Technology,* vol. 55, no. 5, pp. 1516-1526, 2006.

[119] Quill, H., "John Harrison, Copley medallist and the Pound 20,000 longitude prize," *Notes and Records of the Royal Society of London,* vol. 18, no. 2, pp. 146-160, 1963.

[120] Robinson, M. and Psaromiligkos, I., "Received signal strength based location estimation of a wireless LAN client," in *IEEE Wireless Communications and Networking Conference*, New Orleans, USA, 2005, pp. 2350-2354.

[121] Rosencrantz, M., Gordon, G., and Thrun, S., "Decentralized sensor fusion with distributed particle filters," in *19th Annual Conference on Uncertainty in Artificial Intelligence*, San Francisco, USA, 2003.

[122] Roumeliotis, S. I. and Bekey, G. A., "An extended Kalman filter for frequent local and infrequent global sensor data fusion," in *SPIE sensor fusion and decentralized control in autonomous robotic systems*, Pittsburgh, USA, 1997.

[123] Saffiotti, A. and Broxvall, M., "PEIS ecologies: Ambient intelligence meets autonomous robotics," in *Joint Conference on Smart Objects and Ambient Intelligence: Innovative Context-Aware Services: Usages and Technologies*, Grenoble, France, 2005, pp. 277-281.

[124] Saripalli, S., Montgomery, J. F., and Sukhatme, G. S., "Vision-based autonomous landing of an unmanned aerial vehicle," in *IEEE International Conference on Robotics and Automation*, Washington, D.C., USA, 2002, pp. 2799-2804.

[125] Sasaki, Y., Kagami, S., and Mizoguchi, H., "Multiple sound source mapping for a mobile robot by self-motion triangulation," in *IEEE/RSJ International Conference on Intelligent Robots*, Beijing, China, 2006, pp. 380-385.

[126] Sasiadek, J. Z. and Hartana, P., "Sensor data fusion using Kalman filter," in *3rd International Conference on Information Fusion*, Paris, France, 2000, pp. 19-25.

[127] Savvides, A., Han, C. C., and Strivastava, M. B., "Dynamic fine-grained localization in ad-hoc networks of sensors," in *International Conference on Mobile Computing and Networking*, Rome, Italy, 2001, pp. 166-179.

[128] Saxena, A. and Ng, A. Y., "Learning sound location from a single microphone," in *IEEE International Conference on Robotics and Automation*, Kobe, Japan, 2009, pp. 1737-1742.

[129] Sayed, A. H., Tarighat, A., and Khajehnouri, N., "Network-based wireless location: Challenges faced in developing techniques for accurate wireless location information," *IEEE Signal Processing Magazine,* vol. 22, no. 4, pp. 24-40, 2005.

[130] Schmidt, R. O., "A new approach to geometry of range difference location," *IEEE Transactions on Aerospace and Electronic Systems,* pp. 821-835, 1972.

[131] Seow, C. K. and Tan, S. Y., "Non-line-of-sight localization in multipath environment," *IEEE Transactions on Mobile Computing,* vol. 7, no. 5, pp. 647-660, 2008.

[132] Seow, C. K. and Tan, S. Y., "Non-line-of-sight unidirectional mobile localisation in multipath environment," *Electronics Letters,* vol. 44, no. 2, pp. 141-142, 2008.

[133] Seshadri, V., Zaruba, G. V., and Huber, M., "A Bayesian sampling approach to in-door localization of wireless devices using received signal strength indication," in *3rd IEEE International Conference on Pervasive Computing and Communications*, Kauai, USA, 2005, pp. 75-84.

[134] Shimoda, T., Nakashima, T., Kumon, M., Kohzawa, R., Mizumoto, I., and Iwai, Z., "Spectral cues for robust sound localization with pinnae," in *International Conference on Intelligent Robots and Systems*, Beijing, China, 2006, pp. 386-391.

[135] Shkarayev, S., Moschetta, J. M., and Bataill, B., "Aerodynamic Design of VTOL Micro Air Vehicles'," 2007.

[136] Silverman, H. F., Patterson, J. M., and Wr, II, "Performance of real-time source-location estimators for a large-aperture microphone array," *IEEE Transactions on Speech and Audio Processing*, vol. 13, no. 4, pp. 593-606, 2005.

[137] Small, R. H., "Vented-box loudspeaker systems part I: Small-signal analysis," *Journal of the Audio Engineering Society*, vol. 21, no. 5, pp. 363-372, 1973.

[138] Smith, J. and Abel, J., "Closed-form least-squares source location estimation from range-difference measurements," *IEEE Transactions on Acoustics, Speech and Signal Processing*, vol. 35, no. 12, pp. 1661-1669, 1987.

[139] Smith, P., Reid, I., and Davison, A., "Real-time monocular SLAM with straight lines," in *British Machine Vision Conference*, Edinburgh, UK, 2006, pp. 17-26.

[140] Smith, R., Self, M., and Cheeseman, P., "Estimating uncertain spatial relationships in robotics," *Autonomous robot vehicles*, vol. 1, pp. 167-193, 1990.

[141] Smith, R. C. and Cheeseman, P., "On the representation and estimation of spatial uncertainty," *The International Journal of Robotics Research*, vol. 5, no. 4, p. 56, 1986.

[142] Stasse, O., Davison, A., Sellaouti, R., and Yokoi, K., "Real-time 3D SLAM for humanoid robot considering pattern generator information," in *International Conference on Intelligent Robots and Systems*, Beijing, China, 2006, pp. 348-355.

[143] Steiner, C., Althaus, F., Troesch, F., and Wittneben, A., "Ultra-wideband geo-regioning: A novel clustering and localization technique," *EURASIP Journal on Advances in Signal Processing*, vol. 8, no. 1, pp. 1-13, 2008.

[144] Storer, J. A. and Reif, J. H., "Shortest paths in the plane with polygonal obstacles," *Journal of the Association for Computing Machinery*, vol. 41, no. 5, pp. 982-1012, 1994.

[145] Sukkarieh, S., Nebot, E. M., and Durrant-Whyte, H. F., "A high integrity IMU/GPS navigation loop for autonomous land vehicle applications," *IEEE Transactions on Robotics and Automation*, vol. 15, no. 3, pp. 572-578, 1999.

[146] Sun, G., Chen, J., Guo, W., and Liu, K. J. R., "Signal processing techniques in network-aided positioning: A survey of state-of-the-art positioning designs," *IEEE Signal Processing Magazine*, vol. 22, no. 4, pp. 12-23, 2005.

[147] Takanishi, A., Masukawa, S., Mori, Y., and Ogawa, T., "Study on anthropomorphic auditory robot continuous localization of a sound source in horizontal plane," in *11th Annual Conference of the Robotics Society of Japan*, Tokyo, Japan, 1993, pp. 793-796.

[148] Thiele, A. N., "Loudspeakers in vented boxes: Parts I and II," *Journal of the Audio Engineering Society*, vol. 19, pp. 382-392, 1971.

[149] Thomas, N. J., Cruickshank, D. G. M., and Laurenson, D. I., "Calculation of mobile location using scatterer information," *Electronics Letters*, vol. 37, no. 19, pp. 1193-1194, 2001.

[150] Tisse, C., Fauvel, T., and Durrant-Whyte, H., "A micro aerial vehicle motion capture system," in *1st International Conference on Sensing Technology*, Palmerston North, New Zealand, 2005, pp. 533-538.

[151] Valin, J. M., "Auditory system for a mobile robot," PhD dissertation, University ed Sherbrooke, Faculte de genie Genieelectrique et genie informatique, Sherbrooke, Canada, 2005.

[152] Valin, J. M., Michaud, F., Hadjou, B., and Rouat, J., "Localization of simultaneous moving sound sources for mobile robot using a frequency-domain steered beamformer approach," in *IEEE International Conference on Robotics and Automation*, New Orleans, USA, 2004, pp. 1033-1038.

[153] Valin, J. M., Michaud, F., and Rouat, J., "Robust 3D localization and tracking of sound sources using beamforming and particle filtering," in *IEEE International Conference on Acoustics, Speech and Signal Processing*, Toulouse, France, 2006, pp. 841-844.

[154] Valin, J. M., Michaud, F., and Rouat, J., "Robust localization and tracking of simultaneous moving sound sources using beamforming and particle filtering," *Robotics and Autonomous Systems,* vol. 55, no. 3, pp. 216-228, 2007.

[155] Valin, J. M., Michaud, F., Rouat, J., and Letourneau, D., "Robust sound source localization using a microphone array on a mobile robot," in *IEEE/RSJ International Conference on Intelligent Robots and Systems*, Las Vegas, USA, 2003, pp. 1228-1233.

[156] Venkatraman, S. and Caffery Jr, J., "A statistical approach to non-line-of-sight BS identification," in *5th International Symposium on Wireless Personal Multimedia Communications*, Sheraton Waikiki, USA, 2002.

[157] Venkatraman, S. and Caffery Jr, J., "Hybrid TOA/AOA techniques for mobile location in non-line-of-sight environments," in *IEEE Wireless Communications and Networking Conference*, Altanta, USA, 2004, pp. 274-278.

[158] Venkatraman, S., Caffery Jr, J., and You, H. R., "A novel ToA location algorithm using LoS range estimation for NLoS environments," *IEEE Transactions on Vehicular Technology,* vol. 53, no. 5, pp. 1515-1524, 2004.

[159] Wang, C. C., Thorpe, C., and Thrun, S., "Online simultaneous localization and mapping with detection and tracking of moving objects: Theory and results from a ground vehicle in crowded urban areas," in *IEEE International Conference on Robotics and Automation*, Taipei, Taiwan, 2003, pp. 842-849.

[160] Wang, W., Xiong, J. Y., and Zhu, Z. L., "A new NLOS error mitigation algorithm in location estimation," *IEEE Transactions on Vehicular Technology,* vol. 54, no. 6, pp. 2048-2053, 2005.

[161] Wang, X., Wang, Z., and O'Dea, B., "A TOA-based location algorithm reducing the errors due to non-line-of-sight (NLOS) propagation," *IEEE Transactions on Vehicular Technology,* vol. 52, no. 1, pp. 112-116, 2003.

[162] Ward, D. B. and Brandstein, M. S., "Grid-based beamformer design for room-environment microphone arrays," in *IEEE Workshop on Applications of Signal Processing to Audio and Acoustics*, New York, USA, 1999, pp. 23-26.

[163] Ward, D. B., Lehmann, E. A., and Williamson, R. C., "Particle filtering algorithms for tracking an acoustic source in a reverberant environment," *IEEE Transactions on Speech and Audio Processing,* vol. 11, no. 6, pp. 826-836, 2003.

[164]   Whitehouse, K., Karlof, C., and Culler, D., "A practical evaluation of radio signal strength for ranging-based localization," *Association for Computing Machinery SIGMOBILE Mobile Computing and Communications Review,* vol. 11, no. 1, pp. 41-52, 2007.

[165]   Whitty, M., Mak, L. C., Taprell, D., Ma, A., Lee, S., Ng, C. Y., Robinson, N., and Xiao, H., "Development of the MAVSTAR micro aerial vehicle and base station for IMAV09," in *4th US - European Workshop and Flight Competition for Micro Air Vehicles* Pensacola, USA, 2009.

[166]   Wolf, D. F. and Sukhatme, G. S., "Mobile robot simultaneous localization and mapping in dynamic environments," *Autonomous Robots,* vol. 19, no. 1, pp. 53-65, 2005.

[167]   Wu, L. W., Liu, W. H., Cheng, C. C., and Hu, J. S., "Gaussian mixture-sound field landmark model for robot localization applications," *Advanced Robotics,* vol. 21, no. 5, pp. 619-643, 2007.

[168]   Wu, S., Zhang, Q., Fan, R., and Zhang, N., "Match-filtering based TOA estimation for IR-UWB ranging systems," in *International Wireless Communications and Mobile Computing Conference*, Crete Island, Greece, 2008, pp. 1099-1105.

[169]   Xu, C. and Law, C. L., "Delay-dependent threshold selection for UWB TOA estimation," *IEEE Communications Letters,* vol. 12, no. 5, pp. 380-382, 2008.

[170]   Yang, N., Tian, W. F., Jin, Z. H., and Zhang, C. B., "Particle filter for sensor fusion in a land vehicle navigation system," *Measurement Science and Technology,* vol. 16, no. 3, pp. 677-681, 2005.

[171]   Yang, Q., Pan, S. J., and Zheng, V. W., "Estimating Location Using Wi-Fi," *IEEE Intelligent Systems,* vol. 23, no. 1, pp. 8-13, 2008.

[172]   Yang, Y. and Fathy, A. E., "See-through-wall imaging using ultra wideband short-pulse radar system," in *IEEE Antennas and Propagation Society International Symposium*, Washington, D.C., USA, 2005.

[173]   Yin, J., Yang, Q., and Ni, L., "Adaptive temporal radio maps for indoor location estimation," in *3rd IEEE International Conference on Pervasive Computing and Communications*, Hawaii, USA, 2005, pp. 85-94.

[174]   You, C. W., Huang, P., Chu, H., Chen, Y. C., Chiang, J. R., and Lau, S. Y., "Impact of sensor-enhanced mobility prediction on the design of energy-efficient localization," *Ad Hoc Networks,* vol. 6, no. 8, pp. 1221-1237, 2008.

[175]   Yu, K. and Guo, Y. J., "Improved positioning algorithms for nonline-of-sight environments," *IEEE Transactions on Vehicular Technology,* vol. 57, no. 4, pp. 2342-2353, 2008.

[176]   Zakarauskas, P. and Cynader, M. S., "A computational theory of spectral cue localization," *The Journal of the Acoustical Society of America,* vol. 94, p. 1323, 1993.