PHYS30762 Object Oriented Programming in C++

Assignment 5 Report

Kuba Kane
11019699

Department of Physics and Astronomy
The University of Manchester

April 2026

Contents

1 Program summary **1**
1.1 Electron class . . . 1
1.2 Muon class . . . 1
1.3 Tau class . . . 3
1.4 Neutrino class . . . 3
1.5 Main cpp file . . . 3

2 Code design **4**
2.1 Four momentum class . . . 4

3 References **5**

4 Delegation to Generative AI **6**
4.1 Disclosure of Delegation to Generative AI . . . 6
4.2 GAI prompts . . . 6

Note to markers: For version history please see the README file for different branches on the Github repository for assignment 5, as this contains planning and content for this report.

1. Program summary

This program is based around a `Lepton` class, which is an abstract base class from which `Electron`, `Muon`, `Tau`, and `Neutrino` are derived classes. The `Lepton` class contains a unique pointer to a `FourMomentum` object, whose class has energy, x momentum, y momentum, z momentum, and rest mass, as data members (all measured in MeV). The `Lepton` class also contains a rest mass and relative charge, as well as a boolean expression which if true represents an antilepton by flipping the charge data member. The `Lepton` class contains 2 virtual member functions which makes it abstract (along with its virtual destructor). The first is the `info()` function which is used to print out additional properties of derived classes, and `has_decayed()` which is set true if one of the derived leptons have decayed. `Lepton` contains `base_info()` to print out the properties it carries (four momentum, rest mass, and relative charge).

The derived classes inheret all these properties, but also have their own data members and member functions. These additional properties are printed by overriding the `info()` function (using `base_info()` to print the properties from `Lepton`), and are used to determine the outcome of `has_decayed()`. Figure 1 is a UML diagram which shows the heirarcy of the derived classes, and their properties. All of the derived classes use `static constexpr` to store their mass and charge as constants which cannot be modified during compilation or run time, which are printed via `base_info()`.

The lepton class also contains 2 friend functions - one to sum the four momenta of 2 leptons, and the other to compute their dot product.

1.1. Electron class

This class introduces an interaction with a detector, primarily through calculating the shower depth in a tungsten (W) detector via the member function `shower_depth_in_tungsten()`. This function calculates the shower depth X using the equation

$$X = X_0 \frac{ln(E_0/E_c)}{ln2}, \tag{1}$$

where X_0 is the radiation length, E_c is the critical energy, and E_0 is the initial energy of the electron (from its `FourMomentum`). The first two of these are set within the member function, matching the values for tungsten. E_0 is accessed via the pointer to the `FourMomentum` from the Lepton base class. `Electron` also has the function `shower_contained(const double detector_length_in)` which, given a detector length, determines if the shower is contained within the detector.

1.2. Muon class

The `Muon` class introduces the data member `time_in_detector()` which, if greater than the constant `MUON_MEAN_LIFETIME` stored as a private data member in the class, sets `has_decayed()` to be true. A `validate_time()` static function is used to check that the time entered by the user is not negative or greater than 1 second.




Figure 1: UML diagram of assignment 5 program, depicting all the classes in the program. Access online via `https://lucid.app/lucidchart/1bbac6b7-964d-4fed-86ef-e02a48e03f28/view`. Enumerator classes represented as nested classes, and FourMomentum as composition of Lepton (the instance in FourMomentum lives and dies via the unique pointer in the Lepton class). Electron, Muon, Tau, Neutrino are derived classes of Lepton. Virtual functions are denotes in italics, while static functions are underlined. Friends functions are denoted using «friend».

1.3. Tau class

The `Tau` class uses `time_in_detector()` and with `TAU_MEAN_LIFETIME` to handle the `has_decayed()` function, akin to the `Muon` class. Unlike the `Muon` class, however, it takes into account the different decay modes of taus. Using the fact that 64% of the time a taus' decay products are hadronic, 17.8% of the time they involve electrons, and 17.4% of the time they involve muons, a private member function `generate_decay_mode()` uses a basic Monte Carlo simulation to set the `decay_mode` data member to one of the three named values in the enumerator class defined for the decay modes. The getter `get_decay_mode` uses a switch to return the decay products as a string, differing for each named value in the enumerator class, and this is used in the overriden `info()` function.

1.4. Neutrino class

In the neutrino class, the idea of lifetime is discarded and `has_decayed` is always set to false due to the stability of neutrinos. An enumerator class `NeutrinoFlavour` is used with three named values corresponding to the three neutrino flavours. The neutrino flavour is set as a private data member which can be specified via the neutrino constructor or flavour setter. Since a neutrino cannot be flavourless, the default constructor also requires flavour as an input. The `info()` function prints the flavour using a switch returning a string dependent on the named value in the enumerator class, as well as the flavour generation, again dependent on the named value.

1.5. Main cpp file

The main file is split into 6 parts. The first part creates a vector of different leptons called `particles` via unique pointers to the base `Lepton` class, and then prints out all of their info using an iterator through all elements in the vector. The second part accesses 2 electrons by dereferencing the first two elements and sums their four momenta. The third part accesses the anti electron and anti muon and takes the dot product of their four momenta. The fourth part creates a unique pointer to an electron and moves it to a second pointer. The fifth part creates a shared pointer for a tau lepton and assigns into to 2 other pointers. The final part creates 2 vectors of shared particles ("detectors"), and gives them the same tau lepton pointer, which is shown by printing out all elements in both of the vectors.

2. Code design

2.1. Four momentum class

The `FourMomentum` class was changed so that, unlike,

3. References

The following sources were used in the research for this assignment.

[1] https://www.geeksforgeeks.org/cpp/pure-virtual-functions-and-abstract-classes/

[2] https://en.cppreference.com/w/cpp/language/rule_of_three.html

[3] https://www.geeksforgeeks.org/cpp/understanding-constexper-specifier-in-cpp/

[4] https://www.geeksforgeeks.org/cpp/sqrt-sqrtl-sqrtf-cpp/

[5] https://www.geeksforgeeks.org/cpp/enum-classes-in-c-and-their-advantage-over-enum-datatype/

[6] https://www.geeksforgeeks.org/cpp/range-based-loop-c/

[7] https://en.wikipedia.org/wiki/Particle_decay

[8] https://physics.stackexchange.com/questions/282245/muon-decay-mode

[9] https://en.wikipedia.org/wiki/Muon

[10] https://en.wikipedia.org/wiki/Tau_(particle)

[11] https://tikz.net/sm_decay_matrix/

[12] https://www.geeksforgeeks.org/cpp/stduniform_real_-distribution-class-in-c-with-examples/

[13] https://www.w3schools.com/cpp/cpp_switch.asp

[14] https://www.geeksforgeeks.org/cpp/can-constructor-private-cpp/

[15] https://www.w3schools.com/cpp/cpp_constructors_overloading.asp

[16] https://www.geeksforgeeks.org/system-design/factory-method-pattern-c-design-patterns/

[17] https://pdg.lbl.gov/2020/AtomicNuclearProperties/HTML/tungsten_W.html

[18] https://en.wikipedia.org/wiki/Particle_shower

[19] https://indico.capa.unizar.es/event/23/sessions/48/attachments/287/393/COST-TS-Belgrade-Course5-Tutorial.pdf

[20] https://www.ibm.com/docs/en/dma?topic=diagrams-enumerations

4. Delegation to Generative AI

4.1. Disclosure of Delegation to Generative AI

The author (Kuba Kane) declares the use of generative AI in the research and coding process. The following tasks were delegated to GAI tools under full human supervision:

- Idea generation
- Code generation
- Code optimisation
- Code debugging

The GAI tool used for these tasks was: ChatGPT-5.2, **free version**.

The author declares that the work does not contain any AI-generated code or text. GAI was used as a source of information for explaining code only, and as an inspiration to write original code.

Responsibility for the final manuscript lies entirely with the author.

GAI tools are not listed as authors and do not bear responsibility for the final outcomes.

4.2. GAI prompts

While no AI-generated code was directly used in this project, a list of the prompts used in ChatGPT-5.2 which suggested code relevant to this project can be found below.

- *Shared pointers allow multiple pointers to point to the same object, and only when the last pointer goes out of scope does the memory become freed. Does this mean if you want to change FourMomentum object you need to wait until all pointers which are shared go out of scope?*
- Code generation
- Code optimisation
- Code debugging