

Technical drawing of a building facade showing a vertical section with dimensions and annotations.

Annotations:

- Top left: $+2.985$
- Top left: $+2.735$
- Bottom left: -0.75
- Top right: 1.5×25
- Right side vertical dimension: 333.5
- Right side horizontal dimension: 294
- Right side horizontal dimension: 30
- Right side horizontal dimension: 45
- Right side horizontal dimension: 2
- Right side horizontal dimension: $150 \phi 10 \quad L = 369$
- Right side horizontal dimension: 4
- Right side horizontal dimension: $180 \phi 6 \quad L = 23$
- Right side horizontal dimension: 13.5

Dimensions:

- Top horizontal dimension: 1.5×25
- Right side vertical dimension: 333.5
- Right side horizontal dimension: 294
- Right side horizontal dimension: 30
- Right side horizontal dimension: 45
- Right side horizontal dimension: 2
- Right side horizontal dimension: $150 \phi 10 \quad L = 369$
- Right side horizontal dimension: 4
- Right side horizontal dimension: $180 \phi 6 \quad L = 23$
- Right side horizontal dimension: 13.5

Other labels:

- Top right: 1.5×25
- Right side vertical dimension: 333.5
- Right side horizontal dimension: 294
- Right side horizontal dimension: 30
- Right side horizontal dimension: 45
- Right side horizontal dimension: 2
- Right side horizontal dimension: $150 \phi 10 \quad L = 369$
- Right side horizontal dimension: 4
- Right side horizontal dimension: $180 \phi 6 \quad L = 23$
- Right side horizontal dimension: 13.5

Technical drawing of a vertical reinforcement cage for a column. The drawing shows a central vertical reinforcement bar with three horizontal cross-sections. The top section is labeled "2 22 Ø10 co 18 W+Z". The middle section is labeled "5 Ø10 co 18 L=380 /W+Z". The bottom section is labeled "1 Ø6 4szt./m2 L=23". The total height of the cage is 385. The scale is 1:50. The drawing includes dimensions for the cage height (385), the distance from the top reinforcement to the center of the cage (3.10), and the distance from the bottom reinforcement to the center of the cage (0.75). A diamond-shaped label "18" is placed near the center of the cage. The drawing is titled "Skala 1:50".

Nr pręta	ø	Długość	Ilość	Ilość pozycji	Dł. ogólna [m]	
					A-0	A-IIIIN
	[mm]	[cm]	[sztf.]	[sztf.]	ø6	#10
Poz.:	3.12 sciana					
1	6	23	220	1	50,60	
2	10	1200	50	1		600,00
3	10	369	170	1		627,30
6	10	100	60	1		60,00
7	10	93	40	1		37,20
Poz.:	3.13 sciana					
1	6	23	180	1	41,40	
2	10	1200	44	1		528,00
4	10	369	150	1		553,50
6	10	100	57	1		57,00
7	10	93	38	1		35,34
Poz.:	3.14 sciana					
1	6	23	40	1	9,20	
2	10	1200	10	1		120,00
5	10	380	30	1		114,00
7	10	93	136	1		126,48
8	10	91	15	1		13,65
Długość razem:				[m]	101,20	2872,47
Masa jednostkowa:				[kg/m]	0,222	0,617
Masa razem:				[kg]	22,5	1772,3
Masa ogólna:				[kg]	1794,8	

BETON: C25/30
STAL: A-IIIIN RB500W
A-O StOS
OTULINA: 25mm

- Wymiary podano w [cm], poziomy w [m].
- Rozpatrywać łącznie z pozostałymi rysunkami konstrukcyjnymi kondygnacji.

b	skorygowano elementy	31.10.2023	M.Raducki
a	dodano detal dylatacji ściany przy osiach C.a/C.1	05.07.2023	M.Raducki
Rewizja	Opis	Data	Nazwisko

$\pm 0.00 = 225.50m \text{ n.p.m.}$

Inwestor DZMT KROWODRZA SP. Z O. O., ul. Koletek 4/2, 31-069 Kraków

Inwestycja	
------------	--

BUDOWA 28 BUDYNKÓW MIESZKALNYCH JEDNORODZINNYCH W ZABUDOWIE
BLIŹNIACZEJ Z 14 GARAŻAMI ZAMKNIĘTYMI, WBUDOWANYMI ORAZ 14 GARAŻY
ZAMKNIĘTYCH, WOLNOSTOJĄCYCH, Z ZAGOSPODAROWANIEM TERENU,
SCHODAMI ZEWNĘTRZNYMI, MURAMI OPOROWYMI, ZEWNĘTRZNYMI
STANOWISKAMI POSTOJOWYMI, DOUŚCIEM I DOJAZDEM.

Adres	Kraków 126102_9, obr. Krowodrza 0033, 773, 774, 775
-------	---

Zakres	BUDYNEK B1, C1
--------	----------------

Treść rysunku	ŚCIANY 3.12 – 3.14
---------------	--------------------

Projektant mgr inż. Łukasz Sekuła Upr. SWK/P00K/0027/12	Podpis
---	--------

Faza	Skala	Branża	Nr rysunku	Data
PW	1:50	KONSTR.	K-15b	04.2023

Technical drawing of a U-shaped metal part. The left view shows the part in a rectangular frame with a diameter of 10 and a length of 91. The right view shows the U-shape with a height of 40 and a width of 11. A dimension of 15 is shown between the two views.

Technical drawing of a corner detail. It shows a corner of a structure with reinforcement bars. The top horizontal bar is labeled $3 \varnothing 10$. The vertical bar is labeled $L = 100$. A circular callout with the number 6 is shown. The bottom horizontal bar is labeled $117 \varnothing 10 \quad L = 100$. The vertical bar is labeled 50 . The corner is shown with a 45-degree angle.

Technical drawing of a U-channel profile. The top view shows a channel with a width of 40 and a depth of 13. The side view shows a channel with a width of 40 and a depth of 13. The drawing includes a dimension line indicating a length of 93 and a diameter of 10. A circled number 7 is present in the drawing.

rura PVC Ø18
 pręt Ø16 ocynkowany
 guma dylacyjna
 rura PVC Ø18
 pręt Ø16 ocynkowany
 guma dylacyjna
 pręt nr 7 wg detalu
 dozbrojenia krawędzi ścian,
 wykonać co 50cm

DOZBROJENIE OTWORÓW

