

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	1/9		HI-TECH PRODUCTS



BOSAN HITECH CO., LTD

444-2 NonHyun Dong, Namdong Gu, Inchon, Korea.

Tel) 82-32-818-2125

Fax) 82-32-818-8780

E-mail : andy@bosanhitech.com

Specification Sheet


(MODEL : BST-0845A)

<Non Washable Type>

BOSAN HITECH CO., LTD.

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	2/9		HI-TECH PRODUCTS

1. DIMENSION



UNIT : mm
TOLERANCE : ±0.3
HOUSING MATERIAL : LCP

C H A N G						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN


DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	3/9		HI-TECH PRODUCTS

2. SCOPE

THIS SPECIFICATION IS APPLIED TO THE DYNAMIC MAGNET TRANSDUCER ASSEMBLY WHICH IS USED AS ALERT IN A CELLULAR PORTABLE PRODUCTS.

3. ELECTRICAL SPECIFICATIONS

ALL DATA AT 25 °C, HUMIDITY 40% ~ 80% UNLESS OTHERWISE SPECIFIED.

ITEMS	SPECIFICATIONS	CONDITIONS
RATED VOLTAGE	5.0 Vo-p	
OPERATING VOLTAGE	3.0V ~ 7.0Vo-p	
RATED CURRENT	MAX 80mA	
COIL RESISTANCE	30ohm +/- 5	
SOUND PRESSURE LEVEL (AT 10cm)	MIN. 90dBA	* f=2,700Hz, Vo-p=5.0Vdc *1/2 DUTY SQUARE WAVE
RATED FREQUENCY	2,700Hz	
OPERATING TEMP.	-30 °C ~ +75 °C	
STORAGE TEMP.	-40 °C ~ +85 °C	

C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	4/9		HI-TECH PRODUCTS

4. RELIABILITY

TEMPERATURE CHARACTERISTICS # All data taken at -30°C and +85°C will be referenced to initial data taken at +25°C. # Component must be fully stabilized at temperature extremes before data taken, which may require up to a 4 hour soak.
STATIC HUMIDITY # Precondition at 25°C for 60 minutes. After 72 hours at 40°C with 90% to 95% relative humidity, allow to dry at room ambient for 4 hours.
VIBRATION (RANDOM) # To vibrate randomly at 6 g's or 0.04 g /Hz power spectral density from 10 to 2000 Hz for 15 minutes per plane or # Sinusoidal vibration 10 to 60 Hz, 0.06" double amplitude or 15 g's whichever is less for 1/2 hour per plane X,Y,Z.
OPERATING LIFE # To subject samples to 85°C at 85% RH for 168Hr at full rated power.
COMPONENT SHEAR TEST # To subject sample on PC Board to a tensile pull strength of 1Kg force for 30 seconds.
DROP TEST # While assembled in a dummy case, 5 free falls onto a concrete floor from a height of 150cm.

C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN

DATE	03-Jul-07	SPECIFICATION FOR APPROVAL	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	5/9		HI-TECH PRODUCTS

5. Environmental Information

This product meets ROHS standard and information of every parts below can be subjected.
 -. ICP-AES analysis data
 -. MSDS data


Type	Substances / Material	ppm(amount)
Class I	Cadmium and compounds	3.7
	Lead and compounds	477
	Mercury and compounds	Not detected
	Chrom(VI) and compounds	Not detected
	Polybrominated biphenyls (PBBs)	Not detected
	Polybrominated diphenylethers(PBDEs)	Not detected
Class II	Polychlorinated biphenyls (PCBs)	Not detected
	Polychlorinated Terphenyls (PCTs)	Not detected
	Polychlorinated naphthalences (PCNs)	Not detected
	Ozone depleting substances(CFCs, HCFCs, Halons)	Not detected
	Asbestos and compounds	Not detected
	Formaldehydes	Not detected
	Short-chain chlorinated paraffins	Not detected
	(Alkane 10 ~ 13 Carbon chain)	Not detected
	Azo colorants	Not detected
	Nickel and compounds	Not detected
	Organic tin compounds	Not detected
	Arsenic and compounds	Not detected
Class III	Phthalates	Not detected
	PVC	Not detected
	Beryllium and compounds	Not detected
	Other Chlorinated flame retardants	Not detected
	Other Chlorinated flame retardants (TBBP-A)	Not detected

C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	6/9		HI-TECH PRODUCTS

5. ELECTRICAL CHARACTERISTICS MEASUREMENT

1) SETTING UP OF MEASURING SYSTEM





NO	EQUIPMENT	REMARKS
1	CONDENSER MIC.	
2	DEVICE UNDER TEST	MAGNETIC BUZZER
3	F.F.T, OR S.P.L INDICATOR	
4	OSCILLATOR	
5	FREQUENCY COUNTER	
6	VOLTAGE METER	
7	AMPERE METER	
8	SOUND PROOF ROOM	

C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	7/9		HI-TECH PRODUCTS

6. PACKING FORMAT



- REMARK**
- Each corner without specification is max R0.25.
 - Emboss carrier tape is as per JIS C0806 standard.
 - Diameter of reel is $\phi 330$ mm and core is $\phi 80$ mm.
 - Quantity packed in a reel : 1,000pcs

C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	8/9		HI-TECH PRODUCTS

7. SOLDERING CONDITION

1) REFLOW SOLDERING


RECOMMENDABLE REFLOW SOLDERING CONDITION IS AS FOLLOWS.

#. REFLOW SOLDERING IS TWO TIMES

1-1 : IT IS REQUESTED THAT 2ND REFLOW SOLDERING SHOULD BE EXECUTED AFTER THE TEMPERATURE OF PRODUCT GOES DOWN TO NORMAL TEMPERATURE

1-2 : MAXIMUM REFLOW TEMPERATURE IS 240℃ WITH MAXIMUM DURATION OF 45 SECONDS BETWEEN 200℃ AND 240℃.

#. TEMPERATURE PROFILE(℃)




2) MANUAL SOLDERING

THE TEMPERATURE OF SOLDERING IRON : 350℃ WITHIN 10 SECONDS.


C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN

DATE	03-Jul-07	SPECIFICATION	BOSAN HI-TECH CO., LTD.
MODEL NO	BST-0845A		BEST QUALITY, SPECIALIZED SERVICE
PAGE	9/9		HI-TECH PRODUCTS


<Standard Drive Circuit>



<Recommended foot print layout>



Frequency Responce



C H A N G E						
	NO	DATE	BEFORE	AFTER	REASON OF CHANGE	SIGN