

Cross-Model Spec Comparison

Generated: 2026-05-24T09:10:37+00:00

Samples: 18

Task: Sortedness Property

Best pair: gpt-4o 1 vs gpt-3.5-turbo 1

Modes: stable vs unstable

Score: 13

Counterexample: A reordered duplicate pair distinguishes stable sorting from value-only sorting.

```
{"input": [[1, "a"], [1, "b"]], "candidate_output": [[1, "b"], [1, "a"]]}
```

Task: Token-Bucket Rate Limiter

Best pair: gpt-4o 1 vs gpt-3.5-turbo 1

Modes: refill_first vs consume_first

Score: 13

Counterexample: A boundary-timestamp request distinguishes refill-before-consume from consume-before-refill.

```
{"capacity": 1, "refill_rate_per_second": 1, "events": [{"time": 0.0, "request": 1}, {"time": 1.0, "request": 1}], "boundary_decision": "accept_second_request"}
```

Task: Token Expiry Semantics

Best pair: gpt-4o 1 vs gpt-3.5-turbo 1

Modes: inclusive vs exclusive

Score: 13

Counterexample: A token checked exactly at expiry distinguishes inclusive from exclusive validity.

```
{"issue_time": 100, "expiry_time": 200, "now": 200}
```