ALPHA & OMEGA SEMICONDUCTOR

AO3400
N-Channel Enhancement Mode Field Effect Transistor

General Description

The AO3400 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a load switch or in PWM applications. *Standard Product AO3400 is Pb-free (meets ROHS & Sony 259 specifications). AO3400L is a Green Product ordering option. AO3400 and AO3400L are electrically identical.*

Features

V_{DS} (V) = 30V
I_D = 5.8 A (V_{GS} = 10V)
$R_{DS(ON)}$ < 28mΩ (V_{GS} = 10V)
$R_{DS(ON)}$ < 33mΩ (V_{GS} = 4.5V)
$R_{DS(ON)}$ < 52mΩ (V_{GS} = 2.5V)

TO-236 (SOT-23) Top View





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current [A]	T_A=25°C	I_D	5.8	A
	T_A=70°C		4.9	
Pulsed Drain Current [B]		I_{DM}	30	
Power Dissipation [A]	T_A=25°C	P_D	1.4	W
	T_A=70°C		1	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	65	90	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		85	125	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	43	60	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V	30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=24V, V_{GS}=0V			1	µA
		T_J=55°C			5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±12V			100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250µA	0.7	1.1	1.4	V
$I_{D(ON)}$	On state drain current	V_{GS}=4.5V, V_{DS}=5V	30			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=5.8A		22.8	28	mΩ
		T_J=125°C		32	39	
		V_{GS}=4.5V, I_D=5A		27.3	33	mΩ
		V_{GS}=2.5V, I_D=4A		43.3	52	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=5A	10	15		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V		0.71	1	V
I_S	Maximum Body-Diode Continuous Current				2.5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=15V, f=1MHz		823	1030	pF
C_{oss}	Output Capacitance			99		pF
C_{rss}	Reverse Transfer Capacitance			77		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		1.2	3.6	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=4.5V, V_{DS}=15V, I_D=5.8A		9.7	12	nC
Q_{gs}	Gate Source Charge			1.6		nC
Q_{gd}	Gate Drain Charge			3.1		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=15V, R_L=2.7Ω, R_{GEN}=3Ω		3.3	5	ns
t_r	Turn-On Rise Time			4.8	7	ns
$t_{D(off)}$	Turn-Off DelayTime			26.3	40	ns
t_f	Turn-Off Fall Time			4.1	6	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=5A, dI/dt=100A/µs		16	20	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=5A, dI/dt=100A/µs		8.9	12	nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The value in any given application depends on the user's specific board design. The current rating is based on the ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

Rev 4 : June 2005

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Fig 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: On-Resistance vs. Gate-Source Voltage



Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note E)



Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)



Figure 11: Normalized Maximum Transient Thermal Impedance