PROGRAMMABLE PRECISION REFERENCES

The TL431 Series integrated circuits are three-terminal programmable shunt regulator diodes. These monolithic IC voltage reference operate as a low temperature coefficient zener which is programmable from V_{ref} to 36 volts with two external resistors. These devices exhibit a wide operating current range of 1.0 to 100mA with a typical dynamic impedance of 0.22Ω. The characteristics of these references make them excellent replacements for zener diodes in many applications such as digital voltmeters, power supplies, and op amp circuitry. The 2.5 volt reference makes it convenient to obtain a stable reference from 5.0 volt logic supplies, and since the TL431 Series operates as a shunt regulator, it can be used as either a positive or negative voltage reference.

FEATURES

· Divice Code Name :TL431 + V_{ref} Code + Package Code

ITEM	V_{ref} Code		Package Code	
	Code	Tolerance (%)	Code	Package
TL431		±2.2		TO-92
	A	±1.0	F	SOT-89
	B	±0.5		

· Low Dynamic Output Impedance : 0.22Ω(Typ.).
· Sink Current Capability of 1.0 to 10[illegible]mA.
· Equivalent Full-Range Temperatu[illegible]efficient of 50ppm/℃ (Typ.).
· Temperature Compensated for C[illegible]er Full Rated Operating Temperature Range.
· Low Output Noise Voltage.

Be discontinued

LINE UP

Type No.	Operating Voltage(V)	Package	Marking
TL431	2.5~36	TO-92	
TL431A			
TL431B			
TL431F		SOT-89	3D
TL431AF			3E
TL431BF			3F

BLOCK DIAGRAM





MAXIMUM RATINGS (Ta=25℃)
(Full operating ambient temperature range applies unless otherwise noted.)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Cathode To Anode Voltage		V_{KA}	37	V
Cathode Current Range, Continuous		I_K	-100 150	mA
Reference Input Current Range, Continuous		I_{ref}	-0.05 10	mA
Operating Junction Temperature		T_j	150	℃
Operating Temperature		T_{opr}	-40 85	℃
Storage Temperature		T_{stg}	-65 150	℃
Total Power Dissipation	TL431	P_D	700	mW
	TL431F		800	

ELECTRICAL CHARACTERISTICS (Ta=25℃)

Be discontinued

CHARACTERISTICS		SYMBOL	TEST CIRCUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Reference Input Voltage	TL431	V_{ref}	Figure 1	$V_{KA}=V_{ref}$, I_K=10mA	2.440	2.495	2.550	V
	TL431A				2.470	2.495	2.520	V
	TL431B				2.4825	2.495	2.5075	V
Reference Input Voltage Deviation Over Temperature Range		ΔV_{ref}	Figure (Note 1)	$V_{KA}=V_{ref}$, I_K=10mA	-	7.0	30	mV
Ratio of Change in Reference Input Voltage to Change in Cathode to Anode Voltage		$\Delta V_{ref}/\Delta V_{KA}$	Figure 2	I_K=10mA, ΔV_{KA} 10V	-	-1.4	-2.7	mV/V
				ΔV_{KA} 36V 10V	-	-1.0	-2.0	
Reference Input Current	Ta=25℃	I_{ref}	Figure 2	I_K=10mA, R1=10kΩ, R2=∞	-	1.8	4.0	μA
	Ta=T_{opr}				-	-	6.5	
Reference Input Current Deviation Over Temperature Range		ΔI_{ref}	Figure 2	I_K=10mA, R1=10kΩ, R2=∞	-	0.8	2.5	μA
Minimum Cathode Current For Regulation		I_{min}	Figure 1	$V_{KA}=V_{ref}$	-	0.5	1.0	mA
Off-State Cathode Current		I_{off}	Figure 3	V_{KA}=36V, V_{ref}=0V	-	2.6	1000	nA
Dynamic Impedance		Z_{ka}	Figure 1 (Note 2)	$V_{KA}=V_{ref}$, I_K=1.0 100mA, f≦1.0kHz	-	0.22	-	Ω

FIGURE 1-TEST CIRCUIT FOR $V_{KA} = V_{ref}$



FIGURE 2-TEST CIRCUIT FOR $V_{KA} > V_{ref}$



$$V_{KA} = \quad (1+ \frac{R1}{R2}) + I_{ref} \times R1$$

Note 1:

The deviation parameter ΔV_{ref} is defined as the differences between the maximum and minimum values obtained over the full operating ambient temperature range that applies.



$\Delta V_{ref} = V_{ref}$ (Max.) - V_{ref} (Min.)

$\Delta Ta = T_2 - T_1$

AMBIENT TEMPERATURE

The average temperature coefficient of the Reference input voltage, ΔV_{ref}, is defined as:

$$\alpha V_{ref} (\frac{ppm}{°C}) = \frac{(\frac{\Delta V_{ref}}{V_{ref} \text{ at } 25°C}) \times 10^6}{\Delta Ta}$$

$$= \frac{\Delta V_{ref} \times 10^6}{\Delta Ta (V_{ref} \text{ at } 25°C)}$$

αV_{ref} can be positive or negative depending on whether V_{ref} Min. or V_{ref} Max. occurs at the lower ambient temperature.

FIGURE 3-TEST CIRCUIT FOR I_{off}



Example : ΔV_{ref} = 8.0mV and slope is positive, V_{ref} at 25°C=2.495V, ΔTa=70°C

$$\alpha V_{ref} = \frac{0.008 \times 10^6}{70 \times (2.495)} = 45.8 \text{ ppm/°C}$$

Note 2: The dynamic impedance Z_{ka} is defined as:

$$|Z_{ka}| = \frac{\Delta VKA}{\Delta Ik}$$

When the device is programmed with two external resistors, R1 and R2, (refer to Figure 2) the total dynamic impedance of the circuit is defined as:

$$|Z_{ka'}| = |Z_{ka}| (1+\frac{R1}{R2})$$

Be discontinued

I_K - V_{KA}



I_K - V_{KA}



ΔV_{ref} - V_{KA}



| Zka | - f



G_{VO} - f



PULSE RESPONSE



P_D - Ta



Be discontinued



DIM	MILLIMETERS
A	4.70 MAX
B	4.80 MAX
C	3.70 MAX
D	0.45
E	1.00
F	1.27
G	0.85
H	0.45
J	14.00±0.50
K	0.55 MAX
L	2.30
M	0.45 MAX
N	1.00

1. REFERENCE
2. ANODE
3. CATHODE

TO-92



DIM	MILLIMETERS
A	4.70 MAX
B	2.50±0.20
C	1.70 MAX
D	0.45+0.15/-0.10
E	4.25 MAX
F	1.50±0.10
G	0.40 TYP
H	1.75 MAX
J	0.75 MIN
K	0.5+0.10/-0.05

1. REFERENCE
2. ANODE
3. CATHODE

Heat Sink is common to ② (ANODE)

SOT-89

Be discontinued

PRECAUTION FOR USE

Lead-Free Soldering Condition.

Elements mounting styles of electronic devices are gaining in further diversification over recent years, and needs for components are all the more expanding in varieties. Especially, surface mounting is steadily penetrating into industrial segments as a world-wide popular technical trend. Although exposure to high temperature is inevitable during soldering we recommend limiting the soldering temperature to low levels as shown in figure for the sake of retaining inherent excellent reliability.



[Lead-Free Soldering Temperature Profile]

Be discontinued

1. When employing solder reflow method

1) Soldering Condition

ⓐ Standard Condition : 250℃ (Temperature), 10±1sec. (Time)

ⓑ Peak Condition : 260±3℃

2) Recommend temperature profile

3) Precautions on heating method

When resin in kept exposed to high temperature for a long time, device reliability may be marred.

Therefore, it is essential to complete soldering in the shortest time possible to prevent temperature of resin from rising.

2. When employing halogen lamps or infrared-ray heaters

When halogen lamps or infrared-ray heaters are used, avoid direct irradiation onto resin surfaces; such devices cause extensive localized temperature rise.

※ Please keep a reflow solder operating when Surface Mount Package s Soldering.