

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop (master)
```

```
$ mkdir OS_EE24TCD001
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop (master)
```

```
$ cd OS_EE24TCD001
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ git init
```

```
Initialized empty Git repository in C:/Users/Dell/Desktop/OS_EE24TCD001/.git/
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ touch practical02.pdf
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ notepad practical02.pdf
```

```
git status
```

```
$ git status
```

```
$ git status
```

```
q
```

```
clear
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ git status
```

```
On branch master
```

```
No commits yet
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
practical02.pdf
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ git add practical02.pdf
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ git commit -m "Added Practical 02 PDF"
```

```
Author identity unknown
```

```
*** Please tell me who you are.
```

```
Run
```

```
git config --global user.email "you@example.com"
```

```
git config --global user.name "Your Name"
```

```
to set your account's default identity.
```

```
Omit --global to set the identity only in this repository.
```

```
fatal: unable to auto-detect email address (got 'Dell@DESKTOP-D7MT61A.(none)')
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ git config --global user.name "Ayushi Kukde"
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
$ git config --global user.email "kukdeayushi9818@gmail.com"
```

```
Dell@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git help status
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git status -s
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git config --global user.name
Ayushi Kukde
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git ls-files
practical02.pdf
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git add practical02.pdf
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git add.
git: 'add.' is not a git command. See 'git --help'.
```

The most similar command is
add

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git add .
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
```

De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
\$ git commit -m "Added Practical 02 file"
[master (root-commit) 34eb7c6] Added Practical 02 file
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 practical02.pdf

De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
\$ git log --oneline
34eb7c6 (HEAD -> master) Added Practical 02 file

De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
\$ git status
On branch master
nothing to commit, working tree clean

De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
\$ git --version
git version 2.46.0.windows.1

De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
\$ git help
usage: git [-v | --version] [-h | --help] [-C <path>] [-c <name>=<value>]
[--exec-path=<path>] [--html-path] [--man-path] [--info-path]
[-p | --paginate | -P | --no-pager] [--no-replace-objects] [--no-lazy-fetch]
[--no-optional-locks] [--no-advice] [--bare] [--git-dir=<path>]
[--work-tree=<path>] [--namespace=<name>] [--config-env=<name>=<envvar>]
<command> [<args>]

These are common Git commands used in various situations:

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git help
```

```
usage: git [-v | --version] [-h | --help] [-C <path>] [-c <name>=<value>]
          [--exec-path[=<path>]] [--html-path] [--man-path] [--info-path]
          [-p | --paginate | -P | --no-pager] [--no-replace-objects] [--no-lazy-fetch]
          [--no-optional-locks] [--no-advice] [--bare] [--git-dir=<path>]
          [--work-tree=<path>] [--namespace=<name>] [--config-env=<name>=<envvar>]
          <command> [<args>]
```

These are common Git commands used in various situations:

start a working area (see also: git help tutorial)

clone	Clone a repository into a new directory
init	Create an empty Git repository or reinitialize an existing one

work on the current change (see also: git help everyday)

add	Add file contents to the index
mv	Move or rename a file, a directory, or a symlink
restore	Restore working tree files
rm	Remove files from the working tree and from the index

examine the history and state (see also: git help revisions)

bisect	Use binary search to find the commit that introduced a bug
diff	Show changes between commits, commit and working tree, etc
grep	Print lines matching a pattern
log	Show commit logs
show	Show various types of objects
status	Show the working tree status

grow, mark and tweak your common history

branch	List, create, or delete branches
commit	Record changes to the repository
merge	Join two or more development histories together
rebase	Reapply commits on top of another base tip
reset	Reset current HEAD to the specified state
switch	Switch branches
tag	Create, list, delete or verify a tag object signed with GPG

collaborate (see also: git help workflows)

fetch	Download objects and refs from another repository
pull	Fetch from and integrate with another repository or a local branch
push	Update remote refs along with associated objects

'git help -a' and 'git help -g' list available subcommands and some concept guides. See 'git help <command>' or 'git help <concept>' to read about a specific subcommand or concept.
See 'git help git' for an overview of the system.

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git help status
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git commit -m "Second commit check"
On branch master
nothing to commit, working tree clean
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git show
commit 34eb7c68ba7e10bcd23e847acc6a8e500ddd855 (HEAD -> master)
Author: Ayushi Kukde <kukdeayushi9818@gmail.com>
Date: Sat Jan 17 08:05:11 2026 +0200
```

Added Practical 02 file

```
diff --git a/practical02.pdf b/practical02.pdf
new file mode 100644
index 0000000..e69de29
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git log
commit 34eb7c68ba7e10bcd23e847acc6a8e500ddd855 (HEAD -> master)
Author: Ayushi Kukde <kukdeayushi9818@gmail.com>
Date: Sat Jan 17 08:05:11 2026 +0200
```

Added Practical 02 file

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git log --oneline
34eb7c6 (HEAD -> master) Added Practical 02 file
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git log --stat
commit 34eb7c68ba7e10bcd23e847acc6a8e500ddd855 (HEAD -> master)
Author: Ayushi Kukde <kukdeayushi9818@gmail.com>
Date: Sat Jan 17 08:05:11 2026 +0200
```

Added Practical 02 file

```
practical02.pdf | 0
1 file changed, 0 insertions(+), 0 deletions(-)
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git log --stat
commit 34eb7c68ba7e10bcd23e847acc6a8e500ddd855 (HEAD -> master)
Author: Ayushi Kukde <kukdeayushi9818@gmail.com>
Date: Sat Jan 17 08:05:11 2026 +0200
```

Added Practical 02 file

```
practical02.pdf | 0
1 file changed, 0 insertions(+), 0 deletions(-)
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git branch
* master
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git checkout test_branch
error: pathspec 'test_branch' did not match any file(s) known to git
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git brach test_branch
git: 'brach' is not a git command. See 'git --help'.
```

The most similar command is
branch

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git branch test_branch
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git checkout test_branch
Switched to branch 'test_branch'
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (test_branch)
$ git checkout master
Switched to branch 'master'
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git diff
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git diff --staged
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ |
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git diff --staged
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git clean -n
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git reset --soft HEAD
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ git status
On branch master
nothing to commit, working tree clean
```

```
De11@DESKTOP-D7MT61A MINGW64 ~/Desktop/OS_EE24TCD001 (master)
$ |
```