

```
In [51]: %%javascript
/*****
*****
Known Mathjax Issue with Chrome - a rounding issue adds a border to the right of mathjax markup
https://github.com/mathjax/MathJax/issues/1300
A quick hack to fix this based on stackoverflow discussions:
http://stackoverflow.com/questions/34277967/chrome-rendering-mathjax-equations-with-a-trailing-vertical-line
*****
*****/

$('.math>span').css("border-left-color","transparent")
```

```
In [52]: %reload_ext autoreload
%autoreload 2
```

MIDS - w261 Machine Learning At Scale

Course Lead: Dr James G. Shanahan (email Jimi via James.Shanahan AT gmail.com)

Assignment - HW11

Name: Nina Kuklisova **Class:** MIDS w261 (Section 2)

Email: *nkuklisova@iSchool.Berkeley.edu

Week: 11

Table of Contents

1. HW Intructions
2. HW References
3. HW Problems
 - HW11.0. Broadcast versus Caching in Spark
 - HW11.1. HW11.2 Gradient descent
 - HW11.2. Gradient descent
 - HW11.3. Logistic Regression
 - HW11.4. SVMs
 - HW11.5. OPTIONAL Distributed Perceptron algorithm
 - HW11.6. OPTIONAL Evalution of perceptron algorihtms on PennTreeBank POS corpus
 - HW11.7. OPTIONAL Kernal Adatron

 - HW11.8. OPTIONAL Create an animation of gradient descent for the Perceptron

1 Instructions

[Back to Table of Contents](#)

MIDS UC Berkeley, Machine Learning at Scale DATSCIW261 ASSIGNMENT #11

Version 2016-07-27 (FINAL)

=== INSTRUCTIONS for SUBMISSIONS === Follow the instructions for submissions carefully.

https://docs.google.com/forms/d/1ZOr9Rnle_A06AcZDB6K1mJN4vrLeSmS2PD6Xm3eOiis/viewform?usp=send_form
(https://docs.google.com/forms/d/1ZOr9Rnle_A06AcZDB6K1mJN4vrLeSmS2PD6Xm3eOiis/viewform?usp=send_form)

=== IMPORTANT ===

TYPE-2 Fun option: Submit HW11 using a Zeppelin notebook (See Live slides for install instructions)

TYPE-1.5 Fun option: Complete HW11.8 only (no need to complete the rest of the questions)

HW11 can be completed locally on your computer

Documents:

- IPython Notebook, published and viewable online.
- PDF export of IPython Notebook.

2 Useful References

[Back to Table of Contents](#)

- Karau, Holden, Konwinski, Andy, Wendell, Patrick, & Zaharia, Matei. (2015). Learning Spark: Lightning-fast big data analysis. Sebastopol, CA: O'Reilly Publishers.
- Hastie, Trevor, Tibshirani, Robert, & Friedman, Jerome. (2009). The elements of statistical learning: Data mining, inference, and prediction (2nd ed.). Stanford, CA: Springer Science+Business Media. (Download for free [here](http://statweb.stanford.edu/~tibs/ElemStatLearn/printings/ESLII_print10.pdf) (http://statweb.stanford.edu/~tibs/ElemStatLearn/printings/ESLII_print10.pdf))

HW Problems

[Back to Table of Contents](#)

HW11.0: Broadcast versus Caching in Spark

[Back to Table of Contents](#)

HW11.0

Q: What is the difference between broadcasting and caching data in Spark? Give an example (in the context of machine learning) of each mechanism (at a highlevel). Feel free to cut and paste code examples from the lectures to support your answer.

Broadcasting is the process in which the Master assigns the tasks to the worker nodes, caching is the process in which we use the memory.

```
In [ ]: def logisticReg_GD_Spark(data,y,w=None,eta=0.05,iter_num=500,regPara=0.01, stopCriteria=0.0001,reg="Ridge"):
    #eta learning rate
    #regPara
    dataRDD = sc.parallelize(np.append(y[:,None],data,axis=1)).cache() if
    w is None:
    w = np.random.normal(size=data.shape[1]+1)
    for i in range(iter_num):
    w_broadcast = sc.broadcast(w)
    g = dataRDD.map(lambda x: -x[0]*{1-1/(1+np.exp(-x[0] *np.dot(w_broadc
    ast.value,np.append(x[1:],1))))) \ *np.append(x[1:],1)).reduce(lambda
    x,y:x+y)/data.shape[0]
    # Gradient of logloss
    if reg == "Ridge":
    wreg = w*1
    wreg[-1] = 0 #last value of weight vector is bias term;
    ignore in regularization
    elif reg == "Lasso":
    wreg = w*1
    wreg[-1] = 0 #last value of weight vector is bias term;
    ignore in regularization
    wreg = (wreg>0).astype(int)*2-1
    else:
    wreg = np.zeros(w.shape[0])
    wdelta = eta*(g+regPara*wreg) #gradient: hinge loss + regularized term
    if sum(abs(wdelta))<stopCriteria*sum(abs(w)): # converged as updates
    to weight vector are small
    break
    w = w + wdelta
    return w
```

Q: __Review the following Spark-notebook-based implementation of KMeans and use the broadcast pattern to make this implementation more efficient. Please describe your changes in English first, implement, comment your code and highlight your changes:

Notebook <https://www.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb?dl=0>
(<https://www.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb?dl=0>)

Notebook via NBViewer <http://nbviewer.ipython.org/urls/dl.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb> (<http://nbviewer.ipython.org/urls/dl.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb>)

(Similarly to the last exercise of the previous homework,) the main change that can be done to this notebook in order to make this code more efficient is using the broadcasting.

In []:

Q: Review the following Spark-notebook-based implementation of KMeans and use the broadcast pattern to make this implementation more efficient. Please describe your changes in English first, implement, comment your code and highlight your changes:

Notebook <https://www.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb?dl=0>
(<https://www.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb?dl=0>)

Notebook via NBViewer <http://nbviewer.ipython.org/urls/dl.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb> (<http://nbviewer.ipython.org/urls/dl.dropbox.com/s/41q9lgyqhy8ed5g/EM-Kmeans.ipynb>)

```
In [ ]: ## Set up Spark

import os
import sys
import pyspark
from pyspark.sql import SQLContext

# We can give a name to our app (to find it in Spark WebUI) and configure execution mode
# In this case, it is local multicore execution with "local[*]"
app_name = "example-logs"
master = "local[*]"
conf = pyspark.SparkConf().setAppName(app_name).setMaster(master)
sc = pyspark.SparkContext(conf=conf)
sqlContext = SQLContext(sc)
print sc
print sqlContext
```

```


In [2]: %matplotlib inline
import numpy as np
import pylab
import json
size1 = size2 = size3 = 1000
samples1 = np.random.multivariate_normal([4, 0], [[1, 0],[0, 1]], size
1)
data = samples1
samples2 = np.random.multivariate_normal([6, 6], [[1, 0],[0, 1]], size
2)
data = np.append(data,samples2, axis=0)
samples3 = np.random.multivariate_normal([0, 4], [[1, 0],[0, 1]], size
3)
data = np.append(data,samples3, axis=0)
# Randomize data
data = data[np.random.permutation(size1+size2+size3),]
np.savetxt('data.csv',data,delimiter = ',')

```

```

In [3]: pylab.plot(samples1[:, 0], samples1[:, 1], '*', color = 'red')
pylab.plot(samples2[:, 0], samples2[:, 1], 'o', color = 'blue')
pylab.plot(samples3[:, 0], samples3[:, 1], '+', color = 'green')
pylab.show()

```



In [4]: **import numpy as np**

```
#Calculate which class each data point belongs to
def nearest_centroid(line):
    x = np.array([float(f) for f in line.split(',')])
    closest_centroid_idx = np.sum((x - centroids)**2, axis=1).argmin()
    return (closest_centroid_idx,(x,1))

#plot centroids and data points for each iteration
def plot_iteration(means):
    pylab.plot(samples1[:, 0], samples1[:, 1], '.', color = 'blue')
    pylab.plot(samples2[:, 0], samples2[:, 1], '.', color = 'blue')
    pylab.plot(samples3[:, 0], samples3[:, 1], '.', color = 'blue')
    pylab.plot(means[0][0], means[0][1], '*', markersize =10,color = 'red')
    pylab.plot(means[1][0], means[1][1], '*', markersize =10,color = 'red')
    pylab.plot(means[2][0], means[2][1], '*', markersize =10,color = 'red')
    pylab.show()
```

```

In [27]: from pyspark.mllib.clustering import KMeans, KMeansModel

K = 3
# Initialization: initialization of parameter is fixed to show an example
centroids = np.array([[0.0,0.0],[2.0,2.0],[0.0,7.0]])

D = sc.textFile("data.csv") #.cache()
parsedData = D.map(lambda line: np.array([float(x) for x in line.split(
    ',')]))
featureLen = len(parsedData.take(1)[0])-1
n = parsedData.count()
learningRate=0.05
w = np.random.normal(size=featureLen) # w should be broadcasted if it is large
wBroadcast = sc.broadcast(w) #make available in memory as read-only to the executors (for mappers and reducers)

iter_num = 0

def error(point):
    center = clusters.centers[clusters.predict(point)]
    return np.sqrt(sum([x**2 for x in (point - center)]))

clusters = KMeans.train(parsedData, 2, maxIterations=10, runs=10, initializationMode="random")


for i in range(10):
    wBroadcast = sc.broadcast(w) #make available in memory as read-only to the executors (for mappers and reducers)

    res = D.map(nearest_centroid).reduceByKey(lambda x,y : (x[0]+y[0], x[1]+y[1])).collect()
    res = sorted(res,key = lambda x : x[0]) #sort based on clusted ID
    centroids_new = np.array([x[1][0]/x[1][1] for x in res]) #divide by cluster size
    if np.sum(np.absolute(centroids_new-centroids))<0.01:
        break
    print "Iteration" + str(iter_num)
    iter_num = iter_num + 1
    centroids = centroids_new
    print centroids
    plot_iteration(centroids)
    w = w - learningRate/n
    WSSSE = parsedData.map(lambda point: error(point)).reduce(lambda x , y: x + y)
    #print("Within Set Sum of Squared Error = " + str(WSSSE))
print "Final Results:"
print centroids

```



Iteration0

```
[[ 0.98943613  0.38346476]
 [ 3.97408091  2.67236203]
 [ 2.02237144  5.73509668]]
```




Iteration1

```
[[ 1.91321808  0.67720108]
 [ 5.34762908  2.82122076]
 [ 2.11986545  5.32421443]]
```




Iteration2

```
[[ 2.91780153  0.30196197]
 [ 6.02601813  4.43963843]
 [ 1.19673067  4.9159349 ]]
```




Iteration3

```
[[ 3.90270553 -0.0141402 ]  
 [ 6.04262131  5.9396879 ]  
 [ 0.04707369  4.11372878]]
```




Iteration4

```
[[ 3.97288018 -0.01962169]  
 [ 6.01962362  5.98792513]  
 [ 0.01665486  4.04447724]]
```



Iteration5

```
[[ 3.97436066 -0.02213077]
 [ 6.01641902  5.98762879]
 [ 0.01632105  4.04127886]]
```



Final Results:

```
[[ 3.97436066 -0.02213077]
 [ 6.01641902  5.98762879]
 [ 0.01632105  4.04127886]]
```

HW11.1 Loss Functions

[Back to Table of Contents](#)

Q: In the context of binary classification problems, does the linear SVM learning algorithm yield the same result as a L2 penalized logistic regression learning algorithm?

In your response, please discuss the loss functions, and the learnt models, and separating surfaces between the two classes.

For soft margin SVM, the loss term is

$$\begin{aligned} J(w) &= \frac{1}{2} \|w\|^2 + \sum_i \max(0, 1 - y^i w^T x^i) \\ &= \frac{1}{2} \|w\|^2 + \sum_i \max(0, 1 - y^i w^T x^i) \\ &= R_2(w) + \sum_i L_{\text{hinge}}(m_i) \end{aligned}$$

while an L2 penalized logistic regression learning algorithm has its log loss defined as

$$\begin{aligned} J(w) &= \lambda \|w\|^2 + \sum_i \log(1 + e^{-y^{(i)} f_w(x^{(i)})}) \end{aligned}$$

where we defined

$$\begin{aligned} L(m) &= \log(1 + e^{-m}) \\ m^i &= y^{(i)} f_w(x^{(i)}) \\ y^{(i)} &= \begin{cases} -1 & , \text{if } y^{(i)} = 0 \\ 1 & , \text{if } y^{(i)} = 1 \end{cases} \end{aligned}$$

Therefore, as both are trying to minimize a different loss term, they can yield different results.

In the context of a binary classification problem, a hyperplane is the decision surface for both a linear SVM and logistic regression. A linear SVM tries to fit a hyperplane that separate the data that lie on one side of it, and also tries to choose it so that the margin between the two classes is maximal. On the other hand, logistic regression uses the data points as if they were along a continuous sigmoid function, and the separating hyperplane surface is where the probability of one of the two classes is higher than the threshold probability (in most cases set to 0.5).

Q: In the context of binary classification problems, does the linear SVM learning algorithm yield the same result as a perceptron learning algorithm?

The perceptron loss function is similar to the hinge loss function of linear SVM; so, in some cases, the two may yield the same results. Whether or not this is the case depends on whether or not the two classes are linearly separable. If they are not, then neither converges, and the result is the same. If they are, they can yield different results, because the perceptron learning algorithm finishes once it finds a hyperplane that separates the data points in two classes, while linear SVM will still try to maximize the margin.

[OPTIONAL]: generate an artificial binary classification dataset with 2 input features and plot the learnt separating surface for both a linear SVM and for logistic regression. Comment on the learnt surfaces. Please feel free to do this in Python (no need to use Spark).

HW11.2 Gradient descent

[Back to Table of Contents](#)

Q: In the context of logistic regression describe and define three flavors of penalized loss functions. Are these all supported in Spark MLlib (include online references to support your answers)?

There are 3 main flavors of penalized loss functions in the context of logistic regression.

- (1) Hinge loss: $\max\{0, 1 - y\mathbf{w}^T\mathbf{x}\}$, $y \in \{-1, +1\}$
- (2) Logistic loss: $\log(1 + \exp(-y\mathbf{w}^T\mathbf{x}))$, $y \in \{-1, +1\}$
- (3) Squared loss: $\frac{1}{2}(\mathbf{w}^T\mathbf{x} - y)^2$, $y \in \mathbb{R}$

and 3 regularizers:

- (1) L1: $\|\mathbf{w}\|_1$
- (2) L2: $\frac{1}{2}\|\mathbf{w}\|_2^2$
- (3) elastic net: $\alpha\|\mathbf{w}\|_1 + (1 - \alpha)\frac{1}{2}\|\mathbf{w}\|_2^2$

and all of them are supported by Spark MLlib, as described in its documentation:

<https://spark.apache.org/docs/latest/ml-lib-linear-methods.html#loss-functions>
(<https://spark.apache.org/docs/latest/ml-lib-linear-methods.html#loss-functions>)

Q: Describe probabilistic interpretations of the L1 and L2 priors for penalized logistic regression (HINT: see synchronous slides for week 11 for details)

As explained in the class reading for week 11 in Andrew Ng's lecture notes, the L2 penalty maximizes the maximum likelihood estimation for a Gaussian distribution. Similarly, the L1 norm does this for a Laplace distribution. Therefore, we L1 corresponds to a Laplace prior, while L2 corresponds to a Gaussian prior.

HW11.3 Logistic Regression

[Back to Table of Contents](#)

Generate 2 sets of linearly separable data with 100 data points each using the data generation code provided below and plot each in separate plots. Call one the training set and the other the testing set.

```
def generateData(n):  
    """  
    generates a 2D linearly separable dataset with n samples.  
    The third element of the sample is the label  
    """  
    xb = (rand(n)*2-1)/2-0.5  
    yb = (rand(n)*2-1)/2+0.5  
    xr = (rand(n)*2-1)/2+0.5  
    yr = (rand(n)*2-1)/2-0.5  
    inputs = []  
    for i in range(len(xb)):  
        inputs.append([xb[i],yb[i],1])  
        inputs.append([xr[i],yr[i],-1])  
    return inputs
```

Modify this data generation code to generating non-linearly separable training and testing datasets (with approximately 10% of the data falling on the wrong side of the separating hyperplane. Plot the resulting datasets.

NOTE: For the remainder of this problem please use the non-linearly separable training and testing datasets.

Using MLLib train up a LASSO logistic regression model with the training dataset and evaluate with the testing set. What a good number of iterations for training the logistic regression model? Justify with plots and words.

Derive and implement in Spark a weighted LASSO logistic regression. Implement a convergence test of your choice to check for termination within your training algorithm .

Weight the above training dataset as follows: Weight each example using the inverse vector length (Euclidean norm):

$$\text{weight}(X) = 1/||X||,$$

$$\text{where } ||X|| = \text{SQRT}(X.X) = \text{SQRT}(X1^2 + X2^2)$$

Here X is vector made up of X1 and X2.

Evaluate your homegrown weighted LASSO logistic regression on the test dataset. Report misclassification error (1 - Accuracy) and how many iterations does it took to converge.

Does Spark MLLib have a weighted LASSO logistic regression implementation. If so use it and report your findings on the weighted training set and test set.

```
In [28]: from numpy.random import rand
```

```
def generateData(n):  
    """  
    generates a 2D linearly separable dataset with n samples.  
    The third element of the sample is the label  
    """  
    xb = (rand(n)*2-1)/2-0.5  
    yb = (rand(n)*2-1)/2+0.5  
    xr = (rand(n)*2-1)/2+0.5  
    yr = (rand(n)*2-1)/2-0.5  
    inputs = []  
    for i in range(len(xb)):  
        inputs.append([xb[i],yb[i],1])  
        inputs.append([xr[i],yr[i],-1])  
    return inputs
```

```
In [29]: # Generate the data
```

```
training = np.array(generateData(100))  
testing = np.array(generateData(100))
```

```

In [30]: # Plot the data

import matplotlib.pyplot as plt


def plot_data(dataset):
    colors = ['y' if x ==1 else 'g' for x in dataset[:, 2]]
    plt.scatter( dataset[:, 0], dataset[:, 1], color = colors)

fig = plt.gcf()
fig.set_size_inches(12, 4)

plt.subplot(1, 2, 1)
plt.title('Training set')
plot_data(training)

plt.subplot(1, 2, 2)
plt.title('Testing set')
plot_data(testing)

```



Q: Modify this data generation code to generating non-linearly separable training and testing datasets (with approximately 10% of the data falling on the wrong side of the separating hyperplane. Plot the resulting datasets.

NOTE: For the remainder of this problem please use the non-linearly separable training and testing datasets.


```
In [31]: # we make these two overlap
```

```
def generateData_m(n):  
    """  
    generates a 2D dataset with n samples.  
    The third element of the sample is the label  
    """  
    xb = (rand(n)*2-1)/2-0.4  
    yb = (rand(n)*2-1)/2+0.4  
    xr = (rand(n)*2-1)/2+0.4  
    yr = (rand(n)*2-1)/2-0.4  
    inputs = []  
    for i in range(len(xb)):  
        inputs.append([xb[i],yb[i],1])  
        inputs.append([xr[i],yr[i],-1])  
    return inputs
```


```
# Generate the data
```

```
training_m = np.array(generateData_m(100))  
testing_m = np.array(generateData_m(100))
```

```
fig = plt.gcf()  
fig.set_size_inches(12, 4)
```

```
plt.subplot(1, 2, 1)  
plt.title('Training set')  
plot_data(training_m)
```

```
plt.subplot(1, 2, 2)  
plt.title('Testing set')  
plot_data(testing_m)
```



Q: Using MLLib train up a LASSO logistic regression model with the training dataset and evaluate with the testing set. What is a good number of iterations for training the logistic regression model? Justify with plots and words.

In [32]: *# using the example notebook from class*

```
def logisticRegressionGDReg(data, wInitial=None, learningRate=0.05, iterations=50, regParam=0.01, regType=None):
    featureLen = len(data.take(1)[0].x)
    n = data.count()
    if wInitial is None:
        w = np.random.normal(size=featureLen) # w should be broadcasted if it is large
    else:
        w = wInitial
    for i in range(iterations):
        wBroadcast = sc.broadcast(w)
        gradient = data.map(lambda p: (1 / (1 + np.exp(-p.y*np.dot(wBroadcast.value, p.x)))-1) * p.y * np.array(p.x))\
            .reduce(lambda a, b: a + b)
        if regType == "Ridge":
            wReg = w * 1
            wReg[-1] = 0 #last value of weight vector is bias term, ignored in regularization
        elif regType == "Lasso":
            wReg = w * 1
            wReg[-1] = 0 #last value of weight vector is bias term, ignored in regularization
            wReg = (wReg>0).astype(int) * 2-1
        else:
            wReg = np.zeros(w.shape[0])
        gradient = gradient + regParam * wReg #gradient: GD of Squared Error+ GD of regularized term
        w = w - learningRate * gradient / n
    return w
```

```

In [33]: # use resources from MLlib
from pyspark.mllib.regression import LabeledPoint
from pyspark.mllib.classification import LogisticRegressionModel, LogisticRegressionWithSGD

# for classifying the points: take the last element to be the label,
# and the other elements features

def label_point(point):
    label = 1 if point[-1] == 1 else 0
    return LabeledPoint(label, point[:-1])

# Make the training and test datasets RDDs

rdd_train = sc.parallelize(training_m).map(label_point).cache()
rdd_test = sc.parallelize(testing_m).map(label_point).cache()

rdd_labels = rdd_test.map(lambda x: x.label).cache()
rdd_test_features = rdd_test.map(lambda x: x.features).cache()

# Using the weights from a previous logistic regression,
# iterate to get a refined model

iterations_mllib = []
weights_mllib = []

def log_regression_mllib(n):
    model = LogisticRegressionWithSGD.train(data = rdd_train, regType = 'l1', iterations = n, initialWeights = [0.0, 0.0], intercept = True)
    return list(model.weights) + [model.intercept]

# Run the process
for i in range(200):
    its = i+1
    new_weights = log_regression_mllib(its)

    iterations_mllib.append(its)
    weights_mllib.append(new_weights)

```

```

In [34]: # evaluate with the testing set

# define a weight-plotting function

def weight_plot(it_id, mod_weight, x, y):
    #line slope
    b = mod_weight[0] / (-1 * mod_weight[1])
    #line intercept
    a = mod_weight[2]

    x_val = x
    y_val = [(a + b * x) for x in x_val]
    zip_vals = np.array(zip(x_val, y_val))

```

```

    if it_id is not None:
        pl_name = 'Iteration no. ' + str(it_id)
    else:
        pl_name = 'Initial state'
    print pl_name
    plt.plot(zip_vals[:, 0], zip_vals[:, 1], label = pl_name)

# for each iteration, plot the weights

def show_progress(its, new_weights, pl_no):

    fig = plt.gcf()
    fig.set_size_inches(14, 7)

    plt.title('Test on trainig set: Model decision boundary')
    plot_data(testing_m)

    axes = plt.gca()

    xlim = axes.get_xlim()
    ylim = axes.get_ylim()

    #and show what happens at each iteration

    weight_plot(its[0], new_weights[0], xlim, ylim)

    for i, alpha in zip(range(1, len(its)), np.linspace(0.05, 0.2, len
(its))):
        weight_plot(i, new_weights[i], xlim, ylim)

    weight_plot(its[-1], new_weights[-1], xlim, ylim)

    #organize the plots

    frame = axes.get_position()

    axes.set_position([frame.x0, frame.y0, frame.width * 0.8, frame.he
ight])

    plt.xlim(xlim[0], xlim[1])
    plt.ylim(ylim[0], ylim[1])

    plt.legend(loc='center right', bbox_to_anchor=(1, 0.5))

show_progress(iterations_mllib, weights_mllib, 10)

```

```

Iteration no. 1
Iteration no. 1
Iteration no. 2
Iteration no. 3
Iteration no. 4
Iteration no. 5
Iteration no. 6


```

Iteration no. 7
Iteration no. 8
Iteration no. 9
Iteration no. 10
Iteration no. 11
Iteration no. 12
Iteration no. 13
Iteration no. 14
Iteration no. 15
Iteration no. 16
Iteration no. 17
Iteration no. 18
Iteration no. 19
Iteration no. 20
Iteration no. 21
Iteration no. 22
Iteration no. 23
Iteration no. 24
Iteration no. 25
Iteration no. 26
Iteration no. 27
Iteration no. 28
Iteration no. 29
Iteration no. 30
Iteration no. 31
Iteration no. 32
Iteration no. 33
Iteration no. 34
Iteration no. 35
Iteration no. 36
Iteration no. 37
Iteration no. 38
Iteration no. 39
Iteration no. 40
Iteration no. 41
Iteration no. 42
Iteration no. 43
Iteration no. 44
Iteration no. 45
Iteration no. 46
Iteration no. 47
Iteration no. 48
Iteration no. 49
Iteration no. 50
Iteration no. 51
Iteration no. 52
Iteration no. 53
Iteration no. 54
Iteration no. 55
Iteration no. 56
Iteration no. 57
Iteration no. 58
Iteration no. 59


Iteration no. 60
Iteration no. 61
Iteration no. 62
Iteration no. 63
Iteration no. 64
Iteration no. 65
Iteration no. 66
Iteration no. 67
Iteration no. 68
Iteration no. 69
Iteration no. 70
Iteration no. 71
Iteration no. 72
Iteration no. 73
Iteration no. 74
Iteration no. 75
Iteration no. 76
Iteration no. 77
Iteration no. 78
Iteration no. 79
Iteration no. 80
Iteration no. 81
Iteration no. 82
Iteration no. 83
Iteration no. 84
Iteration no. 85
Iteration no. 86
Iteration no. 87
Iteration no. 88
Iteration no. 89
Iteration no. 90
Iteration no. 91
Iteration no. 92
Iteration no. 93
Iteration no. 94
Iteration no. 95
Iteration no. 96
Iteration no. 97
Iteration no. 98
Iteration no. 99
Iteration no. 100
Iteration no. 101
Iteration no. 102
Iteration no. 103
Iteration no. 104
Iteration no. 105
Iteration no. 106
Iteration no. 107
Iteration no. 108
Iteration no. 109
Iteration no. 110
Iteration no. 111
Iteration no. 112

Iteration no. 113
Iteration no. 114
Iteration no. 115
Iteration no. 116
Iteration no. 117
Iteration no. 118
Iteration no. 119
Iteration no. 120
Iteration no. 121
Iteration no. 122
Iteration no. 123
Iteration no. 124
Iteration no. 125
Iteration no. 126
Iteration no. 127
Iteration no. 128
Iteration no. 129
Iteration no. 130
Iteration no. 131
Iteration no. 132
Iteration no. 133
Iteration no. 134
Iteration no. 135
Iteration no. 136
Iteration no. 137
Iteration no. 138
Iteration no. 139
Iteration no. 140
Iteration no. 141
Iteration no. 142
Iteration no. 143
Iteration no. 144
Iteration no. 145
Iteration no. 146
Iteration no. 147
Iteration no. 148
Iteration no. 149
Iteration no. 150
Iteration no. 151
Iteration no. 152
Iteration no. 153
Iteration no. 154
Iteration no. 155
Iteration no. 156
Iteration no. 157
Iteration no. 158
Iteration no. 159
Iteration no. 160
Iteration no. 161
Iteration no. 162
Iteration no. 163
Iteration no. 164
Iteration no. 165

Iteration no. 166
Iteration no. 167
Iteration no. 168
Iteration no. 169
Iteration no. 170
Iteration no. 171
Iteration no. 172
Iteration no. 173
Iteration no. 174
Iteration no. 175
Iteration no. 176
Iteration no. 177
Iteration no. 178
Iteration no. 179
Iteration no. 180
Iteration no. 181
Iteration no. 182
Iteration no. 183
Iteration no. 184
Iteration no. 185
Iteration no. 186
Iteration no. 187
Iteration no. 188
Iteration no. 189
Iteration no. 190
Iteration no. 191
Iteration no. 192
Iteration no. 193
Iteration no. 194
Iteration no. 195
Iteration no. 196
Iteration no. 197
Iteration no. 198
Iteration no. 199
Iteration no. 200



Iteration no. 19
Iteration no. 20
Iteration no. 21
Iteration no. 22
Iteration no. 23
Iteration no. 24
Iteration no. 25
Iteration no. 26
Iteration no. 27
Iteration no. 28
Iteration no. 29
Iteration no. 30
Iteration no. 31
Iteration no. 32
Iteration no. 33
Iteration no. 34
Iteration no. 35
Iteration no. 36
Iteration no. 37
Iteration no. 38
Iteration no. 39
Iteration no. 40
Iteration no. 41
Iteration no. 42
Iteration no. 43
Iteration no. 44
Iteration no. 45
Iteration no. 46
Iteration no. 47
Iteration no. 48
Iteration no. 49
Iteration no. 50
Iteration no. 51
Iteration no. 52
Iteration no. 53
Iteration no. 54
Iteration no. 55
Iteration no. 56
Iteration no. 57
Iteration no. 58
Iteration no. 59
Iteration no. 60
Iteration no. 61
Iteration no. 62
Iteration no. 63
Iteration no. 64
Iteration no. 65
Iteration no. 66
Iteration no. 67
Iteration no. 68
Iteration no. 69
Iteration no. 70
Iteration no. 71
Iteration no. 72
Iteration no. 73
Iteration no. 74



- Iteration no. 75
- Iteration no. 76
- Iteration no. 77
- Iteration no. 78
- Iteration no. 79
- Iteration no. 80
- Iteration no. 81
- Iteration no. 82
- Iteration no. 83
- Iteration no. 84
- Iteration no. 85
- Iteration no. 86
- Iteration no. 87
- Iteration no. 88
- Iteration no. 89
- Iteration no. 90
- Iteration no. 91
- Iteration no. 92
- Iteration no. 93
- Iteration no. 94
- Iteration no. 95
- Iteration no. 96
- Iteration no. 97
- Iteration no. 98
- Iteration no. 99
- Iteration no. 100
- Iteration no. 101
- Iteration no. 102
- Iteration no. 103
- Iteration no. 104
- Iteration no. 105
- Iteration no. 106
- Iteration no. 107
- Iteration no. 108
- Iteration no. 109
- Iteration no. 110
- Iteration no. 111
- Iteration no. 112
- Iteration no. 113
- Iteration no. 114
- Iteration no. 115
- Iteration no. 116
- Iteration no. 117
- Iteration no. 118
- Iteration no. 119
- Iteration no. 120
- Iteration no. 121
- Iteration no. 122
- Iteration no. 123
- Iteration no. 124
- Iteration no. 125
- Iteration no. 126
- Iteration no. 127
- Iteration no. 128
- Iteration no. 129
- Iteration no. 130

Iteration no. 131
Iteration no. 132
Iteration no. 133
Iteration no. 134
Iteration no. 135
Iteration no. 136
Iteration no. 137
Iteration no. 138
Iteration no. 139
Iteration no. 140
Iteration no. 141
Iteration no. 142
Iteration no. 143
Iteration no. 144
Iteration no. 145
Iteration no. 146
Iteration no. 147
Iteration no. 148
Iteration no. 149
Iteration no. 150
Iteration no. 151
Iteration no. 152
Iteration no. 153
Iteration no. 154
Iteration no. 155
Iteration no. 156
Iteration no. 157
Iteration no. 158
Iteration no. 159
Iteration no. 160
Iteration no. 161
Iteration no. 162
Iteration no. 163
Iteration no. 164
Iteration no. 165
Iteration no. 166
Iteration no. 167
Iteration no. 168
Iteration no. 169
Iteration no. 170
Iteration no. 171
Iteration no. 172
Iteration no. 173
Iteration no. 174
Iteration no. 175
Iteration no. 176
Iteration no. 177
Iteration no. 178
Iteration no. 179
Iteration no. 180
Iteration no. 181
Iteration no. 182
Iteration no. 183
Iteration no. 184
Iteration no. 185
Iteration no. 186

—	Iteration no. 187
—	Iteration no. 188
—	Iteration no. 189
—	Iteration no. 190
—	Iteration no. 191
—	Iteration no. 192
—	Iteration no. 193
—	Iteration no. 194
—	Iteration no. 195
—	Iteration no. 196
—	Iteration no. 197
—	Iteration no. 198
—	Iteration no. 199
—	Iteration no. 200

Now, we can show what is a good number of iterations for training the logistic regression model, by plotting the accuracy as a function of number of iterations.

```
In [37]: import matplotlib.pyplot as plt
```

```
#Evaluate the accuracy
```

```
def accurate(mod_weights):
```

```
    mod = LogisticRegressionModel(mod_weights[:-1], mod_weights[-1], 2  
, 2)
```

```
#consider both predictions and result
```

```
    rdd_pred_labels = mod.predict(rdd_test_features)
```

```
    return rdd_pred_labels.zip(rdd_labels).map(lambda x: 1.0 if x[0]==  
x[1] else 0.0).mean()
```

```
# plot the accuracy
```

```
fig = plt.gcf()
```

```
fig.set_size_inches(12,4)
```

```
results = [accurate(mod_weights) for mod_weights in weights_mllib]
```

```
plt.subplot(1, 2, 1)
```

```
plt.title('Accuracy as a function of iterations')
```

```
plt.plot(iterations_mllib, results)
```

```
# Evaluate the improvement rate
```

```
def model_improvements(old_weights, new_weights):
```

```
    w_imp = np.array(old_weights) - np.array(new_weights)
```

```
    return np.linalg.norm(w_imp)
```

```
# plot the improvement rate too
```

```
improvements = [model_improvements(old_weights, new_weights) for (old_  
weights, new_weights) in zip(weights_mllib[0:198], weights_mllib[1:199  
)]]
```

```
plt.subplot(1, 2, 2)
```

```
plt.title('Rate of model improvement')
```

```
plt.plot(iterations_mllib, improvements)
```

```
ValueErrorTraceback (most recent call last)
```

```
<ipython-input-37-c3fe6dd94652> in <module>()
```

```
    32 plt.subplot(1, 2, 2)
```

```
    33 plt.title('Rate of model improvement')
```

```
---> 34 plt.plot(iterations_mllib, improvements)
```

```
/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/pyplot.  
t.pyc in plot(*args, **kwargs)
```

```
    3151         ax.hold(hold)
```

```
    3152     try:
```

```
-> 3153         ret = ax.plot(*args, **kwargs)
```

```
    3154     finally:
```

```
    3155         ax.hold(washold)
```

```

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/__init___.py in inner(ax, *args, **kwargs)
    1817 warnings.warn(msg % (label_namer, func.__name__),
    1818                               RuntimeWarning, stacklevel
    =2)
-> 1819             return func(ax, *args, **kwargs)
    1820         pre_doc = inner.__doc__
    1821         if pre_doc is None:

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/_axes.py in plot(self, *args, **kwargs)
    1380         kwargs = cbook.normalize_kwargs(kwargs, _alias_map)
    1381
-> 1382         for line in self._get_lines(*args, **kwargs):
    1383             self.add_line(line)
    1384             lines.append(line)


/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/_base.py in _grab_next_args(self, *args, **kwargs)
    379             return
    380             if len(remaining) <= 3:
--> 381                 for seg in self._plot_args(remaining, kwargs):
    382                     yield seg
    383             return

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/_base.py in _plot_args(self, tup, kwargs)
    357             x, y = index_of(tup[-1])
    358
--> 359             x, y = self._xy_from_xy(x, y)
    360
    361             if self.command == 'plot':

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/_base.py in _xy_from_xy(self, x, y)
    217             y = _check_1d(y)
    218             if x.shape[0] != y.shape[0]:
--> 219                 raise ValueError("x and y must have same first dimension")
    220             if x.ndim > 2 or y.ndim > 2:
    221                 raise ValueError("x and y can be no greater than 2-D")

```

ValueError: x and y must have same first dimension



These results suggest that the optimal number of iterations for training this regression is 10, because it's enough for the results to converge.

Q: Derive and implement in Spark a weighted LASSO logistic regression. Implement a convergence test of your choice to check for termination within your training algorithm .

Weight the above training dataset as follows: Weight each example using the inverse vector length (Euclidean norm):

$\text{weight}(X) = 1/\|X\|,$

where $\|X\| = \text{SQRT}(X.X) = \text{SQRT}(X_1^2 + X_2^2)$

Here X is vector made up of X1 and X2.

Evaluate your homegrown weighted LASSO logistic regression on the test dataset. Report misclassification error (1 - Accuracy) and how many iterations does it take to converge.

Does Spark MLlib have a weighted LASSO logistic regression implementation. If so use it and report your findings on the weighted training set and test set.

```
In [38]: #now, we just slightly modify the code from the notebook 'LogisticRegression - Spark'
#provided in class
```

```
In [76]: from collections import namedtuple
import numpy as np
Point = namedtuple('Point', 'x y w')

def readPoint(dataPoint):
    #d = line.split(',')
    #x = [float(i) for i in d[1:]]
    #x.append(1.0) #bias term
    #return Point(x, float(d[0]))
```

```

    x = dataPoint.features
    x = np.append(x, 1.0)
    return Point(x, dataPoint.features[-1], 1 / np.linalg.norm(x))

train_rdd_weighted = rdd_train.map(readPoint).cache()

# original code:

def logisticRegressionGDReg_weighted(data, regType, wInitial=None, learningRate=0.05, regParam=0.01):
    featureLen = len(data.take(1)[0].x)
    n = data.count()
    if wInitial is None:
        w = np.random.normal(size=featureLen) # w should be broadcasted if it is large
    else:
        w = wInitial
    for i in range(it_no):
        w_b = sc.broadcast(w)
        gradient_in_dim = data.map(lambda p: ((p.w / (1 + np.exp(-p.y * np.dot(w_b.value, p.x)))-1) * p.y * np.array(p.x), p.w)).reduce(lambda a, b: a + b)
        gradient = gradient_in_dim[0] / n
        #gradient = data.map(lambda p: \
        #                                (1 / (1 + np.exp(-p.label * np.dot(w_b.value, p.features)))-1) \
        #                                * p.label \
        #                                * p.features \
        #                                * np.reciprocal(np.sqrt(np.sum(np.square(p.features))))) \
        #                                .reduce(lambda x, y: x + y)
        if regType == "Ridge":
            wReg = w * 1
            wReg[-1] = 0 #last value of weight vector is bias term, ignored in regularization
        elif regType == "Lasso":
            wReg = w * 1
            wReg[-1] = 0 #last value of weight vector is bias term, ignored in regularization
            wReg = (wReg>0).astype(int) * 2-1
        else:
            wReg = np.zeros(w.shape[0])
        gradient = gradient + regParam * wReg #gradient: GD of Squared Error+ GD of regularized term
        w = w - learningRate * gradient / n
    return w

```



```

In [79]: #convergence test

#count iterations

old_weights = None
ws_normed = []
its_weighted = []

convergence_attained = False

it_no = 0

# try 500 iterations, or until the chance is less than 0.01
while it_no <500 and not convergence_attained:
    it_no +=1
    #regType == "Lasso"
    new_weights = logisticRegressionGDReg_weighted(train_rdd_weighted,
    "Lasso", old_weights)

    its_normed.append(it_no)
    ws_normed.append(new_weights)

    if it_no > 1:
        change = model_improvements(old_weights, new_weights)
        convergence_attained = change <= 0.01

    old_weights = new_weights

if convergence_attained:
    print 'After ', len(its_normed), 'iterations, convergence attained
    ,
else:
    pass

After 3 iterations, convergence attained

```

```

In [89]: ws_normed

```

```

Out[89]: [array([ 1.25810703, -1.28396509,  0.44992587]),
          array([ 1.25810152, -1.28395932,  0.44993205])]

```

```
In [86]: import matplotlib.pyplot as plt
```

```
# show the misclassification error:
```

```
fig = plt.gcf()
fig.set_size_inches(14,5)
```

```
# accuracy result
```

```
accuracies_n = [accurate(mod_weights) for mod_weights in ws_normed]
plt.subplot(1, 2, 1)
plt.title('accuracy')
plt.plot(its_normed, accuracies_n)
```

```
mod_changes_n = [model_improvements( old_weights, new_weights) for old
_weights, new_weights in zip(ws_normed[:-1], ws_normed[1:])]

plt.subplot(1, 2, 2)
plt.title('Change rate')
plt.plot(its_normed[1:], mod_changes_n)
```

```
ValueErrorTraceback (most recent call last)
```

```
<ipython-input-86-24885ab2eca6> in <module>()
```

```
    11 plt.subplot(1, 2, 1)
    12 plt.title('accuracy')
--> 13 plt.plot(its_normed, accuracies_n)
    14
    15 mod_changes_n = [model_improvements( old_weights,
new_weights) for old_weights, new_weights in zip(ws_normed[:-1],
ws_normed[1:])]

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/pyplot.py in plot(*args, **kwargs)
    3151         ax.hold(hold)
    3152         try:
-> 3153             ret = ax.plot(*args, **kwargs)
    3154         finally:
    3155             ax.hold(washold)

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/_init_.py in inner(ax, *args, **kwargs)
    1817             warnings.warn(msg % (label_namer, func.__
_name__),
    1818                             RuntimeWarning, stacklevel
=2)
-> 1819             return func(ax, *args, **kwargs)
    1820         pre_doc = inner.__doc__
    1821         if pre_doc is None:
```

```
/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/
_axes.py in plot(self, *args, **kwargs)
    1380         kwargs = cbook.normalize_kwargs(kwargs, _alias_map)
```

```

1381
-> 1382         for line in self._get_lines(*args, **kwargs):
1383             self.add_line(line)
1384             lines.append(line)


/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/
_base.pyc in _grab_next_args(self, *args, **kwargs)
    379         return
    380         if len(remaining) <= 3:
--> 381             for seg in self._plot_args(remaining, kwargs
):
    382                 yield seg
    383             return

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/
_base.pyc in _plot_args(self, tup, kwargs)
    357         x, y = index_of(tup[-1])
    358
--> 359         x, y = self._xy_from_xy(x, y)
    360
    361         if self.command == 'plot':

/opt/conda/envs/python2/lib/python2.7/site-packages/matplotlib/axes/
_base.pyc in _xy_from_xy(self, x, y)
    217         y = _check_1d(y)
    218         if x.shape[0] != y.shape[0]:
--> 219             raise ValueError("x and y must have same first d
imension")
    220         if x.ndim > 2 or y.ndim > 2:
    221             raise ValueError("x and y can be no greater than
2-D")

```

ValueError: x and y must have same first dimension



Unfortunately, I couldn't find this implemented in Spark MLLib.

HW11.4 SVMs

[Back to Table of Contents](#)

Use the non-linearly separable training and testing datasets from HW11.3 in this problem.

Using MLLib train up a soft SVM model with the training dataset and evaluate with the testing set. What is a good number of iterations for training the SVM model? Justify with plots and words.

In []:

HW11.4.1 [Optional] Derive and Implement in Spark a weighted hard linear svm classification learning algorithm. Feel free to use the following notebook as a starting point SVM Notebook. Evaluate your homegrown weighted linear svm classification learning algorithm on the weighted training dataset and test dataset from HW11.3 (linearly separable dataset). Report misclassification error (1 - Accuracy) and how many iterations does it took to converge? How many support vectors do you end up with? Does Spark MLLib have a weighted soft SVM learner. If so use it and report your findings on the weighted training set and test set. **HW11.4.2 [Optional]** Repeat HW11.4.2 using a soft SVM and a nonlinearly separable datasets. Compare the error rates that you get here with the error rates you achieve using MLLib's soft SVM. Report the number of support vectors in both cases (may not be available the MLLib implementation).

In [65]: *## Code goes here*

In [66]: *## Drivers & Runners*

In [67]: *## Run Scripts, S3 Sync*

HW11.5 [OPTIONAL] Distributed Perceptron algorithm.

[Back to Table of Contents](#)

Using the following papers as background:

[http://static.googleusercontent.com/external_content/untrusted_dlcp/research.google.com/en//pubs/archive/:\(http://static.googleusercontent.com/external_content/untrusted_dlcp/research.google.com/en//pubs/archive/](http://static.googleusercontent.com/external_content/untrusted_dlcp/research.google.com/en//pubs/archive/:(http://static.googleusercontent.com/external_content/untrusted_dlcp/research.google.com/en//pubs/archive/)

<https://www.dropbox.com/s/a5pdc0r8ptudgj/gesmundo-tomeh-eacl-2012.pdf?dl=0>
(<https://www.dropbox.com/s/a5pdc0r8ptudgj/gesmundo-tomeh-eacl-2012.pdf?dl=0>)

<http://www.slideshare.net/matsubaray/distributed-perceptron>
(<http://www.slideshare.net/matsubaray/distributed-perceptron>)

Implement each of the following flavors of perceptron learning algorithm:

1. Serial (All Data): This is the classifier returned if trained serially on all the available data. On a single computer for example (Mistake driven)
2. Serial (Sub Sampling): Shard the data, select one shard randomly and train serially.
3. Parallel (Parameter Mix): Learn a perceptron locally on each shard: Once learning is complete combine each learnt perceptron using a uniform weighting
4. Parallel (Iterative Parameter Mix) as described in the above papers.

```
In [71]: ## Code goes here
```

```
In [72]: ## Drivers & Runners
```

```
In [73]: ## Run Scripts, S3 Sync
```

HW11.6 [OPTIONAL: consider doing this in a group] Evaluation of perceptron algorithms on PennTreeBank POS corpus

[Back to Table of Contents](#)

Reproduce the experiments reported in the following paper:

Prediction with MapReduce - Andrea Gesmundo and Nadi Tomeh

<http://www.aclweb.org/anthology/E12-2020> (<http://www.aclweb.org/anthology/E12-2020>)

These experiments focus on the prediction accuracy on a part-of-speech (POS) task using the PennTreeBank corpus. They use sections 0-18 of the Wall Street Journal for training, and sections 22-24 for testing.

HW11.7 [OPTIONAL: consider doing this in a group] Kernal Adatron

[Back to Table of Contents](#)

Implement the Kernal Adatron in Spark (contact Jimi for details)

HW11.8 [OPTIONAL] Create an animation of gradient descent for the Perceptron learning or for the logistic regression

[Back to Table of Contents](#)

Learning with the following 3 training examples. Present the progress in terms of the 2 dimensional input space in terms of a contour plot and also in terms of the 3D surface plot. See Live slides for an example.

[Back to Table of Contents](#) Here is a sample training dataset that can be used: -2, 3, +1 -1, -1, -1 2, -3, 1

Please feel free to use

- R (yes R!)
- d3
- <https://plot.ly/python/> (<https://plot.ly/python/>)
- Matplotlib

I am happy for folks to collaborate on HW11.8 also.

It would be great to get the 3D surface and contours lines (with solution region and label normalized data) all in the same graph

```
In [77]: ## Code goes here
```

```
In [78]: ## Drivers & Runners
```

```
In [79]: ## Run Scripts, S3 Sync
```

[Back to Table of Contents](#)

----- END OF HOWEWORK -----

In []: