



- Docs
- Guides
- Screencasts
- Changelog
- Starter Kits
- Community

Getting started ^

- Introduction
- Quick start
- Core concepts
- Architecture

Ingest ^

- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector

Query ^

- Overview
- SQL best practices
- Query parameters

Publish ^

- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In



Authenticate

The first step is to check everything works correctly and that you're able to authenticate:

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

It saves your credentials in the `.tinyb` file in your current directory. **Add it to `.gitignore`** (or the ignore list in the SCM you use) because it contains Tinybird credentials.

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In



- Docs
- Guides
- Screencasts
- Changelog
- Starter Kits
- Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

Go to your [Tinybird dashboard](#) to check the Data Source is present there.

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

GitHub repository.

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

Data sources define how your data is going to be stored. You can add data to these Data Sources using [Data Sources API](#).

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

You cannot override Data Sources. If you try to push a Data Source that already exists in your account you'll get an output saying: `events already exists, skipping`. If you

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In


```
$ tb push pipes/top_product_per_day.pipe --populate
** Processing pipes/top product per day.pipe
```

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

When you push an endpoint a TOKEN with PIPE:READ permissions is automatically created. You can see it from the [tokens UI](#) or directly from the CLI with the command

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In



NODE endpoint
DESCRIPTION >

- Docs
- Guides
- Screencasts
- Changelog
- Starter Kits
- Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

```
$ tb push endpoints/top_products_params.pipe --force
```

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

Members management

You can manage Workspace members using the Web UI or the CLI. For the latter, use the

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

Once you've installed the CLI you can access the integrated help:

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

It supports Linux and macOS > 10.14.

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In

```
tb:us-east=>my-workspace ~/dev/analytics/wask $ ls -lha datasources
total 40
drwxr-xr-x  7 alrocar  staff   224B Jan 13 14:29 .
drwxr-xr-x 12 alrocar  staff   384B Jan 18 10:44 ..
```



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes
- S3 Sink

Start building

Sign In