



Docs

Guides

Screencasts

Changelog

Starter Kits

Community

Getting started ^

- Introduction
- Quick start
- Core concepts
- Architecture

Ingest ^

- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector

Query ^

- Overview
- SQL best practices
- Query parameters

Publish ^

- Overview
- API gateways
- Materialized Views
- Copy Pipes

Start building

Sign In



```
{  
  "name": "VendorID",  
  "type": "TEXT"
```

- ^
- Introduction
  - Quick start
  - Core concepts
  - Architecture

- ^
- Overview
  - Data Sources API
  - Events API
  - BigQuery connector
  - Confluent connector
  - Kafka connector
  - RedPanda connector
  - Snowflake connector
  - S3 connector

- ^
- Overview
  - SQL best practices
  - Query parameters

- ^
- Overview
  - API gateways
  - Materialized Views
  - Copy Pipes

Start building

Sign In

- ^
- Introduction
  - Quick start
  - Core concepts
  - Architecture

- ^
- Overview
  - Data Sources API
  - Events API
  - BigQuery connector
  - Confluent connector
  - Kafka connector
  - RedPanda connector
  - Snowflake connector
  - S3 connector

- ^
- Overview
  - SQL best practices
  - Query parameters

- ^
- Overview
  - API gateways
  - Materialized Views
  - Copy Pipes

Start building

Sign In

KEY

TYPE

DESCRIPTION

Javascript - nan. Possible

 Docs  Guides  Screencasts  Changelog  Starter Kits  Community

^

- Introduction
- Quick start
- Core concepts
- Architecture

^

- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector

^

- Overview
- SQL best practices
- Query parameters

^

- Overview
- API gateways
- Materialized Views
- Copy Pipes

Start building

Sign In

Executes a SQL query using the engine, while providing a templated or non templated query string and the custom parameters that will be translated into the query. The custom parameters

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes

Start building

Sign In

```
curl -X POST \
  -H "Authorization: Bearer <PIPE:READ token>" \
  -H "Content-Type: text/plain" \
```

- Docs
- Guides
- Screencasts
- Changelog
- Starter Kits
- Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes

Start building

Sign In

KEY	TYPE	DESCRIPTION
		values: 0 - disabled, 1 -

-  Docs
-  Guides
-  Screencasts
-  Changelog
-  Starter Kits
-  Community



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes

Start building

Sign In

```
"tpep_pickup_datetime": "2002-12-31 23:01:55",  
"tpep_dropoff_datetime": "2003-01-01 14:59:11"
```

- ^
- Introduction
  - Quick start
  - Core concepts
  - Architecture

- ^
- Overview
  - Data Sources API
  - Events API
  - BigQuery connector
  - Confluent connector
  - Kafka connector
  - RedPanda connector
  - Snowflake connector
  - S3 connector

- ^
- Overview
  - SQL best practices
  - Query parameters

- ^
- Overview
  - API gateways
  - Materialized Views
  - Copy Pipes

Start building

Sign In



- If the original timestamp had no time zone associated, you'll read back the same date and time verbatim. If you ingested the timestamp `2022-11-14 11:08:46`, for example, Tinybird



Introduction

Quick start

Core concepts

Architecture



Overview

Data Sources API

Events API

BigQuery connector

Confluent connector

Kafka connector

RedPanda connector

Snowflake connector

S3 connector



Overview

SQL best practices

Query parameters



Overview

API gateways

Materialized Views

Copy Pipes

Start building

Sign In



- Introduction
- Quick start
- Core concepts
- Architecture



- Overview
- Data Sources API
- Events API
- BigQuery connector
- Confluent connector
- Kafka connector
- RedPanda connector
- Snowflake connector
- S3 connector



- Overview
- SQL best practices
- Query parameters



- Overview
- API gateways
- Materialized Views
- Copy Pipes

Start building

Sign In