

# OPERATING SYSTEM

## UNIT- 4

### File System

File system is the part of the operating system which is responsible for file management. It provides a mechanism to store the data and access to the file contents including data and programs. Some Operating systems treats everything as a file for example Ubuntu.

A file is a collection of correlated information which is recorded on secondary or non-volatile storage like magnetic disks, optical disks, and tapes. It is a method of data collection that is used as a medium for giving input and receiving output from that program.

In general, a file is a sequence of bits, bytes, or records whose meaning is defined by the file creator and user. Every File has a logical location where they are located for storage and retrieval.

The File system takes care of the following issues

- o **File Structure**

We have seen various data structures in which the file can be stored. The task of the file system is to maintain an optimal file structure.

- o **Recovering Free space**

Whenever a file gets deleted from the hard disk, there is a free space created in the disk. There can be many such spaces which need to be recovered in order to reallocate them to other files.

- o **Disk space assignment to the files**

The major concern about the file is deciding where to store the files on the hard disk. There are various disks scheduling algorithm.

- o **Tracking data location**

A File may or may not be stored within only one block. It can be stored in the non contiguous blocks on the disk. We need to keep track of all the blocks on which the part of the files reside.

## File Access Methods in Operating System


When a file is used, information is read and accessed into computer memory and there are several ways to access this information of the file. Some systems provide only one access method for files. Other systems, such as those of IBM, support many access methods, and choosing the right one for a particular application is a major design problem.

There are three ways to access a file into a computer system: Sequential-Access, Direct Access, Index sequential Method.

### Sequential Access –

It is the simplest access method. Information in the file is processed in order, one record after the other. This mode of access is by far the most common; for example, editor and compiler usually access the file in this fashion.

Read and write make up the bulk of the operation on a file. A read operation *-read next-* read the next position of the file and automatically advance a file pointer, which keeps track I/O location. Similarly, for the write *write next* append to the end of the file and advance to the newly written material.



Most of the operating systems access the file sequentially. In other words, we can say that most of the files need to be accessed sequentially by the operating system.

In sequential access, the OS read the file word by word. A pointer is maintained which initially points to the base address of the file. If the user wants to read first word of the file then the pointer provides that word to the user and increases its value by 1 word. This process continues till the end of the file.

**Key points:**

- Data is accessed one record right after another record in an order.
- When we use read command, it move ahead pointer by one
- When we use write command, it will allocate memory and move the pointer to the end of the file
- Such a method is reasonable for tape.

**Direct Access –**


Another method is *direct access method* also known as *relative access method*. A fixed-length logical record that allows the program to read and write record rapidly. in no particular order. The direct access is based on the disk model of a file since disk allows random access to any file block. For direct access, the file is viewed as a numbered sequence of block or record. Thus, we may read block 14 then block 59 and then we can write block 17. There is no restriction on the order of reading and writing for a direct access file.

A block number provided by the user to the operating system is normally a *relative block number*, the first relative block of the file is 0 and then 1 and so on.

The Direct Access is mostly required in the case of database systems. In most of the cases, we need filtered information from the database. The sequential access can be very slow and inefficient in such cases.

Suppose every block of the storage stores 4 records and we know that the record we needed is stored in 10th block. In that case, the sequential access will not be implemented because it will traverse all the blocks in order to access the needed record.

Direct access will give the required result despite of the fact that the operating system has to perform some complex tasks such as determining the desired block number. However, that is generally implemented in database applications.



### **Index sequential method –**

It is the other method of accessing a file which is built on the top of the direct access method. These methods construct an index for the file. The index, like an index in the back of a book, contains the pointer to the various blocks. To find a record in the file, we first search the index and then by the help of pointer we access the file directly.

- Provides solutions to problems of contiguous and linked allocation.
- A index block is created having all pointers to files.
- Each file has its own index block which stores the addresses of disk space occupied by the file.
- Directory contains the addresses of index blocks of files.

### **Key points:**


- It is built on top of Sequential access.
- It control the pointer by using index.

### **Directory Structure:-**

Directory can be defined as the listing of the related files on the disk. The directory may store some or the entire file attributes.


To get the benefit of different file systems on the different operating systems, A hard disk can be divided into the number of partitions of different sizes. The partitions are also called volumes or mini disks.

Each partition must have at least one directory in which, all the files of the partition can be listed. A directory entry is maintained for each file in the directory which stores all the information related to that file.



A directory can be viewed as a file which contains the Meta data of the bunch of files.

A **directory** is a container that is used to contain folders and file. It organizes files and folders into a hierarchical manner.




Every Directory supports a number of common operations on the file:

1. File Creation
2. Search for the file
3. File deletion
4. Renaming the file
5. Traversing Files
6. Listing of files

### 1. Single Level Directory

The simplest method is to have one big list of all the files on the disk. The entire system will contain only one directory which is supposed to mention all the files present in the file system. The directory contains one entry per each file present on the file system.



**Single Level Directory**

This type of directories can be used for a simple system.

### Advantages

1. Implementation is very simple.
2. If the sizes of the files are very small then the searching becomes faster.
3. File creation, searching, deletion is very simple since we have only one directory.


### Disadvantages

1. We cannot have two files with the same name.
2. The directory may be very big therefore searching for a file may take so much time.

3. Protection cannot be implemented for multiple users.
4. There are no ways to group same kind of files.
5. Choosing the unique name for every file is a bit complex and limits the number of files in the system because most of the Operating System limits the number of characters used to construct the file name.

## Two Level Directory

In two level directory systems, we can create a separate directory for each user. There is one master directory which contains separate directories dedicated to each user. For each user, there is a different directory present at the second level, containing group of user's file. The system doesn't let a user to enter in the other user's directory without permission.



### Characteristics of two level directory system

1. Each files has a path name as */User-name/directory-name/*
2. Different users can have the same file name.
3. Searching becomes more efficient as only one user's list needs to be traversed.
4. The same kind of files cannot be grouped into a single directory for a particular user.

Every Operating System maintains a variable as **PWD** which contains the present directory name (present user name) so that the searching can be done appropriately.


## Tree Structured Directory

In Tree structured directory system, any directory entry can either be a file or sub directory. Tree structured directory system overcomes the drawbacks of two level directory system. The similar kind of files can now be grouped in one directory.

Each user has its own directory and it cannot enter in the other user's directory. However, the user has the permission to read the root's data but he cannot write or modify this. Only administrator of the system has the complete access of root directory.

Searching is more efficient in this directory structure. The concept of current working directory is used. A file can be accessed by two types of path, either relative or absolute.

Absolute path is the path of the file with respect to the root directory of the system while relative path is the path with respect to the current working directory of the system. In tree structured directory systems, the user is given the privilege to create the files as well as directories.



**The Structured Directory System**

## Permissions on the file and directory


A tree structured directory system may consist of various levels therefore there is a set of permissions assigned to each file and directory.

The permissions are **R W X** which are regarding reading, writing and the execution of the files or directory. The permissions are assigned to three types of users: owner, group and others.



There is a identification bit which differentiate between directory and file. For a directory, it is **d** and for a file, it is dot (**.**)

The following snapshot shows the permissions assigned to a file in a Linux based system. Initial bit **d** represents that it is a directory.

A terminal window titled 'javatpoint@localhost:~/javatpoint' showing the command 'ls -l' and its output. The output lists a directory with permissions 'drwxr-xr-x', owned by 'root', created on '27 Jan 11 14:37', and located on 'CentOS'.

```
javatpoint@localhost:~/javatpoint
File Edit View Search Terminal Help
[javatpoint@localhost javatpoint]$ ls -l
total 0
drwxr-xr-x. 3 root root 27 Jan 11 14:37 CentOS
[javatpoint@localhost javatpoint]$
```


## Acyclic-Graph Structured Directories

The tree structured directory system doesn't allow the same file to exist in multiple directories therefore sharing is major concern in tree structured directory system. We can provide sharing by making the directory an acyclic graph. In this system, two or more directory entry can point to the same file or sub directory. That file or sub directory is shared between the two directory entries.

These kinds of directory graphs can be made using links or aliases. We can have multiple paths for a same file. Links can either be symbolic (logical) or hard link (physical).

If a file gets deleted in acyclic graph structured directory system, then


1. In the case of soft link, the file just gets deleted and we are left with a dangling pointer.
2. In the case of hard link, the actual file will be deleted only if all the references to it gets deleted.



Acyclic-Graph Structured Directory System

### General graph directory structure –

In general graph directory structure, cycles are allowed within a directory structure where multiple directories can be derived from more than one parent directory. The main problem with this kind of directory structure is to calculate total size or space that has been taken by the files and directories.



### Advantages:

- It allows cycles.
- It is more flexible than other directories structure.

### Disadvantages:

- It is more costly than others.
- It needs garbage collection.


## Structures of Directory in Operating System

### Allocation Method

The allocation method defines how the files are stored in the disk blocks. The direct access nature of the disks gives us the flexibility to implement the files. In many cases, different files or many files are stored on the same disk. The main problem that occurs in the operating system is that how we allocate the spaces to these files so that the utilization of disk is efficient and the quick access to the file is possible. There are mainly three methods of file allocation in the disk. Each method has its advantages and disadvantages. Mainly a system uses one method for all files within the system.


**Contiguous Allocation:** – Contiguous allocation is one of the most used methods for allocation. Contiguous allocation means we allocate the block in such a manner, so that in the hard disk, all the blocks get the contiguous physical block.

We can see in the below figure that in the directory, we have three files. In the table, we have mentioned the starting block and the length of all the files. We can see in the table that for each file, we allocate a contiguous block.



## Example of contiguous allocation

We can see in the given diagram, that there is a file. The name of the file is 'mail.' The file starts from the 19<sup>th</sup> block and the length of the file is 6. So, the file occupies 6 blocks in a contiguous manner. Thus, it will hold blocks 19, 20, 21, 22, 23, 24.



## Advantages of Contiguous Allocation

The advantages of contiguous allocation are:

1. The contiguous allocation method gives excellent read performance.
2. Contiguous allocation is easy to implement.
3. The contiguous allocation method supports both types of file access methods that are sequential access and direct access.
4. The Contiguous allocation method is fast because, in this method number of seeks is less due to the contiguous allocation of file blocks.

## Disadvantages of Contiguous allocation

The disadvantages of contiguous allocation method are:

1. In the contiguous allocation method, sometimes disk can be fragmented.


2. In this method, it is difficult to increase the size of the file due to the availability of the contiguous memory block.

## Linked List Allocation

The linked list allocation method overcomes the drawbacks of the contiguous allocation method. In this file allocation method, each file is treated as a linked list of disks blocks. In the linked list allocation method, it is not required that disk blocks assigned to a specific file are in the contiguous order on the disk. The directory entry comprises of a pointer for starting file block and also for the ending file block. Each disk block that is allocated or assigned to a file consists of a pointer, and that pointer points to the next block of the disk, which is allocated to the same file.

### Example of linked list allocation

We can see in the below figure that we have a file named 'jeep.' The value of the start is 9. So, we have to start the allocation from the 9<sup>th</sup> block, and blocks are allocated in a random manner. The value of the end is 25. It means the allocation is finished on the 25<sup>th</sup> block. We can see in the below figure that the block (25) comprised of -1, which means a null pointer, and it will not point to another block.



### Advantages of Linked list allocation

There are various advantages of linked list allocation:

1. In linked list allocation, there is no external fragmentation. Due to this, we can utilize the memory better.
2. In linked list allocation, a directory entry only comprises of the starting block address.
3. The linked allocation method is flexible because we can quickly increase the size of the file because, in this to allocate a file, we do not require a chunk of memory in a contiguous form.


## Disadvantages of Linked list Allocation

There are various disadvantages of linked list allocation:

1. Linked list allocation does not support direct access or random access.
2. In linked list allocation, we need to traverse each block.
3. If the pointer in the linked list break in linked list allocation, then the file gets corrupted.
4. In the disk block for the pointer, it needs some extra space.

## Indexed Allocation

The Indexed allocation method is another method that is used for file allocation. In the index allocation method, we have an additional block, and that block is known as the index block. For each file, there is an individual index block. In the index block, the  $i$ th entry holds the disk address of the  $i$ th file block. We can see in the below figure that the directory entry comprises of the address of the index block.



## **Advantages of Index Allocation**

The advantages of index allocation are:

1. The index allocation method solves the problem of external fragmentation.
2. Index allocation provides direct access.

## **Disadvantages of Index Allocation**

The disadvantages of index allocation are:

1. In index allocation, pointer overhead is more.
2. We can lose the entire file if an index block is not correct.
3. It is totally a wastage to create an index for a small file.

A single index block cannot hold all the pointer for files with large sizes.

To resolve this problem, there are various mechanism which we can use:

1. Linked scheme
2. Multilevel Index
3. Combined Scheme

1. **Linked Scheme:** – In the linked scheme, to hold the pointer, two or more than two index blocks are linked together. Each block contains the address of the next index block or a pointer.
2. **Multilevel Index:** – In the multilevel index, to point the second-level index block, we use a first-level index block that in turn points to the blocks of the disk, occupied by the file. We can extend this up to 3 or more than 3 levels depending on the maximum size of the file.
3. **Combined Scheme:** – In a combined scheme, there is a special block which is called an information node (Inode). The inode comprises of all the information related to the file like authority, name, size, etc. To store the disk block addresses that contain the actual file, the remaining space of inode is used. In inode, the starting pointer is used to point the direct blocks. This means the pointer comprises of the addresses of the disk blocks, which consist of the file data. To indicate the indirect blocks, the next few pointers are used. The indirect blocks are of three types, which are single indirect, double indirect, and triple indirect.

## **Protection in File System:-**

In computer systems, a lot of user's information is stored, the objective of the operating system is to keep safe the data of the user from the improper access to the system. Protection can be provided in number of ways. For a single laptop system, we might provide protection by locking the computer in a desk drawer or file cabinet. For multi-user systems, different mechanisms are used for the protection.

### **Types of Access :**

The files which have direct access of the any user have the need of protection. The files which are not accessible to other users doesn't require any kind of protection. The mechanism of the protection provide the facility of the controlled access by just limiting the types of access to the file. Access can be given or not given to any user depends on several factors, one of which is the type of access required. Several different types of operations can be controlled:

- **Read** – Reading from a file.
- **Write** – Writing or rewriting the file.
- **Execute** – Loading the file and after loading the execution process starts.
- **Append** – Writing the new information to the already existing file, editing must be end at the end of the existing file.
- **Delete** – Deleting the file which is of no use and using its space for the another data.
- **List** – List the name and attributes of the file.

Operations like renaming, editing the existing file, copying; these can also be controlled. There are many protection mechanism. each of them mechanism have different advantages and disadvantages and must be appropriate for the intended application.

### **Access Control :**

There are different methods used by different users to access any file. The general way of protection is to associate *identity-dependent access* with all the files and directories an list called access-control list (ACL) which specify the names of the users and the types of access associate with each of the user. The main problem with the access list is their length. If we want to allow everyone to read a file, we must list all the users with the read access. This technique has two undesirable consequences: Constructing such a list may be tedious and unrewarding task, especially if we do not know in advance the list of the users in the system.



Previously, the entry of the any directory is of the fixed size but now it changes to the variable size which results in the complicates space management. These problems can be resolved by use of a condensed version of the access list. To condense the length of the access-control list, many systems recognize three classification of users in connection with each file:

- **Owner** – Owner is the user who has created the file.
- **Group** – A group is a set of members who has similar needs and they are sharing the same file.
- **Universe** – In the system, all other users are under the category called universe.

The most common recent approach is to combine access-control lists with the normal general owner, group, and universe access control scheme. For example: Solaris uses the three categories of access by default but allows access-control lists to be added to specific files and directories when more fine-grained access control is desired.

### **Other Protection Approaches:**

The access to any system is also controlled by the password. If the use of password are is random and it is changed often, this may be result in limit the effective access to a file. The use of passwords has a few disadvantages:

- The number of passwords are very large so it is difficult to remember the large passwords.
- If one password is used for all the files, then once it is discovered, all files are accessible; protection is on all-or-none basis.

### **Disk scheduling:-**

- As we know, a process needs two type of time, CPU time and IO time. For I/O, it requests the Operating system to access the disk.
- However, the operating system must be fare enough to satisfy each request and at the same time, operating system must maintain the efficiency and speed of process execution.
- The technique that operating system uses to determine the request which is to be satisfied next is called disk scheduling.

Let's discuss some important terms related to disk scheduling.

- **Seek Time** - Seek time is the time taken in locating the disk arm to a specified track where the read/write request will be satisfied.
- **Rotational Latency** - It is the time taken by the desired sector to rotate itself to the position from where it can access the R/W heads.
- **Transfer Time** - It is the time taken to transfer the data.
- **Disk Access Time** - Disk access time is given as,  

$$\text{Disk Access Time} = \text{Rotational Latency} + \text{Seek Time} + \text{Transfer Time}$$
- **Disk Response Time** - It is the average of time spent by each request waiting for the IO operation.
- **Purpose of Disk Scheduling** - The main purpose of disk scheduling algorithm is to select a disk request from the queue of IO requests and decide the schedule when this request will be processed.

### **Goal of Disk Scheduling Algorithm**

- Fairness
- High throughput
- Minimal traveling head time

### **Disk Scheduling Algorithms:-**

- The list of various disks scheduling algorithm is given below. Each algorithm is carrying some advantages and disadvantages. The limitation of each algorithm leads to the evolution of a new algorithm.
- FCFS scheduling algorithm
- SSTF (shortest seek time first) algorithm
- SCAN scheduling
- C-SCAN scheduling
- LOOK Scheduling
- C-LOOK scheduling

### **FCFS Scheduling Algorithm:-**

- It is the simplest Disk Scheduling algorithm. It services the IO requests in the order in which they arrive. There is no starvation in this algorithm, every request is serviced.


### **Disadvantages**

- The scheme does not optimize the seek time.
- The request may come from different processes therefore there is the possibility of inappropriate movement of the head.

**Example:-** Consider the following disk request sequence for a disk with 100 tracks 45, 21, 67, 90, 4, 50, 89, 52, 61, 87, 25 Head pointer starting at 50 and moving in left direction. Find the number of head movements in cylinders using FCFS scheduling.

**Solution:-** Number of cylinders moved by the head

$$\begin{aligned}
 &= (50-45)+(45-21)+(67-21)+(90-67)+(90-4)+(50-4)+(89-50)+(61-52)+(87-61)+(87-25) \\
 &= 5 + 24 + 46 + 23 + 86 + 46 + 49 + 9 + 26 + 62 \\
 &= 376
 \end{aligned}$$



### C-SCAN Algorithm:-

In C-SCAN algorithm, the arm of the disk moves in a particular direction servicing requests until it reaches the last cylinder, then it jumps to the last cylinder of the opposite direction without

servicing any request then it turns back and start moving in that direction servicing the remaining requests.

**Example:** - Consider the following disk request sequence for a disk with 100 tracks 98, 137, 122, 183, 14, 133, 65, 78 Head pointer starting at 54 and moving in left direction. Find the number of head movements in cylinders using C-SCAN scheduling.

**Solution:-** No. of cylinders crossed =  $40 + 14 + 199 + 16 + 46 + 4 + 11 + 24 + 20 + 13 = 387$

