WOODELLO MELAMINE THINNER

WOODELLO™
FACTORIES TO HOMES

High Performance Thinner for Wood Coatings

PRODUCT OVERVIEW

Woodello Melamine Thinner is specially formulated for the dilution of melamine-based wood coating systems. It helps achieve the correct application viscosity, smooth flow, and improved leveling during spray or brush application, ensuring a uniform and high-quality finish on wooden surfaces.

Ideal for:

- Furniture
- Doors & Window Frames
- Cabinets & Wardrobes
- Interior Wooden Panels
- Decorative Wooden Surfaces



PRODUCT CODE - 015

KEY FEATURES

PREMIUM FINISH

QUICK DRY

EASY APPLICATION


COLOURS AVAILABLE



NA

AVAILABLE PACKS

WOODELLO MELAMINE THINNER
1L, 4L & 20L



HOW TO APPLY

SURFACE PREPARATION







SANDING & INSULATING:
Sand the wooden surface along the grain using sandpaper no. 180, followed by 320 or 400 grit to achieve a smooth surface. Wipe the surface to remove loose dust particles.





DENT FILLING:
If the surface has dents or cracks, apply Woodello Wood Filler using a putty knife over the affected area and level the surface properly.





STAINING:
For colouring, apply Woodello Wood Stains for Interiors or Exteriors using the ragging method. Allow the stain to dry for 30–120 minutes before applying further coats.

APPLICATION SYSTEM AND MIXING DETAILS

APPLICATION	CODE	MIXING RATIO OF BASE: HARDENER (BY VOLUME)	THINNER	DILUTION % (BY VOL)
WOODELLO MELAMINE THINNER IN DESIRED PRODUCT AS PER RECOMMENDED RATIO	016	AS PER PRODUCT PIS	WOODELLO MELAMINE THINNER	AS PER PRODUCT PIS

Note:
Use only Woodello Melamine Thinner for dilution of the recommended Woodello Melamine coating systems. Woodello Melamine Thinner should be properly mixed with the coating material in the specified dilution ratio before application. The thinner must not be contaminated with oil, varnish, water, or other local solvents, as this may affect coating performance. Once the container is opened, it is recommended to consume the thinner as early as possible and keep the container tightly closed after use to avoid solvent evaporation and contamination. The recoat period mentioned for coating systems is based on 30°C temperature and 75% relative humidity, which may vary depending on environmental conditions. Recommended spray air pressure: 2.2 – 2.8 kg/cm² for compatible spray applications.

Registered Office: Marudhar Chemicals, G1-42, Boranada Industrial Park, Boranada, Jodhpur, Rajasthan – 342012, India. For feedback or product enquiries, please contact our Customer Care Manager at +91-291-2741060 or email support@marudharchemicals.com. You can also visit our website at www.woodello.in for more information.

Version No. WE01/03/2026. This datasheet supersedes all previous versions. © Marudhar Chemicals. All rights reserved. Terms and conditions apply.
Please refer to the product warranty document for detailed information.

WOODELLO™
FACTORIES TO HOMES

ADDITIONAL INFORMATION

POST APPLICATION CARE

If coating material spills on tiles or metal surfaces, clean immediately using Woodello Melamine Thinner and wipe with a clean cloth. During spraying or brushing, surrounding areas should be properly masked to prevent stains on adjacent surfaces.

PRODUCT SPECIFICATIONS

Drying Time:

- Depends on the coating product used with the thinner.

Flash Point:

- Closed Cup: Approx. 26°C

Shelf Life:

- Up to 18 months from the date of manufacture when stored in original tightly closed containers away from direct sunlight and excessive heat.

APPLICATION RECOMMENDATIONS

For best performance, use Woodello Melamine Thinner with compatible Melamine coating systems at temperatures between 20°C and 40°C and relative humidity below 75%. Do not over-thin the coating material and always follow the recommended dilution ratio. Stir well and strain before use to achieve smooth application and proper finish.

SAFETY INFORMATION

Refer to the Material Safety Data Sheet (MSDS) for detailed handling instructions. Store the product in a cool, well-ventilated area away from heat, sparks, and open flames. Use protective equipment such as gloves, safety goggles, and masks during handling.
Avoid contact with eyes and skin; in case of contact, wash immediately with soap and plenty of water. In case of inhalation, move to fresh air and seek medical attention if discomfort persists.
This product contains no added Lead, Mercury, or Chromium compounds and is flammable. Dispose of leftover material and empty containers responsibly through authorized recycling or waste management agencies

Registered Office: Marudhar Chemicals, G1-42, Boranada Industrial Park, Boranada, Jodhpur, Rajasthan – 342012, India. For feedback or product enquiries, please contact our Customer Care Manager at +91-291-2741060 or email support@marudharchemicals.com. You can also visit our website at www.woodello.in for more information.

Version No. WE01/03/2026. This datasheet supersedes all previous versions. © Marudhar Chemicals. All rights reserved. Terms and conditions apply.
Please refer to the product warranty document for detailed information.