WOODELLO MUTLIPURPOSE THINNER

WOODELLO™
FACTORIES TO HOMES

High Performance Thinner for Wood Coatings

PRODUCT OVERVIEW

Woodello Multipurpose Thinner is specially formulated for efficient thinning and cleaning of NC and Melamine coatings. It ensures excellent flow, smooth application, and quick drying while improving the overall finish quality on wood and metal surfaces.

Ideal for:

- Furniture
- Doors & Window Frames
- Cabinets & Wardrobes
- Interior Wooden Panels
- Decorative Wooden Surfaces



PRODUCT CODE 017

KEY FEATURES

QUICK DRY

UNIFORM FINISH

EASY APPLICATION


COLOURS AVAILABLE



NA

AVAILABLE PACKS

WOODELLO MUTLIPURPOSE THINNER
1L, 4L & 20L



HOW TO APPLY

SURFACE PREPARATION







SANDING & INSULATING:
Sand the wooden surface along the grain using sandpaper no. 180, followed by 320 or 400 grit to achieve a smooth surface. Wipe the surface to remove loose dust particles.





DENT FILLING:
If the surface has dents or cracks, apply Woodello Wood Filler using a putty knife over the affected area and level the surface properly.





STAINING:
For colouring, apply Woodello Wood Stains for Interiors or Exteriors using the ragging method. Allow the stain to dry for 30–120 minutes before applying further coats.

APPLICATION SYSTEM AND MIXING DETAILS

APPLICATION	CODE	MIXING RATIO OF BASE: HARDENER (BY VOLUME)	THINNER	DILUTION % (BY VOL)
WOODELLO MULTIPURPOSE THINNER IN DESIRED PRODUCT AS PER RECOMMENDED RATIO	017	AS PER PRODUCT PIS	WOODELLO MULTIPURPOSE THINNER	AS PER PRODUCT PIS

Note:

- Use only Woodello Multipurpose Thinner for dilution of recommended Woodello coating systems.
- Woodello Multipurpose Thinner should be properly mixed with the coating material in the specified dilution ratio before application.
- The thinner should not be contaminated with oil, varnish, water, or other local solvents, as this may affect coating performance.
- Once the container is opened, it is recommended to consume the thinner as early as possible and keep the container tightly closed after use to avoid solvent evaporation and contamination.
- Recoat period mentioned for coating systems is based on 30°C temperature and 75% relative humidity, which may vary depending on environmental conditions.
- Recommended spray air pressure: 2.2 – 2.8 kg/cm² for compatible spray applications.

Registered Office: Marudhar Chemicals, G1-42, Boranada Industrial Park, Boranada, Jodhpur, Rajasthan – 342012, India. For feedback or product enquiries, please contact our Customer Care Manager at +91-291-2741060 or email support@marudharchemicals.com. You can also visit our website at www.woodello.in for more information.

Version No. WE01/03/2026. This datasheet supersedes all previous versions. © Marudhar Chemicals. All rights reserved. Terms and conditions apply.
Please refer to the product warranty document for detailed information.

WOODELLO™
FACTORIES TO HOMES

ADDITIONAL INFORMATION

POST APPLICATION CARE

Woodello Multipurpose Thinner is specially formulated for thinning NC, lacquer, and melamine coating systems, ensuring proper viscosity, smooth flow, and improved finish quality during application.

PRODUCT SPECIFICATIONS

Drying Time:

- Depends on the coating product used with the thinner.

Flash Point:

- Closed Cup: Approx. 26°C

Shelf Life:

- Up to 18 months from the date of manufacture when stored in original tightly closed containers away from direct sunlight and excessive heat.

APPLICATION RECOMMENDATIONS

For optimum performance, Woodello Multipurpose Thinner should be used at temperatures between 20°C and 40°C with relative humidity below 75%. Do not over-thin the coating material and always follow the recommended dilution ratio for the specific product. Stir well before use and ensure proper mixing with the coating material for best results.

SAFETY INFORMATION

Refer to the Material Safety Data Sheet (MSDS) for detailed safety instructions while handling Woodello Multipurpose Thinner. Store the product in a cool, dry, and well-ventilated area away from heat, sparks, and open flames. Use protective equipment such as rubber gloves, safety goggles, and face masks during handling.
Avoid contact with eyes and skin; in case of contact, wash immediately with soap and plenty of water and seek medical attention if irritation persists.
Do not inhale vapours or ingest the product. In case of inhalation, move to fresh air and seek medical attention if symptoms continue.
This product contains no added Lead, Mercury, or Chromium compounds.
Disposal: Leftover thinner or empty containers should not be disposed of in soil or drains. Consult authorized recycling or waste management agencies for proper disposal.

Registered Office: Marudhar Chemicals, G1-42, Boranada Industrial Park, Boranada, Jodhpur, Rajasthan – 342012, India. For feedback or product enquiries, please contact our Customer Care Manager at +91-291-2741060 or email support@marudharchemicals.com. You can also visit our website at www.woodello.in for more information.

Version No. WE01/03/2026. This datasheet supersedes all previous versions. © Marudhar Chemicals. All rights reserved. Terms and conditions apply.
Please refer to the product warranty document for detailed information.