

Welcome to the new Binance API documentation. [Looking for the previous version?](#)

[Switch to the legacy docs](#)



Feedback

🌟 Ask AI about this page

Market

Endpoint `wss://fstream.binance.com`

Download schema

Aggregate Trade Streams

The Aggregate Trade Streams push market trade information that is aggregated for fills with same price and taking side every 100 milliseconds. Only market trades will be aggregated, which means the insurance fund trades and ADL trades won't be aggregated.

After CM migration, the payload is appended with a new `st` field (`1` = UM, `2` = CM).

WSS `{symbol}@aggTrade`

`wss://fstream.binance.com`

Update Speed **100ms**

Feedback

Stream Parameters

symbol string · required

The symbol parameter

Example: `btcusdt`

Request

You can subscribe to this stream using one of the following options:

Ask AI about this page

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@aggTrade`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@aggTrade`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btcusdt@aggTrade"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Feedback

Responses

Raw Stream

Combined Stream

Aggregate Trade Streams

e string

Event type

Example: `aggTrade`

E integer · int64

Event time

Example: `123456789`

✧ Ask AI about this page

s string

Symbol

Example: `BNBUSDT`

a integer · int64

Aggregate trade ID

Example: `5933014`

p string

Price

Example: `0.001`

q string

Quantity with all the market trades

Example: `100`

nq string

Normal quantity without the trades involving RPI orders

Example: `100`

f integer · int64

First trade ID

Example: `100`

l integer · int64

Last trade ID

Example: `105`

T integer · int64

Trade time

Example: `123456785`

m boolean

Is the buyer the market maker?

Example: `true`

✧ Ask AI about this page

Feedback

Example: `1`

`st` integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: `1`

- Retail Price Improvement(RPI) orders are aggregated into field `q` and without special tags to be distinguished.

WSS `{symbol}`@aggTrade

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@aggTrade"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@aggTrade"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

json

application/json

Feedback

Example Responses

Raw Stream

```
{
  "e": "aggTrade",
  "E": 123456789,
  "s": "BNBUSDT",
  "a": 5933014,
  "p": "0.001",
  "q": "100",
}
```

json

The All Liquidation Order Snapshot Streams push force liquidation order information for all symbols in the market. For each symbol, only the latest one liquidation order within 1000ms will be pushed as the snapshot. If no liquidation happens in the interval of 1000ms, no stream will be pushed.

After CM migration, this stream pushes the merged UM + CM universe (subscribable on both fstream and dstream); each payload is appended with a new st field (1 = UM, 2 = CM) and a new ps field (pair symbol).

WSS

!forceOrder@arr

wss://fstream.binance.com

Update Speed 1000ms

Request

You can subscribe to this stream using one of the following options:

- Raw stream: wss://fstream.binance.com/market/ws/!forceOrder@arr
- Combined stream via URL: wss://fstream.binance.com/market/stream?streams=!forceOrder@arr
- Combined stream via request: Connect to wss://fstream.binance.com/market/stream, then send the SUBSCRIBE request shown below.

Feedback

method string · enum · required

WebSocket Streams method name.

Enum values: SUBSCRIBE

Example: SUBSCRIBE

params string[] · required

List of streams to subscribe to.

Example: ["!forceOrder@arr"]

Ask AI about this page

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

All Market Liquidation Order Streams

e string

Event Type

Example: `forceOrder`

E integer · int64

Event Time

Example: `1568014460893`

o object

Order Type

Order Type

s string

Symbol

Example: `BTCUSDT`

S string

Side

Example: `SELL`

o string

Order Type

Feedback

✧ Ask AI about this page

Order type

Example: `LIMIT`

f string

Time in Force

Example: `IOC`

q string

Original Quantity

Example: `0.014`

p string

Price

Example: `9910`

ap string

Average Price

Example: `9910`

X string

Order Status

Example: `FILLED`

l string

Order Last Filled Quantity

Example: `0.014`

z string

Order Filled Accumulated Quantity

Example: `0.014`

T integer · int64

Order Trade Time

Example: `1568014460893`

🌟 Ask AI about this page

Feedback

ps string

(After CM migration) Pair symbol

Example: `BTCUSDT`

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: `1`

WSS `!forceOrder@arr`

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "!forceOrder@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "!forceOrder@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

`application/json`

Feedback

Example Responses

Raw Stream

All Market Mini Tickers Stream

Ask AI about this page

24hr rolling window mini-ticker statistics for all symbols. These are NOT the statistics of the

24hr rolling window mini-ticker statistics for all symbols. These are NOT the statistics of the UTC day, but a 24hr rolling window from requestTime to 24hrs before. Note that only tickers that have changed will be present in the array.

After CM migration, this stream pushes the merged UM + CM universe (subscribable on both `fstream` and `dstream`); each payload is appended with a new `st` field (`1` = UM, `2` = CM) and a new `ps` field (pair symbol).

WSS `!miniTicker@arr`

`wss://fstream.binance.com`

Update Speed **1000ms**

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/!miniTicker@arr`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams=!miniTicker@arr`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

Feedback

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `[ "!miniTicker@arr" ]`

🌟 Ask AI about this page

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

All Market Mini Tickers Stream

object

e string

Event type

Example: `24hrMiniTicker`

E integer · int64

Event time

Example: `123456789`

s string

Symbol

Example: `BNBUSDT`

c string

Close price

Example: `0.0025`

o string

Open price

Example: `0.0010`

h string

High price

🌟 Ask AI about this page

Feedback

High price

Example: `0.0025`

l string

Low price

Example: `0.0010`

v string

Total traded base asset volume

Example: `10000`

q string

Total traded quote asset volume

Example: `18`

ps string

(After CM migration) Pair symbol

Example: `BTCUSDT`

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: `1`

Feedback

WSS !miniTicker@arr

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "!miniTicker@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "!miniTicker@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

🌟 Ask AI about this page

```
  ],  
  "id": "e9d6b4349871b40611412680b3445fac"  
}
```

application/json

Example Responses

Raw Stream

json

```
[  
  {  
    "e": "24hrMiniTicker",  
    "E": 123456789,  
    "s": "BNBUSDT",  
    "c": "0.0025",  
    "o": "0.0010",
```

All Market Tickers Streams

24hr rolling window ticker statistics for all symbols. These are NOT the statistics of the UTC day, but a 24hr rolling window from requestTime to 24hrs before. Note that only tickers that have changed will be present in the array.

After CM migration, this stream pushes the merged UM + CM universe (subscribable on both `fstream` and `dstream`); each payload is appended with a new `st` field (1 = UM, 2 = CM) and a new `ps` field (pair symbol).

Feedback

`WSS` !ticker@arr

wss://fstream.binance.com

Update Speed 1000ms

Request

You can subscribe to this stream using one of the following options:

- Raw stream: `wss://fstream.binance.com/market/ws/!ticker@arr`

☆ Ask AI about this page

- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams=!ticker@arr`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["!ticker@arr"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

All Market Tickers Streams

object

e string

Event type

Example: `24hrTicker`

E integer · int64

Event time

Example: `123456789`

🌟 Ask AI about this page

Feedback

s string

Symbol

Example: `BNBUSDT`

p string

Price change

Example: `0.0015`

P string

Price change percent

Example: `250.00`

w string

Weighted average price

Example: `0.0018`

c string

Last price

Example: `0.0025`

Q string

Last quantity

Example: `10`

o string

Open price

Example: `0.0010`

h string

High price

Example: `0.0025`

l string

Low price

🌟 Ask AI about this page

Feedback

Low price

Example: 0.0010

v string

Total traded base asset volume

Example: 10000

q string

Total traded quote asset volume

Example: 18

O integer · int64

Statistics open time

Example: 0

C integer · int64

Statistics close time

Example: 86400000

F integer · int64

First trade ID

Example: 0

L integer · int64

Last trade Id

Example: 18150

n integer · int64

Total number of trades

Example: 18151

ps string

(After CM migration) Pair symbol

Example: BTCUSDT

✧ Ask AI about this page

Feedback

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: 1

WSS !ticker@arr

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "!ticker@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "!ticker@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

Example Responses

Raw Stream

Feedback

Composite Index Symbol Information Streams

Composite index information for index symbols pushed every second.

WSS

{symbol}@compositeIndex

Ask AI about this page

wss://fstream.binance.com

Update Speed **1000ms**

Stream Parameters

symbol string · **required**

The symbol parameter

Example: `btcusdt`

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@compositeIndex`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@compositeIndex`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btcusdt@compositeIndex"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

🔮 Ask AI about this page

Feedback

Responses

Raw Stream

Combined Stream

Composite Index Symbol Information Streams

e string

Event type

Example: `compositeIndex`

E integer · int64

Event time

Example: `1602310596000`

s string

Symbol

Example: `DEFIUSDT`

p string

Price

Example: `554.41604065`

C string

Base asset category.

Example: `baseAsset`

c object[]

Composition

b string

Base asset

Example: `BAL`

✧ Ask AI about this page

Feedback

q string

Quote asset

Example: `USDT`

w string

Weight in quantity

Example: `1.04884844`

W string

Weight in percentage

Example: `0.01457800`

i string

Index price

Example: `24.33521021`

WSS `{symbol}@compositeIndex`

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@compositeIndex"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Feedback

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@compositeIndex"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

Example Responses

🌟 Ask AI about this page

Raw Stream

Continuous Contract Kline/Candlestick Streams

Continuous Contract Kline/Candlestick Streams

After CM migration, both `fstream` and `dstream` may subscribe to either UM or CM symbols on this stream.

WSS `{pair}_{contractType}@continuousKline_{interval}`

wss://fstream.binance.com

Update Speed **250ms**

Stream Parameters

pair string · required

Example: `btcusdt`

contractType string · enum · required

Enum values: `perpetual` `current_quarter` `next_quarter` `tradifi_perpetual`

Example: `next_quarter`

interval string · enum · required

Enum values: `1s` `1m` `3m` `5m` `15m` `30m` `1h` `2h` [show 8 more](#)

Example: `1m`

Feedback

🌟 Ask AI about this page

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{pair}_{contractType}@continuousKline_{interval}`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={pair}_{contractType}@continuousKline_{interval}`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btcusdt_next_quarter@continuousKline_1m"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Feedback

Responses

- Raw Stream
- Combined Stream

Continuous Contract Kline/Candlestick Streams

e string

Event type

Example: `continuous_kline`

Ask AI about this page

E integer · int64

Event time

Example: 1607443058651

ps string

Pair

Example: BTCUSDT

ct string

Contract type

Example: PERPETUAL

k object

Kline payload.

Kline payload.

t integer · int64

Kline start time

Example: 1607443020000

T integer · int64

Kline close time

Example: 1607443079999

i string

Interval

Example: 1m

f integer · int64

First updateId

Example: 116467658886

L integer · int64

🌟 Ask AI about this page

Feedback

Last updateId

Example: 116468012423

o string

Open price

Example: 18787.00

c string

Close price

Example: 18804.04

h string

High price

Example: 18804.04

l string

Low price

Example: 18786.54

v string

volume

Example: 197.664

n integer · int64

Number of trades

Example: 543

x boolean

Is this kline closed?

Example: false

q string

Quote asset volume

Example: 3715253.19494

🌟 Ask AI about this page

Feedback

V string

Taker buy volume

Example: 184.769

Q string

Taker buy quote asset volume

Example: 3472925.84746

B string

Ignore

Example: 0

WSS {pair} _{contractType} @continuousKline_{interval}

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt_next_quarter@continuousKline_1m"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt_next_quarter@continuousKline_1m"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

Feedback

Example Responses

Raw Stream

🌟 Ask AI about this page

Contract Info Stream

ContractInfo stream pushes when contract info updates(listing/settlement/contract bracket update). bks field only shows up when bracket gets updated.

After CM migration, this stream pushes the merged UM + CM universe (subscribable on both fstream and dstream); each payload is appended with a new st field (1 = UM, 2 = CM).

WSS

!contractInfo

wss://fstream.binance.com

Update Speed

Real-time

Request

You can subscribe to this stream using one of the following options:

- Raw stream: wss://fstream.binance.com/market/ws/!contractInfo
- Combined stream via URL: wss://fstream.binance.com/market/stream?streams=!contractInfo
- Combined stream via request: Connect to wss://fstream.binance.com/market/stream, then send the SUBSCRIBE request shown below.

method string · enum · required
WebSocket Streams method name.
Enum values: SUBSCRIBE
Example: SUBSCRIBE
params string[] · required

🌟 Ask AI about this page

Feedback

params string **required**

List of streams to subscribe to.

Example: ["!contractInfo"]

id string **required**

Unique WebSocket request ID.

Example: e9d6b4349871b40611412680b3445fac

Responses

Raw Stream

Combined Stream

Contract Info Stream

e string

Event type.

Example: contractInfo

E integer · int64

Event time.

Example: 1669356423908

s string

Symbol.

Example: IOTAUSDT

ct string

Contract type.

Example: PERPETUAL

dt integer · int64

Delivery date time.

Example: 4133404800000

dt integer · int64

Feedback

🌟 Ask AI about this page

ot integer · int64

Onboard date time.

Example: `1569398400000`

cs string

Contract status.

Example: `TRADING`

bks object[]

Notional bracket updates.

bs integer · int64

Notional bracket

Example: `1`

bnf integer · int64

Floor notional of this bracket

Example: `0`

bnc integer · int64

Cap notional of this bracket

Example: `5000`

mmr number · float

Maintenance ratio for this bracket

Example: `0.01`

cf integer · int64

Auxiliary number for quick calculation

Example: `0`

ml integer · int64

Min leverage for this bracket

Example: `21`

🌟 Ask AI about this page

Feedback

ma integer · int64

Max leverage for this bracket

Example: **50**

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: **1**

WSS !contractInfo

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "!contractInfo"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "!contractInfo"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

Feedback

Example Responses

Raw Stream

Individual Symbol Mini Ticker Stream

24hr rolling window mini-ticker statistics for a single symbol. These are NOT the statistics of the UTC day, but a 24hr rolling window from requestTime to 24hrs before.

After CM migration, the payload is appended with a new `st` field (`1` = UM, `2` = CM) and a new `ps` field (pair symbol).

`WSS` `{symbol}@miniTicker`

`wss://fstream.binance.com`

Update Speed `2s`

Stream Parameters

`symbol` string · required

The symbol parameter

Example: `btcusdt`

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@miniTicker`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@miniTicker`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

`method` string · enum · required

WebSocket Streams method name. [Ask AI about this page](#)

Enum values: `SUBSCRIBE`

Feedback

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btcusdt@miniTicker"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

Individual Symbol Mini Ticker Stream

e string

Event type

Example: `24hrMiniTicker`

E integer · int64

Event time

Example: `123456789`

s string

Symbol

Example: `BNBUSDT`

c string

Close price

Example: `0.0025`

o string

Open price

Feedback

✧ Ask AI about this page

Example: `0.0010`

h string

High price

Example: `0.0025`

l string

Low price

Example: `0.0010`

v string

Total traded base asset volume

Example: `10000`

q string

Total traded quote asset volume

Example: `18`

ps string

(After CM migration) Pair symbol

Example: `BTCUSDT`

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: `1`

Feedback

WSS `{symbol}@miniTicker`

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@miniTicker"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

✧ Ask AI about this page


```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@miniTicker"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

Example Responses

Raw Stream

```
{
  "e": "24hrMiniTicker",
  "E": 123456789,
  "s": "BNBUSDT",
  "c": "0.0025",
  "o": "0.0010",
  "h": "0.0025",

```

Individual Symbol Ticker Streams

24hr rolling window ticker statistics for a single symbol. These are NOT the statistics of the UTC day, but a 24hr rolling window from requestTime to 24hrs before.

After CM migration, the payload is appended with a new `st` field (1 = UM, 2 = CM) and a new `ps` field (pair symbol).

Feedback

WSS

`{symbol}@ticker`

wss://fstream.binance.com

Update Speed 2000ms

Stream Parameters

symbol

string · required

The symbol parameter

Ask AI about this page

Example: `btcusdt`

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@ticker`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@ticker`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**
WebSocket Streams method name.
Enum values: `SUBSCRIBE`
Example: `SUBSCRIBE`

params string[] · **required**
List of streams to subscribe to.
Example: `["btcusdt@ticker"]`

id string · **required**
Unique WebSocket request ID.
Example: `e9d6b4349871b40611412680b3445fac`

Feedback

Responses

`Raw Stream` `Combined Stream`

Individual Symbol Ticker Streams

🌟 Ask AI about this page

`e` string

Event type

Example: `24hrTicker`

E integer · int64

Event time

Example: `123456789`

s string

Symbol

Example: `BNBUSDT`

p string

Price change

Example: `0.0015`

P string

Price change percent

Example: `250.00`

w string

Weighted average price

Example: `0.0018`

c string

Last price

Example: `0.0025`

Q string

Last quantity

Example: `10`

o string

Open price

Example: `0.0010`

Feedback

✧ Ask AI about this page

h string

High price

Example: `0.0025`

l string

Low price

Example: `0.0010`

v string

Total traded base asset volume

Example: `10000`

q string

Total traded quote asset volume

Example: `18`

O integer · int64

Statistics open time

Example: `0`

C integer · int64

Statistics close time

Example: `86400000`

F integer · int64

First trade ID

Example: `0`

L integer · int64

Last trade Id

Example: `18150`

n integer · int64

Total number of trades

✧ Ask AI about this page

Feedback

Example: `18151`

ps string

(After CM migration) Pair symbol

Example: `BTCUSDT`

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: `1`

WSS `{symbol}@ticker`

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@ticker"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@ticker"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

json

`application/json`

Feedback

Example Responses

Raw Stream

🌟 Ask AI about this page

Kline/Candlestick Streams

The Kline/Candlestick Stream push updates to the current klines/candlestick every 250 milliseconds (if existing).

After CM migration, both `fstream` and `dstream` may subscribe to either UM or CM symbols on this stream.

WSS `{symbol}@kline_{interval}`

wss://fstream.binance.com

Update Speed **250ms**

Stream Parameters

symbol string · required

The symbol parameter

Example: `btccusdt`

interval string · enum · required

The interval parameter

Enum values: `1m` `3m` `5m` `15m` `30m` `1h` `2h` `4h` [show 7 more](#)

Example: `1m`

Feedback

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@kline_{interval}`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@kline_{interval}`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/`

Combined stream via request connect to `ws://stream.binance.com:80/market/`
`stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btcusdt@kline_1m"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

Kline/Candlestick Streams

e string

Event type

Example: `kline`

E integer · int64

Event time

Example: `1638747660000`

s string

Symbol

Example: `BTCUSDT`

✧ Ask AI about this page

Feedback

k object

Kline payload.

Kline payload.

t integer · int64

Kline start time

Example: 1638747660000

T integer · int64

Kline close time

Example: 1638747719999

s string

Symbol

Example: BTCUSDT

i string

Interval

Example: 1m

f integer · int64

First trade ID

Example: 100

L integer · int64

Last trade ID

Example: 200

o string

Open price

Example: 0.0010

c string

Close price

✧ Ask AI about this page

Feedback

Example: `0.0020`

h string

High price

Example: `0.0025`

l string

Low price

Example: `0.0015`

v string

Base asset volume

Example: `1000`

n integer · int64

Number of trades

Example: `100`

x boolean

Is this kline closed?

Example: `false`

q string

Quote asset volume

Example: `1.0000`

V string

Taker buy base asset volume

Example: `500`

Q string

Taker buy quote asset volume

Example: `0.500`

R string

✧ Ask AI about this page

Feedback

Ignore

Example: 123456

WSS {symbol}@kline_{interval}

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@kline_1m"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

json

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@kline_1m"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

Example Responses

Raw Stream

Feedback

Liquidation Order Streams

The Liquidation Order Snapshot Streams push force liquidation order information for specific symbol. For each symbol, only the latest one liquidation order within 1000ms will be pushed as the snapshot. If no liquidation happens in the interval of 1000ms, no stream will be pushed.

[Ask AI about this page](#)

wss {symbol}@forceOrder

wss://fstream.binance.com

Update Speed **1000ms**

Stream Parameters

symbol string · **required**

The symbol parameter

Example: `btccusdt`

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@forceOrder`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@forceOrder`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

Feedback

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btccusdt@forceOrder"]`

id string · **required**

✧ Ask AI about this page

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

Liquidation Order Streams

e string

Event Type

Example: `forceOrder`

E integer · int64

Event Time

Example: `1568014460893`

o object

Order Type

Order Type

s string

Symbol

Example: `BTCUSDT`

S string

Side

Example: `SELL`

o string

Order Type

Example: `LIMIT`

Feedback

🌟 Ask AI about this page

f string

Time in Force

Example: `IOC`

q string

Original Quantity

Example: `0.014`

p string

Price

Example: `9910`

ap string

Average Price

Example: `9910`

X string

Order Status

Example: `FILLED`

l string

Order Last Filled Quantity

Example: `0.014`

z string

Order Filled Accumulated Quantity

Example: `0.014`

T integer · int64

Order Trade Time

Example: `1568014460893`

Feedback

WSS `{symbol}@forceOrder`

🌟 Ask AI about this page

Shell

```
wscat -C wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@forceOrder"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@forceOrder"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

json

application/json

Example Responses

Raw Stream

Feedback

Mark Price Stream

Mark price and funding rate for a single symbol pushed every 3 seconds or every second.

After CM migration, the payload is appended with a new `st` field (`1` = UM, `2` = CM); both `fstream` and `dstream` may subscribe to either UM or CM symbols on this stream.

WSS `{symbol}@markPrice@{updateSpeed}`

`wss://fstream.binance.com`

🌟 Ask AI about this page

Stream Parameters

symbol string · **required**

The symbol parameter

Example: `btcusdt`

updateSpeed string · enum

WebSocket stream update speed

Enum values: `1s`

Example: `1s`

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/{symbol}@markPrice@{updateSpeed}`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams={symbol}@markPrice@{updateSpeed}`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

Feedback

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["btcusdt@markPrice@1s"]`

id string · **required**

Unique WebSocket request ID

✧ Ask AI about this page

Unique websocket request id.

Example: `e9d6b4349871b40611412680b3445fac`

Responses

Raw Stream

Combined Stream

Mark Price Stream

e string

Event type

Example: `markPriceUpdate`

E integer · int64

Event time

Example: `1562305380000`

s string

Symbol

Example: `BTCUSDT`

p string

Mark price

Example: `11794.15000000`

i string

Index price

Example: `11784.62659091`

P string

Estimated Settle Price, only useful in the last hour before the settlement starts

Example: `11784.25641265`

r string

✧ Ask AI about this page

Feedback

Funding rate

Example: 0.00038167

ap string

Mark price moving average

Example: 11794.15000000

T integer · int64

Next funding time

Example: 1562306400000

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: 1

WSS {symbol}@markPrice@{updateSpeed}

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@markPrice@1s"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Feedback

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "btcusdt@markPrice@1s"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

json

application/json

Example Responses

Raw Stream

```
{
  "e": "markPriceUpdate",
  "E": 1562305380000,
  "s": "BTCUSDT",
  "p": "11794.15000000",
```

json

🌟 Ask AI about this page

```
"i": "11784.62659091",  
"P": "11784.25641265",
```

Mark Price Stream for All market

Mark price and funding rate for all symbols pushed every 3 seconds or every second.

Note:

- TradFi symbols will be pushed through a separate message.

After CM migration, the payload is appended with a new `st` field (`1` = UM, `2` = CM); both `fstream` and `dstream` may subscribe to either UM or CM symbols on this stream.

`WSS` `!markPrice@arr@{updateSpeed}`

`wss://fstream.binance.com`

Update Speed `3s` or `1s`

Feedback

Stream Parameters

`updateSpeed` string · enum

WebSocket stream update speed

Enum values: `1s`

Example: `1s`

Request

You can subscribe to this stream using one of the following options:

🌟 Ask AI about this page

- Raw stream:** `wss://fstream.binance.com/market/ws/!markPrice@arr@{updateSpeed}`

- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams=!markPrice@arr@{updateSpeed}`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["!markPrice@arr@1s"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Feedback

Responses

Raw Stream

Combined Stream

Mark Price Stream for All market

object

e string

Event type

Example: `markPriceUpdate`

E integer · int64

Event time

🌟 Ask AI about this page

Example: `1562305380000`

s string

Symbol

Example: `BTCUSDT`

p string

Mark price

Example: `11185.87786614`

i string

Index price

Example: `11784.62659091`

P string

Estimated Settle Price, only useful in the last hour before the settlement starts

Example: `11784.25641265`

r string

Funding rate

Example: `0.00030000`

ap string

Mark price moving average

Example: `11185.87786614`

T integer · int64

Next funding time

Example: `1562306400000`

st integer

(After CM migration) Symbol type: 1 = UM, 2 = CM

Example: `1`

Feedback

🌟 Ask AI about this page

WSS !markPrice@arr@{updateSpeed}

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "!markPrice@arr@1s"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "!markPrice@arr@1s"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

application/json

json

Example Responses

Raw Stream

```
[
  {
    "e": "markPriceUpdate",
    "E": 1562305380000,
    "s": "BTCUSDT",
    "p": "11185.87786614",
    "i": "11784.62659091",
```

json

Feedback

Multi-Assets Mode Asset Index

Asset index price. Subscribe with `!assetIndex@arr` for all assets, or `<assetSymbol>@assetIndex` for a specific asset.

CM-UM Integration (Effective 2026-06-30): Renamed from *Multi-Assets Mode Asset Index*. The stream `!assetIndex@arr` now additionally pushes COIN-M settlement-asset price index entries (e.g., `BTCUSD`, `ETHUSD`, `BNBUSD`). The on-the-wire stream key is unchanged; existing subscriptions continue to work.

🌟 Ask AI about this page

WSS

!assetIndex@arr

wss://fstream.binance.com

Update Speed 1s

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/!assetIndex@arr`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams=!assetIndex@arr`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `[ "!assetIndex@arr" ]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Feedback

Responses

🌟 Ask AI about this page

Raw Stream

Combined Stream

Multi-Assets Mode Asset Index

object

e string

Event type.

Example: `assetIndexUpdate`**E** integer · int64

Event time.

Example: `1686749230000`**s** string

Asset index symbol.

Example: `ADAUSD`**i** string

Index price.

Example: `0.27462452`**b** string

Bid buffer.

Example: `0.10000000`**a** string

Ask buffer.

Example: `0.10000000`**B** string

Bid rate.

Example: `0.24716207`**A** string

Ask rate.

✧ Ask AI about this page

Feedback

Example: `0.30208698`

q string

Auto exchange bid buffer.

Example: `0.05000000`

g string

Auto exchange ask buffer.

Example: `0.05000000`

Q string

Auto exchange bid rate.

Example: `0.26089330`

G string

Auto exchange ask rate.

Example: `0.28835575`

WSS `!assetIndex@arr`

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "!assetIndex@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Feedback

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "!assetIndex@arr"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

json

application/json

✦ Ask AI about this page

Example Responses

Raw Stream

Trading Session Stream

Trading session information for the underlying assets of TradFi Perpetual contracts, covering the U.S. equity market, Korean equity market, Hong Kong equity market, China equity market, and the commodity market, is updated every second. Trading session information for different underlying markets is pushed in separate messages.

Event type:

- `EquityUpdate`: Session types for the U.S. equity market include "PRE_MARKET", "REGULAR", "AFTER_MARKET", "OVERNIGHT", and "NO_TRADING".
- `CommodityUpdate`: Session types for the commodity market include "REGULAR" and "NO_TRADING".
- `KR_EquityUpdate`: Session types for the Korean equity market include "REGULAR" and "NO_TRADING".
- `HK_EquityUpdate`: Session types for the Hong Kong equity market include "REGULAR" and "NO_TRADING".
- `CN_EquityUpdate`: Session types for the China equity market include "REGULAR" and "NO_TRADING".

Feedback

WSS tradingSession

wss://fstream.binance.com

Update Speed **1s**

🌟 Ask AI about this page

Request

You can subscribe to this stream using one of the following options:

- **Raw stream:** `wss://fstream.binance.com/market/ws/tradingSession`
- **Combined stream via URL:** `wss://fstream.binance.com/market/stream?streams=tradingSession`
- **Combined stream via request:** Connect to `wss://fstream.binance.com/market/stream`, then send the **SUBSCRIBE** request shown below.

method string · enum · **required**

WebSocket Streams method name.

Enum values: `SUBSCRIBE`

Example: `SUBSCRIBE`

params string[] · **required**

List of streams to subscribe to.

Example: `["tradingSession"]`

id string · **required**

Unique WebSocket request ID.

Example: `e9d6b4349871b40611412680b3445fac`

Feedback

Responses

Raw Stream

Combined Stream

Trading Session Stream

e string

Event type, can also be CommodityUpdate, KR_EquityUpdate, HK_EquityUpdate or CN_EquityUpdate

Example: `EquityUpdate`

Ask AI about this page

E integer · int64

Event time

Example: 1765244143062

t integer · int64

Session start time

Example: 1765242000000

T integer · int64

Session end time

Example: 1765270800000

S string

Session type

Example: OVERNIGHT

WSS tradingSession

Shell

```
wscat -c wss://fstream.binance.com/market/stream -x '{
  "method": "SUBSCRIBE",
  "params": [
    "tradingSession"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}' -w 30
```

Feedback

Example Request

```
{
  "method": "SUBSCRIBE",
  "params": [
    "tradingSession"
  ],
  "id": "e9d6b4349871b40611412680b3445fac"
}
```

json

application/json

Example Responses

Ask AI about this page

Raw Stream

```
{
```

json

```
{
  "e": "EquityUpdate",
  "E": 1765244143062,
  "t": 1765242000000,
  "T": 1765270800000,
  "S": "OVERNIGHT"
}
```

Resources

[Announcements](#)
[Terms](#)
[Privacy](#)

Support

[24/7 Chat Support](#)
[Support Center](#)
[Product Feedback](#)
[Fees](#)

Agent Native

[llms.txt](#)
[llms-full.txt](#)
[Agent Native](#)



© 2026 Binance.com. All rights reserved.

Feedback

✦ Ask AI about this page