hidemydoppler — Audacity helpers

Two Nyquist plug-ins that find aircraft flyovers in a recording. They flag or duck the flyover so you know where to run the full privacy pass; they do **not** measure the Doppler curve.

Install

1. Copy both `.ny` files into Audacity's **Plug-Ins** folder: - Windows: `C:\Program Files\Audacity\Plug-Ins` - macOS: `~/Library/Application Support/audacity/Plug-Ins` - Linux: `~/.audacity-files/plug-ins` or `/usr/share/audacity/plug-ins`
2. Audacity → **Tools ▸ Noise Reduction and Repair / Add Plug-ins** (or **Tools ▸ Manage Plug-ins…** on older builds), enable both, restart.

Use

- **Analyze ▸ Label Jet Flyovers** — adds a label track with one `flyover` region per detected pass. Nothing is changed; use it to see where they are.
- **Effect ▸ Jet Flyover Suppressor** — ducks the level during each detected flyover. Broadband, so it dims everything while the jet passes; start gentle.

How detection works

A flyover is a **swell** of low-frequency energy. Each plug-in measures the low band (below the split frequency) in 100 ms blocks, takes the clip's median low-band level as "normal", and flags blocks that rise a set number of dB above that baseline and stay there long enough. Steady low tones (a bass note, a droning fan) raise the baseline too, so they don't trip it — only departures do.

Controls

- **Flyover sensitivity (dB above baseline)** — lower = more sensitive. Default 4.
- **Minimum flyover length (s)** — ignore short low-frequency blips. Default 2 (labeller).
- **Low/high split frequency (Hz)** — where the "low band" ends. Default 500; drop toward 150–250 if voices are triggering it.
- **Reduction (dB)** / **Fade in/out (s)** — suppressor only.

Tune on real audio; the defaults are a starting point, not a guarantee.