Lab Assignment 4
Network and Communication

Name: Kulvir Singh
Reg. No.: 19BCE2074

Question 1:

Client Server Communication using UDP

Aim :

To implement the client server communication using UDP protocol in linux environment.

Algorithm :

UDP Server :
1.Create UDP socket.
2.Bind the socket to server address.
3.Wait until datagram packet arrives from client.
4.Process the datagram packet and send a reply to client.
5.Go back to Step 3.
UDP Client :
1.Create UDP socket.
2.Send message to server.
3.Wait until response from server is recieved.
4.Process reply and go back to step 2, if necessary.
5.Close socket descriptor and exit.

Code Text :

Server.c

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <arpa/inet.h>
#include <netinet/in.h>
#define PORT     8080
```

```
#define MAXLINE 1024
int main() {
	int sockfd;
	char buffer[MAXLINE];
	char *hello = "Hello from server";
	struct sockaddr_in servaddr, cliaddr;

	// Creating socket file descriptor
	if ( (sockfd = socket(AF_INET, SOCK_DGRAM, 0)) < 0 ) {
		perror("socket creation failed");
		exit(EXIT_FAILURE);
	}

	memset(&servaddr, 0, sizeof(servaddr));
	memset(&cliaddr, 0, sizeof(cliaddr));

	// Filling server information
	servaddr.sin_family = AF_INET; // IPv4
	servaddr.sin_addr.s_addr = INADDR_ANY;
	servaddr.sin_port = htons(PORT);

	// Bind the socket with the server address
	if ( bind(sockfd, (const struct sockaddr *)&servaddr,
			sizeof(servaddr)) < 0 )
	{
		perror("bind failed");
		exit(EXIT_FAILURE);
	}

	int len, n;

	len = sizeof(cliaddr); //len is value/resuslt

	n = recvfrom(sockfd, (char *)buffer, MAXLINE,
					MSG_WAITALL, ( struct sockaddr *) &cliaddr,
					&len);
	buffer[n] = '\0';
	printf("Client : %s\n", buffer);
	sendto(sockfd, (const char *)hello, strlen(hello),
		MSG_CONFIRM, (const struct sockaddr *) &cliaddr,
			len);
	printf("Hello message sent.\n");

	return 0;
}
```

Client.c

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <arpa/inet.h>
#include <netinet/in.h>
#define PORT     8080
#define MAXLINE 1024
int main() {
	int sockfd;
	char buffer[MAXLINE];
	char *hello = "Hello from client";
	struct sockaddr_in	servaddr;

	// Creating socket file descriptor
	if ( (sockfd = socket(AF_INET, SOCK_DGRAM, 0)) < 0 ) {
		perror("socket creation failed");
		exit(EXIT_FAILURE);
	}

	memset(&servaddr, 0, sizeof(servaddr));

	// Filling server information
	servaddr.sin_family = AF_INET;
	servaddr.sin_port = htons(PORT);
	servaddr.sin_addr.s_addr = INADDR_ANY;

	int n, len;

	sendto(sockfd, (const char *)hello, strlen(hello),
		MSG_CONFIRM, (const struct sockaddr *) &servaddr,
			sizeof(servaddr));
	printf("Hello message sent.\n");

	n = recvfrom(sockfd, (char *)buffer, MAXLINE,
					MSG_WAITALL, (struct sockaddr *) &servaddr,
					&len);
	buffer[n] = '\0';
	printf("Server : %s\n", buffer);

	close(sockfd);
	return 0;
}
```

Output Screenshots :

Server:



Client:



Question 2:

CHAT Application Using TCP

Aim :

To implement a chat application using TCP protocol in linux environment

Algorithm :

TCP Server –

using create(), Create TCP socket.

using bind(), Bind the socket to server address.

using listen(), put the server socket in a passive mode, where it waits for the client to approach the server to make a connection

using accept(), At this point, connection is established between client and server, and they are ready to transfer data.

Go back to Step 3.

TCP Client –

Create TCP socket.

connect newly created client socket to server.

Code Text :

Server.c

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
void error(const char *msg)
{
perror(msg);
exit(1);
}
int main(int argc, char *argv[])
{
   int socket1, newsocket1, portNum;
   socklen_t clilen;
   char buffer[255];
   struct sockaddr_in serv_addr, cli_addr;
   int n;
   if (argc < 2) {
   fprintf(stderr,"ERROR, port not given\n");
   exit(1);
   }
   socket1 = socket(AF_INET, SOCK_STREAM, 0);
   if (socket1 < 0)
   error("ERROR can't open socket");
   bzero((char *) &serv_addr, sizeof(serv_addr));
   portNum = atoi(argv[1]);

   serv_addr.sin_family = AF_INET;
   serv_addr.sin_addr.s_addr = INADDR_ANY;
   serv_addr.sin_port = htons(portNum);
   if (bind(socket1, (struct sockaddr *) &serv_addr,
   sizeof(serv_addr)) < 0)
   error("ERROR can't bind");
```

```
   listen(socket1,5);
   clilen = sizeof(cli_addr);
   newsocket1 = accept(socket1,
   (struct sockaddr *) &cli_addr,
   &clilen);
   if (newsocket1 < 0)
   error("ERROR can't accept");
   while(1)
   {
   bzero(buffer,255);
   n = read(newsocket1,buffer,255);
   if (n < 0) error("ERROR ,can't read");
   printf("Client: %s\n",buffer);
   bzero(buffer,255);
   fgets(buffer,255,stdin);
   n = write(newsocket1,buffer,strlen(buffer));
   if (n < 0) error("ERROR ,can't write");
   int i=strncmp("Goodbye" , buffer, 7);
   if(i == 0)
   break;
   }
   close(newsocket1);
   close(socket1);
   return 0;
}
```

Client.c

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netdb.h>
void error(const char *msg)
{
perror(msg);
exit(0);
}
int main(int argc, char *argv[])
```

```
{
int socket1, portnum, n;
struct sockaddr_in serv_addr;
struct hostent *server;
char buffer[256];
if (argc < 3) {
fprintf(stderr,"usage %s hostname port\n", argv[0]);
exit(0);
}
portnum = atoi(argv[2]);
socket1 = socket(AF_INET, SOCK_STREAM, 0);
if (socket1 < 0)
error("ERROR, can't open socket");
server = gethostbyname(argv[1]);
if (server == NULL) {
fprintf(stderr,"ERROR, there exists no such host\n");

exit(0);
}
bzero((char *) &serv_addr, sizeof(serv_addr));
serv_addr.sin_family = AF_INET;
bcopy((char *)server->h_addr,
(char *)&serv_addr.sin_addr.s_addr,
server->h_length);
serv_addr.sin_port = htons(portnum);
if (connect(socket1,(struct sockaddr *) &serv_addr,sizeof(serv_addr)) < 0)
error("ERROR,can't connect");
printf("Client: ");
while(1)
{
bzero(buffer,256);
fgets(buffer,255,stdin);
n = write(socket1,buffer,strlen(buffer));
if (n < 0)
error("ERROR, writing to socket");
bzero(buffer,256);
n = read(socket1,buffer,255);
if (n < 0)
error("ERROR, reading from socket");
printf("Server : %s\n",buffer);
int i = strncmp("Goodbye" , buffer , 7);
if(i == 0)
break;
}
}
```

Output Screenshots :

Server:



Client:



Question 3:

Security Protocol

At Sender Side:

Plaintext + Key=> Cipher Text

At Receiver Side:

Cipher Text-Key=> Plain Text

Aim :

To implement a Cesar Cipher encryption and decryption program in C which takes key and message as input and encodes and decodes the same.

Algorithm :

Traverse the given text one character at a time .

For each character, transform the given character as per the rule, depending on whether we're encrypting or decrypting the text.

Return the new string generated.

Code Text :

Encryption.c

```
#include<stdio.h>
int main()
{
	char message[100], ch;
	int i, key;
	printf("Enter a message to encrypt: ");
	gets(message);
	printf("Enter key: ");
	scanf("%d", &key);
	for(i = 0; message[i] != '\0'; ++i){
		ch = message[i];
		if(ch >= 'a' && ch <= 'z'){
			ch = ch + key;
			if(ch > 'z'){
				ch = ch - 'z' + 'a' - 1;
			}
			message[i] = ch;
		}
		else if(ch >= 'A' && ch <= 'Z'){
			ch = ch + key;

			if(ch > 'Z'){
				ch = ch - 'Z' + 'A' - 1;
			}
			message[i] = ch;
		}
	}
	printf("Encrypted message: %s\n", message);
	return 0;
}
```

Decryption.c

```
#include<stdio.h>
```

```
int main()
{
	char message[100], ch;
	int i, key;
	printf("Enter a message to decrypt: ");
	gets(message);
	printf("Enter key: ");
	scanf("%d", &key);
	for(i = 0; message[i] != '\0'; ++i){
		ch = message[i];
		if(ch >= 'a' && ch <= 'z'){
			ch = ch - key;
			if(ch < 'a'){
				ch = ch + 'z' - 'a' + 1;
			}
			message[i] = ch;
		}
		else if(ch >= 'A' && ch <= 'Z'){
			ch = ch - key;

			if(ch < 'A'){
				ch = ch + 'Z' - 'A' + 1;
			}
			message[i] = ch;
		}
	}

	printf("Decrypted message: %s\n", message);
	return 0;
}
```

Output Screenshots :

Encryption :



Decryption :



4. Study about any one Simulations Tools/Network Software

GloMoSim

Global Mobile Information System Simulator (GloMoSim) is a network protocol simulation software that simulates wireless and wired network systems. GloMoSim is designed using the parallel discrete event simulation capability provided by Parsec, a parallel programming language. GloMoSim currently supports protocols for a purely wireless network. It uses the Parsec compiler to compile the simulation protocols. Parsec is a C-based simulation language, developed by the Parallel Computing Laboratory at UCLA, for sequential and parallel execution of discrete-event simulation models.

A number of library based parallel and sequential network simulators have been designed. The paper describes a library, called GloMoSim (Global Mobile system Simulator), for parallel simulation of wireless networks. GloMoSim has been designed to be extensible and composable: the communication protocol stack for wireless networks is divided into a set of layers, each with its own API. Models of protocols at one layer interact with those at a lower (or higher) layer only via these APIs. The modular implementation enables consistent comparison of multiple protocols at a given layer. The parallel implementation of GloMoSim can be executed using a variety of conservative synchronization protocols, which include the null message and conditional event algorithms. The paper describes the GloMoSim library, addresses a number of issues relevant to its parallelization, and presents a set of experimental results on the IBM 9076 SP, a distributed memory multicomputer. These experiments use models constructed from the library modules. A model project in GloMoSim workspace looks like this.