

## Technical Data & Instruction Sheet

### PRODUCT BENEFITS

Removes residues, stains & marks of Epoxy Grout

No toxic fumes

Water base formulation

Does not damage substrate

Excellent cleaning properties

#### RECOMMENDED SURFACES

Tiles, Glass Mosaics

## **AVAILABLE SIZES**

1 Ltr

#### TECHNICAL INFORMATION

Form: Liquid

Appearance: Yellow transparent

liquid

Specific Gravity: 1.0-1.1 g/cm<sup>3</sup>

Flash Point: NA

Freeze point: 0°C

pH: 12-13

Shelf Life: 2 Years approx. if stored in tightly sealed container & cool place

## DESCRIPTION

XC3 Epoxy is a detergent used to remove traces of epoxy grout EG150 from ceramic and glass mosaic surface. The main purpose is to facilitate the removal of spray residues after the final wash with water. It can also be used to remove any light surface haze that may remain once the grout has dried the next day

#### DIRECTIONS

Read entire label before using. Use only as directed. Always test on a small area with a 24 hours curing to check desired results. Ensure that that area is well ventilated during the application and the surface is dry. Surface temperature should be between 10°C and 45°C.

- 1. Ensure surface is dry
- 2. Mask any surface not intended to be treated.
- Apply XC3 on the surface to be cleaned or on the traces of grout and leave standing for a few minutes
- 4. Then rub the surface with a scrubber provided along with product kit and rinse thoroughly with water
- 5. The product is particularly efficient on fresh grout
- If cleaning is carried out a few hours after applying the grout, it may be necessary to leave it standing for longer (at least 15-20 minutes), or repeat the cycle
- 7. Remove the water with vacuum cleaner so as to dry out the surface.
- 8. If stain is not removed completely, repeat the process second time.
- Clean tools with water immediately after application and allow them dry in a well ventilated area.

## **Special Instructions**

- 1. Do not use on polished marble or stone
- Do not use on wood
- 3. Do not use on methacrylate pools
- 4. Before using XC3 on materials with an unknown surface resistance, test the product beforehand to make sure it does not damage the surface
- 5. Not suitable for removing heavy deposits of epoxy grout and for use with fully cured material. Use RachTR XC4

## METHOD OF APPLICATION

USE GLOVES & GOGGLES WHILE APPLYING

## STORAGE AND HANDLING NSTRUCTIONS

May be harmful if swallowed. May cause skin, eye and respiratory irritation. Do not spray. Avoid prolong exposure to vapors. Use in a well ventilated area. Do not ingest. KEEP OUT OF THE REACH OF THE CHILDREN. Do not freeze or store above 40° C. Do not mix with other chemicals.

# EMERGENCY/ FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Call a physician

Eye Contact: Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if applicable, and continue flushing. Call a physician if eye irritation persists.

Skin Contact: Wash skin with mild soap and water. Call a physician if skin irritation persists. Wash clothes before wearing again.

Inhalation: Remove to fresh air. Call a physician if respiratory irritation persists.

The above information is based on the latest stage of our development and application technology. Due to multiplicity of influencing factors, this information must be considered as non-binding. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any us of this information.