



OAUTH-2 SETUP FOR APEX REST API'S

ABSTRACT

Below documents will guide to setup the oauth-2 configuration to secure the rest API.


Rajkumar L @ 4i Apps

OAuth: Client Credentials

The client credentials flow is a two-legged process that seems the most natural to me as I mostly deal with server-server communication, which should have no human interaction. For this flow we use the client credentials to return an access token, which is used to authorize calls to protected resources. The example steps through the individual calls, but in reality, it would be automated by the application.

This flow involves the following high level steps:

1. You develop a REST service in ORDS and secure it. You then register a 'client' application with ORDS.
2. You provide the client application (usually to the administrator) the client id and client secret generated from the client registration. The client application stores the client id and client secret securely on their server.
3. The client application makes a call to a special ORDS URL passing their client id and client secret.
4. ORDS responds with an authorization token. By default, the token will remain active for 3,600 seconds (1 Hour).
5. Once the token is obtained, the client calls the appropriate service, passing the token to gain access to the service.



By default, a newly created web service is unsecured. Follow these steps to create a privilege and associate it with a service in order to secure it.

- Enabled ORDS in schema 'REST' using ORDS.ENABLE_SCHEMA.
- Created a module called 'hr' using ORDS.DEFINE_MODULE.

The screenshot shows the APEX SQL Workshop interface. The 'SQL Commands' tab is active, displaying a PL/SQL block. The block starts with a comment: '#Commands to the Create Role (change the role name as per the project)'. It then contains the following code: `BEGIN`, `ORDS.create_role(`, `p_role_name => 'security_role'`, `);`, `COMMIT;`, `END;`. The 'Run' button is highlighted in green. Below the code editor, the 'Results' tab shows the message 'Statement processed.' and '0.08 seconds'.

```

1 #Commands to the Create Role (change the role name as per the project)
2 BEGIN
3   ORDS.create_role(
4     p_role_name => 'security_role'
5   );
6   COMMIT;
7 END;
8

```

Statement processed.
0.08 seconds

#Commands to the Create Role (Change the role name as per the project)

BEGIN

ORDS.create_role(

p_role_name => 'security_role'

);

COMMIT;

END;

/

The screenshot shows the APEX SQL Workshop interface. The 'SQL Commands' tab is active, displaying a PL/SQL block. The block starts with a comment: '#Commands to the Create Role (change the role name as per the project)'. It then contains the following code: `BEGIN`, `ORDS.create_role(`, `p_role_name => 'security_role'`, `);`, `COMMIT;`, `END;`, `/`. Below this, there is a comment: '#Check the Role:' followed by a query: `SELECT id, name FROM user_ords_roles WHERE name = 'security_role';`. The 'Run' button is highlighted in green. Below the code editor, the 'Results' tab shows a table with two columns: 'ID' and 'NAME'. The table contains one row with the values '31823' and 'security_role'. The 'security_role' value is highlighted with a red box. Below the table, it says '1 rows returned in 0.01 seconds' and 'Download'.

```

1 #Commands to the Create Role (change the role name as per the project)
2 BEGIN
3   ORDS.create_role(
4     p_role_name => 'security_role'
5   );
6   COMMIT;
7 END;
8 /
9
10 #Check the Role:
11 SELECT id, name FROM user_ords_roles WHERE name = 'security_role';
12


```

ID	NAME
31823	security_role

1 rows returned in 0.01 seconds Download

#Check the Role:

```
SELECT id, name FROM user_ords_roles WHERE name = 'security_role';
```



#Create the Privilege and define the base url pattern to protect and map the privilege to the role using the below command:

```
DECLARE
```

```
l_roles_arr OWA.vc_arr;
```

```
l_patterns_arr OWA.vc_arr;
```

```
BEGIN
```

```
l_roles_arr(1) := 'security_role';
```

```
l_patterns_arr(1) := '/haya/hr/*';
```

```
ORDS.define_privilege (  
p_privilege_name => 'security_priv',  
p_roles => l_roles_arr,  
p_patterns => l_patterns_arr,  
p_label => 'OcidadminRJ',  
p_description => 'Oauth.2 setup to protect API Data.'  
);
```

```
COMMIT;
```

```
END;
```

```
/
```

SQL Commands

Schema: OWWSCTST

Language: SQL Rows: 10 Clear Command Find Tables Save Run

```

1 SELECT id, name FROM user_ords_privileges WHERE name = 'security_priv';
2

```

Results Explain Describe Saved SQL History

ID	NAME
31840	security_priv

1 rows returned in 0.04 seconds Download

#Check the Privilege

SELECT id, name FROM user_ords_privileges WHERE name = 'security_priv';

SQL Commands

Schema: OWWSCTST

Language: SQL Rows: 10 Clear Command Find Tables Save Run

```

1 SELECT privilege_id, privilege_name, role_id, role_name FROM user_ords_privilege_roles WHERE role_name = 'security_role';
2

```

Results Explain Describe Saved SQL History

PRIVILEGE_ID	PRIVILEGE_NAME	ROLE_ID	ROLE_NAME
31840	security_priv	31825	security_role

1 rows returned in 0.01 seconds Download

#Check the Privilege and role mapping:

SELECT privilege_id, privilege_name, role_id, role_name FROM user_ords_privilege_roles WHERE role_name = 'security_role';

SQL Commands

Schema: OWWSCTST

Language: SQL Rows: 10 Clear Command Find Tables Save Run

```

1 #Check the Privilege base url
2 SELECT privilege_id, name, pattern FROM user_ords_privilege_mappings WHERE name = 'security_priv';
3

```


Results Explain Describe Saved SQL History

PRIVILEGE_ID	NAME	PATTERN
31840	security_priv	/haya/hr/*

1 rows returned in 0.01 seconds Download

#Check the Privilege base url

```
SELECT privilege_id, name, pattern FROM user_ords_privilege_mappings WHERE name = 'security_priv';
```

A screenshot of a SQL IDE interface. The top bar shows 'SQL Commands' and 'Schema: OWWSCTST'. Below the bar, there are tabs for 'Results', 'Explain', 'Describe', 'Saved SQL', and 'History'. The main editor area contains a PL/SQL block with the following code:

```
1 BEGIN
2   OAUTH.create_client(
3     p_name => 'securty_client',
4     p_grant_type => 'client_credentials',
5     p_owner => 'Haya',
6     p_description => 'Oauth client for Rest Api management',
7     p_support_email => 'rajkumar.kl@4iapps.com',
8     p_privilege_names => 'security_priv'
9   );
10  COMMIT;
11  END;
```

The bottom status bar indicates 'Statement processed.' and '0.77 seconds'.

#Check the Oauth client:

```
BEGIN

OAUTH.create_client(

p_name => 'securty_client',

p_grant_type => 'client_credentials',

p_owner => 'Haya',

p_description => 'Oauth client for Rest Api management',

p_support_email => 'rajkumar.kl@4iapps.com',

p_privilege_names => 'security_priv'

);

COMMIT;

END;

/
```

SQL Commands

Schema: OWWSCTST

Language: SQL Rows: 10 Clear Command Find Tables Save Run

```

1 SELECT id, name, client_id, client_secret FROM user_ords_clients;
2

```

Results Explain Describe Saved SQL History

ID	NAME	CLIENT_ID	CLIENT_SECRET
31716	securty_client	NWpXlIFxHl.dsnuBaW3ewA.	bc5GcNwcmgYP5Yfdgw.epg.
31859	securty_client1	ZxNSTXf-wluO6dyB85ZYmw.	cplJDTVsIBfbrRqoV8Vaw.

2 rows returned in 0.01 seconds Download

#Check the Oauth clients

```
SELECT id, name, client_id, client_secret FROM user_ords_clients;
```

SQL Commands

Schema: OWWSCTST

Language: SQL Rows: 10 Clear Command Find Tables Save Run

```

1 #Check the Oauth clients and Privilege mapping;
2 SELECT name, client_name FROM user_ords_client_privileges;
3

```

Results Explain Describe Saved SQL History

NAME	CLIENT_NAME
security_priv	securty_client1

1 rows returned in 0.01 seconds Download

#Check the Oauth clients and Privilege mapping:

```
SELECT name, client_name FROM user_ords_client_privileges;
```

SQL Commands

Schema: OWWSCTST

Language: SQL Rows: 10 Clear Command Find Tables Save Run

```

1 BEGIN
2 OAUTH.grant_client_role(
3 p_client_name => 'securty_client1',
4 p_role_name => 'security_role'
5 );
6 COMMIT;
7 END;
8
9

```

Results Explain Describe Saved SQL History

Statement processed.

0.07 seconds

#Grant client role to clients:


BEGIN

```
OAUTH.grant_client_role(  
p_client_name => 'securty_client1',  
p_role_name => 'security_role'  
);
```

COMMIT;

END;

/




The screenshot shows the SQL Developer interface with the 'SQL Commands' tab active. The command window contains the query: `SELECT client_name, role_name FROM user_ords_client_roles;`. The 'Results' tab is selected, displaying a table with two columns: 'CLIENT_NAME' and 'ROLE_NAME'. The table contains one row with the values 'security_client1' and 'security_role'. The status bar at the bottom indicates '1 rows returned in 0.01 seconds'.

CLIENT_NAME	ROLE_NAME
security_client1	security_role

Check the Oauth clients and Role mapping:

SELECT client_name, role_name FROM user_ords_client_roles;



This screenshot is identical to the previous one, showing the same SQL query and result set. A red rectangular box highlights the single row of data in the results table, containing 'security_client1' and 'security_role'.

CLIENT_NAME	ROLE_NAME
security_client1	security_role

Note down the Oauth clients:

Client ID: 2xN3TXFwlu06diyB85ZYmw..

Client Secret: cpiJDTVs1BIFbRHjoV8Vaw..

SQL Commands

Language: SQL Rows: 10

```

1 #Check the Oauth clients
2 SELECT id, name, client_id, client_secret FROM user_ords_clients;
3

```

Results

ID	NAME	CLIENT_ID	CLIENT_SECRET
31716	security_client	NWpXlIfxIl.dsnuBwSewA...	bc5GchwcmgYPSYfdgw_..._...
31859	security_client1	ZxN3TXF-wluOoddyB85ZYmw...	cpUDTVsIBfBfRqoV8Vaw...

2 rows returned in 0.00 seconds

Now protect the module with the newly created privilege.

APEX App Builder SQL Workshop Team Development Gallery

RESTful Services Privileges Privilege Definition

RESTful Data Services

- Enabled Objects
- Modules
- Privileges
 - oracle.dbtools.autoreset.privilege.OVWSCSTST
 - oracle.dbtools.sqldev
 - oracle.soda.privilege.developer
 - security_priv**
- Roles

Privilege Definition

Owner: OVWSCSTST

Name: security_priv

Title: OcicadminRJ

Description: Oauth2 setup to protect API Data.


Comments:

Roles:

- OAuth2 Client Developer
- SQL Developer
- RESTful Services
- Schema Administrator
- oracle.dbtools.autoreset.any.schema
- SODA Developer
- OAuth Client Developer
- oracle.dbtools.role.autoreset.OVWSCSTST

Protected Modules

- FoodRequestFeedback
- RedwoodResearchModule
- MailNotification
- PINormalisation
- MobileModule
- AdminModule



Click save apply changes.

Check the module is protected status.

The screenshot shows the 'Modules' page in the APEX SQL Workshop. The 'Modules' table lists various modules and their status. The 'Protected by Privilege' column for 'oracle.example.hr' is highlighted with a red box and a green checkmark.

Name	URI Prefix	Items Per Page	Published Status	Comments	Origins Allowed	Created On	Updated On	Protected by Privilege
oracle.example.hr	/hr/	25	PUBLISHED	-	-	6 months ago	6 months ago	✓
FoodRequestFeedBack	/foodfeedback/	0	PUBLISHED	-	-	4 months ago	4 months ago	✗
RedwoodResearchModule	/redwood/module/	25	PUBLISHED	-	-	5 months ago	5 months ago	✗
MailNotification	/mailnotification/	0	PUBLISHED	-	-	5 months ago	5 months ago	✗
PMSNormalization	/pmsnormalization/	0	PUBLISHED	-	-	5 months ago	5 months ago	✗
MobileModule	/mobile/	25	PUBLISHED	-	-	5 days ago	5 days ago	✗
AdminModule	/admin/module/	0	PUBLISHED	-	-	6 months ago	6 months ago	✗
ApprovalModule	/ApprovalModule/	0	PUBLISHED	-	-	6 months ago	6 months ago	✗
AttachmentModule	/attachment/	0	PUBLISHED	-	-	6 months ago	6 months ago	✗
CustomReport	/report/	0	PUBLISHED	-	-	6 months ago	6 months ago	✗
ExcelUpload	/excelupload/	0	PUBLISHED	-	-	6 months ago	6 months ago	✗
GenericApproval	/approval/	0	PUBLISHED	-	-	6 months ago	2 months ago	✗

Use postman to validate the Oauth.

https://owwscoratput.nws.nama.om/ords/haya/hr/employees/

GET https://owwscoratput.nws.nama.om/ords/haya/hr/employees/ Send

Params Authorization Headers (6) Body Pre-request Script Tests Settings

Type OAuth 2.0

The authorization data will be automatically generated when you send the request. [Learn more about authorization](#)

Add authorization data to Request Headers

Current Token

Token restapitoken

Header Prefix Bearer

Auto-refresh token Your expired token will be auto-refreshed before sending a request

Share token Sharing this token will allow anyone with access to this request to view and use it.

Configure New Token

Configuration Options Advanced Options

Token Name restapitoken

Grant Type Client Credentials

Access Token URL https://owwscoratput.nws.nama.om/ords/...

Status: 200 OK Time: 336 ms Size: 3.98 KB Save Response

Token URL:

Sample: `https://<apex-hostname>/ords/<schema_alias>/oauth/token`

`https://owwscoratput.nws.nama.om/ords/haya/oauth/token`

GET https://owwscoratput.nws.nama.om/ords/haya/hr/employees/ Send

Params Authorization Headers (6) Body Pre-request Script Tests Settings

Type OAuth 2.0

The authorization data will be automatically generated when you send the request. [Learn more about authorization](#)

Add authorization data to Request Headers

Current Token

Token restapitoken

Header Prefix Bearer

Auto-refresh token Your expired token will be auto-refreshed before sending a request

Share token Sharing this token will allow anyone with access to this request to view and use it.

Configure New Token

Configuration Options Advanced Options

Token Name restapitoken

Grant Type Client Credentials

Access Token URL https://owwscoratput.nws.nama.om/ords/...

Client ID NWpXJfXtHLDsnuB9W3ewIA...

Client Secret bc5GcNwcmgYPSYfdgw_egg...

Scope e.g. read:org



Client Authentication Send as Basic Auth header

Clear cookies Get New Access Token


Status: 200 OK Time: 336 ms Size: 3.98 KB Save Response

Obtaining An Authorization Token

Before the client application can call our secured service, they will first need to obtain an authorization token. This is done by calling a special ORDS REST service `'.../oauth2/token'`. By default, the token expires after 3,600 seconds (or 1 Hour).



Use the token.



https://owwscoratpuat.nws.nama.om/ords/haya/hr/employees/

GEThttps://owwscoratpuat.nws.nama.om/ords/haya/hr/employees/

Send

ParamsAuthorizationHeaders (7)BodyPre-request ScriptTestsSettingsCookies

TypeOAuth 2.0

Current Token
This token is only available to you. Sync the token to let collaborators on this request use it.

The authorization data will be automatically generated when you send the request. [Learn more about authorization](#)

Tokenrestapitoken

BodyCookiesHeaders (13)Test Results

Status: 200 OKTime: 1116 msSize: 3.98 KBSave Response

PrettyRawPreviewVisualizeJSON

```
1  {
2    "items": [
3      {
4        "in": 1,
5        "empno": 7369,
6        "ename": "SMITH",
7        "job": "CLERK",
8        "hiredate": "1980-12-17T00:00:00Z",
9        "mgr": 7902,
10       "sal": 800,
11       "comm": null,
12       "deptno": 20,
13       "links": [
14         {
15           "rel": "uri",
16           "href": "https://owwscoratpuat.nws.nama.om/ords/haya/hr/employees/7369"
17         }
18       ]
19     }
20   ]
21 }
```